LEGEND

FIELD INVESTIGATION

[P] PHOTOGRAPHY: Stereoscopic

[A] RADIOACTIVITY: Airborne

[S] STREAM SEDIMENTS: Stations, Traverses

[W] WATER: Wells

[G] GEOLOGY: Landforms, Bedrock

[R] ROCKS: Landforms, Bedrock

[M] MINERAL DEPOSITS: Landforms

[D] DRILLING: Landforms, Bedrock

GEOLOGY

[M] Mafic

[U] Ultramafic

[F] Felsic

[I] Intermediate

[C] Felsic to Intermediate

[S] Sedimentary

[Mt] Metamorphosed

[Mi] Migmatite, granitic gneiss

[Ig] Ingneous/gneissic granite

Geological contact.....

Fault.....

Dyke.....

Geology derived from the 1:1,000,000 Ontario Geology map at the scale of 1:1,000,000. Compiled by J.E. Thomas, A.H. Poole and J.F. Wright, 1972

Geological cartography by the Geological Survey of Canada

Base-map at the same scale published by the Surveys and Mapping Branch, Department of Energy, Mines and Resources, Ottawa, 1974

Mean magnetic declination 1972, 17°51.2' West decreasing 3.1' annually. Readings vary from 16°51' in the S.E. corner to 19°11.2' in the N.W. corner of the map area.

Elevation in feet above mean sea-level

Province of Ontario
Ministry of Natural Resources
Geological Branch

Canada
Department of Energy, Mines and Resources
Geological Survey of Canada

Geochemical Symbol and Data Presentation

The concentration of an element at a sample site is graphically represented on one of the following symbols: a circle, a square, a triangle, a diamond, a pentagon or a 12 pointed star. The symbols are symmetrically arranged so that the first increase in size to the eighth symbol and then increase in blackness to the fifteenth. The two largest symbols, the 14th and 15th, are used to represent the highest concentrations below the anomalous threshold limit, or, in the data group containing the detection limit. The data are grouped on a semi-logarithmic scale, i.e. 1,1.5,2,3,4,5,6,7,8,9,10, 12, 15, 20, 30, 40, 50, 60, 70, 80, 90, 100 and so on. The use of a semi-logarithmic scale ensures that values constituting the National Geochemical Reconnaissance threshold limit will be represented by the same symbol regardless of the element. It is based on the arithmetic and cumulative frequency plot for the total survey data distributions. The threshold limit, or the concentration above which the 97.5 percentile symbol is used for the model areas as defined by the histograms. This group usually includes the median of the data as defined by the 0.5 (50%) point on the cumulative frequency plot. The use of the 97.5 percentile as the threshold limit is an achieved on appropriate graphical inspection. An example of all 15 symbols is given below.

The symbol maps, being based on the total survey data distributions, are unaffected by the availability of exact increasing levels of knowledge in bedrock and surficial geology, and other environmental factors. Therefore, the raw data symbol maps are the most objective maps that can be produced from the data at the present time. However, to facilitate the needs of a more scientific and thorough interpretation, the raw symbol maps should be modified using the field and analytical data provided in the data tables. The modification of the raw symbol maps can be done by a careful examination of the data in terms of the symbol and bedrock geology, a table of summary statistics and proposed threshold values for each mapped bedrock unit, or broad lithologic unit, and the histograms. The data tables, the histograms and the raw symbol maps can also be used, in conjunction, with the sample location map and data listings, to investigate the significance of individual sample sites. The histograms, and the table grid also illustrate, more clearly than the map, the dependence of mean concentration values on the bedrock geology. The histograms and the table grid data appears to approximate a log-normal distribution the data for individual map or lithologic units appears to approximate a normal distribution. The proposed threshold values for each bedrock unit, or group of units, can be used, for detailed exploration purposes, locations of samples with concentrations in excess of the threshold for the rock unit they appear to be derived from, should be studied carefully. Such locations may indicate the presence of a mineral deposit, or other environmental features, but one of these could be the presence of abnormal concentrations of the element in a form of interest to the mineral exploration.

Other considerations, such as the effects of topographic, environmental and recorable data should be outlined. The data separation by bedrock type can often be improved by constructing new data subsets and deriving fiscal thresholds levels based on the new data subsets and the histograms.

The term reliability factor and value that appears below the table is an estimate of the reliability of the geochemical map. On the basis of duplicate sampling by 12 to 15 percent of the field crews, and the analysis of the duplicate samples by the recognized and identical methods of sample preparation and analysis and used the new data, the reliability factor is calculated. The reliability factor is a measure of the factor times this account for reliability due to both heterogeneity of the centre-late bedrock sediments and sample preparation and analytical causes.

NATIONAL GEOCHEMICAL RECONNAISSANCE MAP 1-1976
MISSION 16 LAKE SEDIMENTS

CANADA-ONTARIO SUBSIDIARY AGREEMENT ON MINERAL EXPLORATION AND DEVELOPMENT

Scale 1:250,000

Kilometres 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190 195 200

Miles 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125

Universal Transverse Mercator Projection
© Crown Copyright Reserved

This map has been digitized from a scribecoat original using a Hycograph digitizer and computer processed by GSC staff





Table of Thresholds for Major Geological Units

Lithology	No. of Samples	Mean	S.D.	C.V.	Threshold
Limestone	13	103	151	101	350
Dolostone	53	53	28	53	130
Siltstone	10	64	35	55	150
Slate	37	64	39	61	200
Argillite	5	54	26	48	110
Conglomerate	3	40	17	43	80
Andesite	19	102	57	56	250
Basalt	5	140	132	94	450
Syenite	20	111	244	220	1000
Granite	102	147	80	54	350
Granodiorite	93	130	49	38	250
Gabbro	7	124	46	37	200
Anorthosite	4	100	27	27	150
Amphibolite	42	100	37	37	200
Gneiss	57	112	64	57	300
Migmatite	93	102	66	65	350
Unknown	8	116	37	32	200

Data units are ppb

Reliability Factor = 1.95

NATIONAL GEOCHEMICAL RECONNAISSANCE MAP 1-1976
OPEN FILE 426
SASKATOON CHERNOZEM, 1976

NATIONAL GEOCHEMICAL RECONNAISSANCE MAP 1-1976

OPEN FILE 426

Resource Geophysics and Geochemistry Division

Geological Survey of Canada, Ottawa

Geochemistry and Federal-Provincial coordination by E.A.w. Hornbrook
Field operation supervised by F.C. Bonham-Carter
Analytical chemistry by J.C. Lynch
Data processing by K.L. Garrett, D.G. Lund and D. Ellwood

Ontario Geological Branch

Federal-Provincial coordination by R.D. Card

Contractors:

Sample preparation by Golder Associates
Chemical analyses by Chemex Labs Ltd.

This map forms one of a series of 23 sheets released under Geological Survey of Canada, Open Files 426-456.
Open File 426 is a folded map, 44 inches wide, per cent loss or tyrrition and sample site location.

The data are also available in digital form. For further information please contact:

The Director
Publication Service Centre,
Department of Energy, Mines and Resources,
Ottawa, Ontario K1A 0E8