

COBALT  
CANADA

EDITION 3

11 K/15

Co

LEGEND


Sample number ..... e.g. 82-1-025  
Analytical value in p.p.m. (unless otherwise specified) ... e.g. 106

Geochemical Sample Medium

Stream sediment, sieved .....  
Stream sediment, unsieved .....  
Lake sediment .....  
Heavy mineral / panned concentrate .....  
Soil .....  
Rock .....  
Peat .....  
Till .....  
Other .....

Note: Two (2) sample numbers per sample location indicates duplicate sample site... e.g. 82-1-025,026

HISTOGRAM AND BASIC STATISTICS



Note: Only data within this 1:50,000 sheet is included.


Average: 17.21  
Number of samples: 135  
Standard deviation: 0.58  
Range: 4.00 - 33.00  
Detection limit: 2 ppm

Sample collection and Geochemistry: P.J. Rogers and M.A. MacDonald  
Analyses: Chemex Laboratories Ltd., North Vancouver, B.C.  
Sample digestion: Hot  $\text{HNO}_3$  - HCL Extraction  
Analytical technique: Air-Acetylene AAS

TABLIER D'ASSEMBLAGE DU SYSTÈME NATIONAL DE RÉFÉRENCE CARTOGRAPHIQUE


	IIN/2	IIN/1
	IIK/10	IIK/9
IIK/11	IIK/10	IIK/9

INDEX TO GEOGRAPHIC MAPS OF THE NATIONAL TOPOGRAPHIC SYSTEM



PLEASANT BAY  
NOVA SCOTIA

Scale 1:50,000 Échelle



Information concerning location and precise elevation of bench marks can be obtained by referring to the Geodetic Survey, Survey and Mapping Branch, Ottawa.

CONVERSION SCALE FOR ELEVATIONS

Feet 100 200 300 400 500 600 700 800 900 1000

Metres 30 60 90 120 150 180 210 240 270 300

Feet 100 200 300 400 500 600 700 800 900 1000

Metres 30 60 90 120 150 180 210 240 270 300

On peut obtenir des renseignements sur la localité et l'altitude exacte des points de repère en consultant les données des levés géodésiques. Direction des levés et de la cartographie (Ottawa).

ÉCHELLE DE CONVERSION DES ALTITUDES

Pieds 100 200 300 400 500 600 700 800 900 1000

Mètres 30 60 90 120 150 180 210 240 270 300

Pieds 100 200 300 400 500 600 700 800 900 1000

Mètres 30 60 90 120 150 180 210 240 270 300

On peut obtenir des renseignements sur la localité et l'altitude exacte des points de repère en consultant les données des levés géodésiques. Direction des levés et de la cartographie (Ottawa).

ÉCHELLE DE CONVERSION DES ALTITUDES

Pieds 100 200 300 400 500 600 700 800 900 1000

Mètres 30 60 90 120 150 180 210 240 270 300

Pieds 100 200 300 400 500 600 700 800 900 1000

Mètres 30 60 90 120 150 180 210 240 270 300

OPEN FILE  
DOSSIER PUBLIC  
986  
Geological  
Survey  
Commission  
Géologique  
Ottawa

OPEN FILE  
OF M 84-12  
Nova Scotia  
Department of  
Mines and Energy

CONTRIBUTION TO CANADA-NOVA SCOTIA  
CO-OPERATIVE MINERAL PROGRAM 1981-84