

GEOLOGICAL SURVEY OF CANADA OPEN FILE 1643

(64E, parts of 74A and 74H)

CANADA – SASKATCHEWAN MINERAL DEVELOPMENT AGREEMENT (1984 – 1989)

REGIONAL LAKE SEDIMENT AND WATER GEOCHEMICAL DATA, NORTHEASTERN SASKATCHEWAN



Project Director: E.H.W. Hornbrook

Project Coordinator: P.W.B. Friske

Subproject Leaders: J.J. Lynch, H.R. Schmitt


Members: S. Cook, C.C. Durham, A. Galletta, H. Gross, M. McCurdy, D. Wright

This document was produced
by scanning the original publication.

Ce document est le produit d'une
numérisation par balayage
de la publication originale.

August, 1988

**REGIONAL LAKE SEDIMENT AND WATER GEOCHEMICAL DATA, SASKATCHEWAN 1988,
GSC OPEN FILE 1643, NGR 108-1988,
NTS 64E; PARTS 74A, 74H**



NATIONAL TOPOGRAPHIC SYSTEM REFERENCE AND INDEX
TO ADJOINING GEOLOGICAL SURVEY OF CANADA MAPS
SYSTÈME NATIONAL DE RÉFÉRENCE CARTOGRAPHIQUE
ET INDEX DES CARTES ATTENANTES PUBLIÉES PAR
LA COMMISSION GÉOLOGIQUE DU CANADA

Open File 1643 represents a contribution to the Canada – Saskatchewan Mineral Development Agreement (1984 – 1989), a subsidiary agreement under the Economic and Regional Development Agreement. This project was funded and managed by the Geological Survey of Canada.

TABLE OF CONTENTS

	page
INTRODUCTION	I-1
CREDITS	I-1
DESCRIPTION OF SURVEY AND SAMPLE MANAGEMENT	I-2
ANALYTICAL PROCEDURES	I-2
PRESENTATION AND INTERPRETATION OF GOLD DATA	I-3
REFERENCES	I-5
SUMMARY OF ANALYTICAL DATA AND METHODS	I-6
DATA LIST LEGEND AND DIGITAL FIELD RECORD FORMAT	I-7
DATA LISTINGS	II-1 to II-64
SUMMARY STATISTICS	III-1 to III-48
ELEMENT SYMBOL-TREND PLOTS	in pocket
SAMPLE LOCATION OVERLAY	in pocket
GEOLOGY OVERLAY	in pocket
SAMPLE LOCATION MAP (1:250,000 SCALE)	in pocket
GOLD VALUE MAP (1:250,000 SCALE)	in pocket

REGIONAL LAKE SEDIMENT AND WATER GEOCHEMICAL DATA, SASKATCHEWAN 1988, GSC OF 1643, NGR 108-1988, NTS 64E; PARTS OF 74A, 74H

Geological Survey of Canada Open File 1643

**Regional Lake Sediment and Water Geochemical Reconnaissance Data
North-East Saskatchewan, consisting of parts of NTS 64E, 74A, and 74H**

INTRODUCTION

Open File 1643 is one of three open files (1642, 1643, 1644) covering parts of northern Saskatchewan which were sampled in 1978, 1984 and 1985 respectively and previously published as Open Files 556, 1106 and 1213. The new open files represent additional analyses of archived lake sediment material for 28 elements by instrumental neutron activation.

The reconnaissance survey was originally undertaken in 1984 by the Geological Survey of Canada in conjunction with the Saskatchewan Department of Energy and Mines under the Canada - Saskatchewan Mineral Development Agreement (1984 - 1989).

The data base of the survey contributes to a national geochemical reconnaissance and are used for resource assessment, mineral exploration and geological mapping. Regional survey sample collection and preparation procedures, analytical methods and repeatability of results are therefore strictly specified and controlled. In this way, consistent data can be systematically obtained in different areas in different years from different analytical laboratories

CREDITS

E.H.W. Hornbrook directed the survey and archived analysis programs.

P.W.B. Friske coordinated the operational activities of contract and Geological Survey of Canada staff.

Contracts were let to the following companies for sample collection, preparation and analysis and were managed by the following staff of the Exploration Geochemistry Subdivision:

Collection: Marshall, Macklin, Monaghan Ltd., Toronto, Ontario
E.H.W. Hornbrook
P.W.B. Friske

Preparation: Golder Associates, Ottawa, Ontario
J.J. Lynch

Analysis: Barringer Magenta Ltd., Rexdale, Ontario (1984)
Barringer Magenta (Alberta) Ltd., Calgary, Alberta (1984)
Bondar Clegg and Company Ltd., Ottawa (1988)
J.J. Lynch

H.R. Schmitt coordinated and edited open file production.

A.C. Galletta and D. Wright managed the digital geochemical data, provided computer processing support, and developed software to plot the open file, symbol and regional trend maps. Computing services were provided by the Computer Science Centre, EMR. The plotting was done by Canada Lands Data Systems staff at Environment Canada, Hull, Quebec.

H.A. Gross developed microcomputer software to produce data listings and summary statistics

J. Yelle and F. Williams of the Geological Information Division supervised the preparation of open file base maps by Cartography Unit A-2.

M. McCurdy, S. Cook and C.C. Durham provided technical support and editing assistance.

J.C. Bélec provided word processing support.

DESCRIPTION OF SURVEY AND SAMPLE MANAGEMENT

Helicopter supported sample collection was carried out during the summer of 1984.

Lake sediment and water samples were collected at an average density of one sample per 13 square kilometres throughout the 18,800 square kilometres of the north-east Saskatchewan survey area.

Sample site duplicate samples were routinely collected in each analytical block of twenty samples.

In Ottawa, field dried samples were air-dried, crushed, ball milled and sieved. The minus 80 mesh (177 microns) fraction was used for subsequent analyses. At this time, control reference and blind duplicate samples were inserted into each block of twenty sediment samples. For the water samples, only control reference samples were inserted into the block. There were no blind duplicate water samples.

On receipt, field and analytical data were processed with the aid of computers.

The field data were recorded by the field contract staff on standard lake sediment field cards (Rev. 74) used by the Geological Survey of Canada (Garrett, 1974).

The sample site positions were marked on appropriate 1/250,000 scale NTS maps in the field. These maps were digitized at the Geological Survey in Ottawa to obtain the sample site UTM coordinates.

The sample site coordinates were checked as follows: a sample location map was produced on a Calcomp 1051 drum plotter using the digitized coordinates; the field contractor's sample location map was then overlayed with the Calcomp map; the two sets of points were checked for coincidence. The dominant rock types in the lake catchment basins were identified on appropriate geological maps used as the bedrock geological base on RGR maps.

Thorough inspections of the field and analytical data were made to check for any missing information and/or gross errors.

Quality control and monitoring of the geochemical data was undertaken by a standard method used by the Exploration Geochemistry Subdivision at the Geological Survey of Canada.

ANALYTICAL PROCEDURES

Instrumental Neutron Activation Analysis (INAA)

The weighed sample (generally 5 to 10 g) is irradiated for 20 minutes in a neutron flux whose approximate density is 5.3×10^{11} neutrons/square cm/second. Counting is begun seven days after irradiation. The counting time is somewhat variable (6 to 11 minutes) and is matrix dependent. Counting is done on a germanium-lithium co-axial counter. The counting data is accumulated on a VAX computer and is subsequently converted to concentrations. Numerous international reference samples are irradiated with each batch of routine samples.

Elements determined by INA analyses include: Na, Sc, Cr, Fe, Co, Ni, Zn, As, Se, Br, Rb, Zr, Mo, Ag, Cd, Sn, Sb, Te, Cs, Ba, La, Ce, Sm, Eu, Tb, Yb, Lu, Hf, Ta, W, Ir, Au, Th, and U. Data for Zn, Se, Zr, Ag, Cd, Sn, Te and Ir are not published because of inadequate detection limits and/or precision.

Atomic Absorption Spectroscopy (AAS) and Other Analyses

For the determination of Zn, Cu, Pb, Ni, Co, Ag, Mn, Fe, Cd, As and Sb a 1 gram sample was reacted with 6 mL of a mixture of 4 M HNO₃ and M HCl in a test-tube overnight at room temperature. After digestion, the test-tube was immersed in a hot water bath at room temperature and brought up to 90°C and held at this temperature for 2 hours with periodic shaking. The sample solution was then diluted to 20 mL with metal free water and mixed. Zn, Cu, Pb, Ni, Co, Ag, Mn, Fe and Cd were determined by atomic absorption spectroscopy using an air-acetylene flame. Background corrections were made for Pb, Ni, Co, Ag and Cd.

Arsenic and Sb were determined by atomic absorption using a hydride evolution method wherein the hydride (AsH₃ or SbH₃) is evolved and passed through a

heated quartz tube in the light path of an atomic absorption spectrophotometer. The method is described by Aslin (1976). Detection limit = 1 ppm (As); 0.2 ppb (Sb).

Molybdenum and vanadium were determined by atomic absorption spectroscopy using a nitrous oxide acetylene flame. A 0.5 gram sample was reacted with 1.5 mL concentrated HNO₃ at 90°C for 30 minutes. At this point 0.5 mL concentrated HCl was added and the digestion was continued at 90°C for an additional 90 minutes. After cooling, 8 mL of 1250 ppm Al solution were added and the sample solution was diluted to 10 mL before aspiration. Detection limit = Mo - 2 ppm; V - 5 ppm.

Mercury was determined by the Hatch and Ott Procedure with some modifications. The method is described by Jonasson et al. (1973). A 0.5 gram sample was reacted with 20 mL concentrated HNO₃ and 1 mL concentrated HCl in a test-tube for 10 minutes at room temperature prior to 2 hours of digestion with mixing at 90°C in a hot water bath. After digestion, the sample solutions were cooled and diluted to 100 mL with metal free water. The Hg present was reduced to the elemental state by the addition of 10 mL 10% w/v SnSO₄ in M H₂SO₄. The Hg vapour was then flushed by a stream of air into an absorption cell mounted in the light path of an atomic absorption spectrophotometer. Absorption measurements were made at 253.7 nm. Detection limit = 10 ppb.

Loss on ignition was determined using a 500 mg sample. The sample, weighed into 30 ml beaker, was placed in a cold muffle furnace and brought up to 500°C over a period of 2 – 3 hours. The sample was left at this temperature for 4 hours, then allowed to cool to room temperature for weighing. Detection limit = 1.0 pct.

Uranium was determined using a neutron activation method with delayed neutron counting. A detailed description of the method is provided by Boulanger et al. (1975). In brief, a 1 gram sample is weighed into a 7 dram polyethylene vial, capped and sealed. The irradiation is provided by the Slowpoke reactor with an operating flux of 10** 12 neutrons/sq cm/sec. The samples are pneumatically transferred from an automatic loader to the reactor, where each sample is irradiated for 60 seconds. After irradiation, the sample is again transferred pneumatically to the counting facility where after a 10 second delay the sample is counted for 60 seconds with six BF₃ detector tubes embedded in paraffin. Following counting, the samples are automatically ejected into a shielded storage

container. Calibration is carried out twice a day as a minimum, using natural materials of known uranium concentration. Detection limit = 0.5 ppm.

Fluoride in lake water samples was determined using a fluoride electrode. Prior to measurement an aliquot of the sample was mixed with an equal volume of TISAB II buffer solution (total ionic strength adjustment buffer). The TISAB II buffer solution is prepared as follows: to 50 mL metal free water add 57 mL glacial acetic acid, 58 gm NaCl and 4 gm CDTA (cyclohexylene dinitrilo tetraacetic acid). Stir to dissolve and cool to room temperature. Using a pH meter, adjust the pH between 5.0 and 5.5 by slowly adding 5 M NaOH solution. Cool and dilute to one litre in a volumetric flask. Detection limit = 20 ppb.

Hydrogen ion activity (pH) was measured with a combination glass-calomel electrode and a pH meter.

Uranium in waters was determined by a laser-induced fluorometric method using a Scintrex UA-3 uranium analyser. A complexing agent, known commercially as fluran and composed of sodium pyrophosphate and sodium monophosphate (Hall, 1979) is added to produce the uranyl pyrophosphate species which fluoresces when exposed to the laser. Since organic matter in the sample can cause unpredictable behaviour, a standard addition method was used. Further, there have been instances at the GSC where the reaction of uranium with fluran is either delayed or sluggish; for this reason an arbitrary 24 hour time delay between the addition of the fluran and the actual reading was incorporated into this method. In practice 500 µL of fluran solution were added to a 5 mL sample and allowed to stand for 24 hours. At the end of this period fluorescence readings were made with the addition of 0.0, 0.2 and 0.4 ppb U. For high samples the additions were 0.0, 2.0 and 4.0 (20 µL aliquots of either 55 or 550 ppb U were used). All readings were taken against a sample blank. Detection limit = .05 ppb.

Table 1 provides a summary of analytical data and methods.

PRESENTATION AND INTERPRETATION OF GOLD DATA

The following discussion reviews the format used to present the Au geochemical data and outlines some important points to consider when interpreting this data. This discussion is included in recognition of the special geochemical behaviour and

mode of occurrence of Au in nature and the resultant difficulties in obtaining and analyzing samples which reflect the actual concentration level at a given site.

To correctly interpret Au geochemical data from regional stream sediment or lake sediment surveys requires an appreciation of the unique chemical and physical characteristics of Au and its mobility in the surficial environment. Key properties of Au that distinguish its geochemical behaviour from most other elements include (Harris, 1982):

- (1) Au occurs most commonly in the native form which is chemically and physically resistant. A high proportion of the metal is dispersed in micron-sized particulate form. Gold's high specific gravity results in heterogeneous distribution, especially in stream sediment and clastic-rich (low LOI) lake sediment environments. Au distribution appears to be more homogeneous in organic-rich fluvial and lake sediment environments.
- (2) Gold typically occurs at low concentrations in the ppb range. Whereas gold concentrations of only a few ppm may represent economic deposits, background levels encountered from stream and centre-lake sediments seldom exceed 10 ppb, and commonly are near the detection limit of 1 ppb.

These factors result in a particle sparsity effect wherein very low concentrations of Au are heterogeneously enriched in the surficial environment. Hence, a major problem facing the geochemist is to obtain a representative sample. In general, the lower the actual concentration of Au the larger the sample size, or the smaller the grain size required to reduce uncertainty over whether subsample analytical values truly represent actual values. Conversely, as actual Au concentrations increase or grain size decreases, the number of Au particles to be shared in random subsamples increases and the variability of results decreases (Clifton et al., 1969; Harris, 1982). The limited amount of material collected during the rapid, reconnaissance-style regional surveys and the need to analyze for a broad spectrum of elements, precludes the use of a significantly large sample weight for the Au analyses. Therefore, to the extent that sample representivity can be increased, sample grain size is reduced by sieving and ball milling of all samples.

The following control methods are currently employed to evaluate and monitor the sampling and analytical variability which are inherent in the analysis of Au in geochemical mediums:

- (1) For each block of twenty samples:
 - (a) random insertion of a standard reference sample to control analytical accuracy and long-term precision;
 - (b) collection of a field duplicate (two samples from one site) to control sampling variance;
 - (c) analysis of a second subsample (blind duplicate) from one sample to control short-term precision.
- (2) For both stream sediments and lake sediments, routine repeat analyses on a second subsample are performed for all samples having values that are statistically above approximately the 90th percentile of total data set. This applies only to gold analyses by fire assay preconcentration followed by neutron activation. Such routine repeat analyses are not performed for INA analyses of archived samples.
- (3) For lake sediments only, a routine repeat analysis on a second subsample is performed on those samples with LOI values below 10%, indicating a large clastic component. On-going studies suggest that the Au distribution in these samples is more likely to be variable than in samples with a higher LOI content. Again, routine repeat analyses are performed only when the fire assay preconcentration/neutron activation method is used.

Au data presentation, statistical treatment and the value map format are different than for other elements. Au data listed in the open file may include initial analytical results, values determined from repeat analyses, together with sample weights and corresponding detection limits for all analyzed samples. The gold, statistical parameters and regional symbol trend plots are determined using the following data population selection criteria:

- (1) Only the first analytical value is utilized.
- (2) Au values determined from sample weights less than 10 g are excluded, except where determined by instrumental neutron activation analyses.

- (3) Au values less than the detection limit (<1 ppb) for 10 g samples are set to 0.5 ppb.

On the value map, repeat analysis values, where determined (not field duplicates), are placed in brackets following the initial value determination. All values determined on a sample less than 10 g are denoted by an asterisk. Actual sample weight used can be determined from the text. Following are possible variations in data presentation on a value map:

*	No data
+ 27	Single analysis, 10 g sample weight
+ 27*	single analysis, <10 g sample weight
+ 27 (14)	Repeat analysis, both samples 10 g
+ 27 (14*)	Repeat analysis, first sample 10 g, repeat <10 g
+ <1	Single analysis, 10 g sample, less than detection limit of 1 ppb

In summary, geochemical follow-up investigations for Au should be based on a careful consideration of all geological and geochemical information, and especially a careful appraisal of gold geochemical data and its variability. In some instances, prospective follow-up areas may be indirectly identified by pathfinder element associations in favourable geology, although a complementary Au response due to natural variability may be lacking. Once an anomalous area has been identified, field investigations should be designed to include detailed geochemical follow-up surveys and collection of large representative samples. Subsequent repeat subsample analyses will increase the reliability of results and permit a better understanding of natural variability which can then be used to improve sampling methodology and interpretation.

LAKE SEDIMENT DATA LIST LEGEND AND DIGITAL FIELD RECORD FORMAT

Table 2 lists both the field and map information which is recorded at each sample site and is listed in the accompanying data listings, and the digital record format for the tape or diskette version of the open file. For the digital record A = alpha; X = numeric, unless indicated otherwise.

REFERENCES

- Aslin, G.E.M. (1976) The determination of arsenic and antimony in geological materials by flameless atomic absorption spectrophotometer; *Journal of Geochemical Exploration*, Vol. 6, pp. 321-330.
- Boulanger, A., Evans, D.J.R., and Raby, B.F. (1975) Uranium analysis by neutron activation delayed neutron counting; *Proceedings of the 7th Annual Symposium of Canadian Mineral Analysts*, Thunder Bay, Ontario, September 22 - 23, 1975.
- Clifton, H.E., Hunter, R.E., Swanson, F.J., and Phillips, R.L. (1969) Sample size and meaningful gold analysis; *U.S. Geological Survey Professional Paper 625-C*.
- Garrett, R.G. (1974) Field data acquisition methods for applied geochemical surveys at the Geological Survey of Canada: *Geol. Surv. Can. Paper 74-52*.
- Hall, G.E.M. (1979) A study of the stability of uranium in waters collected from various geological environments in Canada; *In Current Research, Part A, Geological Survey of Canada Paper 79-1A*, p. 361-365.
- Harris, J.F. (1982) Sampling and analytical requirements for effective use of geochemistry in exploration for gold; *In Levinson, A.A., Editor, Precious Metals in the Northern Cordillera*, proceedings of a symposium sponsored by the Association of Exploration Geochemists and the Cordilleran Section of the Geological Association of Canada, pp. 53-67.
- Jonasson, I.R., Lynch, J.J., and Trip, L.J. (1973) Field and laboratory methods used by the Geological Survey of Canada in geochemical surveys; No. 12, Mercury in Ores, Rocks, Soils, Sediments and Water, *Geological Survey of Canada Paper 73-21*.

TABLE 1. Summary of Analytical Data and Methods

Element	Detection level (1985)	Detection level (1988)	Method(s)
SEDIMENTS:			
Zn Zinc	2 ppm	100 ppm	AAS/INA
Cu Copper	2 ppm		AAS
Pb Lead	2 ppm		AAS
Ni Nickel	2 ppm	20 ppm	AAS/INA
Co Cobalt	2 ppm	5 ppm	AAS/INA
Ag Silver	0.2 ppm	2 ppm	AAS/INA
Mn Manganese	5 ppm		AAS
As Arsenic	1 ppb	0.5 ppm	AAS/INA
Mo Molybdenum	2 ppm	1 ppm	AAS/INA
Fe Iron	0.02 pct	0.2 pct	AAS/INA
Hg Mercury	10 ppb		AAS
LOI Loss-on-ignition	1.0 pct		GRAV
U Uranium	0.5 ppm	0.2 ppm	NADNC/INA
V Vanadium	5 ppm		AAS
Cd Cadmium	0.2 ppm	5 ppm	AAS/INA
Sb Antimony	0.2 ppm	0.1 ppm	AAS/INA
Na Sodium		0.02 pct	INA
Sc Scandium		0.2 ppm	INA
Cr Chromium		20 ppm	INA
Se Selenium		5 ppm	INA
Br Bromine		0.5 ppm	INA
Rb Rubidium		5 ppm	INA
Zr Zirconium		200 ppm	INA
Sn Tin		100 ppm	INA
Te Tellurium		10 ppm	INA

TABLE 1 – Continued

Element	Detection level (1985)	Detection level (1988)	Method(s)
Cs Cesium		0.5 ppm	INA
Ba Barium		50 ppm	INA
La Lanthanum		2 ppm	INA
Ce Cerium		5 ppm	INA
Sm Samarium		0.05 ppm	INA
Eu Europium		1 ppm	INA
Tb Terbium		0.5 ppm	INA
Yb Ytterbium		2 ppm	INA
Lu Lutetium		0.2 ppm	INA
Hf Hafnium		1 ppm	INA
Ta Tantalum		0.5 ppm	INA
W Tungsten		1 ppm	INA
Ir Iridium		50 ppb	INA
Au Gold		2 ppb	INA
Th Thorium		0.2 ppm	INA
WATERS:			
F Fluoride	20 ppb		ISE
pH			GCM
U Uranium	0.05 ppb		LIF
wt Test weight		± 0.01 g	GRAV

AAS – Atomic absorption spectrometry
 INA – Instrumental Neutron Activation Analyses
 GRAV – Gravimetry
 ISE – Ion selective electrode
 GCM – Glass Calomel electrode and pH meter
 LIF – Laser-induced fluorescence
 NADNC – Neutron Activation delayed neutron counting

TABLE 2. DATA LIST AND DIGITAL FORMAT LEGEND
Record 1 – Field Data

FIELD RECORD	DEFINITION	TEXT CODE	DIGITAL RECORD COLUMN AND CODE
MAP	National topographic system (NTS): lettered quadrangle (1:250,000 scale) or (1:50,000 scale). Part of sample number.		1 – 6 "XXXAXX"
SAMPLE ID	Remainder of sample number: Year Field crew Sample sequence number	19XX 1, 3, 5, 7 001 – 999	7 – 12 "XX" " " X " " " XXX "
UTM COORDINATES	Universal Transverse Mercator (UTM) Coordinate system; digitized sample location coordinates.		
ZN	Zone 7 to 22		13 – 14 "XX"
EASTING	UTM Easting in metres		15 – 20 "XXXXXX"
NORTHING	UTM Northing in metres		21 – 27 "XXXXXXX"
ROCK TYPE	Major rock type of lake catchment area: Precambrian Wollaston Domain Granite pegmatite Granite and alaskite Biotite granodiorite Quartz muscovite schist Calc-silicate gneiss Meta-arkosic gneiss Impure meta-quartzite Pelitic and psammopelitic gneiss Graphic pelitic gneiss Mixed metasediments Metaquartzite Meta-arkose	WPEG WG WGDB WSH WCN WRN WRQ WPSN WPF WS WQ WR	"WPEG" "WG" "WGDB" "WSH" "WCN" "WRN" "WRQ" "WPSN" "WPF" "WS" "WQ" "WR"

TABLE 2 – Continued

FIELD RECORD	DEFINITION	TEXT CODE	DIGITAL RECORD COLUMN AND CODE
ROCK TYPE (continued)	Amphibolite Felsic granitoid gneiss Biotite-hornblende gneiss Diabase, gabbro Fluvial sandstone Conglomerate Cataclasite Rottenstone Domain Megacrystic granitoids Sheared granitoids Monzogranite Quartz monzodiorite Tonalite Amphibolite Pelitic gneiss Peter Lake Domain Mylonite Felsic gneiss Hornblende-biotite gneiss Mafic gneiss Granitic dykes Felsic granitoid Megacrystic granitoid Sheared PGP Mafic granitoids Layered metagabbro Quartz-feldspathic gneiss Slate, biotite schist La Ronge Domain Granodiorite Quartz monzodiorite Unknown	WV WFN WFB DD MFC MFB X RGP RGPX RGM RBD RGT RMG RNG PX PGN PN PBN PBNG PG PGP PGPX PBG PBA PQF PSL LGD LGM UKNN	"WV" "WFN" "WFB" "DD" "MFC" "MFB" "X" "RGP" "RGPX" "RGM" "RBD" "RGT" "RMG" "RNG" "PX" "PGN" "PN" "PBN" "PBNG" "PG" "PGP" "PGPX" "PBG" "PBA" "PQF" "PSL" "LGD" "LGM" "UKNN"
LAKE AREA	The area of the water body sampled: Pond ½ to 1 sq km 1 to 5 sq km greater than 5 sq km	POND .25 – 1 1 – 5 >5	32 – 35 "1 " 1 " 1 " 1

TABLE 2 – Continued

FIELD RECORD	DEFINITION	TEXT CODE	DIGITAL RECORD COLUMN AND CODE
LAKE DEP	Sample depth from surface of water body to lake bottom in metres	1 - 999	36 - 38 "XXX"
RS	Replicate status; the relationship of the sample to others within the analytical block of 20: Routine regional sample First of field duplicate Second of field duplicate	00 10 20	"00" "10" "20"
RLF	Relief of the lake catchment basin: Low Medium High	Lw Md Hi	41 - 43 "1" " 1 " " 1 "
CNT	Contamination; human or natural: None Work Camp Fuel Gossan	Wo Ca Fu Go	48 - 51 " " " 1 " " 1 " " 1 "
COLR	Sediment sample colour; up to two colours may be selected: Tan Yellow Green Grey Brown Black	Tn Yl Gn Gy Br Bk	52 - 57 " 1 " " 1 " " 1 " " 1 " " 1 "
SUSP	Suspended matter in water: None Heavy Light	Hvy Lgt	58 - 59 " 1 " " 1 "
AGE	Stratigraphic age of dominant rock type in catchment basin: Proterozoic	04	"04"

Record 2 – Neutron Activation Analytical Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
Na	Sodium in lake sediments	pct	0.02	16 - 21
Sc	Scandium in lake sediments	ppm	0.2	22 - 27
Cr	Chromium in lake sediments	ppm	20	28 - 33
Fe	Iron in lake sediments	pct	0.2	34 - 39
Co	Cobalt in lake sediments	ppm	5	40 - 45
Ni	Nickel in lake sediments	ppm	20	46 - 51
Zn*	Zinc in lake sediments	ppm	100,	52 - 57
As	Arsenic in lake sediments	ppm	0.5	58 - 63
Se*	Selenium in lake sediments	ppm	5	64 - 69
Br	Bromine in lake sediments	ppm	0.5	70 - 75

Record 3 – Neutron Activation Analytical Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
Rb	Rubidium in lake sediments	ppm	5	16 - 21
Zr*	Zirconium in lake sediments	ppm	200	22 - 27
Mo	Molybdenum in lake sediments	ppm	1	28 - 33
Ag*	Silver in lake sediments	ppm	2	34 - 39
Cd*	Cadmium in lake sediments	ppm	5	40 - 45
Sn*	Tin in lake sediments	ppm	100	46 - 51
Sb	Antimony in lake sediments	ppm	0.1	52 - 57
Te*	Tellurium in lake sediments	ppm	10	58 - 63
Cs	Cesium in lake sediments	ppm	0.5	64 - 69
Ba	Barium in lake sediments	ppm	10	70 - 75

Record 4 – Neutron Activation Analytical Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
La	Lanthanum in lake sediments	ppm	2	16 – 21
Ce	Cerium in lake sediments	ppm	5	22 – 27
Sm	Samarium in lake sediments	ppm	0.05	28 – 33
Eu	Europium in lake sediments	ppm	1	34 – 39
Tb	Terbium in lake sediments	ppm	0.5	40 – 45
Yb	Ytterbium in lake sediments	ppm	2	46 – 51
Lu	Lutetium in lake sediments	ppm	0.2	52 – 57
Hf	Hafnium in lake sediments	ppm	1	58 – 63
Ta	Tantalum in lake sediments	ppm	0.5	64 – 69
W	Tungsten in lake sediments	ppm	1	70 – 75

Record 6 – Atomic Absorption Spectrometry and other Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
Zn – SEDS	Zinc in lake sediments	ppm	2	21 – 25
Cu – SEDS	Copper in lake sediments	ppm	2	26 – 30
Pb – SEDS	Lead in lake sediments	ppm	2	31 – 35
Ni – SEDS	Nickel in lake sediments	ppm	2	36 – 40
Co – SEDS	Cobalt in lake sediments	ppm	2	41 – 45
Ag – SEDS	Silver in lake sediments	ppm	0.2	46 – 50
Mn – SEDS	Manganese in lake sediments	ppm	5	51 – 55
As – SEDS	Arsenic in lake sediments	ppm	1	56 – 60
Mo – SEDS	Molybdenum in lake sediments	ppm	2	61 – 65
Fe – SEDS	Iron in lake sediments	pct	0.02	66 – 70
Hg – SEDS	Mercury in lake sediments	ppb	10	71 – 75
LOI – SEDS	Loss-on-ignition	pct	1	76 – 80

Record 5 – Neutron Activation Analytical Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
Ir*	Iridium in lake sediments	ppb	50	16 – 21
Au	Gold in lake sediments	ppb	2	22 – 27
Th	Thorium in lake sediments	ppm	0.2	28 – 33
U	Uranium in lake sediments	ppm	0.2	34 – 39
Wt	Sample weight	gram		40 – 45

Record 7 – Atomic Absorption Spectrometry and other Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
U – SEDS	Uranium in lake sediments	ppm	0.5	21 – 25
V – SEDS	Vanadium in lake sediments	ppm	5	31 – 35
Cd – SEDS	Cadmium in lake sediments	ppm	0.2	36 – 40
Sb – SEDS	Antimony in lake sediments	ppm	0.2	51 – 55

* Data not included in Open File release because of inadequate detection limit and/or precision

Record 8 – Atomic Absorption Spectrometry and Other Data

FIELD RECORD	DEFINITION	UNITS	DETECTION LEVEL	DIGITAL RECORD COLUMN AND CODE
F – WATERS	Fluoride in lake waters	ppb	20	26 – 30
pH – WATERS	pH of lake waters			31 – 35
U – WATERS	Uranium in lake waters	ppb	0.05	36 – 40

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Map	ID	ZN	Field Data							Sample Media: Sediments															Waters							
			UTM			Rock		Lake		Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep	RS				Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppm	ppb	ppb	0.05	
			Detection Limit:			2	2	2	2				ppm	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	1.0	0.5	5	0.2	0.2	20	pH	0.05	
			25-1	1	00	Lw	-	Br	Lgt	150	5	<	3	6	<	575	5.0	2	7.10	100	64.6	1.1	15	.2	<	260	5.7	<				
64E	841002	13	564680	6349341	PG	04	.25-1	1	00	Lw	-	Br	-	79	7	<	10	3	<	135	<	2	.52	50	43.8	1.9	20	.6	<	150	5.6	<
64E	841003	13	569028	6348533	PG	04	.25-1	1	00	Lw	-	Br	-	76	4	<	6	5	<	180	<	2	2.59	25	14.2	2.7	25	.2	<	180	6.4	<
64E	841004	13	570628	6346030	PG	04	.25-1	1	00	Lw	-	Br	-	150	7	<	10	7	.2	220	<	4	3.91	50	39.4	4.6	35	<	<	190	6.4	<
64E	841005	13	572219	6347346	PBG	04	.25-1	1	00	Lw	-	Br	-	91	12	<	13	8	<	390	<	2	1.99	78	46.2	7.0	25	.2	<	150	5.8	0.06
64E	841006	13	576142	6346466	PG	04	.25-1	3	10	Lw	-	Br	-	100	7	<	11	7	<	330	<	2	2.06	78	46.2	6.4	30	.2	<	150	5.8	0.07
64E	841007	13	576142	6346466	PG	04	.25-1	3	20	Lw	-	Br	-	76	13	<	8	5	.2	340	<	2	.92	64	62.8	5.1	20	.4	<	110	6.1	<
64E	841008	13	573920	6344571	PG	04	.25-1	1	00	Lw	-	Br	-	80	15	<	9	5	<	345	<	2	1.17	99	51.6	2.0	15	.6	<	110	6.1	<
64E	841009	13	571608	6341765	PG	04	pond	2	00	Lw	-	Br	Lgt	80	12	<	9	8	<	260	1.0	2	2.84	34	39.6	4.4	20	.4	<	160	6.4	0.05
64E	841010	13	566494	6342678	PG	04	>5	1	00	Lw	-	Br	-	92	13	<	11	8	<	415	<	2	2.46	74	27.0	4.7	20	.4	<	150	6.6	<
64E	841011	13	561685	6334755	PBG	04	.25-1	2	00	Lw	-	Br	-	70	8	<	9	10	<	1160	2.0	<	6.30	47	16.8	5.7	30	<	<	48	6.5	<
64E	841012	13	566013	6401198	WPSN	04	>5	8	00	Md	-	Gn	-	48	8	<	11	6	.2	185	<	<	1.12	34	23.2	3.8	20	.2	<	98	6.2	0.05
64E	841013	13	566893	6396506	WPSN	04	.25-1	1	00	Md	-	Br	-	53	8	<	9	6	.2	205	<	<	1.47	50	29.4	3.1	30	<	<	84	6.3	0.1
64E	841014	13	567991	6393992	WPSN	04	1-5	3	00	Lw	-	Br	-	110	11	<	13	9	<	250	1.0	2	.89	41	47.4	5.7	30	.4	<	98	6.3	0.05
64E	841017	13	567204	6388618	WRN	04	.25-1	2	00	Lw	-	Br	-	97	9	<	11	7	.2	260	<	2	.77	33	62.0	2.5	25	.4	<	90	6.4	<
64E	841018	13	565139	6383529	WRN	04	.25-1	17	00	Md	-	Br	-	80	16	<	10	4	<	310	<	2	1.43	75	49.4	9.3	20	.4	<	84	6.3	0.1
64E	841019	13	566755	6380237	WRN	04	.25-1	2	00	Md	-	Gn	-	65	10	<	9	4	<	55	<	<	.25	48	40.6	5.8	5	.6	<	88	6.3	0.05
64E	841020	13	567280	6376097	WRN	04	1-5	4	00	Lw	-	Br	-	82	13	<	8	4	<	205	<	2	1.44	48	58.8	7.8	10	.4	<	120	6.5	<
64E	841022	13	566347	6373351	WFN	04	1-5	6	00	Lw	-	Br	-	110	13	<	11	8	.6	345	<	2	2.42	64	38.2	6.2	20	.6	<	110	6.2	<
64E	841023	13	566022	6369467	WPSN	04	.25-1	3	00	Md	-	Br	-	70	8	<	8	5	<	200	<	<	2.96	56	39.6	2.2	25	.2	<	110	6.0	<
64E	841024	13	567540	6366606	WS	04	.25-1	2	00	Md	-	Br	-	50	8	<	9	4	.2	90	<	<	.39	48	39.0	2.4	10	.4	<	170	5.9	<
64E	841025	13	566025	6361401	PG	04	.25-1	9	10	Md	-	Gn	-	180	23	<	7	7	<	1530	11.0	18	18.8	112	33.0	17.9	80	<	<	210	6.5	0.06
64E	841026	13	566025	6361401	PG	04	.25-1	9	20	Md	-	Gn	-	170	22	<	6	6	.2	1380	11.0	20	18.4	104	33.4	17.3	75	<	<	210	6.5	0.05
64E	841027	13	563823	6357148	PGN	04	1-5	15	00	Lw	-	Gn	-	69	10	4	7	4	.2	330	3.0	<	2.63	24	23.0	4.0	30	.2	<	280	6.6	<
64E	841029	13	566336	6357810	PG	04	.25-1	4	00	Lw	-	Bk	-	30	5	<	2	<	<	150	2.0	<	4.38	28	13.6	3.7	40	<	<	230	6.7	<
64E	841030	13	569471	6361179	PGN	04	1-5	8	00	Lw	-	Gy	-	55	5	<	5	4	<	1100	1.0	<	3.35	21	3.2	3.1	25	.2	<	200	6.6	<
64E	841031	13	570599	6364348	PG	04	.25-1	2	00	Md	-	Gn	Lgt	96	8	<	4	6	<	250	7.0	4	6.38	49	36.4	3.0	75	.2	<	180	6.3	<
64E	841032	13	571313	6368545	WS	04	1-5	4	00	Md	-	Gn	-	220	13	<	9	12	.2	960	15.0	2	6.34	70	29.2	4.1	30	.4	<	110	6.5	<
64E	841033	13	569430	6372823	WFN	04	1-5	11	00	Md	-	Gn	-	170	18	<	8	11	<	1110	2.0	4	11.9	91	38.0	10.4	75	.2	<	130	6.6	<
64E	841034	13	570327	6377100	WRN	04	.25-1	2	00	Lw	-	Br	-	100	6	3	6	4	.4	230	<	<	1.04	49	38.8	2.2	10	.4	<	180	5.9	<
64E	841035	13	568515	6379351	WRN	04	1-5	10	00	Lw	-	Gn	-	76	10	<	6	4	.2	240	1.0	<	1.54	63	25.4	10.4	20	.4	<	110	6.6	0.1
64E	841036	13	569128	6383508	WRN	04	.25-1	2	00	Lw	-	Gn	-	65	7	<	5	3	<	125	<	<	.87	49	43.0	3.0	20	.2	<	150	6.2	<
64E	841037	13	569107	6385917	WPSN	04	.25-1	1	00	Lw	-	Br	-	70	10	<	11	6	<	475	<	<	1.13	67	41.6	2.4	10	.2	<	98	5.6	<
64E	841038	13	571501	6390460	WRN	04	1-5	6	00	Md	-	Br	-	74	10	<	8	3	<	340	<	<	2.05	60	28.0	4.2	25	<	<	110	6.1	<
64E	841039	13	570440	6394659	WG	04	.25-1	2	00	Md	-	Br	-	65	11	<	14	4	<	235	<	<	1.25	34	29.2	4.8	15	.2	<	130	6.4	0.05
64E	841040	13	571083	6398905	WPSN	04	.25-1	2	00	Md	-	Gn	-	95	16	3	15	4	<	230	1.0	<	.80	34	59.6	25.7	20	.4	<	280	5.9	0.08
64E	84																															

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																											
Element:	Units:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U		
Detection Limit:		0.02	0.2	ppm	20	0.2	ppm	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2
Map	ID	RS																											
64E	841002	00	0.09	1.6	<	9.1	12	<	10.0	45.0	<	3	0.3	<	120	19	27	2.20	<	<	<	0.2	<	<	<	4	3.0	1.0	
64E	841003	00	0.84	3.1	<	0.7	<	<	1.8	34.0	32	2	0.1	1.0	250	43	72	4.80	<	0.6	<	0.4	2	<	<	<	6.9	2.0	
64E	841004	00	2.05	6.3	20	3.4	8	<	1.5	8.9	93	2	0.3	2.6	650	61	100	5.90	<	0.9	3	0.5	7	1.2	<	<	13.0	2.5	
64E	841005	00	0.27	5.4	28	5.1	9	<	3.1	26.0	19	5	0.2	1.0	140	130	200	13.00	3	1.5	4	0.8	2	<	<	3	13.0	4.3	
64E	841006	10	0.24	4.3	23	3.0	10	<	2.2	50.0	<	3	0.1	0.9	120	110	182	12.00	1	1.8	4	0.9	1	<	<	<	11.0	6.1	
64E	841007	20	0.21	4.4	29	3.0	10	<	2.3	52.0	<	4	0.1	<	98	110	195	12.00	2	1.8	4	0.8	2	<	<	<	12.0	5.7	
64E	841008	00	0.12	3.3	28	1.5	10	<	2.6	45.0	<	4	0.1	0.7	110	69	117	7.30	<	1.1	3	0.7	<	<	<	<	7.5	5.1	
64E	841009	00	0.19	2.6	22	1.8	8	<	1.6	32.0	7	3	0.1	<	140	42	73	4.20	<	0.5	<	0.4	1	<	<	10	6.0	2.0	
64E	841010	00	1.20	4.6	<	4.4	11	<	3.8	19.0	45	5	0.2	1.5	360	64	100	6.30	2	1.0	3	0.6	5	<	<	<	10.0	4.3	
64E	841011	00	1.40	6.3	46	3.7	12	<	2.1	22.0	48	3	0.1	0.7	400	82	130	8.70	<	1.3	4	0.6	6	0.7	<	<	12.0	3.9	
64E	841012	00	1.30	6.8	41	8.6	13	<	3.6	13.0	72	3	0.2	2.3	500	40	66	4.50	<	0.9	3	0.5	5	0.5	1	2	12.0	5.4	
64E	841013	00	1.10	4.6	35	1.6	9	<	1.8	16.0	42	3	0.1	1.2	370	35	54	3.90	<	0.7	2	0.4	4	0.6	1	2	10.0	3.7	
64E	841014	00	0.76	4.0	32	2.1	7	<	2.3	23.0	29	3	0.2	1.1	260	39	62	4.50	<	0.9	2	0.5	4	<	<	<	9.5	2.5	
64E	841016	00	0.64	4.7	35	1.4	10	<	3.5	31.0	27	3	0.2	<	220	40	67	4.30	1	0.9	2	0.5	2	<	<	<	18	10.0	
64E	841017	00	0.30	2.7	21	1.3	10	<	3.5	29.0	11	4	0.2	<	190	21	40	2.30	<	<	<	0.3	2	<	<	5	5.4	2.5	
64E	841018	00	0.23	4.3	26	1.9	7	<	2.8	41.0	<	3	0.3	0.7	120	73	119	7.60	2	1.0	3	0.8	2	<	<	<	10.0	11.0	
64E	841019	00	0.10	1.9	<	0.4	6	<	1.7	20.0	<	3	0.3	<	91	36	52	4.30	<	0.6	<	0.4	<	<	<	<	6.2	6.1	
64E	841020	00	0.15	2.5	25	1.9	5	<	2.6	31.0	<	6	0.2	<	80	43	60	4.50	<	0.8	<	0.5	<	<	1	4	7.1	8.5	
64E	841022	00	0.92	4.9	33	3.6	10	25	2.8	32.0	45	5	0.2	1.1	250	67	105	6.60	<	1.2	3	0.7	3	<	<	<	12.0	6.5	
64E	841023	00	0.17	3.1	<	3.8	9	<	2.0	33.0	6	5	0.1	0.6	<	42	74	4.30	<	0.6	3	0.4	<	<	<	7.4	2.2		
64E	841024	00	0.17	2.2	21	0.7	5	<	3.1	23.0	15	4	0.1	<	110	29	48	3.30	<	0.6	<	0.3	<	<	<	2	6.6	2.4	
64E	841025	10	0.48	12.0	<	26.8	13	<	18.0	40.0	21	17	0.2	1.1	290	233	331	22.30	3	3.5	11	2.5	2	<	4	7	29.9	16.0	
64E	841026	20	0.43	10.0	50	25.1	14	<	16.0	40.0	20	20	0.2	1.3	190	222	341	22.00	4	3.6	11	2.1	2	<	3	<	30.0	15.0	
64E	841027	00	1.70	7.0	37	4.0	9	<	5.2	27.0	77	4	0.4	2.0	490	76	126	7.40	2	1.1	4	0.9	7	0.7	2	<	20.0	4.2	
64E	841029	00	2.00	4.4	<	6.0	<	<	3.1	11.0	81	2	0.2	1.3	510	67	94	7.10	1	1.2	3	0.6	5	0.6	<	<	12.0	4.2	
64E	841030	00	2.23	5.9	<	4.5	<	<	1.9	4.8	110	1	0.2	2.3	720	50	77	5.30	1	0.8	3	0.5	7	1.1	<	<	13.0	3.4	
64E	841031	00	0.39	4.7	34	7.8	18	<	21.0	30.0	14	7	0.2	1.0	220	88	146	10.00	<	1.3	4	0.9	2	<	3	9	14.0	4.8	
64E	841032	00	0.61	9.5	69	18.0	17	<	4.4	43.0	25	7	0.2	1.8	380	200	303	19.00	4	2.8	8	1.6	3	<	4	<	26.4	10.0	
64E	841033	00	0.65	10.0	69	18.0	18	<	4.6	43.0	28	6	0.2	1.5	420	200	307	19.00	2	2.9	8	1.6	3	0.6	4	<	27.0	10.0	
64E	841034	00	0.24	2.0	<	1.6	8	<	2.4	28.0	8	3	0.2	<	140	24	38	2.70	<	<	0.3	<	<	3	5.5	2.4			
64E	841035	00	0.44	3.3	29	2.1	7	<	2.2	21.0	17	4	0.2	<	170	53	91	5.80	<	0.9	3	0.6	1	<	2	13	8.5	10.0	
64E	841036	00	0.24	2.0	20	1.3	6	<	2.6	19.0	8	3	0.2	0.5	130	20	30	2.30	<	0.5	<	0.3	<	<	1	4	4.9	2.6	
64E	841037	00	0.17	2.1	<	1.4	10	<	2.3	26.0	9	2	0.2	<	110	30	54	3.50	<	0.6	<	0.3	<	<	4	<	5.3	2.2	
64E	841038	00	0.91	4.5	26	2.7	7	<	2.4	30.0	42	2	0.2	1.5	300	45	68	5.20	1	0.9	2	0.5	3	<	2	<	12.0	3.8	
64E	841039	00	1.00	4.6	21	1.8	9	<	2.8	22.0	48	3	0.2	1.3	360	47	70	6.10	1	0.9	2	0.5	3	0.5	<	<	14.0	5.6	
64E	841040	00	0.45	5.2	40	1.4	11	<	3.3	39.0	22	2	0.2	1.1	200	39	61	7.90	<	2.2	8	1.8	3	0.5	<	9	13.0	26.8	
64E	841042	00	1.50	4.2	22	2.7	8	<	2.4	14.0	63	4	0.2	1.4	430	42	68	4.60	<	0.7	2	0.5	7	0.5	2	<	12.0	3.5	
64E	841043	00	1.40	4.5	30	1.6	6	<	2.2	18.0	68	3	0.2	1.6	480	35	54	3.90	<	0.8	2	0.4	4	<	2	<	11.0	6.0	
64E	841044	10	2.00	5.6	36	1.9	8	<	1.9	38.0	84	2	0.2	1.9	560	38	61	4.20	<	0.8	2	0.4	6	0.9	1	8	12.0	5.0	
64E	841045	20	2.00	5.0	39	2.1	9	<	1.6	19.0	76	2	0.1	2.1	490	38	62	4.10	<	0.8	2	0.4	6	<	1	3	12.0	4.5	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments													Waters							
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep							2	ppm	ppm	ppm	ppm	ppm	5	ppm	ppm	pct	ppb	10	1.0	ppm	ppm	5	ppm	ppm	20
64E	841046	13	588863	6406222	WRN	04	.25-1	5	00	Md	-	Br	-	55	8	<	3	3	<	115	<	2	2.68	34	13.8	9.8	25	<	<	130	6.5	0.06	
64E	841047	13	591081	6406006	WG	04	.25-1	2	00	Md	-	Gn	-	70	6	<	6	2	<	130	<	<	.92	41	39.4	4.4	25	<	<	170	5.8	<	
64E	841048	13	607445	6406219	WFN	04	.25-1	2	00	Lw	-	Br	Lgt	78	10	<	14	8	<	215	1.0	2	1.43	62	40.4	9.3	25	.2	<	120	5.2	0.12	
64E	841049	13	610995	6406241	PGPX	04	.25-1	2	00	Md	-	Br	-	71	8	2	9	3	<	125	<	2	1.00	76	35.4	6.0	15	.4	<	120	5.6	0.13	
64E	841050	13	612523	6406482	PGPX	04	>5	16	00	Md	-	Br	-	120	11	<	7	8	<	680	2.0	4	4.57	97	29.2	6.3	30	<	<	110	6.2	0.06	
64E	841051	13	611691	6410673	WFN	04	.25-1	3	00	Md	-	Br	-	88	9	<	5	4	<	270	<	<	1.14	55	63.6	2.0	15	.2	<	80	5.6	<	
64E	841052	13	609341	6409519	WFN	04	.25-1	21	00	Md	-	Br	-	160	11	<	6	24	<	530	2.0	12	14.4	76	36.6	8.9	35	<	<	120	6.1	0.05	
64E	841054	13	609676	6412926	WFN	04	.25-1	3	00	Md	-	Br	-	110	13	<	11	10	.2	105	<	2	.58	48	53.0	3.6	30	.4	.2	130	6.0	<	
64E	841055	13	612574	6416037	WFN	04	1-5	7	00	Md	-	Gn	-	110	11	<	8	9	<	835	1.0	6	4.04	69	23.6	6.8	35	<	<	110	6.3	0.05	
64E	841056	13	612569	6419933	WFN	04	.25-1	2	00	Md	-	Br	-	45	6	<	7	5	<	170	<	4	.50	41	36.0	1.9	20	.2	<	140	6.4	<	
64E	841057	13	618470	6418731	WPSN	04	.25-1	3	00	Lw	-	Br	-	120	12	<	7	9	<	245	<	6	3.22	69	50.2	5.2	35	.4	<	92	5.3	<	
64E	841058	13	620010	6418356	WPSN	04	1-5	2	00	Md	-	Br	-	140	15	<	10	9	<	230	<	4	3.28	48	39.2	17.2	20	1.0	<	98	5.8	0.05	
64E	841059	13	624050	6419353	WPSN	04	.25-1	5	00	Md	-	Br	-	110	8	<	4	10	.2	380	<	6	5.05	62	31.2	3.3	15	.2	<	92	5.9	<	
64E	841060	13	625491	6416866	WPSN	04	1-5	13	00	Md	-	Br	-	85	10	3	10	15	<	1550	2.0	12	3.55	34	10.4	23.3	25	.2	<	180	6.2	0.15	
64E	841062	13	621490	6416860	WPSN	04	.25-1	11	10	Md	-	Gn	-	160	24	2	8	10	<	710	<	10	6.50	104	38.2	54.1	45	.4	<	100	6.1	0.26	
64E	841063	13	621490	6416860	WPSN	04	.25-1	11	20	Md	-	Gn	-	140	25	<	8	9	<	655	<	8	4.91	131	39.8	51.4	40	.6	<	110	6.1	0.27	
64E	841064	13	615787	6416331	WPSN	04	.25-1	4	00	Md	-	Gn	-	120	12	<	10	5	<	255	<	6	1.66	76	53.0	5.4	25	.4	<	110	5.6	<	
64E	841065	13	613135	6413995	WFN	04	.25-1	8	00	Md	-	Gn	-	240	13	<	12	33	<	3600	<	8	11.3	104	28.6	8.8	35	.4	<	110	6.1	0.05	
64E	841066	13	616553	6411598	PGPX	04	>5	8	00	Md	-	Gn	-	140	10	<	11	20	<	950	1.0	6	7.19	69	17.4	17.6	35	.2	<	130	6.1	0.21	
64E	841067	13	621484	6413218	PGPX	04	1-5	4	00	Md	-	Gn	-	100	11	<	5	8	<	375	1.0	8	6.24	62	36.4	24.1	25	<	<	170	5.8	0.15	
64E	841068	13	620914	6409793	LKNN	04	pond	2	00	Md	-	Br	-	90	5	<	4	5	<	125	<	2	2.12	55	32.2	2.9	25	.4	<	200	6.1	<	
64E	841069	13	618187	6409343	WPSN	04	1-5	5	00	Md	-	Br	-	130	12	<	4	7	.2	730	<	8	9.60	62	37.0	19.6	30	.2	<	350	6.0	0.1	
64E	841070	13	616903	6406666	UKNN	04	.25-1	4	00	Lw	-	Br	-	92	8	<	4	6	.2	180	<	2	1.16	48	62.4	4.7	15	.4	<	130	5.5	<	
64E	841071	13	620650	6405656	UKNN	04	1-5	5	00	Md	-	Br	-	140	35	<	13	12	<	180	<	12	6.44	83	45.4	21.6	30	.4	<	230	6.3	0.05	
64E	841072	13	624410	6404671	UKNN	04	.25-1	7	00	Md	-	Br	-	110	21	<	5	9	<	405	<	6	8.24	76	42.4	19.2	60	.4	<	360	6.3	0.08	
64E	841073	13	626263	6404887	UKNN	04	.25-1	5	00	Lw	-	Gn	-	150	18	<	4	6	.8	445	<	12	9.40	99	56.6	12.1	35	<	<	420	6.0	<	
64E	841074	13	623346	6409677	UKNN	04	pond	2	00	Md	-	Br	-	110	9	<	6	3	<	95	<	6	5.88	50	41.4	9.2	50	<	<	420	6.1	0.05	
64E	841075	13	624529	6412975	WPSN	04	.25-1	3	00	Md	-	Br	-	110	14	<	9	6	<	430	<	8	3.81	50	33.4	10.4	25	<	<	290	6.2	0.05	
64E	841076	13	627420	6409532	UKNN	04	pond	5	00	Md	-	Br	-	130	9	<	9	7	.2	70	<	6	1.08	36	50.2	2.5	25	.4	<	140	5.7	<	
64E	841077	13	628800	6411880	PX	04	1-5	5	00	Lw	-	Gn	-	120	10	<	2	5	<	1080	<	12	17.1	57	51.0	3.8	40	<	<	170	6.0	<	
64E	841078	13	635906	6412559	PG	04	>5	10	00	Md	-	Br	-	89	8	<	5	8	<	3050	1.0	6	9.90	50	17.8	8.5	30	<	<	170	6.2	0.06	
64E	841079	13	634407	6415064	PG	04	.25-1	2	00	Lw	-	Br	-	89	15	2	14	6	<	105	<	<	.66	50	50.2	7.3	10	.2	<	270	5.9	0.06	
64E	841082	13	631793	6417655	WFN	04	.25-1	6	00	Hi	-	Br	-	90	15	4	9	5	<	295	<	4	1.38	50	21.2	61.8	15	<	<	740	5.9	0.7	
64E	841083	13	631374	6418937	WFN	04	.25-1	54	00	Hi	-	Br	-	58	9	2	9	5	<	585	1.0	2	2.29	21	5.4	22.6	20	<	<	210	6.5	0.3	
64E	841084	13	628132	6417167	PGPX	04	.25-1	9	10	Md	-	Br	-	180	11	<	11	26	<	13000	2.0	14	13.7	36	22.0	25.3	35	.2	<	240	6.0	0.11	
64E	841085	13	628132	6417167	PGPX	04	.25-1	9	20	Md	-	Br	-	170	14	<	9	24	.2	10500	2.0	14	14.0	64	26.2	28.1	40	<	<	240	6.1	0.1	
64E	841086	13	629048	642																													

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																												
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Mn ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb	Th ppm	U ppm			
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
	Map	ID	RS																										
64E	841046	00	1.70	4.4	23	3.5	7	<	1.7	15.0	71	4	0.2	1.2	400	85	115	9.00	2	1.3	4	0.9	3	0.7	<	<	13.0	10.0	
64E	841047	00	0.20	2.9	24	1.2	7	<	1.8	29.0	7	4	0.2	<	95	46	76	5.20	<	0.8	3	0.5	<	<	2	<	8.1	4.9	
64E	841048	00	0.52	3.0	23	1.9	13	<	2.2	23.0	23	4	0.2	0.8	230	31	53	3.60	<	0.7	<	0.5	2	<	<	2	7.5	8.5	
64E	841049	00	0.12	2.0	<	1.2	<	<	1.6	24.0	6	5	<	<	130	32	63	3.90	1	0.8	<	0.4	<	<	<	<	5.4	5.7	
64E	841050	00	0.70	5.4	24	5.6	10	<	2.8	32.0	42	6	0.2	2.3	260	58	110	6.20	1	1.1	4	0.6	3	<	2	<	13.0	6.0	
64E	841051	00	0.06	1.4	<	1.7	9	<	1.4	47.0	<	3	<	<	63	17	31	2.00	<	<	<	0.2	<	<	<	<	2.9	1.8	
64E	841052	00	0.45	4.8	<	22.2	34	<	3.7	58.0	19	14	0.2	1.4	350	79	141	8.60	2	1.6	6	1.0	2	<	<	<	13.0	9.0	
64E	841054	00	0.20	3.0	22	0.8	13	<	2.2	38.0	10	4	0.2	0.9	150	38	59	4.30	<	0.7	2	0.5	1	<	<	4	6.9	3.6	
64E	841055	00	1.00	5.5	34	5.0	12	<	2.0	25.0	53	6	<	1.7	350	52	93	6.00	<	1.1	3	0.7	4	<	3	3	14.0	6.6	
64E	841056	00	0.32	2.0	24	0.7	6	<	1.8	24.0	12	3	0.1	0.7	140	23	43	2.70	<	<	<	<	1	<	<	7	5.4	1.6	
64E	841057	00	0.17	2.7	25	4.0	11	<	1.9	30.0	8	5	0.2	0.6	120	42	76	5.20	<	1.0	3	0.6	<	<	<	<	7.2	4.9	
64E	841058	00	1.10	4.3	21	4.6	10	<	2.1	18.0	58	4	0.2	1.7	360	81	131	11.00	<	2.4	7	1.4	5	<	<	<	16.0	17.0	
64E	841059	00	0.22	2.7	<	6.1	15	<	2.0	27.0	11	8	<	1.0	140	27	52	3.10	<	0.6	<	0.3	<	<	<	<	6.5	3.8	
64E	841060	00	2.10	7.4	29	4.9	23	<	3.0	14.0	130	16	0.2	3.2	700	74	123	7.70	<	1.3	4	1.3	7	1.3	2	<	19.0	25.2	
64E	841062	10	0.36	6.5	32	8.6	13	<	2.2	42.0	17	12	0.1	0.8	190	84	170	10.00	2	1.8	6	2.4	1	<	2	<	16.0	54.6	
64E	841063	20	0.29	6.1	56	6.4	14	<	2.2	48.0	10	11	0.1	0.8	160	89	177	10.00	<	1.4	5	2.2	2	<	<	<	5	15.0	49.9
64E	841064	00	0.15	2.7	<	2.6	6	<	2.0	49.0	<	8	0.1	0.6	98	31	50	3.80	<	0.6	3	0.4	1	<	<	<	5.7	5.2	
64E	841065	00	0.73	6.3	32	16.0	43	<	2.5	22.0	35	10	0.2	1.1	440	76	150	8.30	<	1.3	5	1.0	3	0.5	2	3	15.0	8.7	
64E	841066	00	1.40	7.6	57	8.3	26	<	2.1	16.0	95	9	0.1	3.3	560	73	132	7.80	<	1.5	4	1.0	4	1.0	2	5	18.0	17.0	
64E	841067	00	0.15	3.3	24	8.4	9	<	2.2	30.0	9	10	0.1	0.6	100	58	113	7.10	<	1.3	5	1.2	<	<	<	<	10.0	24.7	
64E	841068	00	0.10	1.4	<	2.9	6	<	1.7	21.0	<	4	<	<	83	29	52	3.50	<	0.6	2	0.4	<	<	<	6	4.3	2.4	
64E	841069	00	0.11	3.9	30	12.0	11	<	2.5	28.0	11	12	0.1	<	100	73	128	8.10	<	1.5	7	1.6	<	<	<	<	13.0	18.0	
64E	841070	00	0.08	2.2	<	1.7	9	<	1.3	44.0	<	4	0.2	<	90	35	55	3.10	<	<	2	0.4	<	<	<	3	5.6	3.9	
64E	841071	00	0.28	4.6	35	8.1	13	27	2.6	28.0	11	14	0.2	1.0	97	120	185	11.00	2	1.6	6	1.5	1	<	<	<	15.0	21.1	
64E	841072	00	0.14	7.7	44	12.0	13	27	2.8	39.0	<	9	0.2	<	<	251	422	24.10	3	4.3	17	3.1	2	<	<	5	24.3	21.3	
64E	841073	00	0.21	4.6	<	12.0	8	<	3.2	34.0	8	13	0.2	1.3	160	100	179	12.00	2	1.9	10	1.8	1	<	<	<	11.0	11.0	
64E	841074	00	0.06	2.1	<	7.1	7	<	1.4	25.0	<	9	<	<	110	65	102	7.20	<	1.3	6	1.0	<	<	2	4	6.3	8.1	
64E	841075	00	0.25	3.8	<	4.4	10	<	1.5	26.0	25	11	0.2	0.9	160	59	101	6.30	<	1.1	4	0.8	1	<	<	3	10.0	11.0	
64E	841076	00	0.10	1.8	<	1.3	9	<	1.7	29.0	<	9	0.2	0.6	100	18	35	2.00	<	<	<	<	<	<	<	5	4.1	2.5	
64E	841077	00	0.37	3.8	<	20.9	11	<	3.3	41.0	23	16	0.1	1.3	140	63	101	7.00	1	1.3	4	0.8	3	<	1	<	11.0	4.4	
64E	841078	00	1.70	6.3	<	12.0	12	<	2.5	18.0	98	8	0.2	2.5	630	73	118	7.60	1	1.2	5	1.0	7	0.9	2	<	16.0	9.3	
64E	841079	00	0.09	2.7	25	0.9	10	30	1.8	28.0	<	3	0.1	<	140	78	136	10.00	<	1.4	6	1.1	<	<	<	8.7	6.9		
64E	841082	00	1.20	5.9	33	2.0	10	<	1.3	23.0	64	5	0.1	1.4	360	130	204	17.00	<	3.9	14	4.1	4	0.6	<	<	23.0	57.0	
64E	841083	00	2.06	7.2	32	3.4	11	<	1.6	13.0	150	3	0.2	3.0	780	73	125	7.50	<	1.1	3	1.2	8	1.1	2	3	19.0	21.7	
64E	841084	10	1.20	5.8	<	20.9	36	<	3.6	11.0	71	13	<	0.9	610	120	261	12.00	<	1.9	7	2.0	6	<	2	6	19.0	28.6	
64E	841085	20	1.00	6.5	20	20.7	30	26	3.2	17.0	64	14	0.1	1.8	570	140	286	14.00	2	2.2	8	2.0	5	<	3	5	21.3	28.3	
64E	841086	00	2.08	4.5	<	3.3	8	<	0.9	7.8	99	3	<	1.8	660	55	91	5.70	<	1.2	3	0.7	9	0.7	<	3	15.0	7.8	
64E	841087	00	1.30	6.9	38	17.0	20	<	4.5	37.0	76	26	0.2	2.3	960	92	153	9.30	2	1.5	5	1.5	5	0.7	2	<	17.0	18.0	
64E	841088	00	1.80	5.2	27	3.6	8	<	1.3	20.0	89	8	0.1	1.9	460	44	69	4.60	<	1.0	3	0.5	7	0.8	<	<	14.0	3.8	
64E	841089	00	0.89	4.7	28	5.4	12	<	1.9	22.0	39	9	0.1	0.9	250	54	95	5.90	<	1.0	3	0.9	4	<	<	<	13.0	18.0	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data, Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct 0.02	Sc ppm 0.2	Cr ppm 20	Fe pct 0.2	Co ppm 5	Ni ppm 20	As ppm 0.5	Br ppm 0.5	Rb ppm 5	Mo ppm 1	Sb ppm 0.1	Cs ppm 0.5	Ba ppm 50	La ppm 2	Ce ppm 5	Sm ppm 0.05	Eu ppm 1	Tb ppm 0.5	Yb ppm 2	Lu ppm 0.2	Hf ppm 1	Ta ppm 0.5	W ppm 1	Au ppb 2	Th ppm 0.2	U ppm 0.2		
	Map	ID	RS																									
64E	841090	00	0.85	6.8	45	7.5	11	<	2.9	43.0	49	9	0.1	1.6	360	68	106	7.40	<	1.3	5	1.0	4	0.5	1	<	14.0	15.0
64E	841091	00	0.18	2.7	31	3.2	9	<	2.1	28.0	9	4	<	0.6	100	28	50	3.40	<	<	<	0.4	1	<	<	6.1	5.3	
64E	841092	00	0.13	2.2	<	0.8	6	<	0.9	29.0	7	4	<	<	120	26	49	3.10	<	<	<	0.4	<	<	<	4	4.9	10.0
64E	841093	00	0.38	2.6	24	3.3	6	<	1.9	27.0	19	5	0.1	<	150	24	50	3.00	<	0.6	<	0.4	1	<	2	4	6.3	2.3
64E	841094	00	0.23	1.9	27	1.3	6	<	2.1	18.0	8	3	0.1	0.6	94	23	44	2.90	<	<	<	0.3	<	<	<	3	4.7	1.4
64E	841095	00	0.66	5.2	22	9.2	14	<	3.4	41.0	26	11	0.2	1.4	340	56	91	7.40	1	1.6	4	0.8	4	<	<	<	13.0	7.1
64E	841096	00	1.00	4.5	25	2.7	10	<	2.4	20.0	65	5	0.2	1.9	430	38	61	4.80	<	0.9	3	0.4	4	0.6	2	<	12.0	6.4
64E	841098	00	0.33	4.1	32	1.8	9	<	2.6	47.0	14	5	0.2	<	120	44	80	6.20	<	1.2	5	0.8	2	<	<	4	8.5	7.1
64E	841099	00	0.15	1.7	<	1.6	10	<	2.5	22.0	8	2	0.1	<	130	15	28	1.70	<	<	<	<	<	<	<	3.4	1.5	
64E	841100	00	0.12	1.4	<	2.1	8	<	1.4	20.0	<	6	0.2	<	94	26	44	3.10	<	<	<	0.3	<	<	4	3	4.0	3.3
64E	841103	00	0.36	2.5	27	1.9	11	21	1.9	28.0	21	3	0.1	0.7	160	27	46	3.40	<	0.5	<	0.4	2	<	1	3	6.7	1.9
64E	841104	00	0.25	1.8	<	0.5	<	<	1.0	19.0	11	2	0.1	0.7	150	21	32	2.30	<	0.5	<	0.2	1	<	2	2	4.6	1.7
64E	841105	00	0.50	10.0	56	26.2	18	<	4.4	47.0	43	13	0.2	2.0	320	120	193	14.00	2	2.4	8	1.7	4	<	<	<	22.5	13.0
64E	841106	10	0.24	2.4	25	1.3	<	<	1.0	22.0	12	5	0.1	<	130	31	53	4.30	1	0.9	3	0.5	1	<	<	<	5.3	7.3
64E	841107	20	0.25	2.6	24	1.6	5	<	0.8	21.0	12	4	<	<	110	31	61	4.40	<	0.7	3	0.5	1	<	<	<	5.9	6.8
64E	841108	00	0.62	5.0	<	4.4	12	<	3.0	33.0	37	8	0.1	1.1	260	110	178	12.00	<	2.1	7	1.8	3	<	1	8	19.0	35.1
64E	841109	00	2.65	7.0	37	2.4	11	<	2.1	7.8	140	3	0.2	2.5	820	59	93	6.20	1	1.1	3	0.8	8	0.9	2	<	16.0	12.0
64E	841110	00	0.38	5.9	58	20.4	12	<	3.2	35.0	22	11	0.2	0.8	190	120	198	10.00	<	1.8	8	1.7	3	<	<	5	16.0	15.0
64E	841111	00	1.20	8.5	41	19.0	13	<	2.8	23.0	73	12	0.2	3.0	400	110	171	10.00	2	1.7	8	1.5	5	0.6	<	5	21.4	17.0
64E	841112	00	0.65	4.3	37	3.1	7	<	1.7	21.0	21	7	0.1	1.6	250	70	106	8.70	1	1.6	6	1.3	3	<	<	<	14.0	16.0
64E	841113	00	0.77	5.8	31	13.0	18	22	2.9	31.0	49	7	0.2	1.1	340	83	150	8.50	1	1.5	6	1.0	3	0.6	<	<	15.0	11.0
64E	841114	00	1.90	5.7	40	5.4	14	<	1.5	11.0	110	5	0.1	2.4	690	65	103	7.20	2	1.3	4	0.7	7	0.9	2	<	17.0	6.6
64E	841115	00	0.15	4.9	<	3.0	8	<	2.5	75.0	<13	2	0.1	0.9	160	130	204	15.00	<	2.0	5	0.9	2	<	<	<	12.0	5.6
64E	841116	00	0.14	3.7	21	3.2	9	<	1.9	23.0	<	5	0.1	0.6	97	110	190	12.00	3	1.6	4	0.9	<	<	<	<	10.0	4.7
64E	841117	00	1.50	5.6	<	11.0	27	<	3.2	18.0	69	7	0.2	1.6	480	73	130	7.40	<	1.3	5	1.0	5	0.6	2	<	16.0	10.0
64E	841118	00	0.10	2.3	<	5.1	13	<	2.1	43.0	<	9	0.1	<	150	55	87	5.20	1	1.0	3	0.5	<	<	<	6.2	3.5	
64E	841119	00	1.20	4.8	<	5.3	7	<	2.4	23.0	64	4	0.2	1.5	360	51	82	5.50	1	1.0	3	0.7	4	0.7	1	<	13.0	6.6
64E	841120	00	2.28	3.7	<	3.4	5	<	1.4	4.9	100	2	0.1	1.6	660	35	58	3.50	<	0.5	<	0.4	6	0.6	<	3	10.0	3.1
64E	841122	00	0.08	2.8	<	1.5	7	<	1.6	37.0	<	4	0.1	<	120	70	128	7.50	<	1.2	4	0.7	<	<	<	8.5	5.1	
64E	841124	00	0.16	3.1	25	4.3	14	<	2.6	39.0	<	3	0.2	0.5	110	75	127	7.10	<	1.0	5	0.9	1	<	<	<	10.0	8.8
64E	841125	00	0.07	3.2	29	2.3	8	<	1.8	31.0	<	3	<	<	150	110	210	12.00	2	1.8	6	1.2	<	<	<	6	11.0	6.6
64E	841126	10	0.22	3.0	24	2.3	10	<	2.2	45.0	11	3	0.1	0.7	110	37	68	4.10	1	0.7	<	0.4	<	<	1	<	7.8	3.0
64E	841127	20	0.20	3.2	<	2.2	10	<	2.6	42.0	<	3	0.2	0.8	96	40	68	4.30	<	0.5	<	<	<	<	<	8.3	3.3	
64E	841128	00	0.73	7.7	<	23.4	21	25	3.6	37.0	45	9	0.2	2.5	640	140	200	13.00	2	2.1	8	1.8	3	<	2	<	18.0	11.0
64E	841129	00	1.70	7.9	45	5.3	13	<	2.3	36.0	83	6	0.2	3.0	680	130	243	12.00	<	1.8	7	1.5	6	0.9	1	5	20.7	11.0
64E	841130	00	0.11	5.3	<	3.3	9	<	1.7	29.0	<	8	<	0.7	120	160	289	20.00	3	2.7	5	0.9	<	<	<	11.0	5.1	
64E	841131	00	0.50	2.8	29	1.9	5	<	1.4	30.0	19	1	0.1	0.6	210	48	76	5.40	<	0.9	3	0.5	2	0.5	<	<	7.1	2.0
64E	841132	00	0.32	2.9	25	1.4	8	<	1.4	29.0	11	3	<	1.1	80	73	130	8.30	<	1.3	4	0.6	<	<	<	8.6	2.3	
64E	841133	00	0.79	7.8	28	20.1	19	21	2.2	34.0	40	8	0.1	1.2	290	95	163	11.00	<	1.4	6	0.9	4	0.7	2	<	19.0	4.7
64E	841134	00	0.07	2.3	<	3.5	7	<	1.3	51.0	<	2	<	0.6	110	64	104	7.60	<	0.8	<	0.4	<	<	4	5.5	2.0	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments												Waters								
Map	ID	ZN	UTM			Rock			Lake			Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W	
			Easting	Northing	Type	Age	Area	Dep	RS	Rlf	Cont		Units:	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppb	ppb	0.05								
Detection Limit:												2	2	2	2	2	0.2	5	.1	2	0.02	10	1.0	0.5	5	0.2	0.2	20	pH	0.05		
64E	841135	13	649016	6413932	PG	04	.25-1	3	00	Lw	-	Br	-	40	7	2	4	3	<	165	<	<	1.14	20	11.6	4.5	15	<	<	130	6.4	<
64E	841136	13	650718	6417062	PBA	04	.25-1	4	00	Lw	-	Br	-	120	32	<	13	11	.4	715	<	2	1.97	60	44.2	7.7	40	.6	<	62	6.3	<
64E	841137	13	649922	6420034	PGP	04	.25-1	4	00	Lw	-	Br	-	100	20	<	6	10	<	560	<	10	3.07	54	46.2	33.3	35	.6	<	180	5.9	0.1
64E	841138	13	650400	6424300	PGP	04	.25-1	5	00	Md	-	Br	-	100	17	<	9	9	<	325	<	2	2.17	74	41.8	7.3	35	.6	<	88	5.8	0.05
64E	841139	13	649669	6425883	PGP	04	.25-1	5	00	Md	-	Br	-	90	6	<	<	8	<	725	1.0	2	6.54	54	15.0	7.0	25	<	<	160	6.3	0.05
64E	841140	13	649528	6429560	PGP	04	.25-1	4	00	Md	-	Br	-	110	12	<	5	8	.2	280	<	2	3.95	67	32.2	10.5	30	.4	<	140	6.1	0.07
64E	841142	13	651799	6429899	PGP	04	.25-1	7	10	Md	-	Br	-	120	13	<	5	7	<	780	<	4	4.98	94	40.0	5.0	30	.6	<	150	6.1	<
64E	841143	13	651799	6429899	PGP	04	.25-1	7	20	Md	-	Br	-	130	13	<	5	8	.2	780	<	2	4.53	80	38.8	6.0	30	.4	<	150	6.1	<
64E	841144	13	655548	6429136	PGP	04	.25-1	6	00	Md	-	Br	-	100	28	3	15	10	<	485	<	<	2.04	74	49.8	26.4	15	.4	<	70	5.8	0.1
64E	841145	13	660647	6430289	PGP	04	1-5	7	00	Md	-	Br	-	87	13	<	10	15	<	2700	<	<	5.19	47	10.2	15.0	30	<	<	110	6.3	0.2
64E	841146	13	663728	6429551	PGP	04	.25-1	3	00	Md	-	Br	-	120	15	<	14	16	<	1320	1.0	<	5.22	34	9.0	13.1	30	<	<	130	6.3	0.18
64E	841147	13	667341	6430216	PGP	04	1-5	13	00	Lw	-	Br	-	75	15	6	18	14	<	1120	1.0	<	2.59	27	4.0	7.3	40	<	<	140	6.7	0.06
64E	841148	13	674753	6427570	PGP	04	.25-1	2	00	Lw	-	Br	Lgt	95	28	4	15	9	.4	335	<	<	1.56	40	25.0	6.5	40	<	<	84	5.7	<
64E	841149	13	673282	6424330	PGP	04	pond	2	00	Lw	-	Br	Lgt	60	30	<	12	3	.2	60	<	<	.42	87	54.2	3.3	20	.4	<	88	5.5	<
64E	841150	13	672515	6420920	PG	04	pond	3	00	Lw	-	Br	Lgt	130	34	3	16	14	.2	425	1.0	<	2.99	60	31.4	5.3	50	.2	<	120	5.8	<
64E	841152	13	673562	6416765	PG	04	pond	2	00	Lw	-	Br	Lgt	90	32	2	10	4	.6	60	<	<	.30	74	70.6	6.8	10	.2	<	110	5.8	<
64E	841153	13	669606	6413386	PG	04	.25-1	2	00	Lw	-	Br	-	79	35	2	11	8	<	310	<	2	1.21	60	37.6	4.3	20	.2	<	210	6.9	<
64E	841154	13	668184	6408628	PGP	04	.25-1	5	00	Lw	-	Br	Lgt	65	63	<	12	7	<	120	<	<	1.90	89	63.8	3.2	25	<	<	110	5.4	<
64E	841155	13	670247	6407901	PGP	04	.25-1	2	00	Lw	-	Br	-	100	24	2	13	9	<	255	<	<	1.05	60	44.4	4.0	25	.2	<	150	6.6	<
64E	841156	13	669052	6406497	PGP	04	pond	2	00	Lw	-	Br	-	97	17	2	18	6	<	130	<	<	.69	67	45.6	2.6	25	.4	<	110	6.1	<
64E	841157	13	671381	6405483	PGP	04	1-5	6	00	Lw	-	Br	-	71	15	2	7	7	.2	565	<	<	2.67	34	17.6	5.5	25	<	<	130	6.6	<
64E	841158	13	669557	6402445	PGP	04	pond	2	00	Lw	-	Br	Lgt	140	21	<	10	8	.2	165	<	<	1.36	54	41.8	2.3	20	.2	<	110	5.9	<
64E	841159	13	668119	6401793	PGP	04	pond	3	00	Lw	-	Br	Lgt	94	45	<	13	5	<	130	<	<	1.20	60	56.2	3.0	20	.2	<	90	5.2	<
64E	841160	13	665667	6395685	PG	04	pond	2	00	Lw	-	Br	Lgt	100	28	3	18	14	<	465	1.0	<	3.00	40	23.8	6.9	25	<	<	94	5.8	<
64E	841162	13	665277	6396421	PG	04	pond	3	00	Lw	-	Br	-	81	24	2	15	12	<	375	<	<	2.55	34	14.8	6.8	30	<	<	94	6.0	<
64E	841163	13	662193	6406910	PGP	04	pond	2	00	Lw	-	Br	-	120	67	3	16	11	.4	180	2.0	2	1.36	87	48.6	4.1	35	.4	<	70	4.9	<
64E	841164	13	663594	6412087	PGP	04	pond	2	10	Lw	-	Br	Lgt	120	38	<	16	13	<	285	<	2	1.86	67	60.6	6.1	30	.4	<	110	6.1	<
64E	841165	13	663594	6412087	PGP	04	pond	2	20	Lw	-	Br	Lgt	110	38	<	16	12	.2	290	<	2	2.19	67	61.8	6.4	30	.2	<	110	5.9	<
64E	841166	13	661834	6412649	PG	04	pond	4	00	Md	-	Br	-	72	27	<	9	5	.2	165	<	2	.91	127	39.6	3.0	35	.2	<	68	5.6	<
64E	841167	13	663982	6417358	PG	04	.25-1	2	00	Lw	-	Br	-	100	45	<	16	13	<	180	<	2	.95	74	53.2	5.2	30	.2	<	94	6.0	<
64E	841168	13	666517	6417537	PG	04	1-5	5	00	Md	-	Gy	-	52	10	4	9	6	<	330	<	<	1.21	20	4.2	5.1	25	<	<	98	6.8	0.05
64E	841169	13	666474	6420428	PG	04	.25-1	13	00	Lw	-	Br	-	98	19	5	14	13	<	680	<	<	3.09	60	12.8	5.0	45	<	<	94	6.6	0.05
64E	841170	13	664148	6419993	PG	04	1-5	6	00	Lw	-	Gy	-	88	16	2	14	11	<	505	<	<	2.24	47	9.2	5.7	40	<	<	100	6.5	0.05
64E	841171	13	666309	6422701	PGP	04	1-5	9	00	Lw	-	Gy	-	96	22	3	17	12	<	1040	<	<	2.70	34	10.0	7.8	35	<	<	76	6.7	0.05
64E	841172	13	666034	6427399	PGP	04	>5	18	00	Md	-	Gy	-	83	12	5	14	13	<	3800	1.0	<	4.22	54	4.6	6.9	40	<	<	160	6.3	<
64E	841173	13	663898	6426351	PGP	04	.25-1	11	00	Md	-	Br	-	95	24	5	11	7	.2	455	<	2	1.96	100	29.2	10.4	35	.2	<	130	6.4	<
64E	84117																															

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb	Th ppm	U ppm		
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
	Map	ID	RS																									
64E	841135	00	1.80	5.3	36	1.9	7	<	1.0	13.0	100	2	0.2	1.8	570	55	84	5.80	<	0.8	3	0.5	6	0.8	<	3	14.0	4.1
64E	841136	00	0.45	6.4	43	3.1	19	<	2.3	41.0	17	4	0.1	0.8	250	100	150	11.00	2	1.3	4	0.8	<	<	1	5	13.0	6.7
64E	841137	00	0.28	4.9	<	5.0	15	<	1.7	35.0	18	13	0.1	0.5	120	100	176	9.20	2	1.4	4	1.5	1	<	<	<	13.0	33.2
64E	841138	00	0.30	4.1	22	3.8	11	<	2.3	43.0	11	4	0.1	0.8	140	78	131	7.90	2	1.1	4	0.8	1	<	<	<	13.0	6.6
64E	841139	00	1.80	5.1	<	10.0	8	<	1.4	12.0	93	5	<	1.8	520	80	135	8.10	<	1.4	5	0.9	7	0.9	2	3	16.0	6.5
64E	841140	00	0.66	4.3	27	6.3	12	<	1.3	26.0	34	5	<	0.9	250	100	181	12.00	2	1.7	6	1.3	3	<	<	7	18.0	9.2
64E	841142	10	0.38	3.9	31	7.2	11	<	2.1	42.0	23	7	<	1.0	110	45	78	4.70	2	0.7	3	0.6	3	<	<	<	11.0	4.8
64E	841143	20	0.38	3.8	35	7.2	12	<	2.7	42.0	21	7	0.2	1.5	140	43	77	4.70	<	1.0	3	0.6	2	<	<	6	11.0	5.0
64E	841144	00	0.26	4.8	37	3.5	13	<	2.0	48.0	10	4	<	0.6	170	130	224	12.00	<	2.0	7	1.7	1	<	<	6	13.0	25.3
64E	841145	00	2.00	6.7	30	5.8	14	<	1.2	10.0	110	3	0.1	2.9	730	88	143	7.90	<	1.5	4	1.0	7	0.8	<	3	18.0	15.0
64E	841146	00	2.04	8.5	39	6.6	18	<	2.2	13.0	140	4	0.2	4.3	710	95	153	9.10	2	1.4	4	1.0	7	1.0	<	<	21.8	13.0
64E	841147	00	2.22	9.3	46	3.4	13	32	1.7	7.2	180	3	0.2	5.3	800	78	129	7.60	<	1.0	4	0.6	6	1.5	2	4	22.7	7.4
64E	841148	00	1.30	7.1	42	2.2	16	<	1.9	21.0	97	3	0.2	3.8	490	97	170	10.00	<	1.5	4	0.7	5	0.7	1	<	19.0	6.5
64E	841149	00	0.24	2.9	32	0.6	7	<	1.1	39.0	17	2	<	0.5	120	79	127	6.90	<	0.9	2	0.3	2	<	<	10	11.0	3.2
64E	841150	00	1.00	6.1	40	3.7	20	23	2.3	28.0	85	4	0.2	3.1	360	97	170	8.20	2	1.3	3	0.6	2	<	1	<	15.0	5.0
64E	841152	00	0.14	2.8	29	0.3	6	<	1.4	38.0	<	2	0.1	0.6	120	130	200	10.00	2	1.3	3	0.6	<	<	<	14.0	6.5	
64E	841153	00	0.79	4.9	37	1.5	9	<	1.3	21.0	59	4	<	2.0	440	58	84	6.00	<	0.9	<	0.4	3	<	<	8	13.0	3.8
64E	841154	00	0.12	3.9	49	2.4	8	<	2.2	52.0	<	3	0.1	<	150	170	257	13.00	2	1.5	3	0.6	1	<	<	7	10.0	3.5
64E	841155	00	0.69	4.4	26	1.7	12	25	2.2	28.0	49	3	0.1	1.6	330	88	139	6.90	2	0.8	3	0.5	2	<	<	12.0	4.3	
64E	841156	00	0.49	3.4	42	1.1	12	21	1.7	33.0	28	2	0.1	0.7	230	50	86	5.30	<	0.6	<	0.4	2	<	<	10.0	2.4	
64E	841157	00	1.90	7.1	25	3.4	8	<	1.8	19.0	94	2	0.2	2.7	700	100	143	9.00	<	1.3	3	0.7	8	1.1	1	<	19.0	5.2
64E	841158	00	0.46	3.5	21	2.1	9	20	1.5	26.0	26	2	0.1	0.8	250	110	173	9.40	1	1.1	3	0.5	2	<	2	4	11.0	2.4
64E	841159	00	0.10	2.2	30	1.5	6	<	1.5	45.0	<	3	0.1	0.5	140	94	162	9.40	<	1.3	3	0.5	<	<	<	9.4	2.5	
64E	841160	00	1.50	8.1	53	3.5	17	35	2.2	15.0	130	1	0.2	4.1	650	98	148	8.70	<	1.4	4	0.6	3	1.0	1	<	20.0	6.5
64E	841162	00	1.90	8.6	60	3.3	14	23	1.5	11.0	130	3	0.2	3.8	710	90	149	8.40	<	1.2	3	0.7	5	1.1	1	5	20.1	6.8
64E	841163	00	0.79	5.8	41	2.1	13	32	3.1	36.0	49	4	0.1	1.3	300	160	261	12.00	2	1.3	4	0.6	3	<	1	5	14.0	4.0
64E	841164	10	0.30	4.5	43	2.8	17	32	2.2	27.0	15	3	0.1	1.3	230	120	204	11.00	2	1.5	5	0.7	1	<	1	<	12.0	6.3
64E	841165	20	0.32	4.9	40	2.7	21	26	1.9	28.0	16	3	0.1	0.9	180	120	203	11.00	2	1.4	4	0.8	2	<	<	12.0	6.6	
64E	841166	00	0.44	4.3	25	1.4	7	<	1.2	43.0	26	3	0.1	1.1	220	97	164	8.70	<	1.1	2	0.5	2	0.6	1	<	11.0	2.8
64E	841167	00	0.31	4.3	<	1.4	13	<	1.6	31.0	12	2	<	0.5	260	110	169	10.00	1	1.2	3	0.7	1	<	<	11.0	4.4	
64E	841168	00	2.37	7.2	46	2.0	13	<	1.3	14.0	130	2	0.1	2.7	800	55	93	5.70	<	0.9	2	0.5	8	1.0	1	<	17.0	4.6
64E	841169	00	1.80	8.3	48	3.9	19	34	2.3	19.0	140	3	0.2	4.1	720	84	152	8.10	<	1.2	3	0.6	4	1.3	2	<	20.8	5.5
64E	841170	00	1.90	8.0	46	3.0	12	<	1.6	15.0	140	2	0.2	4.0	730	78	134	7.80	<	1.1	3	0.6	5	1.2	2	<	20.4	4.9
64E	841171	00	1.90	8.4	51	3.3	15	<	1.6	14.0	140	3	0.2	4.2	800	88	151	9.20	<	1.3	4	0.7	6	1.2	2	3	24.1	7.6
64E	841172	00	1.80	7.8	47	5.0	12	36	1.9	5.8	160	2	0.2	4.9	840	68	110	7.60	<	1.2	2	0.5	5	1.4	2	<	21.5	7.4
64E	841173	00	0.94	7.3	39	2.9	8	<	1.8	41.0	60	3	0.2	2.0	400	130	211	14.00	<	2.2	6	1.1	4	0.6	<	<	19.0	10.0
64E	841174	00	1.50	7.6	33	3.1	11	20	1.3	22.0	100	4	0.1	3.3	490	93	153	8.80	1	1.2	3	0.7	5	0.8	<	<	19.0	6.1
64E	841175	00	1.20	5.8	30	3.2	8	31	1.5	32.0	72	4	0.2	2.6	440	72	120	7.30	<	1.2	3	0.8	4	0.8	1	<	16.0	14.0
64E	841176	00	0.78	6.1	38	3.8	14	22	2.2	47.0	54	9	0.2	1.5	340	99	169	10.00	2	1.3	4	0.8	3	0.6	2	<	17.0	9.4
64E	841177	00	1.50	7.3	59	3.9	23	<	1.8	64.0	96	5	0.2	3.2	570	92	161	8.70	<	1.2	3	0.7	4</td					

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments													Waters							
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep							2	ppm	ppm	ppm	ppm	ppm	ppm	5	ppm	ppm	pct	ppb	10	pct	ppm	ppm	0.5	5	0.2
64E	841178	13	657007	6419174	PG	04	.25-1	3	00	Md	-	Br	-	97	15	2	13	12	<	475	<	<	1.89	54	15.4	5.3	25	<	<	76	6.2	0.11	
64E	841179	13	655708	6417571	PG	04	.25-1	8	00	Md	-	Br	-	91	20	2	11	9	.2	415	<	<	1.77	80	23.6	3.9	25	<	<	58	6.1	<	
64E	841182	13	656024	6422294	PGP	04	.25-1	13	00	Md	-	Br	-	80	19	3	9	7	<	340	<	2	1.38	63	25.8	9.8	30	.2	<	68	6.2	0.08	
64E	841183	13	656529	6425470	PGP	04	1-5	12	00	Md	-	Br	-	120	20	3	13	8	<	725	1.0	10	3.19	57	19.4	12.4	40	.2	<	90	6.3	0.05	
64E	841184	13	653685	6425806	PGP	04	.25-1	4	10	Md	-	Br	-	110	30	10	10	11	1.0	220	1.0	2	.86	69	69.4	12.0	30	.4	<	46	5.0	<	
64E	841185	13	653685	6425806	PGP	04	.25-1	4	20	Md	-	Br	-	87	24	2	9	10	.2	210	<	2	.82	63	70.4	9.1	20	.4	<	44	4.9	<	
64E	841186	13	653107	6422444	PGP	04	.25-1	3	00	Md	-	Br	-	90	24	2	15	10	<	355	<	2	1.78	69	38.2	19.8	35	.2	<	100	5.9	0.15	
64E	841187	13	652687	6419175	PBA	04	.25-1	4	00	Md	-	Br	-	80	17	<	7	9	<	490	<	2	4.00	88	22.2	5.0	55	<	<	50	6.1	<	
64E	841188	13	652424	6413048	PG	04	>5	22	00	Md	-	Gy	-	92	17	5	12	11	.6	965	2.0	2	4.36	63	12.8	6.4	40	<	<	92	6.7	<	
64E	841189	13	651358	6408615	PBG	04	.25-1	10	00	Md	-	Br	-	120	97	<	13	18	<	870	<	2	3.55	113	55.6	3.9	55	.6	<	36	6.3	<	
64E	841190	13	648667	6406615	PGP	04	.25-1	14	00	Md	-	Gn	-	190	23	<	9	20	.4	1260	<	2	9.40	227	43.2	3.0	55	<	<	60	6.2	<	
64E	841191	13	648488	6410610	PG	04	pond	2	00	Lw	-	Br	-	130	16	2	16	4	<	90	<	<	1.03	76	62.8	1.3	35	.4	<	26	5.2	<	
64E	841192	13	645721	6407343	PG	04	.25-1	2	00	Md	-	Br	-	43	9	<	6	3	<	140	<	2	.69	69	35.6	2.8	25	.2	<	78	6.1	<	
64E	841193	13	634462	6407946	PG	04	.25-1	2	00	Md	-	Br	-	98	16	3	12	10	.4	285	<	4	1.69	57	35.4	7.1	30	.2	<	160	5.5	0.05	
64E	841194	13	636044	6405042	PQF	04	pond	2	00	Md	-	Br	-	48	10	<	9	4	.2	135	<	<	.63	69	25.6	3.2	20	.4	<	140	6.2	<	
64E	841195	13	638272	6405996	PBG	04	.25-1	3	00	Md	-	Br	-	100	21	<	9	8	<	370	<	2	1.07	50	68.4	3.4	20	.6	<	60	6.2	<	
64E	841197	13	642613	6404527	PG	04	.25-1	11	00	Md	-	Br	-	150	20	<	6	15	.4	1110	<	6	7.70	176	46.4	5.2	40	.2	<	86	6.7	<	
64E	841198	13	645038	6404132	PG	04	.25-1	6	00	Md	-	Br	-	280	19	<	10	22	<	1750	<	6	13.5	113	32.2	5.9	60	<	<	84	6.4	<	
64E	841199	13	646493	6401937	PGP	04	1-5	3	00	Lw	-	Br	-	140	34	<	24	14	.2	295	<	<	4.36	122	50.6	2.8	45	.4	<	50	6.1	<	
64E	841200	13	645641	6397623	PGP	04	.25-1	4	00	Lw	-	Br	-	140	45	<	13	12	.4	515	<	<	5.65	98	56.6	3.0	50	.4	<	48	6.1	<	
64E	841202	13	644294	6396222	PG	04	pond	2	00	Lw	-	Br	Lgt	56	16	3	9	6	<	345	<	<	1.24	30	28.0	3.4	25	.2	<	74	6.3	<	
64E	841203	13	640697	6395710	PG	04	>5	5	00	Md	-	Br	-	84	20	5	15	10	<	2600	2.0	2	3.83	37	10.0	7.1	30	<	<	130	6.6	<	
64E	841204	13	640473	6398057	PG	04	1-5	15	00	Md	-	Br	-	100	15	3	13	9	<	760	1.0	2	3.14	55	20.2	6.2	40	<	<	130	6.4	<	
64E	841205	13	641982	6401311	PG	04	.25-1	9	10	Md	-	Br	-	91	11	4	10	8	<	485	<	<	2.34	61	18.2	5.0	30	.2	<	100	6.5	<	
64E	841206	13	641982	6401311	PG	04	.25-1	9	20	Md	-	Br	-	96	11	5	9	8	<	450	<	<	2.38	79	19.8	4.7	30	<	<	100	6.5	<	
64E	841207	13	637312	6400694	PG	04	.25-1	3	00	Md	-	Br	-	120	17	<	18	7	<	310	<	12	4.33	67	51.0	17.3	25	<	<	530	6.1	0.06	
64E	841208	13	635392	6402918	PBG	04	1-5	16	00	Md	-	Br	-	84	8	4	6	6	<	650	<	2	3.58	61	14.6	6.7	25	<	<	170	6.4	0.05	
64E	841209	13	631548	6400672	PG	04	1-5	2	00	Md	-	Br	-	150	18	<	11	5	.2	290	<	12	4.82	30	41.8	7.6	30	.2	<	330	6.4	<	
64E	841211	13	627676	6400568	UKNN	04	.25-1	2	00	Lw	-	Br	-	82	9	4	6	5	<	130	<	4	1.38	37	17.6	6.6	15	.2	<	300	6.1	0.05	
64E	841212	13	622984	6401731	UKNN	04	.25-1	2	00	Md	-	Br	-	130	9	<	2	6	<	255	<	10	9.90	55	33.4	6.7	55	<	<	300	6.3	<	
64E	841213	13	619575	6400727	UKNN	04	.25-1	20	00	Md	-	Gn	-	160	56	2	6	8	<	345	2.0	8	8.30	140	61.4	34.4	140	.4	<	76	6.0	<	
64E	841214	13	616686	6400770	UKNN	04	.25-1	4	00	Lw	-	Br	-	90	17	3	12	7	.2	155	<	4	1.80	85	43.6	4.9	25	.4	<	170	6.2	<	
64E	841215	13	612549	6402185	WPSN	04	>5	3	00	Md	-	Br	-	45	4	2	4	6	<	260	<	<	1.85	36	8.2	2.8	15	<	<	100	6.2	<	
64E	841216	13	607985	6403643	WFN	04	.25-1	2	00	Md	-	Br	-	100	10	<	8	6	<	380	<	4	3.68	55	38.4	5.6	40	<	<	110	6.0	<	
64E	841217	13	605522	6402055	WFN	04	.25-1	3	00	Md	-	Br	Lgt	50	8	<	8	3	<	155	<	<	1.00	50	36.4	5.4	15	.2	<	100	5.7	<	
64E	841218	13	602144	6402056	WFN	04	>5	19	00	Md	-	Br	-	200	13	<	12	16	.2	13000	5.0	24	11.3	40	23.4	6.5	35	.4	<	120	6.5	0.11	
64E	841219																																

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																											
Element:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U			
Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm				
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
Map	ID	RS																											
64E	841178	00	1.40	7.2	50	2.5	13	<	1.2	21.0	110	2	0.2	3.5	560	66	109	6.50	<	0.7	3	0.5	4	0.8	1	4	16.0	5.1	
64E	841179	00	1.20	5.9	37	2.7	11	<	1.4	30.0	66	2	0.2	2.8	420	66	115	7.20	2	1.0	3	0.5	3	0.6	<	<	15.0	3.7	
64E	841182	00	1.40	6.8	41	2.3	12	<	1.8	32.0	82	2	0.2	2.6	410	74	119	6.80	<	1.0	3	0.7	4	1.0	1	<	16.0	9.1	
64E	841183	00	1.30	7.7	26	4.4	10	<	1.8	24.0	76	11	0.2	3.5	460	80	131	7.50	2	1.3	3	0.8	4	1.0	2	<	18.0	13.0	
64E	841184	10	0.20	4.3	28	1.4	16	<	2.5	52.0	<	4	0.1	1.0	240	93	169	8.20	2	1.0	4	1.0	<	<	<	4	9.2	11.0	
64E	841185	20	0.17	4.0	41	1.4	15	<	2.2	55.0	<	2	0.1	0.8	170	81	135	7.00	1	1.0	3	0.8	<	<	<	9	7.7	8.6	
64E	841186	00	0.73	6.7	58	2.9	23	<	2.4	39.0	39	4	0.2	1.7	300	100	193	11.00	2	1.7	4	1.2	2	0.6	2	<	20.0	20.8	
64E	841187	00	1.00	5.8	30	5.0	13	<	1.5	22.0	63	3	0.1	2.3	410	92	166	9.00	2	1.2	3	0.6	3	0.8	<	<	16.0	4.2	
64E	841188	00	1.60	8.2	51	6.0	13	23	3.0	27.0	110	4	0.2	4.0	650	71	110	7.00	<	1.2	3	0.7	4	1.0	3	<	17.0	7.2	
64E	841189	00	0.20	5.5	32	5.3	26	<	2.0	58.0	<	3	<	0.8	280	75	129	6.20	1	0.8	2	0.5	<	<	1	<	6.0	3.9	
64E	841190	00	0.29	4.9	32	11.0	34	<	2.2	54.0	16	3	0.1	1.2	260	100	187	10.00	1	1.4	4	0.6	1	<	<	<	10.0	3.0	
64E	841191	00	0.10	2.2	21	1.4	8	22	1.9	45.0	<	2	<	0.6	140	33	56	4.40	<	0.6	<	0.2	<	<	<	<	5.2	1.4	
64E	841192	00	0.24	2.1	<	0.9	6	<	0.9	24.0	11	2	0.1	0.6	140	44	77	4.70	<	0.6	<	0.4	<	<	1	4	7.2	2.8	
64E	841193	00	1.00	5.4	20	2.5	14	29	2.0	19.0	69	5	0.2	1.9	360	72	117	7.00	<	1.1	4	0.8	2	<	<	1	4	13.0	7.3
64E	841194	00	0.54	2.9	<	1.0	7	<	1.2	20.0	34	4	0.1	1.3	200	48	90	5.30	<	0.6	2	0.3	1	0.5	1	<	8.1	3.1	
64E	841195	00	0.21	3.8	<	1.6	11	<	1.4	36.0	7	4	0.1	<	120	73	114	6.60	<	1.0	3	0.5	1	<	<	<	7.8	3.4	
64E	841197	00	0.32	5.1	46	10.0	23	<	2.1	57.0	<	5	<	1.0	240	110	179	10.00	2	1.0	5	0.8	1	<	<	<	11.0	5.3	
64E	841198	00	0.77	8.6	38	17.0	32	<	1.8	26.0	42	7	<	2.1	320	130	229	12.00	2	1.8	7	1.1	3	0.6	1	<	20.0	5.9	
64E	841199	00	0.38	6.1	61	6.7	24	<	2.2	37.0	14	3	0.2	1.0	210	86	148	8.60	1	1.2	4	0.6	2	<	<	<	10.0	2.9	
64E	841200	00	0.21	4.1	<	7.7	20	25	2.1	46.0	9	3	0.1	1.0	94	77	119	6.50	<	0.6	3	0.4	<	<	2	<	8.0	3.3	
64E	841202	00	1.00	4.6	23	1.7	10	<	1.0	19.0	55	3	0.1	1.5	430	46	84	4.60	<	0.9	3	0.4	4	0.6	<	<	9.5	3.3	
64E	841203	00	2.00	8.5	54	5.2	17	<	3.0	25.0	130	4	0.2	3.8	810	67	97	6.60	1	1.0	2	0.7	7	1.2	<	<	17.0	7.1	
64E	841204	00	1.40	7.8	48	4.3	12	<	2.3	25.0	85	5	0.2	3.1	540	76	134	7.70	2	1.2	3	0.7	4	0.5	1	<	17.0	5.5	
64E	841205	10	1.40	6.9	42	3.3	13	<	1.6	23.0	97	3	0.1	3.0	540	68	120	7.10	<	1.2	3	0.6	4	1.0	2	<	16.0	4.3	
64E	841206	20	1.30	6.2	45	3.1	14	28	1.3	25.0	83	2	0.1	2.2	450	71	110	7.00	<	1.0	3	0.5	3	0.7	<	3	15.0	3.8	
64E	841207	00	0.15	3.1	<	5.9	14	25	1.1	26.0	7	14	0.1	0.6	100	50	88	5.30	<	0.9	3	0.7	<	<	<	<	5.7	15.0	
64E	841208	00	1.50	6.2	45	4.8	9	<	1.9	17.0	85	4	0.2	2.5	540	63	103	6.70	1	1.2	4	0.7	5	0.9	2	<	14.0	6.4	
64E	841209	00	0.60	5.4	37	6.3	10	<	1.9	30.0	25	13	0.1	1.2	250	100	135	14.00	2	2.3	7	1.1	3	<	2	<	13.0	7.2	
64E	841211	00	1.60	4.9	35	2.3	8	<	1.2	18.0	83	3	<	1.4	520	76	122	8.50	<	1.4	4	0.8	6	0.7	<	5	15.0	6.3	
64E	841212	00	0.17	4.1	32	13.0	<	<	2.4	26.0	9	13	0.2	1.6	<	84	141	10.00	<	1.7	8	1.3	2	<	2	<	11.0	8.0	
64E	841213	00	0.16	13.0	71	12.0	14	<24	4.9	79.0	<16	7	0.2	<	140	351	572	41.30	7	6.2	21	4.6	4	<	4	<6	47.5	36.0	
64E	841214	00	0.15	3.4	<	2.4	11	<	1.9	27.0	11	7	<	1.2	77	43	81	4.60	<	0.7	2	0.5	1	<	<	<	7.8	4.2	
64E	841215	00	2.01	4.2	23	2.6	8	<	1.3	8.3	92	2	0.1	1.5	590	41	67	4.40	<	0.8	3	0.5	8	0.8	<	<	12.0	2.8	
64E	841216	00	0.27	3.1	34	5.0	7	<	2.2	39.0	11	7	<	0.8	140	33	58	3.80	<	0.7	3	0.5	2	<	2	4	7.8	4.7	
64E	841217	00	0.33	2.3	<	1.4	<	<	1.1	24.0	12	3	<	0.6	140	33	59	3.50	<	0.6	<	0.3	1	<	<	7	5.9	5.2	
64E	841218	00	0.74	5.4	21	14.0	20	<	7.7	48.0	47	24	0.2	1.6	1100	82	141	8.20	1	1.4	5	0.9	3	0.5	1	<	13.0	9.1	
64E	841219	00	0.16	3.7	31	8.5	11	20	2.1	31.0	10	8	0.2	0.7	59	71	118	8.30	<	1.4	5	1.0	2	<	<	<	12.0	9.0	
64E	841220	00	0.26	2.6	35	2.5	<	<	1.4	27.0	17	3	<	<	78	35	64	4.50	<	0.9	3	0.6	1	<	1	<	7.2	5.2	
64E	841222	10	0.35	1.8	<	1.5	<	<	1.4	20.0	17	2	0.1	0.7	140	24	42	4.40	<	1.1	5	0.7	1	<	<	<	6.3	6.1	
64E	841223	20	0.32	1.7	<	1.3	<	<	2.1	22.0	14	2	0.1	0.7	97	22	44	4.10	<	1.1	4	0.6	<	<	<	<	5.6	5.4	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data															Sample Media: Sediments															Waters				
Map	ID	ZN	UTM			Rock		Lake		RS	Rlf	Cont	Colr	Susp	Detection Limit:															F-W	pH	U-W		
			Easting	Northing	Type	Age	Area	Dep	Br						-	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	ppb	ppb	ppb
64E	841224	13	587282	6400793	WPSN	04	.25-1	2	00	Md	-	Br	-	70	9	<	7	3	.2	225	<	<	.89	40	37.0	4.7	15	.2	<	130	6.2	<		
64E	841225	13	583746	6401032	WRN	04	1-5	12	00	Md	-	Br	-	93	14	<	5	11	<	32500	3.0	4	17.8	50	31.6	10.2	35	<	<	120	6.7	0.05		
64E	841226	13	581244	6400835	WRN	04	1-5	2	00	Md	-	Br	-	58	7	<	6	3	<	220	<	2	1.66	30	58.8	3.0	15	.2	<	92	6.1	<		
64E	841227	13	583439	6398172	WRN	04	1-5	13	00	Md	-	Br	-	79	12	<	8	4	.4	370	<	<	2.18	80	29.6	10.2	45	.2	<	110	6.5	<		
64E	841228	13	580763	6397399	WRN	04	.25-1	3	00	Lw	-	Br	-	49	5	<	8	4	<	195	<	<	.80	40	35.2	2.9	15	.2	<	120	6.3	<		
64E	841229	13	577662	6399542	WRN	04	>5	9	00	Md	-	Br	-	80	7	<	5	7	<	875	1.0	<	4.59	30	14.6	4.5	20	<	<	90	6.5	<		
64E	841230	13	573463	6397225	WPEG	04	1-5	5	00	Md	-	Br	-	82	11	<	8	4	.2	340	<	<	3.53	90	29.0	4.9	25	<	<	110	6.6	<		
64E	841231	13	575262	6394357	WRN	04	.25-1	2	00	Md	-	Br	-	68	9	<	12	5	<	325	<	<	.92	50	42.8	3.7	15	.4	<	96	6.2	<		
64E	841232	13	576871	6393391	WRN	04	1-5	2	00	Md	-	Br	-	69	7	<	7	3	.2	235	<	<	1.05	30	28.8	4.3	10	.4	<	82	6.1	<		
64E	841233	13	574439	6390520	WPSN	04	.25-1	5	00	Md	-	Br	-	110	17	32	15	8	<	470	<	<	1.27	60	49.0	11.0	20	.4	<	100	6.4	<		
64E	841235	13	573273	6387305	WFN	04	>5	12	00	Md	-	Br	-	80	11	<	8	4	<	450	<	<	2.35	50	35.2	4.3	15	.2	<	100	6.4	<		
64E	841236	13	574782	6383960	WFN	04	.25-1	5	00	Md	-	Br	-	93	10	<	7	6	.2	415	<	4	3.33	30	36.2	4.2	30	<	<	110	6.4	<		
64E	841237	13	573260	6379086	WFN	04	1-5	16	00	Md	-	Br	-	70	8	<	5	5	<	630	1.0	2	4.03	80	28.6	5.5	45	<	<	130	6.5	<		
64E	841238	13	574352	6377869	WFN	04	.25-1	2	00	Md	-	Br	-	30	7	<	10	4	<	285	<	<	.69	430	41.0	3.6	5	<	<	170	6.5	<		
64E	841239	13	578265	6375527	WS	04	1-5	21	00	Md	-	Gn	-	170	18	<	12	10	<	5500	3.0	2	9.80	80	33.8	4.9	35	<	<	140	6.9	<		
64E	841240	13	574532	6372819	WRN	04	pond	2	00	Lw	-	Br	-	63	5	<	7	3	<	260	<	<	1.35	50	37.2	4.4	15	.2	<	120	6.7	<		
64E	841242	13	572446	6368829	WQ	04	pond	3	10	Md	-	Br	-	280	13	11	13	12	<	170	13.0	2	2.56	40	34.4	3.0	15	1.2	<	90	6.5	<		
64E	841243	13	572446	6368829	WQ	04	pond	3	20	Md	-	Br	-	280	14	11	13	10	<	195	13.0	2	2.58	60	34.2	2.9	20	1.2	<	88	6.4	<		
64E	841245	13	573385	6366325	PG	04	.25-1	5	00	Md	-	Br	-	52	8	<	7	2	<	215	<	<	.98	160	26.0	1.7	10	.4	<	74	5.8	<		
64E	841246	13	572528	6360663	PG	04	.25-1	6	00	Md	-	Br	-	47	6	<	9	5	<	315	<	<	2.01	20	9.4	3.3	15	.4	<	190	6.1	<		
64E	841247	13	570951	6359277	PG	04	1-5	4	00	Md	-	Br	-	44	5	<	8	3	<	240	<	<	1.55	20	7.4	2.9	15	<	<	190	6.3	<		
64E	843002	13	563535	6354949	PG	04	.25-1	5	10	Lw	-	Gn	Lgt	68	15	<	12	5	.4	320	3.0	6	4.04	30	56.0	7.6	30	<	<	260	6.8	<		
64E	843003	13	563535	6354949	PG	04	.25-1	5	20	Lw	-	Gn	Lgt	68	15	<	10	3	<	315	3.0	4	3.43	40	50.0	6.1	25	<	<	270	6.7	<		
64E	843004	13	567318	6355052	PBG	04	1-5	1	00	Lw	-	Br	Lgt	74	8	<	3	3	<	230	<	<	1.45	30	35.6	2.7	15	.2	<	88	5.7	<		
64E	843005	13	571031	6355808	PG	04	>5	5	00	Lw	-	Gy	Lgt	30	3	<	4	3	<	280	<	<	1.70	10	3.8	2.9	10	<	<	140	6.5	<		
64E	843006	13	574354	6355729	PG	04	.25-1	1	00	Lw	-	Br	Lgt	54	15	<	8	3	<	260	<	<	.86	60	44.0	2.4	10	.4	<	150	6.2	<		
64E	843007	13	577028	6355263	PG	04	1-5	8	00	Lw	-	Br	Lgt	88	25	<	10	5	.2	510	<	2	2.34	50	30.8	3.8	25	.2	<	130	6.3	<		
64E	843008	13	580038	6354555	PG	04	.25-1	2	00	Lw	-	Br	Lgt	110	21	<	10	5	<	205	<	4	1.02	40	52.6	5.6	25	.4	<	200	5.6	0.05		
64E	843009	13	584222	6354983	PG	04	pond	14	00	Lw	-	Br	Lgt	230	27	<	9	11	.2	555	<	6	3.67	110	48.8	6.9	35	.8	<	180	6.4	<		
64E	843010	13	588149	6353252	PGN	04	.25-1	2	00	Lw	-	Gn	Lgt	140	26	<	13	7	<	195	<	<	5.90	60	49.2	5.3	45	<	<	160	6.0	0.05		
64E	843011	13	592969	6354653	PG	04	1-5	2	00	Lw	-	Gn	Lgt	130	18	<	9	7	.2	280	<	10	6.30	70	39.2	7.9	40	<	<	350	6.4	0.08		
64E	843012	13	596370	6354468	PG	04	.25-1	6	00	Lw	-	Br	Lgt	97	17	<	5	8	.4	415	<	2	2.80	80	32.8	8.9	35	<	<	220	5.9	0.16		
64E	843013	13	599740	6355211	PBG	04	.25-1	6	00	Lw	-	Gn	Br	Lgt	110	34	2	7	7	<	370	<	6	1.44	140	37.2	5.0	25	.6	<	250	6.4	0.06	
64E	843014	13	602157	6356563	PBG	04	1-5	2	00	Lw	-	Gn	Lgt	83	22	2	4	5	<	215	<	4	1.54	60	59.6	5.2	20	<	<	180	6.5	0.05		
64E	843016	13	605973	6355274	PSL	04	1-5	6	00	Lw	-	Br	Lgt	160	25	<	13	8	.4	670	<	<	5.60	140	36.8	2.9	35	<	<	140	6.6	<		
64E	843017	13	609788	6355746	RGPX	04	.25-1	7	00	Lw	-	Br	Lgt	110	30	<	7	9	.2	690	<	<	1.57	130	49.6	5.1	40	.4	<	120	6.3	<		
64E	843018	13	611916	6355218	RGPX	04	.25-1	3	00	Lw	-	Br	Lgt	150	43	<	14	12	<															

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																											
Element:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U			
Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppb	ppm	ppm			
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
Map	ID	RS																											
64E	841224	00	0.34	2.2	<	1.3	6	<	1.4	30.0	14	2	0.1	<	170	25	40	3.10	<	0.5	<	0.3	<	<	1	<	5.7	4.3	
64E	841225	00	0.52	5.9	<	24.2	17	<	4.9	28.0	25	8	0.2	1.1	900	89	125	8.70	2	1.5	5	1.1	2	0.5	2	<	14.0	11.0	
64E	841226	00	0.14	2.3	<	2.3	8	<	1.9	33.0	6	5	0.1	<	130	32	52	2.90	<	<	<	0.3	<	<	<	4.7	2.4		
64E	841227	00	1.00	6.1	44	3.4	9	<	2.7	35.0	39	4	0.2	0.8	320	65	105	7.30	<	1.3	5	0.8	4	<	<	<	16.0	8.7	
64E	841228	00	0.57	3.0	22	1.2	6	<	1.7	25.0	22	2	0.1	0.7	230	26	37	3.10	<	0.6	<	0.3	3	<	<	<	7.0	2.8	
64E	841229	00	1.30	4.0	31	5.4	9	<	2.9	15.0	80	4	0.2	1.3	540	38	62	4.60	<	0.7	2	0.4	5	0.5	3	4	11.0	4.0	
64E	841230	00	0.39	4.7	23	4.8	9	<	2.8	35.0	26	3	0.1	1.1	170	54	72	6.20	2	1.1	2	0.6	<	<	<	13.0	5.4		
64E	841231	00	0.24	2.7	<	1.5	11	22	2.8	32.0	<	4	0.2	<	180	27	43	2.90	<	<	<	0.3	<	<	<	6.9	3.4		
64E	841232	00	1.30	4.3	22	1.7	10	<	2.2	24.0	49	4	0.2	0.9	360	41	73	4.60	1	0.7	3	0.5	4	0.8	3	<	10.4	4.3	
64E	841233	00	0.29	4.0	28	1.9	9	<	2.4	50.0	18	3	0.1	<	150	38	66	4.70	<	0.8	3	0.6	<	<	<	5	8.5	10.0	
64E	841235	00	0.91	4.7	28	3.5	7	20	3.0	35.0	36	3	0.2	1.2	270	51	85	5.70	<	1.0	3	0.6	3	<	<	<	11.0	4.9	
64E	841236	00	0.46	4.0	32	4.6	11	<	3.5	39.0	21	9	0.3	1.0	120	50	91	5.60	1	1.1	3	0.6	2	<	<	<	11.0	3.8	
64E	841237	00	1.20	5.2	34	5.7	10	<	2.7	29.0	48	5	0.2	1.1	400	59	103	6.40	1	1.0	3	0.6	6	0.8	1	<	14.0	5.6	
64E	841238	00	0.11	1.6	<	1.0	5	<	1.7	31.0	<	3	0.1	0.6	63	28	45	3.40	<	<	<	0.3	<	<	<	3	5.2	3.3	
64E	841239	00	0.48	6.0	<	14.0	13	<	7.0	47.0	23	5	0.2	<	650	94	142	10.00	<	1.6	6	0.9	2	<	<	4	<	16.0	5.3
64E	841240	00	0.13	2.0	<	2.1	7	<	1.7	27.0	<	2	0.2	<	140	49	77	5.10	<	0.6	3	0.5	<	<	<	6.8	3.9		
64E	841242	10	0.11	2.6	<	3.5	13	<	21.0	66.0	<	6	<	<	110	39	65	5.10	1	0.8	2	0.5	<	<	<	7.6	2.7		
64E	841243	20	0.15	2.7	<	3.5	15	23	20.0	68.0	<	4	<	0.7	<	39	67	5.20	1	1.0	<	0.5	1	<	<	7.7	2.8		
64E	841245	00	0.11	1.7	23	1.4	7	<	1.5	24.0	7	3	0.1	0.6	65	33	58	3.90	<	0.7	<	0.2	<	<	<	4.4	1.7		
64E	841246	00	2.00	6.3	34	2.8	7	26	1.7	9.4	110	1	0.2	2.4	680	42	66	4.70	<	0.7	2	0.4	7	1.0	1	<	14.0	3.0	
64E	841247	00	1.80	5.2	24	2.2	6	<	1.5	7.5	100	2	0.2	2.4	680	40	62	4.80	1	0.7	<	0.3	6	1.1	<	<	13.0	2.9	
64E	843002	10	1.00	7.1	38	6.7	13	20	8.4	49.0	40	8	0.3	1.3	270	95	129	8.90	2	1.6	6	1.1	5	<	5	<	19.0	6.1	
64E	843003	20	1.00	7.0	34	5.0	9	26	8.4	42.0	36	7	0.3	1.7	310	87	121	8.30	2	1.3	5	0.9	5	0.7	5	<	18.0	5.4	
64E	843004	00	1.90	5.1	32	2.8	10	<	1.7	29.0	62	3	0.1	1.1	500	49	77	4.80	<	0.6	3	0.5	8	0.6	<	3	11.0	2.7	
64E	843005	00	2.48	5.5	24	2.7	6	<	1.3	4.5	100	<	0.2	1.9	680	46	67	5.00	1	0.9	3	0.5	9	1.0	1	<	13.0	2.9	
64E	843006	00	0.29	3.4	20	1.3	11	<	2.1	28.0	14	3	0.1	1.1	160	69	119	6.50	1	0.7	3	0.4	2	<	1	<	8.2	2.7	
64E	843007	00	0.49	5.2	55	3.5	10	<	1.9	30.0	32	7	<	1.7	260	91	157	9.40	<	1.0	4	0.6	3	0.5	<	<	13.0	3.4	
64E	843008	00	0.17	3.9	<	1.7	10	<	2.3	37.0	<	8	0.1	0.8	150	120	196	11.00	<	1.5	5	0.7	1	<	<	7	11.0	5.7	
64E	843009	00	0.32	7.6	<	5.9	13	<	3.6	75.0	18	10	0.2	2.0	110	265	352	27.30	3	3.4	8	1.4	3	0.5	<	<	16.0	6.7	
64E	843010	00	0.07	4.8	<	7.4	12	<	2.0	27.0	<	3	0.2	<	110	180	316	18.00	2	1.9	5	1.0	1	<	<	<	11.0	4.9	
64E	843011	00	0.29	5.5	21	8.1	6	<	2.1	25.0	13	14	0.1	<	94	150	240	16.00	1	2.2	6	1.0	2	<	<	<	15.0	7.2	
64E	843012	00	0.38	4.8	42	3.8	11	<	1.7	28.0	14	4	<	1.5	180	150	271	18.00	2	2.1	6	1.1	2	<	<	6	16.0	8.8	
64E	843013	00	0.67	6.5	41	2.4	14	<	2.3	46.0	22	8	0.2	1.1	290	130	222	14.00	2	1.9	5	0.9	4	<	<	<	14.0	5.9	
64E	843014	00	0.33	3.1	<	2.3	6	<	1.6	18.0	7	8	<	<	180	61	94	5.30	<	0.6	2	0.5	<	<	4	<	5.8	5.6	
64E	843016	00	0.45	5.9	26	6.9	11	<	2.6	35.0	21	4	0.1	1.3	220	87	148	9.40	<	1.2	3	0.6	2	<	<	4	10.0	2.7	
64E	843017	00	0.20	5.6	22	2.2	11	<	1.2	48.0	<	4	0.1	0.5	220	98	168	10.00	3	1.2	4	0.7	<	<	<	9.0	4.3		
64E	843018	00	0.94	6.4	<	2.9	16	28	2.2	32.0	35	2	0.2	1.0	360	110	202	13.00	3	1.7	5	0.8	5	0.8	<	<	13.0	4.6	
64E	843019	00	0.48	3.8	37	2.2	12	<	2.6	33.0	19	2	0.1	1.3	220	59	105	5.90	<	0.9	2	0.4	1	<	<	<	8.1	2.2	
64E	843020	00	0.75	5.0	27	3.2	14	<	2.0	35.0	42	3	0.1	1.5	420	70	110	7.70	2	1.3	<	0.5	3	0.8	1	<	10.0	3.7	
64E	843022	00	0.36	3.8	28	1.6	12	<	1.8	33.0	17	3	0.1	1.0	280	84	139	9.20	2	1.2	2	0.4	<	<	1	<	9.4	2.7	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments														Waters							
Map	ID	ZN	UTM Easting	Northing	Rock Type	Age	Area	Dep	RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
														Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	1.0	0.5	ppm	ppm	0.2	0.2	ppb	20	0.05
Detection Limit:												2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	F-W	pH	U-W			
64E	843023	13	622961	6351559	RGPX	04	1-5	1	00	Lw	-	Br	Lgt	62	17	<	10	7	.2	410	<	<	1.09	40	57.2	3.0	35	.2	<	94	6.0	<	
64E	843024	13	619782	6351450	RGPX	04	1-5	6	00	Lw	-	Gn	Lgt	110	18	<	111	13	.4	8000	2.0	<	9.60	10	14.8	8.7	45	<	<	100	6.4	0.05	
64E	843025	13	616988	6350833	RGPX	04	1-5	4	10	Lw	-	Gn	Lgt	82	13	<	13	8	.2	410	<	<	3.50	20	17.4	3.6	35	<	<	130	6.3	<	
64E	843026	13	616988	6350833	RGPX	04	1-5	4	20	Lw	-	Gn	Lgt	84	13	<	11	8	.2	435	<	<	3.28	30	16.8	1.9	35	<	<	130	6.4	<	
64E	843027	13	612983	6350733	RGPX	04	.25-1	1	00	Lw	-	Br	Lgt	70	13	<	10	5	<	430	<	<	1.03	40	64.8	.7	20	.2	<	84	6.1	<	
64E	843029	13	610033	6350291	RGPX	04	1-5	2	00	Lw	-	Br	Lgt	70	11	<	10	5	<	350	<	<	1.53	40	58.2	2.0	25	.4	<	200	6.2	<	
64E	843030	13	605112	6351119	RGPX	04	.25-1	5	00	Lw	-	Br	Lgt	65	25	<	11	5	<	225	<	<	.93	70	49.6	1.8	30	.4	<	78	5.8	<	
64E	843031	13	602259	6351944	PSL	04	.25-1	9	00	Md	-	Br	Lgt	93	22	<	13	5	<	275	<	<	1.32	90	34.4	4.1	20	.6	<	260	6.7	<	
64E	843032	13	599611	6350721	PSL	04	1-5	2	00	Md	-	Gn	Lgt	82	12	<	10	4	.2	355	<	<	1.85	40	31.0	6.2	25	.4	<	310	6.4	0.06	
64E	843033	13	596079	6352079	PG	04	.25-1	3	00	Md	-	Br	Lgt	98	15	<	4	4	<	165	<	6	2.78	60	34.2	7.1	25	.2	<	210	6.2	0.06	
64E	843034	13	592975	6352721	PG	04	1-5	1	00	Md	-	Gn	Lgt	110	17	<	5	4	.2	250	<	16	6.70	30	36.2	7.9	35	<	<	350	6.2	0.05	
64E	843035	13	588872	6351728	PGN	04	pond	2	00	Lw	-	Br	Lgt	60	17	<	6	2	.4	50	<	<	1.30	80	41.0	2.9	25	.4	<	150	5.4	<	
64E	843036	13	585450	6351010	PGN	04	.25-1	7	00	Lw	-	Gn	Lgt	160	30	<	6	11	.4	540	<	8	10.5	70	45.2	5.8	55	.4	<	230	6.4	<	
64E	843037	13	580196	6350979	PGN	04	1-5	3	00	Md	-	Gn	Lgt	110	17	<	9	5	.8	325	<	4	1.48	50	46.4	4.8	25	.6	<	140	5.9	<	
64E	843038	13	577055	6351551	PGN	04	.25-1	4	00	Lw	-	GnBr	Lgt	170	21	<	13	6	.2	330	<	2	3.16	40	39.0	5.7	35	.4	<	230	6.2	<	
64E	843039	13	574868	6351513	PGN	04	pond	4	00	Lw	-	Gn	Lgt	100	17	<	8	5	.2	130	<	2	2.38	50	65.6	1.5	20	.4	<	140	5.6	<	
64E	843040	13	571486	6350694	PG	04	.25-1	3	00	Lw	-	Gn	Lgt	98	6	<	8	2	<	450	<	<	1.60	40	58.6	1.0	5	.4	<	180	5.9	<	
64E	843042	13	565351	6351153	PGN	04	1-5	2	00	Md	-	Br	Lgt	78	10	<	5	3	.2	375	1.0	2	3.05	60	62.8	2.1	20	.4	<	140	6.0	<	
64E	843043	13	580163	6346784	PGN	04	.25-1	6	00	Md	-	Br	-	120	20	<	6	5	<	590	<	2	9.50	80	41.4	10.9	50	.4	<	260	6.2	0.07	
64E	843044	13	584331	6349036	PGN	04	1-5	3	00	Md	-	Gn	-	65	7	<	6	12	.2	1160	<	2	4.00	10	5.0	4.3	15	<	<	210	6.3	0.05	
64E	843045	13	587800	6347619	PGN	04	.25-1	4	10	Lw	-	Br	Lgt	77	15	<	7	5	<	210	1.0	4	2.95	70	32.0	11.7	25	.2	<	330	6.2	0.15	
64E	843046	13	587800	6347619	PGN	04	.25-1	4	20	Lw	-	Br	Lgt	84	17	<	8	5	<	150	1.0	4	1.72	50	28.6	11.0	15	.4	<	350	6.2	0.16	
64E	843047	13	591133	6348266	PBG	04	.25-1	14	00	Lw	-	Br	-	120	28	<	10	5	.2	920	<	4	1.69	100	45.8	3.9	20	.6	<	140	6.4	<	
64E	843048	13	595503	6349613	PG	04	.25-1	1	00	Md	-	GnBr	-	84	9	<	5	4	<	90	<	2	.55	30	24.0	5.3	5	.4	<	190	6.2	0.05	
64E	843049	13	599594	6348629	PG	04	1-5	2	00	Lw	-	Gn	Hvy	130	15	<	16	5	<	475	<	8	2.25	110	44.0	4.3	20	.4	<	230	6.1	<	
64E	843050	13	603282	6348037	RGPX	04	.25-1	5	00	Lw	-	Gn	-	70	12	<	6	6	<	445	1.0	8	4.20	80	40.4	3.3	30	.4	<	350	6.5	<	
64E	843051	13	606814	6348636	RGPX	04	.25-1	10	00	Md	-	Gn	-	100	11	<	10	8	<	605	<	<	2.00	70	49.4	2.9	30	.4	<	100	6.2	<	
64E	843052	13	611337	6348958	RGPX	04	1-5	5	00	Md	-	Gn	Lgt	110	14	<	8	14	<	915	<	<	4.30	70	23.8	3.4	35	.2	<	130	6.4	<	
64E	843054	13	613347	6347346	RGPX	04	pond	2	00	Hi	-	Br	Lgt	64	8	<	8	8	.2	270	<	<	1.19	80	12.0	2.0	20	<	<	140	6.3	0.1	
64E	843055	13	617717	6348694	RGPX	04	1-5	14	00	Lw	-	GnGy	-	75	8	<	7	10	.2	1000	<	<	3.90	30	22.2	3.9	25	<	<	100	6.5	0.05	
64E	843056	13	620370	6348029	RGPX	04	1-5	1	00	Md	-	Br	Lgt	120	22	<	15	12	.6	280	<	2	1.65	40	26.2	3.9	30	.4	<	150	6.0	<	
64E	843057	13	624574	6346450	RGT	04	1-5	4	00	Md	-	GnBr	-	85	18	<	12	9	.4	530	1.0	<	2.17	70	44.0	3.2	30	.2	<	110	6.5	<	
64E	843058	13	627033	6348248	RGT	04	1-5	2	00	Md	-	Br	-	60	10	<	12	5	<	225	<	<	.87	30	1.2	2.2	15	.4	<	94	6.0	<	
64E	843059	13	628830	6350363	RGT	04	1-5	2	00	Md	-	Gn	-	85	15	<	12	11	<	345	<	2	1.76	50	52.6	3.3	25	.6	<	80	6.1	<	
64E	843060	13	630522	6352387	RGT	04	.25-1	2	00	Lw	-	Bk	-	110	24	<	14	8	.2	95	<	<	.97	40	67.6	3.1	30	.8	<	52			

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As 0.5	Br 0.5	Rb 5	Mo 1	Sb 0.1	Cs 0.5	Ba 50	La 2	Ce 5	Sm 0.05	Eu 1	Tb 0.5	Yb 2	Lu 0.2	Hf 1	Ta 0.5	W 0.5	Au 1	Th 0.2	U 0.2		
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
Map	ID	RS																										
64E	843023	00	0.40	3.5	28	1.5	7	<	2.0	31.0	27	3	0.1	0.8	260	62	101	5.30	2	0.6	<	0.3	<	<	1	<	8.3	2.7
64E	843024	00	1.80	10.0	37	13.0	23	<	4.1	21.0	95	4	0.2	2.6	890	100	175	10.00	<	1.5	4	0.9	7	1.1	<	3	19.0	8.8
64E	843025	10	1.40	6.7	36	4.3	16	<	2.0	19.0	83	2	0.1	3.0	570	62	103	5.90	2	0.7	3	0.5	4	0.6	2	<	13.0	3.4
64E	843026	20	1.50	7.2	31	4.4	14	29	2.5	19.0	82	2	0.2	2.6	570	62	106	6.00	<	0.9	3	0.5	4	0.8	<	<	13.0	3.4
64E	843027	00	0.12	1.8	22	1.4	9	<	1.6	34.0	<	2	<	<	170	38	65	3.40	<	<	<	0.2	<	<	<	<	3.3	0.9
64E	843029	00	0.26	2.6	21	2.4	13	<	2.5	45.0	9	3	0.1	<	190	29	48	2.70	<	<	<	0.3	<	<	<	<	4.8	1.7
64E	843030	00	0.25	4.2	21	1.4	11	<	1.6	55.0	<	4	0.1	0.6	210	64	109	6.00	2	0.7	3	0.4	<	<	<	<	6.4	2.0
64E	843031	00	0.49	4.1	36	1.7	9	<	1.4	37.0	21	5	<	1.3	230	80	114	8.30	<	1.0	3	0.5	2	<	<	<	8.3	4.0
64E	843032	00	0.54	4.2	34	2.5	10	<	1.8	24.0	21	5	0.1	0.9	230	67	103	7.50	<	1.0	3	0.6	2	<	3	3	10.0	5.9
64E	843033	00	0.28	4.0	21	1.9	<	<	1.4	31.0	<	7	<	0.5	160	120	196	14.00	<	1.9	4	0.9	<	<	1	<	12.0	7.2
64E	843034	00	0.43	5.0	25	7.7	8	<	1.7	26.0	<	15	<	0.8	210	130	206	14.00	2	2.0	5	1.0	2	<	<	<	13.0	7.3
64E	843035	00	0.06	2.5	<	0.9	<	<	1.0	27.0	<	1	<	<	69	78	133	9.40	<	1.3	4	0.6	<	<	<	4	7.3	2.6
64E	843036	00	0.66	7.9	32	12.0	15	<	2.7	32.0	39	9	0.2	1.4	210	150	234	16.00	1	2.2	6	1.2	4	<	3	<	19.0	7.3
64E	843037	00	0.56	5.5	26	3.9	10	21	2.5	39.0	17	7	0.2	1.2	200	100	168	10.00	<	1.6	4	0.7	4	0.6	<	<	13.0	5.1
64E	843038	00	0.53	5.2	32	4.2	15	<	2.8	34.0	26	4	0.2	1.6	170	100	163	11.00	<	1.7	5	0.9	3	<	<	<	15.0	5.0
64E	843039	00	0.15	2.3	<	3.2	8	<	2.7	53.0	<	4	0.2	0.6	120	32	58	3.50	<	<	<	0.3	<	<	<	4	5.4	1.7
64E	843040	00	0.07	1.4	<	2.4	10	<	3.2	49.0	<	2	<	<	120	27	44	3.10	<	<	<	0.2	<	<	1	3	2.5	0.8
64E	843042	00	0.43	3.4	36	4.0	10	<	4.2	44.0	8	5	0.2	0.5	190	28	48	3.10	<	<	<	0.3	2	<	1	3	6.3	2.1
64E	843043	00	0.16	8.0	37	11.0	8	<	3.5	33.0	<11	5	0.1	0.9	<	231	414	27.20	<	3.6	8	1.6	2	<	<	7	20.0	10.0
64E	843044	00	2.19	5.1	29	5.9	15	20	1.2	6.7	100	4	0.1	1.6	620	80	130	8.90	<	1.2	4	0.7	7	0.6	2	<	12.0	5.4
64E	843045	10	0.25	3.8	26	3.9	12	<	3.7	31.0	10	7	0.1	<	170	130	228	17.00	<	2.4	5	1.0	2	<	<	<	14.0	11.0
64E	843046	20	0.33	3.7	24	2.2	8	<	2.6	28.0	11	7	0.1	0.7	140	110	194	15.00	2	2.2	5	0.9	3	<	<	<	13.0	10.0
64E	843047	00	0.29	6.3	35	2.4	9	<	3.0	49.0	<	8	0.2	0.9	150	110	180	12.00	2	1.9	6	0.9	2	<	2	<	13.0	4.9
64E	843048	00	1.50	4.2	<	1.2	9	<	1.5	18.0	60	4	0.1	1.3	450	49	77	5.70	<	0.8	3	0.6	4	<	<	4	7.4	4.7
64E	843049	00	0.31	3.6	<	3.1	10	21	3.4	37.0	11	11	0.2	0.9	160	55	93	5.70	1	0.8	2	0.4	<	<	<	4	6.3	3.9
64E	843050	00	0.49	4.7	<	5.5	12	<	3.1	42.0	24	10	0.1	1.4	200	67	110	6.20	2	0.9	3	0.6	2	<	4	<	10.0	3.0
64E	843051	00	0.43	5.4	<	3.0	14	<	3.0	56.0	11	2	0.2	1.4	220	88	141	8.60	<	1.0	3	0.5	2	<	2	<	9.2	2.5
64E	843052	00	1.20	6.7	24	5.3	23	<	2.6	18.0	49	2	0.2	1.7	490	97	168	10.00	2	1.3	4	0.6	4	0.7	1	<	14.0	3.3
64E	843054	00	1.10	4.7	<	1.8	9	<	2.0	17.0	50	2	0.1	1.3	460	37	60	3.80	<	0.6	<	0.3	3	<	<	7.9	1.9	
64E	843055	00	2.03	8.6	53	5.2	14	<	1.9	10.0	94	2	0.2	2.0	770	67	112	7.30	2	1.0	3	0.6	8	1.0	<	<	14.0	4.2
64E	843056	00	0.71	4.4	25	2.2	17	<	3.2	29.0	41	4	0.1	1.6	310	43	75	3.90	<	<	<	0.3	2	0.6	<	3	9.4	3.4
64E	843057	00	0.73	5.9	25	2.7	12	<	2.4	34.0	48	1	0.1	1.4	380	85	138	8.20	1	1.1	3	0.5	3	0.5	<	<	13.0	3.0
64E	843058	00	1.00	4.5	28	1.5	12	<	1.7	33.0	61	2	0.1	2.0	460	46	78	5.10	1	0.7	<	0.3	3	0.7	<	<	10.0	2.8
64E	843059	00	1.10	6.0	33	2.7	14	22	2.7	28.0	54	3	0.2	2.0	470	70	108	6.20	<	0.6	3	0.4	3	0.5	<	<	12.0	3.8
64E	843060	00	0.18	5.5	47	1.6	13	<	3.0	45.0	13	3	0.2	<	140	170	278	13.00	2	1.3	4	0.7	<	<	5	11.0	3.3	
64E	843062	10	0.22	2.9	25	1.5	16	<	2.4	33.0	14	3	0.2	<	140	82	133	7.00	1	1.0	<	0.4	<	<	<	7.6	2.5	
64E	843063	20	0.26	3.1	<	1.5	10	<	1.9	35.0	<	3	<	0.6	220	91	153	7.90	1	1.0	2	0.4	2	<	2	<	8.7	2.6
64E	843064	00	1.20	7.2	57	3.9	18	<	3.1	26.0	45	2	0.2	0.9	440	100	156	10.00	<	1.3	4	0.7	5	<	1	<	13.0	3.7
64E	843065	00	0.46	3.7	32	2.2	12	<	2.2	31.0	28	2	<	<	230	69	108	6.70	1	0.9	2	0.4	1	<	<	8.8	2.4	
64E	843066	00	2.60	5.7	20	1.7	7	<	1.3	12.0	64	1	<	1.2	1200	47	78	5.10	<	0.6	2	0.3	4	0.7	<	<	7	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct 0.02	Sc ppm 0.2	Cr ppm 20	Fe pct 0.2	Co ppm 5	Ni ppm 20	As ppm 0.5	Br ppm 0.5	Rb ppm 5	Mo ppm 1	Sb ppm 0.1	Cs ppm 0.5	Ba ppm 50	La ppm 2	Ce ppm 5	Sm ppm 0.05	Eu ppm 1	Tb ppm 0.5	Yb ppm 2	Lu ppm 0.2	Hf ppm 1	Ta ppm 0.5	W ppm 1	Au ppb 2	Th ppm 0.2	U ppm 0.2		
	Map	ID	RS																									
64E	843067	00	0.21	3.3	23	0.8	6	<	1.2	27.0	7	2	<	0.9	160	59	101	6.00	1	0.7	<	0.4	<	<	<	6.5	2.6	
64E	843068	00	1.80	10.0	55	6.3	18	28	2.2	18.0	95	2	0.2	3.1	1100	88	161	8.90	2	1.2	4	0.8	7	0.8	2	<	17.0	7.9
64E	843069	00	1.00	6.7	27	2.6	10	<	2.0	40.0	64	4	0.1	2.0	500	84	135	7.40	2	1.2	2	0.5	3	0.6	2	<	13.0	4.3
64E	843070	00	1.70	8.3	32	8.7	21	25	2.3	11.0	89	3	0.2	2.4	640	81	132	8.60	2	1.2	4	0.7	6	1.1	1	<	16.0	5.2
64E	843071	00	1.20	7.5	35	9.3	17	<	2.4	21.0	72	3	0.2	2.1	520	80	138	8.30	<	1.4	4	0.6	5	0.9	<	<	16.0	4.5
64E	843072	00	0.17	5.5	32	4.5	22	<	1.9	50.0	<	3	0.1	0.7	230	76	120	8.20	2	0.9	2	0.6	<	<	<	<	6.1	4.1
64E	843073	00	0.94	5.5	26	3.3	7	<	1.7	30.0	46	7	<	1.6	330	69	115	7.40	1	1.2	3	0.7	4	0.6	3	<	11.0	6.6
64E	843074	00	0.50	5.2	<	3.7	10	<	2.6	42.0	18	8	0.2	1.2	210	75	123	8.50	1	1.3	4	0.7	3	<	2	5	9.4	6.2
64E	843075	00	0.27	2.4	<	2.9	9	<	1.9	43.0	<	7	0.1	<	120	28	44	3.20	<	0.5	2	0.3	2	<	<	<	4.9	2.2
64E	843076	00	0.43	3.9	29	6.5	10	21	2.9	31.0	14	5	0.1	0.8	220	47	84	5.70	2	0.9	2	0.5	3	<	<	<	8.4	3.1
64E	843077	00	0.09	1.8	<	0.4	8	<	1.5	33.0	<	4	0.1	<	77	29	46	3.80	<	<	<	0.3	<	<	<	<	3.9	2.3
64E	843078	00	0.16	4.5	22	4.2	8	<	2.1	66.0	<	4	0.2	0.9	100	110	181	10.00	<	1.1	4	0.5	1	<	<	<	8.9	3.1
64E	843079	00	0.07	1.0	<	0.3	<	<	0.8	18.0	<	5	<	0.5	84	24	50	2.60	<	<	<	<	<	<	<	<	3.2	1.0
64E	843082	10	0.08	5.0	29	3.5	11	<	2.4	38.0	<	7	0.1	0.7	110	180	322	18.00	2	1.9	4	0.9	2	<	<	<	18.0	5.4
64E	843083	20	0.11	4.9	34	4.0	10	<	2.7	35.0	<	6	0.1	1.0	88	180	312	18.00	2	2.0	5	0.8	<	<	<	<	17.0	5.1
64E	843084	00	1.40	5.5	27	2.4	7	<	1.6	13.0	74	2	0.2	2.3	440	65	99	7.10	<	1.1	3	0.6	5	0.9	1	<	14.0	4.2
64E	843085	00	0.20	8.9	38	12.0	5	<	2.1	21.0	<	25	0.3	<	110	278	440	31.10	3	3.7	9	2.2	3	<	<	<	24.6	22.5
64E	843086	00	0.91	5.9	32	2.0	8	<	1.6	25.0	48	13	0.1	2.4	270	79	112	8.90	<	1.4	4	1.1	3	0.7	<	<	13.0	20.1
64E	843087	00	0.82	6.1	33	5.4	16	<	3.2	30.0	28	9	0.2	1.4	320	180	297	22.40	2	3.3	8	1.6	3	<	<	<	19.0	18.0
64E	843088	00	0.14	3.1	23	1.3	9	<	1.9	27.0	<	2	0.1	<	100	120	210	15.00	2	2.1	5	0.8	1	<	<	<	10.0	5.8
64E	843089	00	0.39	2.9	24	1.7	<	<	1.4	17.0	14	5	<	0.7	130	57	85	5.00	<	0.7	<	0.4	1	<	<	<	5.6	5.5
64E	843090	00	0.13	2.9	29	5.4	13	<	2.2	36.0	<	5	<	0.6	140	66	103	5.40	<	0.7	<	0.4	1	<	<	<	6.2	3.5
64E	843091	00	0.34	6.0	<	5.0	11	<	1.3	37.0	16	3	<	0.7	140	71	120	7.70	1	1.0	3	0.5	1	<	1	<	7.7	2.4
64E	843092	00	0.33	1.9	<	1.9	8	<	2.2	23.0	18	3	0.1	0.5	210	15	32	1.70	<	<	<	<	1	<	<	<	3.7	1.2
64E	843093	00	0.18	3.1	24	1.7	13	<	1.5	22.0	8	3	<	0.6	200	59	96	4.80	<	0.6	<	0.3	<	<	<	4	5.0	1.3
64E	843094	00	0.34	2.8	21	1.2	10	<	1.9	29.0	29	3	0.1	1.0	180	39	75	4.20	<	<	<	0.3	<	<	1	3	6.7	2.3
64E	843095	00	1.80	8.7	63	3.9	15	20	2.4	10.0	140	2	0.2	4.7	780	63	104	6.80	<	1.0	2	0.6	5	1.2	2	4	19.0	5.7
64E	843096	00	1.80	8.2	56	5.9	20	30	2.5	12.0	130	2	0.2	3.9	840	60	97	7.00	1	1.1	3	0.5	5	1.2	2	<	19.0	5.5
64E	843098	00	1.50	8.4	44	3.8	16	23	2.2	19.0	98	3	0.2	2.6	690	86	139	8.40	<	1.2	4	0.7	6	0.7	<	<	16.0	6.8
64E	843099	00	1.20	5.9	41	1.5	10	<	1.6	22.0	71	2	0.2	1.9	480	47	77	5.10	<	0.8	<	0.4	3	0.8	<	3	12.0	3.0
64E	843100	00	0.81	6.0	56	3.3	11	<	1.1	39.0	33	4	0.1	1.3	380	110	183	12.00	2	1.8	4	0.9	3	0.6	3	<	12.0	8.6
64E	843103	10	0.50	8.6	77	4.5	17	<	4.0	66.0	18	5	0.2	1.3	300	150	214	14.00	3	1.7	6	1.2	4	<	<	<	15.0	11.0
64E	843104	20	0.43	7.7	47	4.3	18	23	3.6	61.0	<	6	0.2	1.2	260	130	204	13.00	2	1.7	6	1.0	3	<	<	<	14.0	10.0
64E	843105	00	2.23	5.3	38	4.0	9	<	0.8	12.0	81	4	<	1.1	610	57	95	5.80	2	0.9	2	0.5	5	<	2	<	9.2	4.5
64E	843106	00	0.27	5.4	<	15.0	15	<	3.8	37.0	10	10	0.2	0.6	180	87	155	9.30	2	1.5	4	0.7	1	<	<	<	10.0	4.3
64E	843107	00	0.89	4.9	21	7.0	12	<	2.0	20.0	34	15	0.1	1.2	340	94	151	10.00	<	1.3	4	0.7	3	<	2	<	10.0	6.2
64E	843108	00	0.09	3.7	21	3.5	11	<	1.4	32.0	<	5	0.1	0.6	80	150	242	16.00	1	2.0	5	0.9	<	<	<	<	11.0	6.0
64E	843109	00	0.06	2.9	36	4.5	10	<	1.6	27.0	<	8	<	<	61	91	162	11.00	2	1.5	3	0.7	<	<	<	<	7.0	5.0
64E	843110	00	0.21	5.0	26	6.0	13	<	2.9	34.0	12	8	0.2	0.8	88	95	159	11.00	<	1.6	5	1.0	<	<	2	6	13.0	6.5
64E	843111	00	0.50	4.9	<	2.8	11	<	2.3	32.0	23	5	0.1	1.7	190	120	205	12.00	<	1.5	4	0.8	3	<	<	<	13.0	6.6

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element:	Lake Sediment - INAA Data																											
	Units:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U	
		pct	ppm	ppm	pct	ppm	5	20	ppm	0.5	5	1	0.1	0.5	50	2	5	0.05	ppm	1	0.5	2	0.2	1	0.5	1	2	0.2
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.02	0.5	5	1	0.1	0.5	50	2	5	0.05	ppm	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2
Map	ID	RS																										
64E	843155	00	0.52	1.8	<	1.2	<	<	2.3	23.0	21	4	0.2	0.8	180	17	23	1.80	<	<	<	2	<	<	3	4.8	2.7	
64E	843157	00	0.34	2.7	34	1.0	7	<	1.8	31.0	9	4	0.3	0.6	100	29	43	3.70	1	0.5	<	0.7	1	<	1	<	7.2	12.0
64E	843158	00	0.48	2.8	<	0.8	8	<	1.7	20.0	27	4	0.1	0.9	200	33	68	4.30	<	0.9	2	1.4	<	<	<	7.2	43.0	
64E	843159	00	0.93	4.1	<	2.1	9	<	2.7	36.0	42	4	0.2	0.7	310	36	51	3.80	<	0.7	2	0.5	3	<	<	8.4	6.5	
64E	843160	00	0.34	4.9	<	2.1	11	<	2.8	39.0	16	3	0.2	0.9	180	54	88	6.60	1	1.2	3	0.7	<	<	<	4	10.0	4.5
64E	843162	00	2.59	5.7	29	2.6	7	<	2.3	24.0	110	3	0.2	1.9	680	43	68	4.60	<	0.8	3	0.6	8	1.1	<	3	14.0	6.8
64E	843163	10	1.00	4.0	27	1.6	6	<	1.7	25.0	41	3	0.2	1.0	290	30	52	3.10	<	0.7	<	0.4	3	<	<	9.4	5.6	
64E	843164	20	1.00	4.5	21	1.7	8	<	1.2	27.0	48	4	0.2	1.3	310	33	50	3.30	<	0.6	3	0.4	3	<	1	<	9.3	6.2
64E	843165	00	0.44	2.5	<	2.4	<	<	1.9	28.0	16	4	0.3	1.1	130	32	41	3.30	<	0.5	<	0.7	1	<	<	4	5.8	20.0
64E	843166	00	0.16	3.1	29	0.4	5	<	1.6	25.0	10	3	0.3	0.7	140	39	59	4.30	<	0.8	3	0.5	<	<	1	<	6.2	4.6
64E	843167	00	0.66	4.6	42	2.6	9	<	3.2	44.0	29	5	0.2	1.9	290	41	65	4.40	<	0.9	3	0.6	2	0.5	3	4	9.1	7.5
64E	843168	00	0.60	3.5	31	1.6	6	<	1.6	19.0	28	4	0.2	0.9	210	35	58	3.90	1	0.6	2	0.5	1	<	2	<	7.9	5.7
64E	843169	00	0.12	2.7	<	2.3	12	<	2.4	37.0	<	4	0.1	0.7	100	27	49	3.30	<	0.6	<	0.3	<	<	<	5.6	1.7	
64E	843170	00	0.86	3.1	<	0.9	7	<	1.1	17.0	42	2	0.1	1.0	290	25	43	2.80	<	0.6	<	0.3	1	0.5	1	<	6.3	3.3
64E	843171	00	1.40	4.3	26	2.4	9	24	2.2	24.0	57	4	0.2	1.0	420	42	66	4.70	<	0.8	<	0.4	4	0.7	3	<	11.0	3.4
64E	843173	00	0.09	2.6	<	1.8	15	<	2.1	39.0	<	2	0.1	<	130	35	58	4.00	<	0.7	<	0.3	<	<	<	6.1	2.2	
64E	843174	00	0.12	1.9	<	1.3	8	<	1.1	26.0	<	4	<	<	99	36	61	4.80	<	0.8	3	0.5	<	<	<	5.8	4.3	
64E	843175	00	1.70	7.7	33	8.1	17	<	2.5	21.0	91	5	0.2	2.1	630	64	102	7.00	<	1.2	4	0.7	6	0.8	<	3	14.0	5.3
64E	843176	00	0.12	3.5	22	2.0	9	<	2.3	43.0	<	4	0.2	<	200	65	110	6.80	<	1.1	4	0.8	<	<	<	8.4	7.0	
64E	843177	00	1.10	5.5	39	7.3	28	22	2.8	27.0	60	7	0.1	1.5	410	64	131	7.10	<	1.3	4	0.7	4	<	<	15.0	4.2	
64E	843178	00	0.18	3.1	<	1.0	14	<	2.5	76.0	<	3	0.2	0.8	160	24	37	2.70	<	<	<	0.3	2	<	<	6.5	1.9	
64E	843179	00	0.35	6.1	<	0.8	7	<	1.6	22.0	21	6	0.2	1.2	180	70	116	9.50	<	1.4	6	1.9	<	<	<	14.0	45.5	
64E	843180	00	0.46	3.4	24	4.3	13	<	1.5	25.0	21	6	0.1	<	170	44	90	5.90	<	0.8	4	0.8	1	<	<	10.0	8.5	
64E	843182	00	0.32	3.1	21	2.4	6	<	2.4	39.0	12	4	0.1	0.6	120	35	57	4.80	<	0.9	4	0.6	2	<	1	<	7.3	4.5
64E	843183	00	1.00	4.7	29	5.0	10	<	2.9	31.0	43	4	0.1	0.7	300	43	79	5.20	<	0.8	3	0.6	4	0.6	2	<	11.0	4.1
64E	843184	10	0.09	1.3	21	1.3	7	<	1.5	34.0	<	4	0.1	<	76	14	25	1.70	<	<	<	0.3	<	<	1	<	4.0	6.2
64E	843185	20	0.10	1.3	<	1.2	7	<	1.6	33.0	<	5	0.2	<	69	16	27	1.90	<	<	<	0.3	<	<	4.6	<	6.2	
64E	843186	00	0.55	4.1	<	1.5	11	<	3.1	62.0	17	4	0.3	1.0	230	46	71	5.20	2	0.9	4	0.8	3	<	<	11.0	14.0	
64E	843188	00	0.29	3.3	<	1.0	6	<	2.6	21.0	16	3	0.1	<	160	40	66	3.90	<	0.6	2	0.5	<	<	<	8.6	7.4	
64E	843189	00	0.19	2.7	<	1.1	9	<	2.1	28.0	11	2	0.1	<	130	34	54	3.80	<	0.6	<	0.4	<	<	3	7.2	5.8	
64E	843190	00	1.00	5.6	45	2.3	10	<	1.5	27.0	57	4	0.1	1.8	380	71	118	6.80	<	0.9	3	0.5	4	0.8	2	<	15.0	4.0
64E	843191	00	2.36	5.4	38	7.7	10	<	1.1	9.5	130	6	0.1	1.8	910	110	161	15.00	<	2.3	4	0.8	6	1.1	2	3	13.0	5.4
64E	843192	00	0.76	7.9	43	4.8	14	21	2.0	40.0	38	3	0.2	0.8	380	77	117	9.10	2	1.4	4	0.7	5	0.5	2	<	12.0	4.9
64E	843193	00	2.08	6.7	40	2.3	7	<	0.9	8.4	95	2	0.1	1.8	630	58	100	6.80	1	1.1	3	0.7	10	1.2	1	<	14.0	4.1
64E	843194	00	0.37	3.2	<	5.4	14	<	2.4	33.0	17	4	0.2	0.7	230	33	59	3.90	<	<	0.4	2	<	<	6.4	<	1.6	
64E	843195	00	0.87	4.6	25	1.7	11	21	2.1	32.0	32	6	0.2	1.1	340	61	110	6.80	2	1.0	3	0.5	4	0.5	1	<	10.0	4.4
64E	843196	00	0.24	2.4	<	1.3	9	<	1.8	25.0	10	4	0.1	<	170	44	63	5.50	2	0.7	<	0.4	<	<	1	<	5.4	2.0
64E	843197	00	0.36	3.3	25	1.8	14	<	2.5	59.0	11	2	0.1	1.0	230	38	64	3.80	<	<	<	0.3	2	<	1	<	6.1	2.6
64E	843198	00	1.90	9.0	37	7.8	19	21	2.0	11.0	91	3	0.2	2.4	690	83	137	8.70	<	1.6	4	0.8	8	1.1	2	4	17.0	6.2
64E	843199	00	0.88	6.4	41	3.5	13	<	2.1	28.0	46	4	0.1	2.6	480	110	180	9.00	<	1.1	3	0.6	3	0.7	<	3	13.0	5.9

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																											
Element:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U			
Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm				
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
Map	ID	RS																											
64E	843290	00	0.34	2.4	<	1.0	7	<	1.8	34.0	14	2	0.1	<	190	39	59	3.90	1	0.6	<	0.3	2	<	<	5.1	2.2		
64E	843291	00	0.10	3.5	22	4.0	12	<	1.8	35.0	7	5	0.1	<	130	68	119	6.80	<	0.9	2	0.5	<	<	2	<	8.7	4.4	
64E	843292	00	0.10	2.7	<	1.5	5	<	1.7	29.0	<	2	0.1	0.7	96	45	74	4.90	<	0.6	<	0.4	<	<	1	<	5.9	4.9	
64E	843293	00	0.09	3.5	<	0.9	11	<	2.0	36.0	<	2	0.2	<	120	76	129	7.40	1	0.9	3	0.4	<	<	<	<	6.7	2.3	
64E	843294	00	1.50	7.8	51	3.7	7	20	2.1	51.0	72	3	0.2	2.0	540	67	107	7.10	1	1.3	3	0.5	6	0.8	2	<	15.0	4.1	
64E	843295	00	1.80	5.8	23	1.3	6	<	1.2	13.0	80	2	0.2	2.5	610	41	69	4.30	<	0.8	2	0.4	6	0.9	<	<	11.0	2.5	
64E	843296	00	0.35	5.0	39	3.0	7	<	2.1	50.0	13	4	0.2	<	230	61	108	6.60	<	1.0	3	1.3	2	<	<	<	7.3	39.3	
64E	843297	00	2.11	7.7	37	2.7	10	<	1.5	9.3	85	2	0.1	1.6	760	54	90	5.90	1	1.0	3	0.6	7	0.9	<	<	13.0	5.7	
64E	843298	00	1.30	7.9	39	6.1	18	21	2.3	18.0	74	6	0.1	2.2	710	84	146	8.40	1	1.4	3	0.7	5	0.6	<	<	15.0	7.9	
64E	843299	00	0.65	6.1	36	16.0	46	23	5.3	28.0	37	7	0.1	0.9	370	110	235	10.00	2	1.3	4	0.8	2	0.5	2	<	14.0	10.0	
64E	843300	00	1.00	4.1	28	1.6	7	<	1.4	26.0	45	1	0.1	1.0	370	43	70	4.40	<	0.6	<	0.3	3	0.6	<	<	7.7	2.9	
64E	843302	00	1.20	7.3	33	18.0	32	<	2.9	17.0	79	3	<	2.2	780	85	150	7.90	<	1.3	4	0.7	3	0.7	2	<	14.0	8.2	
64E	843304	00	1.50	8.5	61	12.0	32	<	4.5	16.0	88	6	0.1	2.4	700	100	183	11.00	2	1.6	5	0.9	7	0.9	2	<	19.0	13.0	
64E	843305	00	1.60	6.3	40	2.3	8	<	1.6	19.0	99	<	0.2	2.3	740	53	90	6.30	1	1.1	<	0.4	6	0.9	<	<	14.0	5.5	
64E	843306	00	1.50	6.2	33	4.5	25	<	2.2	21.0	75	3	0.2	1.9	670	67	116	6.50	1	1.0	3	0.5	5	<	1	<	12.0	4.7	
64E	843307	10	1.30	7.7	51	5.7	22	<	2.3	20.0	73	5	0.2	2.0	620	81	150	8.00	1	1.0	3	0.7	5	0.7	<	<	14.0	10.0	
64E	843308	20	1.30	7.8	40	5.3	23	28	2.0	18.0	75	5	0.2	1.7	590	73	138	7.60	1	1.1	3	0.7	6	0.7	<	<	14.0	9.2	
64E	843309	00	0.52	4.4	36	1.9	11	<	1.5	37.0	20	2	0.1	0.8	250	75	132	7.90	<	1.1	2	0.6	2	<	<	<	7.6	10.0	
64E	843310	00	2.14	8.7	46	5.8	21	<	1.9	10.0	100	2	0.1	2.2	830	58	104	7.20	<	1.2	4	0.6	8	1.0	<	<	15.0	6.7	
64E	843311	00	0.60	7.5	32	14.0	38	25	2.5	28.0	33	5	<	1.3	520	97	170	10.00	2	1.3	4	0.8	3	<	<	<	12.0	9.0	
64E	843312	00	0.54	6.4	36	4.8	20	<	1.6	49.0	23	5	0.1	0.7	370	97	158	10.00	2	1.4	3	0.6	2	<	<	<	10.0	7.3	
64E	843313	00	0.42	4.5	24	7.7	38	<	1.8	41.0	17	2	0.1	0.6	310	77	138	7.60	1	1.1	3	0.5	2	<	<	<	7.2	5.6	
64E	843314	00	2.08	6.4	36	1.9	10	<	1.5	12.0	87	2	0.1	1.5	770	50	87	5.70	<	0.9	3	0.5	8	0.7	<	<	11.0	4.4	
64E	843315	00	1.20	6.3	28	2.6	11	<	1.8	31.0	58	2	0.1	1.7	520	58	101	6.50	<	1.1	3	0.6	4	<	<	<	11.0	6.3	
64E	843316	00	0.51	5.7	42	6.2	21	<	3.3	32.0	24	3	0.1	0.8	280	82	147	8.50	1	1.2	4	0.5	2	<	<	<	10.0	5.3	
64E	843317	00	2.60	4.6	<	1.9	6	<	1.0	6.8	95	<	<	1.0	920	32	54	3.90	<	<	0.3	6	<	<	<	7.5	1.5		
64E	843318	00	0.20	3.8	32	23.0	8	21	6.3	41.0	22	10	0.3	0.7	150	78	107	6.10	<	0.6	2	0.5	<	<	<	<	6.4	6.9	
64E	843319	00	0.30	2.5	<	1.4	5	<	2.0	48.0	13	2	0.2	0.6	200	19	34	2.00	<	<	<	2	<	<	<	3.6	0.9		
64E	843320	00	0.59	3.0	<	23.5	8	<	5.6	29.0	28	7	0.1	0.9	300	39	53	3.70	<	0.6	<	0.3	3	<	<	<	6.1	1.5	
64E	843322	10	0.39	3.7	21	1.6	11	<	1.6	33.0	21	1	0.1	0.9	230	35	68	4.20	<	0.7	<	0.5	2	<	<	<	6.7	12.0	
64E	843323	20	0.41	3.0	26	1.5	7	<	1.3	33.0	21	1	0.1	1.1	190	33	59	4.00	<	0.6	<	0.4	2	<	<	<	3	6.1	12.0
64E	843324	00	1.40	5.5	27	2.4	13	26	2.1	24.0	90	2	0.2	2.2	680	51	95	6.60	1	1.1	3	0.4	5	0.8	<	<	13.0	7.4	
64E	843325	00	1.90	5.5	28	1.2	7	<	1.0	14.0	81	<	0.2	1.7	760	41	70	4.90	<	0.9	2	0.5	8	0.7	<	5	11.0	5.9	
64E	843326	00	2.20	9.0	42	3.3	14	<	1.9	11.0	120	2	0.2	2.6	960	63	111	7.30	2	1.2	3	0.7	9	1.1	2	<	17.0	10.0	
64E	843327	00	0.21	4.1	<	2.5	8	<	1.8	43.0	<	1	<	0.5	220	94	161	9.10	1	1.1	3	0.6	<	<	<	<	7.5	8.5	
64E	843328	00	1.30	6.9	40	3.5	14	23	1.6	20.0	81	<	0.1	2.0	540	63	105	6.60	2	1.0	3	0.5	4	0.8	<	<	13.0	5.1	
64E	843329	00	0.16	3.9	<	1.5	8	<	2.1	65.0	<	1	0.2	0.8	120	50	75	5.40	1	0.8	2	0.7	2	<	<	<	5.3	21.5	
64E	843330	00	0.76	4.1	22	1.4	8	<	1.1	28.0	37	2	0.1	1.4	370	45	73	4.70	<	0.5	3	0.3	3	0.6	<	<	8.3	3.4	
64E	843331	00	0.59	3.5	24	2.1	11	<	1.6	30.0	26	2	0.1	0.9	290	49	86	5.00	<	0.8	<	0.3	2	<	<	<	7.9	3.1	
64E	843332	00	0.25	4.6	<	6.5	28	<	1.8	45.0	8	4	<	0.8	150	75	138	6.50	2	0.9	2	0.5	1	<	<	<	7.1	4.4	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data, Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																									
	Na pct 0.02	Sc ppm 0.2	Cr ppm 20	Fe pct 0.2	Co ppm 5	Ni ppm 20	As ppm 0.5	Br ppm 0.5	Rb ppm 5	Mo ppm 1	Sb ppm 0.1	Cs ppm 0.5	Ba ppm 50	La ppm 2	Ce ppm 5	Sm ppm 0.05	Eu ppm 1	Tb ppm 0.5	Yb ppm 2	Lu ppm 0.2	Hf ppm 1	Ta ppm 0.5	W ppm 1	Au ppb 2	Th ppm 0.2	U ppm 0.2
	ID	RS																								
64E 843334 00	0.28	4.7	26	2.4	8	<	1.9	39.0	13	2	<	0.5	230	66	120	7.10	<	1.2	3	0.5	2	<	<	3	7.6	5.8
64E 843335 00	0.21	2.9	<	4.3	11	<	2.1	43.0	11	3	<	0.7	140	34	62	3.60	<	0.5	2	0.3	2	<	<	<	4.6	1.2
64E 843336 00	0.10	2.1	<	2.3	8	<	1.4	29.0	<	4	0.1	<	150	40	66	3.90	<	<	<	0.2	<	<	<	<	4.2	3.4
64E 843337 00	0.53	4.3	31	2.9	10	<	1.8	35.0	21	4	<	<	250	66	108	6.30	1	0.9	2	0.4	2	<	<	<	8.1	2.3
64E 843338 00	0.68	6.7	30	11.0	18	<	2.3	36.0	38	8	0.1	1.0	400	96	175	9.40	2	1.3	4	0.6	3	0.6	<	<	12.0	6.5
64E 843339 00	0.41	4.8	31	3.3	14	<	2.4	45.0	17	3	<	1.2	280	80	140	7.80	<	0.9	3	0.6	1	<	<	<	8.9	9.4
64E 843340 00	0.63	5.8	27	4.3	9	<	1.7	35.0	33	4	0.1	0.8	350	81	122	8.00	2	1.1	3	0.6	3	<	<	<	10.0	5.7
64E 843342 00	1.40	5.7	30	3.2	6	<	1.5	20.0	69	3	0.1	1.6	610	49	83	5.80	<	1.0	<	0.4	7	0.5	<	<	10.0	3.9
64E 843343 00	1.40	7.4	44	10.0	32	<	2.1	14.0	74	6	0.1	1.6	820	86	157	10.00	1	1.6	4	0.7	6	0.8	<	<	15.0	8.0
64E 843344 00	0.47	6.3	28	3.5	17	<	3.2	46.0	20	3	0.2	1.0	220	93	155	10.00	2	1.3	4	0.7	2	<	<	<	13.0	4.4
64E 843345 00	2.34	10.0	63	2.7	15	25	2.2	21.0	150	3	0.2	4.0	900	72	134	7.60	2	0.9	4	0.6	10	1.5	<	<	22.2	6.5
64E 843346 00	0.15	3.0	23	1.7	10	<	2.1	30.0	8	2	0.1	<	83	65	109	7.90	<	1.0	<	0.4	<	<	<	3	6.3	3.1
64E 843347 00	1.60	7.0	37	6.8	24	<	1.9	19.0	54	7	0.1	1.2	640	85	173	9.50	2	1.3	4	0.7	5	<	<	<	12.0	7.9
64E 843348 00	1.30	7.2	24	6.0	19	<	1.6	16.0	50	5	0.2	1.3	540	80	148	8.80	1	1.3	4	0.7	5	0.6	<	<	13.0	5.4
64E 843349 00	0.28	4.9	35	2.5	14	<	1.8	52.0	7	3	0.1	0.8	260	69	125	6.40	1	0.8	<	0.5	<	0.5	1	5	8.3	5.2
64E 843350 00	0.45	2.8	<	1.6	9	<	1.7	22.0	14	3	0.2	0.7	230	29	54	3.10	<	0.5	<	0.3	2	<	<	<	5.1	2.5
64E 843352 10	0.51	6.0	31	5.6	14	<	2.6	41.0	27	5	0.1	<	250	83	127	8.30	1	1.1	3	0.9	2	<	<	<	10.0	22.6
64E 843353 20	0.55	6.1	42	6.1	16	<	2.6	40.0	23	7	0.1	1.0	280	87	140	8.60	2	1.0	3	1.0	3	<	<	<	11.0	24.0
64E 843354 00	0.14	2.7	<	3.4	11	<	1.7	45.0	<	5	<	<	120	38	64	3.90	<	0.5	<	0.3	<	<	<	4.7	3.6	
64E 843355 00	2.00	9.0	52	5.5	18	32	2.5	26.0	97	3	0.2	2.5	970	96	175	10.00	2	1.4	4	0.8	7	1.0	<	<	16.0	9.5
64E 843356 00	0.47	4.3	<	4.3	13	<	1.4	41.0	21	2	0.2	0.9	240	71	124	6.80	<	0.9	2	0.4	2	<	<	<	8.2	1.6
64E 843357 00	0.49	4.4	46	2.7	12	29	2.0	33.0	18	2	0.1	0.6	230	79	127	7.50	<	1.0	3	0.5	2	<	<	3	8.4	2.3
64E 843358 00	1.80	8.6	47	3.1	17	39	3.7	32.0	100	3	0.2	2.8	800	86	157	8.20	<	1.2	4	0.7	7	1.2	<	<	19.0	6.0
64E 843359 00	1.20	6.8	39	4.1	20	22	1.9	19.0	52	4	0.1	1.1	460	94	174	10.00	2	1.3	3	0.6	5	0.6	2	<	14.0	4.0
64E 843360 00	0.16	3.3	29	1.0	10	<	2.0	35.0	<	3	0.2	<	160	56	91	4.90	1	0.7	2	0.3	<	<	<	6.6	2.1	
64E 843362 00	0.89	6.0	40	2.4	7	23	2.5	56.0	48	3	0.1	1.9	490	80	123	8.90	<	1.4	3	0.5	3	<	<	<	14.0	4.5
64E 843363 10	0.29	4.8	32	4.6	16	24	2.6	46.0	<	3	0.1	0.5	210	78	127	7.20	<	0.9	3	0.5	2	<	<	8.7	2.5	
64E 843364 20	0.33	5.0	<	4.5	15	21	3.0	46.0	9	1	0.1	1.2	160	81	121	7.30	2	0.9	3	0.5	2	<	<	8.6	2.4	
64E 843365 00	0.07	1.6	<	2.2	8	<	2.8	42.0	<	3	0.1	<	120	29	51	2.90	<	<	<	0.3	<	<	<	3.5	1.7	
64E 843366 00	2.00	7.4	44	4.7	14	<	2.0	12.0	92	2	0.2	2.1	620	59	101	6.40	1	1.1	4	0.6	8	1.0	1	<	14.0	4.0
64E 843367 00	0.42	4.7	23	1.6	9	24	1.6	31.0	19	3	<	1.3	180	61	107	6.10	<	0.8	3	0.5	2	<	<	<	7.9	3.3
64E 843368 00	0.34	5.1	26	2.6	9	<	1.9	44.0	15	2	<	<	190	67	124	7.30	<	0.9	3	0.5	2	<	2	<	11.0	4.5
64E 843369 00	0.45	4.7	24	2.8	12	<	2.7	37.0	18	5	0.1	1.2	200	55	96	5.90	1	0.9	3	0.6	3	<	<	<	10.0	5.4
64E 843370 00	0.75	4.9	31	2.2	7	<	1.3	35.0	29	3	0.1	0.6	270	52	96	5.70	1	0.7	3	0.5	4	<	<	<	10.0	2.7
64E 843372 00	1.60	7.7	41	11.0	16	<	2.2	12.0	80	2	0.2	2.3	690	93	160	10.00	1	1.2	5	0.7	6	0.8	<	<	16.0	5.3
64E 843373 00	0.37	5.9	33	3.8	7	20	1.6	46.0	14	3	<	0.7	220	120	162	12.00	2	1.5	4	0.8	2	<	2	<	14.0	5.9
64E 843374 00	1.50	8.4	50	7.6	19	20	3.0	20.0	76	5	0.2	2.3	510	90	146	9.30	2	1.5	5	0.9	6	0.7	<	<	18.0	6.7
64E 843375 00	0.35	8.0	320	6.4	21	52	2.5	47.0	9	4	<	0.6	230	75	119	7.90	1	1.1	4	0.7	2	<	<	<	9.2	2.9
64E 843376 00	0.12	2.5	<	1.2	6	<	1.9	29.0	<	2	0.1	0.6	93	42	69	4.40	<	0.7	<	0.3	<	<	<	6.1	2.0	
64E 843377 00	0.24	2.9	23	2.9	9	<	2.4	36.0	17	4	0.1	0.5	150	55	100	6.60	<	1.1	3	0.5	1	<	2	<	8.0	2.3

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments													Waters											
Map	ID	ZN	UTM		Rock		Lake		Type	Age	Area	Dep	RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing														Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	10	1.0	ppm	ppm	ppm	ppm	ppb	20
Detection Limit:													2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	20	pH	0.05						
64E	843378	13	585509	6369362	PBG	04	1-5	9	00	Hi	-	Gn	-	130	15	<	12	8	<	460	<	6	5.20	61	34.2	3.2	35	.4	<	78	6.3	<					
64E	843379	13	588311	6368574	PBG	04	1-5	4	00	Md	-	Gn	-	160	12	<	9	10	.2	775	2.0	2	6.80	52	22.0	2.8	35	.4	<	140	6.0	<					
64E	843380	13	592356	6369610	PBG	04	.25-1	3	00	Md	-	Br	-	160	20	<	14	12	.2	615	<	2	4.30	78	40.6	3.6	20	.4	<	130	6.2	<					
64E	843382	13	596073	6370182	PG	04	.25-1	2	10	Md	-	Br	-	150	15	<	10	9	<	380	<	4	5.30	84	42.2	4.0	20	.4	<	320	6.4	<					
64E	843384	13	596073	6370182	PG	04	.25-1	2	20	Md	-	Br	-	190	15	<	10	9	.2	430	<	6	6.60	80	42.6	4.1	25	.4	<	290	6.5	<					
64E	843385	13	599165	6371179	PG	04	1-5	10	00	Hi	-	Gn	-	210	17	<	11	18	<	2350	1.0	8	1.11	97	25.6	9.8	40	.4	<	160	6.3	0.05					
64E	843386	13	603223	6370874	PG	04	1-5	1	00	Md	-	Br	-	26	3	<	2	3	<	145	<	4	.86	17	3.0	2.7	5	<	<	220	6.3	0.08					
64E	843387	13	604963	6370350	PG	04	.25-1	1	00	Md	-	Br	-	120	10	<	10	10	.2	275	1.0	10	3.50	74	35.6	3.2	25	.4	<	210	5.8	<					
64E	843388	13	610570	6368926	PBG	04	1-5	1	00	Md	-	Gn	-	240	10	<	10	10	.2	1060	2.0	8	10.4	148	60.4	1.7	15	.4	<	210	6.5	<					
64E	843389	13	617481	6370110	PBG	04	.25-1	3	00	Md	-	Br	Lgt	130	27	<	18	13	<	335	<	2	2.80	131	54.4	3.6	30	.6	<	86	6.1	<					
64E	843390	13	619394	6369227	PBG	04	1-5	2	00	Hi	-	Gn	-	100	15	<	17	11	.4	630	1.0	2	2.70	97	18.6	4.9	30	.4	<	88	6.3	0.05					
64E	843391	13	625247	6369245	RGPX	04	1-5	1	00	Md	-	GnGy	Lgt	73	5	<	8	9	<	730	<	2	2.80	34	6.8	3.5	25	<	<	180	6.5	0.05					
64E	843392	13	637671	6370255	RGPX	04	.25-1	4	00	Lw	-	Br	-	97	19	<	13	11	.2	435	<	2	2.50	103	39.4	2.8	45	.4	<	76	6.2	<					
64E	843393	13	637668	6373687	RGPX	04	1-5	3	00	Lw	-	Gn	-	68	12	2	10	9	<	410	<	<	1.85	108	17.6	3.1	20	<	<	76	6.4	<					
64E	843394	13	635276	6373676	RGPX	04	.25-1	1	00	Lw	-	Gn	-	90	15	3	17	13	<	435	1.0	<	2.90	60	27.0	4.9	45	<	<	120	6.2	<					
64E	843395	13	632168	6373225	RGPX	04	1-5	3	00	Md	-	Gn	-	84	11	2	14	13	.4	1110	1.0	2	4.30	78	6.6	5.1	35	<	<	140	6.5	0.05					
64E	843396	13	632341	6375422	PBG	04	1-5	4	00	Md	-	Gy	-	61	8	2	9	14	<	800	2.0	<	2.40	78	7.2	3.5	20	<	<	60	6.5	0.05					
64E	843397	13	634267	6375207	RGPX	04	1-5	2	00	Md	-	GyBr	-	44	7	2	8	10	<	575	1.0	<	2.40	72	4.8	4.2	25	<	<	120	6.4	<					
64E	843398	13	634375	6379480	PBG	04	.25-1	1	00	Md	-	Br	-	97	33	<	18	16	.4	450	1.0	4	1.29	222	53.2	5.0	30	.4	<	60	6.4	<					
64E	843399	13	637210	6378642	RGPX	04	pond	1	00	Lw	-	Br	-	120	14	2	16	11	<	365	<	2	1.93	102	65.6	3.9	35	.2	<	42	5.7	<					
64E	843400	13	637898	6385140	PBG	04	1-5	12	00	Md	-	Br	-	93	18	4	20	12	<	1130	3.0	4	2.30	156	8.8	5.8	35	.2	<	84	6.7	<					
64E	843402	13	636242	6383962	PBG	04	.25-1	1	10	Md	-	Br	-	110	23	3	18	12	<	370	<	2	2.30	52	34.2	4.4	30	.2	<	52	5.8	<					
64E	843403	13	636242	6383962	PBG	04	.25-1	1	20	Md	-	Br	-	120	22	3	18	13	<	365	<	2	2.14	43	36.2	5.0	25	.2	<	54	6.0	<					
64E	843404	13	634570	6386178	PG	04	.25-1	3	00	Md	-	Br	-	120	22	3	17	9	<	420	<	2	1.45	70	42.0	5.9	30	.2	<	84	6.5	0.06					
64E	843405	13	637343	6389495	PBG	04	1-5	1	00	Md	-	Br	-	67	19	2	14	7	<	170	<	2	.90	87	40.0	2.1	15	.2	<	70	6.6	<					
64E	843406	13	635140	6389933	PBG	04	.25-1	3	00	Md	-	Br	-	110	45	<	22	14	<	290	<	4	4.30	87	52.2	3.4	30	.2	<	56	6.1	<					
64E	843407	13	634517	6393881	PGP	04	1-5	14	00	Md	-	Gn	-	51	9	<	4	5	<	980	<	6	2.45	61	30.0	7.9	35	<	<	84	6.4	0.05					
64E	843408	13	638490	6398653	PBG	04	.25-1	3	00	Md	-	Br	-	120	15	2	14	7	<	460	<	2	2.22	52	28.6	6.2	25	<	<	140	6.4	0.06					
64E	843409	13	634169	6397408	PG	04	.25-1	1	00	Md	-	Br	-	73	13	<	11	5	<	305	<	4	1.15	70	46.2	2.8	5	.2	<	200	6.1	0.05					
64E	843410	13	631064	6397408	PG	04	.25-1	2	00	Md	-	Br	-	103	13	<	18	7	<	250	<	2	2.22	70	54.2	.7	25	.4	<	62	5.7	<					
64E	843411	13	628883	6397052	PG	04	pond	3	00	Hi	-	Br	-	150	11	<	8	5	<	180	<	2	3.60	83	35.4	8.0	20	.4	<	550	6.1	0.15					
64E	843412	13	623287	6398222	UKNN	04	.25-1	1	00	Lw	-	Br	-	96	10	2	8	6	<	50	<	2	1.95	48	29.8	3.0	25	.2	<	210	6.2	0.06					
64E	843413	13	621956	6398652	UKNN	04	1-5	6	00	Md	-	Gn	-	110	16	2	11	6	<	235	1.0	6	6.90	35	44.8	8.8	45	<	<	260	6.1	0.1					
64E	843414	13	612593	6398906	PG	04	.25-1	2	00	Md	-	Br	-	110	17	<	16	9	<	250	<	4	1.98	74	41.8	5.5	25	.2	<	130	6.0	0.11					
64E	843415	13	608303	6398698	WPSN	04	1-5	2	00	Md	-	Gn	-	100	8	<	8	9	<	280	<	4	3.00	33	14.8	2.6	20	.8									

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																										
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U	
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm		
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.5	1	0.2	1	0.2	0.2		
Map	ID	RS																										
64E	843378	00	0.21	3.9	28	6.2	12	<	2.5	30.0	17	7	0.1	1.2	130	71	126	7.60	2	1.1	3	0.5	1	<	<	<	11.0	3.1
64E	843379	00	1.20	5.4	37	7.8	13	<	4.6	30.0	58	6	0.2	2.2	470	65	109	6.90	<	1.1	4	0.6	5	0.6	3	<	14.0	3.4
64E	843380	00	0.12	3.7	26	4.8	14	<	1.9	32.0	<	5	<	<	120	80	142	8.60	2	1.3	3	0.6	1	<	<	<	11.0	3.5
64E	843382	10	0.09	3.3	26	6.0	10	<	1.2	30.0	<	7	<	0.6	92	92	163	11.00	1	1.6	4	0.7	1	<	<	<	9.3	4.5
64E	843384	20	0.10	3.4	<	7.1	14	<	1.5	31.0	<11	9	0.1	<	120	90	163	10.00	2	1.1	4	0.7	1	<	<	<	8.5	4.4
64E	843385	00	0.87	8.6	41	14.0	23	<	1.7	21.0	47	9	0.1	1.5	320	170	308	19.00	2	2.7	7	1.2	5	0.6	<2	<	22.4	8.9
64E	843386	00	2.49	3.5	<	1.6	<	<	0.6	3.1	120	3	<	1.3	730	26	43	3.00	1	<	2	0.4	8	0.7	<	<	7.1	2.2
64E	843387	00	0.55	3.6	22	4.7	11	<	2.3	26.0	27	10	0.2	1.2	210	48	85	5.20	<	0.8	3	0.6	3	0.5	3	<	9.3	3.6
64E	843388	00	0.16	3.2	<	14.0	12	<	4.5	38.0	9	8	0.2	0.7	180	43	74	4.60	<	0.7	2	0.5	<	<	<	5.0	1.5	
64E	843389	00	0.27	5.7	32	3.9	17	24	2.4	33.0	7	2	0.1	<	140	130	247	13.00	3	1.7	4	0.7	1	<	<	<	12.0	3.5
64E	843390	00	1.40	7.1	47	3.4	15	<	1.9	17.0	78	3	0.2	1.9	490	79	139	9.00	1	1.2	4	0.6	4	0.9	<	<	14.0	4.2
64E	843391	00	2.28	7.8	40	3.9	11	<	1.2	4.8	110	1	0.2	2.7	770	51	82	5.60	1	1.0	3	0.6	8	0.9	1	4	14.0	3.8
64E	843392	00	0.41	4.2	26	3.4	12	<	1.5	36.0	24	2	0.1	0.6	220	95	164	7.90	2	1.0	3	0.5	2	<	<	<	9.0	2.1
64E	843393	00	2.15	6.8	45	3.2	14	<	1.5	17.0	89	2	<	1.7	770	58	103	6.10	<	0.9	3	0.4	5	0.7	<	<	10.0	3.0
64E	843394	00	1.30	6.8	44	3.4	17	20	1.9	18.0	88	4	0.2	3.1	520	61	101	5.90	<	0.9	3	0.4	4	0.9	2	3	14.0	4.6
64E	843395	00	2.05	9.3	46	5.4	18	<	1.8	7.3	140	3	0.2	3.7	820	71	121	7.50	1	1.2	3	0.6	6	1.2	<	<	18.0	5.4
64E	843396	00	2.49	8.5	38	4.0	21	<	2.0	6.9	110	2	0.1	1.8	920	63	109	7.10	2	1.0	3	0.5	9	0.9	1	3	14.0	3.9
64E	843397	00	2.44	8.6	39	3.7	16	<	1.5	3.0	120	1	0.1	2.4	920	49	83	5.80	<	1.0	3	0.5	8	0.9	<	<	14.0	4.0
64E	843398	00	0.17	4.0	35	1.7	20	<	1.3	27.0	12	3	0.1	<	160	83	146	8.20	1	1.0	2	0.5	<	<	<	10.0	4.3	
64E	843399	00	0.81	4.5	35	2.5	13	<	2.3	25.0	70	4	0.2	2.3	380	52	90	4.90	<	0.7	<	0.3	2	0.8	<	<	10.0	2.8
64E	843400	00	1.90	8.6	49	3.0	16	<	3.1	28.0	130	3	0.2	3.8	890	66	106	7.50	<	1.3	2	0.5	7	1.2	<	<	18.0	7.5
64E	843402	10	1.20	7.0	41	3.3	18	<	2.1	31.0	64	4	0.1	2.1	530	81	132	7.70	<	1.2	3	0.6	4	0.7	<	3	14.0	4.8
64E	843403	20	1.00	6.4	41	2.8	18	<	2.5	28.0	64	4	0.2	1.6	420	83	139	7.70	2	1.2	4	0.6	3	0.6	<	<	13.0	4.7
64E	843404	00	0.56	5.0	38	1.7	13	<	1.9	49.0	31	2	0.1	1.0	250	87	157	8.10	1	1.2	3	0.6	2	<	<	<	11.0	5.9
64E	843405	00	0.36	3.2	29	1.0	10	<	1.2	26.0	21	2	0.1	1.1	190	64	116	6.40	2	0.8	2	0.3	<	<	<	<	7.6	2.5
64E	843406	00	0.17	4.8	32	4.9	17	<	1.5	40.0	<2	0.1	0.5	82	130	231	11.00	2	1.4	3	0.5	1	<	<	<	8.7	2.7	
64E	843407	00	0.91	9.0	45	10.0	22	<	2.3	38.0	56	6	0.1	2.0	410	140	207	13.00	2	1.8	6	1.0	3	0.7	2	<	18.0	7.0
64E	843408	00	0.91	5.4	25	2.6	9	20	1.1	32.0	56	3	<	1.8	400	75	120	7.20	2	1.0	3	0.6	3	0.6	<	<	12.0	5.0
64E	843409	00	0.18	2.6	21	1.2	8	<	1.1	26.0	12	5	<	<	140	63	120	7.40	2	1.1	3	0.5	<	<	<	5.9	2.9	
64E	843410	00	0.05	1.8	<	2.7	10	25	2.3	33.0	<2	<	<	<	80	46	82	4.70	<	<	<	0.3	<	<	<	5	3.1	0.9
64E	843411	00	0.14	3.5	<	3.9	7	<	1.7	22.0	<4	0.1	0.6	110	110	214	16.00	<	2.8	7	1.1	<	<	<	<	10.0	6.1	
64E	843412	00	0.28	3.1	21	2.3	8	<	1.6	15.0	16	4	0.3	1.0	130	72	129	9.20	<	1.5	5	1.0	2	<	2	<	11.0	4.8
64E	843413	00	1.10	8.8	41	8.7	8	<	2.9	21.0	67	8	0.2	2.3	320	100	167	9.00	1	1.5	7	1.1	6	0.7	<	4	22.3	9.0
64E	843414	00	0.18	3.6	21	2.3	12	<	1.8	27.0	10	6	<	0.6	94	78	147	8.30	<	1.3	3	0.8	1	<	<	5	10.0	9.0
64E	843415	00	2.00	4.4	24	4.0	13	<	1.4	10.0	93	4	0.1	1.4	540	42	74	4.30	<	0.8	3	0.5	6	0.7	<	<	11.0	2.8
64E	843416	00	1.00	3.5	24	3.1	11	<	1.8	16.0	45	2	0.2	1.3	340	36	62	3.70	<	0.7	3	0.4	4	<	<	<	8.3	3.2
64E	843417	00	0.18	3.0	26	1.4	9	<	2.5	36.0	<6	0.1	0.8	130	53	92	5.60	<	0.9	3	0.5	<	<	2	<	10.0	3.1	
64E	843419	00	0.08	1.9	<	2.5	7	20	2.3	38.0	<4	0.1	<	100	27	43	3.60	<	0.7	2	0.2	<	<	<	6.3	4.6		
64E	843420	00	0.10	2.0	<	2.4	6	<	1.2	30.0	<4	0.1	<	78	30	54	5.00	<	0.9	4	0.7	<	<	<	6.1	8.1		
64E	843422	10	0.21	2.0	20	4.4	8	<	2.2	28.0	11	4	0.1	0.6	140	17	33	2.60	<	<	3	0.4	<	<	<	4.7	3.4	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments												Waters														
Map	ID	ZN	UTM		Rock		Lake		Type	Age	Area	Dep	RS	Rlf	Cont	Colr	Susp	Variable:		Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing														Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppm	ppb	20	0.05	
Detection Limit:		2		2		2		2		2		0.2		5		1		2		0.02		10		1.0		0.5		5		0.2		0.2		F-W	pH	U-W		
64E	843423	13	588278	6398296	WPSN	04	.25-1	2	20	Md	-	Br	-	79	11	<	9	4	<	285	<	2	2.15	50	35.0	7.8	20	.2	<	130	5.9	0.11						
64E	843424	13	582552	6394346	WFN	04	1-5	9	00	Md	-	Gn	-	62	8	<	6	5	<	410	1.0	2	4.30	36	17.2	6.3	25	<	<	90	6.5	0.06						
64E	843425	13	583506	6394353	WFN	04	.25-1	3	00	Md	-	Br	-	79	13	<	11	8	<	225	<	4	1.02	43	52.4	3.4	10	.4	<	80	5.7	<						
64E	843426	13	588540	6394246	WFN	04	1-5	12	00	Md	-	Gn	-	150	16	<	8	6	<	590	<	8	6.00	93	35.8	8.0	30	.4	<	68	6.0	0.06						
64E	843427	13	592133	6394008	WFN	04	.25-1	2	00	Md	-	Br	-	73	13	<	11	7	<	160	<	4	.97	50	46.0	4.4	10	.2	<	88	6.2	<						
64E	843428	13	594147	6393502	WFN	04	.25-1	3	00	Md	-	Br	Lgt	51	9	<	10	5	<	160	<	6	.75	43	29.2	6.4	5	.2	<	140	6.5	0.11						
64E	843429	13	597571	6394742	WFN	04	1-5	13	00	Md	-	Bk	-	250	13	<	7	14	<	4500	7.0	28	29.6	36	31.0	10.2	65	<	<	86	6.7	0.05						
64E	843430	13	601638	6393623	WPSN	04	1-5	7	00	Md	-	Gn	-	120	11	<	9	8	<	505	1.0	4	4.30	50	35.4	3.4	20	.4	<	66	6.2	<						
64E	843431	13	606613	6393331	WV	04	pond	3	00	Lw	-	Br	-	67	18	<	8	3	<	95	<	2	1.08	100	46.4	27.0	25	.2	<	76	5.3	<						
64E	843432	13	609852	6393594	WQ	04	.25-1	12	00	Lw	-	Gn	-	160	30	<	10	14	<	3400	1.0	20	14.5	107	39.8	14.2	40	.2	<	120	6.3	0.08						
64E	843433	13	612938	6395557	WQ	04	1-5	2	00	Md	-	Gn	-	92	17	<	14	6	<	240	<	6	2.14	43	38.0	5.8	15	.2	<	130	6.1	0.05						
64E	843434	13	618235	6395322	UKNN	04	pond	2	00	Lw	-	Br	-	140	21	<	8	7	<	130	1.0	14	4.70	50	43.8	10.9	55	.2	<	140	5.9	<						
64E	843435	13	619632	6393164	UKNN	04	pond	1	00	Lw	-	Br	-	110	6	<	9	5	<	215	1.0	10	4.80	50	41.4	1.9	40	.2	<	180	6.3	<						
64E	843436	13	623761	6394780	UKNN	04	pond	4	00	Md	-	Br	-	90	10	<	9	8	<	320	<	14	3.05	29	29.0	5.3	20	.2	<	320	6.4	<						
64E	843438	13	627780	6393521	UKNN	04	pond	2	00	Lw	-	Br	-	210	14	<	12	4	<	215	<	2	1.40	57	45.2	3.9	<	.4	<	520	6.5	<						
64E	843439	13	631067	6394643	PG	04	.25-1	2	00	Md	-	Br	-	130	25	<	21	14	<	365	<	4	4.50	57	49.4	3.0	40	.2	<	100	6.3	<						
64E	843440	13	630423	6390409	PG	04	.25-1	5	00	Md	-	Br	-	97	26	<	15	8	<	355	<	2	2.80	100	37.6	<	25	.2	<	120	6.3	0.07						
64E	843442	13	632809	6387756	PG	04	.25-1	2	10	Lw	-	Br	-	140	23	<	10	9	<	305	<	2	1.52	57	63.4	2.6	15	.4	<	44	6.7	<						
64E	843443	13	632809	6387756	PG	04	.25-1	2	20	Lw	-	Br	-	140	23	<	12	11	<	300	<	2	1.55	61	64.2	2.6	15	.4	<	44	6.6	<						
64E	843444	13	632805	6383707	PBG	04	.25-1	2	00	Md	-	Br	-	60	8	2	7	3	<	255	<	2	.75	44	22.6	2.9	5	.2	<	86	6.6	<						
64E	843445	13	632458	6379931	PBG	04	.25-1	4	00	Md	-	Gn	-	130	34	<	22	13	<	920	<	4	4.30	70	42.2	5.4	35	.4	<	48	6.6	<						
64E	843446	13	628923	6376858	PBG	04	.25-1	1	00	Md	-	Br	Lgt	100	20	<	18	11	<	295	<	2	1.55	67	48.4	2.8	25	.4	<	52	5.9	<						
64E	843447	13	625714	6377645	PBG	04	1-5	1	00	Lw	-	GnGy	-	71	6	2	10	6	<	345	<	2	2.20	27	11.0	<	5	<	<	200	6.5	<						
64E	843448	13	621424	6377456	PG	04	.25-1	2	00	Md	-	Br	-	110	16	2	17	8	<	190	<	4	1.05	68	38.6	4.8	10	.2	<	92	6.2	<						
64E	843450	13	618526	6375617	PG	04	.25-1	2	00	Md	-	GyBr	Lgt	110	16	2	18	10	<	195	<	2	1.11	43	24.2	3.7	10	.4	<	100	6.3	<						
64E	843451	13	613514	6378210	PGP	04	pond	1	00	Lw	-	Br	Lgt	35	6	<	5	2	<	125	<	2	1.28	38	46.6	3.0	10	<	<	<	5.0	<						
64E	843452	13	608532	6375324	PGP	04	1-5	2	00	Lw	-	Br	-	125	5	<	9	7	<	195	<	4	2.21	32	27.8	3.2	10	.2	<	120	5.9	<						
64E	843453	13	606716	6377124	PGP	04	pond	1	00	Md	-	Br	-	140	8	<	10	7	<	185	<	4	1.93	54	51.8	2.7	10	.4	<	110	5.8	<						
64E	843454	13	602874	6376092	PGP	04	.25-1	8	00	Md	-	Gn	-	180	22	<	11	6	<	680	<	6	4.70	59	34.6	7.0	15	.4	<	150	6.3	<						
64E	843455	13	598401	6378124	PG	04	.25-1	2	00	Md	-	Br	-	85	18	<	9	4	<	200	<	4	1.40	54	42.4	18.9	5	.2	<	250	6.0	0.18						
64E	843456	13	596123	6376800	PG	04	1-5	4	00	Md	-	Br	-	100	20	2	19	10	<	285	<	10	1.56	76	52.4	11.5	15	.4	<	180	6.2	0.07						
64E	843457	13	593106	6375912	PG	04	1-5	2	00	Md	-	Gn	-	220	22	7	15	9	<	445	<	4	3.60	81	50.6	5.6	15	.8	<	92	5.9	0.05						
64E	843458	13	586883	6375658	WR	04	.25-1	2	00	Md	-	Br	-	83	9	<	12	5	<	310	<	2	1.54	52	43.8	2.1	15	.4	<	74	6.1	<						
64E	843459	13	583669	6377035	WS	04	.25-1	1	00	Md	-	Br	-	140	13	<	12	8	<	575	4.0	2	4.70	76	49.4	3.1	20	.4	<	66	6.2	<						
64E	843460	13	581195	6376654	WS																																	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																												
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U			
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	5	1	0.1	0.5	ppm	ppm	50	2	5	0.05	ppm	1	0.5	2	0.2	1	0.5	1	0.2	0.2
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	2	0.2	1	0.5	1	0.2	0.2
Map	ID	RS																												
64E	843423	20	0.07	2.1	<	2.2	<	<	1.7	26.0	<	3	0.1	<	<	28	55	4.60	<	0.9	4	0.7	<	<	<	<	5.6	7.4		
64E	843424	00	2.02	6.5	46	5.2	9	<	2.3	15.0	85	2	0.2	1.6	550	58	101	6.10	<	1.2	4	0.6	8	0.8	<	4	17.0	6.1		
64E	843425	00	0.28	2.8	21	1.2	9	<	2.0	36.0	11	4	0.1	0.5	130	35	63	3.90	<	0.7	<	0.4	<	<	2	<	6.7	3.7		
64E	843426	00	0.54	4.5	45	6.5	8	<	2.4	37.0	26	8	0.1	0.8	240	50	96	6.50	1	1.1	4	0.8	2	<	<	<	13.0	7.7		
64E	843427	00	0.09	2.2	<	1.2	9	<	2.2	28.0	<	5	0.1	<	86	49	98	5.70	<	0.9	3	0.6	<	<	2	<	7.2	3.9		
64E	843428	00	0.15	2.3	<	0.9	<	<	0.8	30.0	11	7	0.1	<	94	50	92	5.50	<	1.0	2	0.5	<	<	<	<	9.2	6.4		
64E	843429	00	0.52	4.1	<	35.6	23	<	8.6	25.0	35	28	0.1	0.9	360	95	129	9.20	<	1.6	6	1.1	3	<	7	<	12.0	11.0		
64E	843430	00	1.20	4.3	33	5.3	10	<	3.1	26.0	48	5	0.1	1.3	260	41	69	4.20	<	0.8	3	0.4	4	0.6	<	<	11.0	3.4		
64E	843431	00	0.16	2.4	23	1.3	<	<	1.6	41.0	6	4	0.1	<	110	48	90	5.20	1	0.9	3	0.4	1	<	<	<	7.3	3.1		
64E	843432	00	0.25	6.8	28	16.0	20	<	3.1	63.0	23	18	0.2	1.7	300	130	219	15.00	3	2.6	7	1.4	2	<	<2	<	18.0	14.0		
64E	843433	00	0.28	3.7	25	2.4	10	<	1.5	35.0	17	8	<	1.2	140	58	97	6.20	2	1.1	3	0.6	1	<	<	<	9.4	5.5		
64E	843434	00	0.45	6.1	43	5.3	12	<	3.2	34.0	34	13	0.2	1.5	220	120	209	13.00	2	2.1	8	1.3	3	<	2	6	18.0	11.0		
64E	843435	00	0.08	2.4	26	5.2	10	<	2.3	29.0	<	11	<	<	80	23	45	2.70	<	0.5	<	0.4	2	<	5	<	6.2	1.8		
64E	843436	00	0.67	3.1	22	3.4	12	<	1.7	31.0	35	14	0.2	0.8	310	34	59	4.50	1	0.8	3	0.5	4	<	6	<	8.9	4.8		
64E	843438	00	<0.04	1.8	<	1.4	<	<	<	31.0	<	3	<	<	90	77	135	15.00	<	2.5	4	0.8	<	<	<2	<	5.3	3.6		
64E	843439	00	0.17	4.0	35	4.9	21	<	2.0	31.0	9	5	0.1	<	110	74	136	7.30	1	0.9	3	0.5	1	<	<	<	9.2	2.9		
64E	843440	00	0.30	5.2	45	3.2	12	<	1.8	41.0	19	3	0.1	0.8	180	140	253	14.00	1	1.8	4	0.7	2	<	<2	<	13.0	5.0		
64E	843442	10	0.12	3.6	<	1.9	13	<	0.8	33.0	<	3	0.1	0.6	160	47	81	4.00	<	<	<	0.3	<	<	<	5.0	2.3			
64E	843443	20	0.14	3.7	23	2.0	15	<	1.6	33.0	8	3	<	0.7	150	53	88	4.60	1	0.6	<	0.4	<	<	<	5.5	2.7			
64E	843444	00	2.26	6.5	27	1.8	8	<	0.7	13.0	79	2	0.1	1.3	700	49	80	5.20	1	0.8	3	0.5	7	0.7	<	<	10.0	3.4		
64E	843445	00	0.63	7.1	49	5.6	18	26	1.2	60.0	26	5	<	1.4	340	100	181	9.40	2	1.4	4	0.7	3	<	<2	<	14.0	6.0		
64E	843446	00	0.42	4.8	36	2.2	16	<	1.4	26.0	30	3	0.1	0.8	270	96	182	10.00	2	1.3	3	0.6	2	<	<	<	11.0	3.3		
64E	843447	00	1.90	7.6	34	2.9	9	<	0.7	6.7	110	2	0.1	2.9	740	53	90	5.80	1	1.0	3	0.5	7	1.0	<	<	15.0	3.9		
64E	843448	00	0.74	4.7	35	1.5	11	<	1.7	24.0	41	3	0.2	1.5	310	77	138	8.70	2	1.2	4	0.5	3	<	<	<	12.0	4.3		
64E	843450	00	1.30	5.1	37	2.4	10	<	1.3	13.0	67	3	0.2	1.7	460	57	94	6.10	<	0.9	3	0.5	4	0.7	<	3	11.0	3.4		
64E	843451	00	1.30	4.0	<	1.8	<	<	1.5	18.0	61	2	<	1.0	390	40	65	4.30	<	0.9	3	0.5	7	0.7	2	<	12.0	3.0		
64E	843452	00	1.40	4.6	<	2.8	10	<	2.0	17.0	63	4	0.2	1.5	460	49	82	5.40	1	0.9	3	0.5	5	0.6	<	<	10.0	2.7		
64E	843453	00	0.27	2.5	<	2.4	9	<	3.0	33.0	10	5	0.2	<	160	59	110	6.40	<	0.9	3	0.5	2	<	<	<	7.0	2.4		
64E	843454	00	0.53	7.4	48	5.3	8	<	3.4	51.0	21	8	0.1	1.3	240	232	379	22.80	3	2.7	6	1.1	3	<	<3	<	20.0	7.4		
64E	843455	00	0.06	3.1	32	1.6	<	<	1.4	34.0	<	6	<	<	110	150	273	17.00	2	2.1	6	1.0	<	<	<2	<	15.0	18.0		
64E	843456	00	0.11	4.3	31	5.0	12	<	2.0	37.0	14	12	0.1	0.7	66	130	212	13.00	2	1.9	4	0.9	1	<	2	5	18.0	11.0		
64E	843457	00	0.19	3.5	22	3.8	15	<	3.1	43.0	12	6	0.2	1.2	160	100	200	17.00	<	1.8	4	0.6	1	0.5	<	<	13.0	6.7		
64E	843458	00	0.24	2.3	<	1.9	8	<	4.1	110.0	<	2	0.2	<	180	27	51	4.10	<	0.6	<	0.3	1	<	<	<	5.9	1.5		
64E	843459	00	0.37	4.2	<	5.6	12	<	8.5	53.0	23	4	0.2	0.8	220	51	88	7.10	<	1.0	3	0.5	1	<	<	<	9.4	3.4		
64E	843460	00	0.18	2.4	<	2.0	8	<	2.5	37.0	<	4	0.2	0.7	140	30	65	4.30	<	0.6	<	0.3	<	<	<	<	5.8	1.5		
64E	843462	10	0.11	3.1	28	4.5	8	<	4.7	39.0	<	3	0.4	0.7	160	76	150	11.00	<	1.4	4	0.6	1	<	1	6	6.9	3.0		
64E	843463	20	0.11	3.4	<	4.7	10	<	5.7	43.0	<	3	0.2	<	94	85	160	13.00	2	1.6	5	0.7	2	<	2	<	7.9	3.1		
64E	843464	00	0.48	4.1	32	2.4	10	<	4.0	57.0	16	3	0.2	1.0	230	34	65	4.90	<	0.7	3	0.5	2	<	2	<	7.7	1.9		
64E	843466	00	0.15	2.0	<	1.0	7	<	3.5	24.0	12	3	0.1	0.8	170	23	46	3.50	<	<	<	<	<	<	<	<	4.6	1.7		
64E	843467	00	0.11	1.5	21	0.7	<	<	1.1	22.0	<	2	<	0.6	66	27	47	4.60	<	0.5	<	<	<	<	<	<	5.1	1.7		

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments													Waters							
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep							ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppb	20	0.05		
64E	843468	13	587571	6372284	PG	04	1-5	2	00	Md	-	Br	-	51	3	<	3	5	<	210	<	<	1.75	19	5.6	2.7	10	<	<	68	6.2	<	
64E	843469	13	591103	6371561	PBG	04	.25-1	1	00	Md	-	Br	-	73	13	<	11	4	<	205	<	4	1.52	76	57.2	3.5	15	.4	<	88	5.8	<	
64E	843470	13	595364	6371623	PG	04	.25-1	3	00	Hi	-	Br	-	180	19	2	13	11	<	585	<	4	6.00	110	43.2	6.6	15	.6	<	160	5.9	0.05	
64E	843471	13	597960	6371962	PG	04	.25-1	3	00	Hi	-	Br	-	95	13	<	13	5	<	185	<	2	.87	40	29.4	8.4	10	.2	<	210	6.4	0.06	
64E	843472	13	600927	6372505	PG	04	1-5	4	00	Md	-	Br	-	31	4	<	3	3	<	205	<	2	1.31	19	5.8	3.5	10	<	<	150	6.3	0.06	
64E	843473	13	606028	6372521	PGP	04	.25-1	3	00	Md	-	Br	Lgt	130	17	<	12	7	<	555	<	8	4.90	71	35.0	7.2	20	.2	<	320	6.1	0.07	
64E	843474	13	609931	6373668	PGP	04	pond	2	00	Lw	-	Br	-	18	2	4	2	2	<	25	<	<	.13	27	12.6	1.8	<	<	<	48	3.7	<	
64E	843475	13	613684	6374348	PG	04	.25-1	2	00	Md	-	Bk	Lgt	140	9	<	12	6	<	415	<	2	4.10	64	61.0	1.4	5	.2	<	130	6.0	<	
64E	843476	13	618049	6374005	PG	04	1-5	3	00	Md	-	Br	-	77	8	2	8	4	<	545	1.0	<	2.20	41	13.2	3.0	5	.2	<	110	6.1	<	
64E	843477	13	621741	6372580	PBG	04	.25-1	3	00	Md	-	BrBk	-	110	18	3	16	11	<	760	<	4	2.27	55	40.6	7.0	20	.4	<	130	6.1	0.05	
64E	843478	13	625219	6372333	PBG	04	.25-1	1	00	Md	-	Gn	-	98	7	3	13	9	<	335	<	<	3.20	32	13.2	4.1	10	<	<	200	6.0	<	
64E	843479	13	627083	6373954	PBG	04	.25-1	4	00	Md	-	Br	-	91	11	4	15	13	<	630	1.0	2	3.40	32	10.8	4.9	30	<	<	58	6.3	<	
64E	843480	13	627773	6379104	PBG	04	pond	3	00	Md	-	Br	-	84	21	<	18	8	<	215	<	2	1.14	73	42.0	3.5	15	.4	<	56	5.8	<	
64E	843482	13	626530	6388741	PG	04	.25-1	3	10	Md	-	Gn	-	150	41	4	24	15	<	265	<	2	1.33	59	60.0	5.8	15	.6	<	78	5.3	<	
64E	843483	13	626530	6388741	PG	04	.25-1	3	20	Md	-	Gn	-	160	44	2	24	14	<	235	<	2	1.32	59	61.8	5.9	20	.6	<	72	5.3	<	
64E	843484	13	626673	6391267	PG	04	1-5	2	00	Md	-	Br	-	260	16	<	16	13	<	465	1.0	8	5.40	36	25.2	5.0	25	.2	.3	290	5.6	<	
64E	843485	13	624338	6390253	UKNN	04	.25-1	6	00	Md	-	Gn	-	110	18	5	15	5	<	180	<	6	.86	41	34.6	3.6	20	.4	<	180	5.8	<	
64E	843486	13	621639	6390014	UKNN	04	pond	1	00	Md	-	Br	-	64	9	2	5	3	<	130	<	2	1.33	64	55.2	3.0	40	.4	<	120	5.4	<	
64E	843488	13	616790	6390074	UKNN	04	pond	1	00	Lw	-	Bk	Lgt	150	5	<	10	5	<	210	<	4	2.28	59	55.0	2.6	15	.6	<	210	5.6	<	
64E	843489	13	611084	6391699	PG	04	.25-1	2	00	Md	-	Br	-	78	8	2	7	3	<	105	<	4	1.06	64	31.6	1.7	15	.4	.2	110	5.4	<	
64E	843490	13	607124	6391892	WG	04	1-5	13	00	Md	-	Gn	-	20	25	<	19	15	<	3050	1.0	12	7.40	45	24.8	15.9	30	.6	<	98	6.2	<	
64E	843491	13	603410	6390176	WR	04	1-5	5	00	Md	-	Gn	-	97	9	2	10	7	<	665	1.0	4	3.70	36	17.2	5.5	25	.2	<	96	6.1	0.05	
64E	843492	13	597730	6391465	WFN	04	1-5	3	00	Md	-	Br	-	150	9	2	10	6	<	400	<	4	4.10	73	39.8	3.3	25	.4	<	68	6.0	<	
64E	843493	13	595407	6391494	WFN	04	pond	2	00	Md	-	Br	-	59	5	<	5	2	<	100	<	2	.92	50	59.2	.7	15	.2	<	96	5.2	<	
64E	843494	13	593129	6390844	WFN	04	1-5	10	00	Hi	-	Gn	-	230	11	<	7	19	<	3500	3.0	20	24.3	77	34.0	8.1	60	.2	<	90	6.3	<	
64E	843495	13	589154	6390807	WFN	04	.25-1	2	00	Md	-	Br	Lgt	73	6	<	8	6	<	220	<	2	2.41	55	38.0	3.0	45	.2	<	74	5.7	<	
64E	843496	13	584279	6391261	WFN	04	.25-1	5	00	Md	-	Br	-	100	7	<	6	5	<	350	<	2	3.50	55	28.6	6.2	35	.2	<	82	6.0	0.07	
64E	843497	13	582130	6391496	WFN	04	1-5	5	00	Md	-	GnBk	-	150	10	<	9	7	<	495	<	2	5.20	64	28.2	8.2	45	.2	<	90	6.4	<	
64E	843498	13	578748	6390385	WFN	04	.25-1	10	00	Md	-	Br	-	110	12	<	11	6	<	450	<	2	3.35	59	46.0	6.0	25	.4	<	72	5.9	<	
64E	843499	13	563285	6390921	WFN	04	.25-1	2	00	Md	-	Br	-	53	10	<	12	5	<	200	<	2	.81	64	39.4	8.3	15	.4	<	74	6.1	0.11	
64E	843500	13	567913	6404307	WPSN	04	.25-1	5	00	Md	-	Br	-	76	10	<	8	7	<	985	1.0	2	3.10	59	36.8	4.7	30	.2	<	68	6.6	<	
64E	843502	13	570965	6400435	WPSN	04	.25-1	2	00	Md	-	Gy	-	28	5	2	5	3	<	130	<	2	.90	27	8.8	2.2	15	<	<	68	5.9	<	
64E	843503	13	573971	6402886	WPSN	04	1-5	3	00	Hi	-	Br	-	24	3	2	4	3	<	330	<	<	1.00	18	8.0	1.9	15	<	<	42	6.3	<	
64E	843504	13	571193	6404749	WPSN	04	1-5	7	00	Md	-	GnBr	-	25	<	<	3	4	<	515	1.0	2	2.28	14	4.4	2.2	10	<	<	38	6.3	<	
64E	843505	13	566639	6410307	WRN	04	pond	2	00	Md	-	Gn	-	38	8	<	8	3	<	165	<	2	1.13	23	15.4	12.1	20	<	<	100	6.8	0.18	
64E	843506	13	571098	6410347	WPSN	04	.25-1	2	00	Md	-	Br	Hvy	50	12	<	13	5	<	265	<	2	.82	36	40.8	2.6	25	.2	<	110	5.1	<	
64E	843507	13	574301	6415771	WPEG	04	pond	10	10	Hi	-	Br	-	72	20	<	12	6	<	435	<	12	1.55	59									

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC.OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct 0.02	Sc ppm 0.2	Cr ppm 20	Fe pct 0.2	Co ppm 5	Ni ppm 20	As ppm 0.5	Br ppm 0.5	Rb ppm 5	Mo ppm 1	Sb ppm 0.1	Cs ppm 0.5	Ba ppm 50	La ppm 2	Ce ppm 5	Sm ppm 0.05	Eu ppm 1	Tb ppm 0.5	Yb ppm 2	Lu ppm 0.2	Hf ppm 1	Ta ppm 0.5	W ppm 1	Au ppb 2	Th ppm 0.2	U ppm 0.2		
	Map	ID	RS																									
64E	843468 00	2.59	4.5	<	2.7	7	<	2.1	7.5	110	2	<	1.5	750	46	84	6.50	1	0.8	3	0.5	11	0.9	<	<	13.0	2.6	
64E	843469 00	0.10	2.7	30	1.8	9	<	1.3	46.0	<	5	0.2	0.8	140	52	100	7.10	<	0.8	<	0.4	<	<	<	<	7.2	2.9	
64E	843470 00	0.18	4.1	<	6.0	14	<	1.8	33.0	13	5	0.2	<	77	120	240	18.00	2	2.0	5	1.0	1	<	<	<	17.0	6.2	
64E	843471 00	0.50	3.9	<	1.0	6	<	1.6	24.0	19	2	0.1	1.2	220	120	190	18.00	2	2.1	4	0.8	2	<	<	<	13.0	7.4	
64E	843472 00	2.21	5.2	44	2.1	<	<	0.8	6.3	95	2	0.1	1.6	630	55	96	9.20	<	1.3	4	0.6	11	0.8	<	<	13.0	3.6	
64E	843473 00	0.22	4.5	28	5.0	9	<	2.1	43.0	9	9	0.2	1.3	84	100	200	15.00	<	1.7	5	0.9	<	<	<	<	14.0	7.0	
64E	843474 00	2.15	3.4	<	0.4	<	<	<	7.7	110	<	<	1.5	720	29	50	3.60	<	<	2	0.4	10	1.0	1	<	11.0	2.0	
64E	843475 00	0.05	1.2	<	3.8	8	<	1.6	49.0	<	2	0.1	<	150	24	49	4.60	<	0.5	<	0.3	<	<	<	<	2.5	1.3	
64E	843476 00	2.01	5.5	31	2.8	9	20	1.5	15.0	100	2	0.1	2.0	740	44	69	7.60	<	1.0	2	0.5	8	0.8	<	<	12.0	3.4	
64E	843477 00	0.79	5.7	36	2.8	14	31	2.2	43.0	49	6	0.1	2.3	400	67	130	8.40	1	1.0	3	0.5	3	0.7	<	<	11.0	7.8	
64E	843478 00	2.00	7.9	46	3.9	16	<	0.9	8.3	110	2	0.2	3.2	740	51	86	7.10	1	1.1	3	0.6	6	0.9	2	<	15.0	3.8	
64E	843479 00	2.06	10.0	59	4.5	18	<	2.0	12.0	120	4	0.2	3.8	800	74	140	10.00	2	1.1	4	0.6	7	1.2	<	4	18.0	5.0	
64E	843480 00	0.34	4.1	36	1.4	8	20	1.4	31.0	17	2	0.1	0.6	240	69	140	11.00	1	1.0	2	0.5	<	<	<	<	8.5	3.5	
64E	843482 10	0.37	6.6	45	2.0	22	29	2.4	54.0	19	4	0.3	1.2	230	130	240	18.00	2	1.6	7	1.1	3	<	<	<	12.0	6.6	
64E	843483 20	0.32	5.7	37	1.7	20	<	1.1	52.0	11	3	<	1.3	150	120	210	16.00	3	2.0	6	1.0	<	<	<	<	12.0	6.2	
64E	843484 00	1.40	6.6	42	8.3	22	23	2.0	21.0	78	10	<	2.7	500	66	120	10.00	<	1.5	5	0.8	5	0.7	<	<	13.0	5.7	
64E	843485 00	0.26	3.1	<	1.1	<	<	1.7	41.0	8	7	0.4	0.9	85	53	99	9.00	<	0.7	3	0.6	<	<	<	<	7.9	3.6	
64E	843486 00	0.56	4.6	23	2.2	<	<	2.5	47.0	23	4	0.3	0.6	200	54	110	7.70	<	0.9	3	0.6	2	<	<	<	12.0	2.5	
64E	843488 00	0.10	1.2	<	2.9	7	<	2.5	36.0	<	6	0.1	<	110	19	40	3.00	<	<	<	0.4	<	<	<	<	3.5	2.0	
64E	843489 00	0.11	1.4	<	1.3	<	<	1.0	25.0	<	3	0.2	<	110	28	46	4.50	<	<	<	0.3	<	<	<	<	3.4	1.6	
64E	843490 00	0.92	7.3	41	11.0	17	31	2.8	34.0	49	12	0.2	1.7	510	140	260	20.00	2	2.5	8	1.2	6	0.6	<	<	22.8	16.0	
64E	843491 00	1.70	6.8	51	4.7	11	<	2.3	22.0	93	4	0.2	3.0	580	70	120	10.00	1	1.1	4	0.7	7	0.8	2	<	17.0	5.9	
64E	843492 00	0.64	3.5	<	4.9	8	24	2.9	31.0	23	4	0.2	0.8	220	38	65	5.10	<	0.7	2	0.4	4	<	<	<	9.4	3.1	
64E	843493 00	0.08	0.6	<	1.2	<	<	2.1	39.0	<	3	0.2	<	<	7	15	1.20	<	<	<	<	<	<	<	<	1.6	0.5	
64E	843494 00	0.58	5.3	<	27.3	29	<	5.7	29.0	32	19	0.1	1.4	320	82	150	12.00	<	1.7	5	0.9	3	0.7	4	<	16.0	8.1	
64E	843495 00	0.13	2.4	32	2.5	8	<	2.1	29.0	8	3	0.2	<	150	45	84	8.20	<	1.1	3	0.4	<	<	<	<	8.4	3.0	
64E	843496 00	0.31	3.4	42	3.4	7	<	2.2	34.0	11	4	0.2	0.8	80	75	130	12.00	<	1.7	5	0.7	1	<	<	<	13.0	5.9	
64E	843497 00	1.50	7.9	66	7.7	12	<	2.9	28.0	67	4	0.2	1.5	470	87	140	12.00	2	1.5	5	0.8	5	1.0	<	<	21.7	8.8	
64E	843498 00	0.40	4.4	<	4.2	9	<	3.6	45.0	15	3	0.2	0.6	170	72	140	12.00	1	1.4	4	0.7	2	<	<	<	12.0	7.0	
64E	843499 00	0.13	3.1	<	0.9	5	<	<	28.0	<	2	0.1	0.6	72	49	88	8.00	1	1.0	<	0.4	<	<	<	<	8.0	2.6	
64E	843500 00	0.31	4.3	<	3.6	6	<	3.7	41.0	22	3	0.2	0.6	210	32	52	5.20	<	0.8	<	0.3	<	<	<	<	7.5	3.4	
64E	843502 00	1.90	6.3	41	1.3	<	<	1.9	6.2	96	1	0.2	2.0	640	32	54	4.70	<	0.6	<	0.3	7	1.1	2	<	11.0	2.3	
64E	843503 00	2.00	4.1	27	1.4	5	<	1.4	7.0	86	<	0.2	1.5	630	26	44	3.90	<	0.6	<	0.3	8	0.6	1	<	8.6	2.4	
64E	843504 00	1.90	3.5	24	2.9	5	<	1.6	4.3	80	1	0.2	1.3	570	25	44	3.60	<	<	<	0.3	8	0.5	<	<	7.9	2.2	
64E	843505 00	1.70	6.5	33	1.9	<	<	2.4	19.0	75	2	0.2	2.4	590	40	75	5.00	<	0.8	2	0.5	8	1.0	2	5	15.0	16.0	
64E	843506 00	0.42	3.6	27	1.1	5	<	2.8	27.0	23	3	0.2	0.8	200	33	61	4.80	<	0.6	<	0.3	1	<	<	<	8.4	2.6	
64E	843507 10	0.20	5.7	<	1.7	9	<	2.2	54.0	15	8	0.2	0.7	120	64	110	10.00	1	1.5	5	1.3	<	<	<	<	15.0	51.6	
64E	843509 20	0.37	5.6	32	2.8	7	26	2.2	45.0	13	13	0.2	0.7	190	67	120	9.00	1	1.7	4	1.4	2	<	<	<	5	14.0	52.1
64E	843510 00	0.16	4.6	31	2.5	14	<	2.4	32.0	11	3	0.2	<	160	38	64	6.20	<	0.9	3	0.6	1	<	<	<	7.8	7.2	
64E	843511 00	0.29	2.6	23	1.0	<	<	1.7	36.0	19	3	0.1	0.7	110	28	45	3.30	<	<	<	<	1	<	<	<	6.1	2.5	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																					Th ppm	U ppm				
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb			
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	0.5	1		
	Map	ID	RS																								
64E	843556 00	0.04	1.1	<	0.9	<	<	1.1	22.0	<	2	0.1	<	60	24	37	3.40	<	<	<	0.2	<	<	<	<	3.3	2.6
64E	843557 00	0.18	1.3	<	0.5	<	<	<	26.0	6	2	<	0.7	82	16	31	2.50	<	<	<	<	<	<	<	4	3.6	1.8
64E	843558 00	0.42	4.7	50	4.2	11	<	4.4	37.0	17	3	<	1.4	160	67	130	10.00	<	1.1	4	0.6	2	<	<	<	13.0	4.8
64E	843559 00	0.15	2.1	23	1.7	6	<	5.7	27.0	11	2	0.2	0.9	69	39	75	5.60	<	0.7	<	0.3	<	<	<	<	6.2	1.9
64E	843560 00	0.37	3.0	25	2.1	10	<	4.0	34.0	15	7	0.2	0.8	170	31	53	4.10	<	0.5	<	0.3	2	<	3	<	6.6	2.3
64E	843562 00	1.30	5.6	<	6.0	11	<	4.7	16.0	70	2	0.3	2.1	570	60	120	8.60	<	1.2	4	0.7	6	0.6	<	<	15.0	4.0
64E	843563 00	0.13	1.3	24	1.0	<	<	1.8	29.0	8	2	0.2	<	84	23	40	3.80	<	<	<	0.2	<	<	<	<	3.9	1.5
64E	843564 00	0.09	3.2	<	3.1	10	<	2.3	32.0	<	2	0.2	<	120	85	160	13.00	<	1.5	3	0.6	1	<	<	<	8.3	3.5
64E	843566 00	1.60	5.6	27	3.7	10	<	2.9	24.0	74	4	0.2	1.9	540	58	100	8.10	<	1.1	3	0.5	6	0.8	<	<	14.0	3.5
64E	843567 10	0.06	1.8	20	1.3	8	<	1.7	35.0	<	9	0.2	0.8	110	36	77	5.30	<	0.6	2	0.3	<	<	<	<	5.7	3.9
64E	843568 20	0.04	1.7	<	1.0	7	<	1.5	31.0	<	7	<	0.7	81	35	62	4.60	<	<	<	0.3	<	<	2	<	4.9	3.3
64E	843569 00	0.34	5.7	36	7.9	20	27	2.6	33.0	14	9	0.3	1.7	140	130	220	17.00	1	2.1	7	1.4	2	<	<	6	14.0	10.0
64E	843570 00	0.11	4.1	<	4.0	9	<	2.0	38.0	<	2	0.2	<	83	110	210	16.00	2	1.9	5	0.8	<	<	<	<	13.0	6.8
64E	843571 00	0.31	6.2	46	7.6	15	<	2.7	46.0	17	6	0.3	1.8	210	120	210	21.40	<	2.6	5	0.9	3	0.6	<	5	19.0	7.4
64E	843572 00	1.20	6.5	<	14.0	18	<	3.8	42.0	56	13	0.2	1.7	480	99	180	15.00	1	1.6	5	0.8	5	0.6	<	<	15.0	8.0
64E	843573 00	1.20	7.6	30	4.3	13	<	1.5	6.5	75	2	0.2	2.8	510	130	240	19.00	2	1.9	6	0.9	6	0.7	<	<	20.0	10.0
64E	843574 00	0.32	5.0	50	1.7	<	<	3.2	48.0	20	4	0.2	1.6	200	120	240	22.00	1	2.3	3	0.9	2	<	<	4	13.0	6.8
64E	843575 00	0.07	2.3	<	4.7	13	<	2.8	34.0	<	2	0.3	0.9	150	61	110	8.80	2	1.1	3	0.5	<	<	<	<	4.6	1.7
64E	843576 00	0.24	2.4	<	2.1	6	<	2.3	25.0	16	2	0.1	<	170	48	97	8.10	1	0.8	2	0.4	<	<	<	<	4.9	1.2
64E	843577 00	0.13	3.1	31	1.1	6	<	1.3	39.0	16	3	0.2	0.8	160	51	94	7.30	<	0.8	<	0.3	<	<	<	6	7.4	6.2
64E	843578 00	0.12	3.1	<	1.5	7	<	2.3	43.0	<	1	0.3	0.7	170	73	140	8.50	<	0.6	<	0.3	1	<	<	<	5.9	1.3
64E	843579 00	0.36	3.8	<	2.2	13	<	2.5	46.0	21	3	0.3	0.7	230	64	120	7.00	1	0.7	3	0.3	1	<	<	<	7.9	3.6
64E	843580 00	1.00	6.9	37	2.4	9	<	2.2	27.0	65	3	0.2	2.4	510	120	220	14.00	2	1.1	3	0.6	3	0.6	<	<	15.0	4.7
64E	843582 10	1.30	6.5	23	2.2	12	<	2.1	22.0	78	1	0.2	2.3	610	69	130	9.20	1	1.0	3	0.5	5	0.9	<	<	14.0	3.6
64E	843583 20	1.40	6.4	30	2.4	11	22	2.3	25.0	82	<	0.2	2.7	530	73	130	9.40	2	1.0	2	0.5	5	0.8	<	<	15.0	3.6
64E	843584 00	1.60	6.7	31	2.8	12	<	2.0	11.0	95	2	0.2	2.4	670	69	120	8.60	<	1.1	2	0.4	4	0.9	<	<	14.0	3.5
64E	843585 00	0.58	3.1	<	2.1	9	<	2.3	37.0	24	2	0.2	1.1	270	62	120	7.20	<	0.8	2	0.4	2	<	<	<	7.0	1.8
64E	843586 00	1.50	6.4	47	3.3	14	<	1.2	19.0	87	2	0.1	2.3	550	64	120	8.20	2	0.6	3	0.4	5	0.7	<	<	14.0	3.8
64E	843587 00	1.40	7.7	61	2.7	11	<	1.2	35.0	87	<	0.1	3.2	540	90	160	11.00	2	1.1	3	0.6	5	0.8	<	<	17.0	4.8
64E	843588 00	1.50	6.9	50	2.9	14	<	1.7	14.0	97	3	0.2	2.8	630	82	140	10.00	<	0.9	3	0.5	5	0.9	<	4	16.0	4.4
64E	843589 00	0.22	4.2	27	3.3	12	24	3.1	48.0	<	2	0.2	<	170	110	200	14.00	2	1.3	4	0.6	2	<	<	<	11.0	3.8
64E	843590 00	0.92	5.8	39	2.8	12	<	<1.4	43.0	59	3	0.2	2.3	490	150	280	18.00	<	1.6	3	0.5	3	0.6	<	8	20.2	4.8
64E	843591 00	1.00	4.5	25	3.5	9	<	2.7	33.0	57	1	0.2	1.3	480	47	78	6.20	1	0.6	<	0.4	3	0.6	<	<	10.0	2.4
64E	843592 00	1.60	5.8	43	2.1	6	<	1.1	10.0	100	3	0.1	2.8	550	63	100	7.40	<	0.8	2	0.4	5	0.7	<	<	14.0	4.0
64E	843593 00	0.51	3.4	<	13.0	22	<	4.2	55.0	19	1	0.2	<	290	44	73	4.30	1	<	<	0.3	3	<	<	6.4	1.6	
64E	843594 00	0.17	2.1	<	2.1	6	<	3.6	41.0	6	2	0.2	<	150	26	52	3.10	<	<	<	<	<	<	<	<	3.5	0.5
64E	843595 00	0.36	4.3	23	9.0	12	<	3.0	56.0	18	2	0.2	0.5	140	61	110	8.00	2	1.0	3	0.5	2	<	<	<	7.7	2.1
64E	843596 00	2.12	6.9	38	2.6	7	<	2.1	33.0	110	2	0.2	2.5	730	66	120	8.60	1	0.9	3	0.6	8	1.0	<	<	16.0	4.2
64E	843598 00	0.72	4.5	21	1.8	8	<	1.3	25.0	59	<	0.2	2.4	370	37	72	5.20	<	0.6	<	0.3	2	0.6	<	<	9.3	1.9
64E	843599 00	0.12	4.2	25	16.0	25	<	3.9	58.0	<	2	0.2	<	280	110	190	13.00	2	1.4	4	0.6	1	<	<	<	7.4	1.4

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments														Waters						
Map	ID	ZN	UTM		Rock		Lake		Rif	Cont	Colr	Susp	Variable: Zn Cu Pb Ni Co Ag Mn As Mo Fe Hg LOI U V Cd Sb F-W pH U-W																			
			Easting	Northing	Type	Age	Area	Dep					ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppb	ppb	F-W	pH	U-W				
Detection Limit:												2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	20	0.05			
64E	843600	13	676896	6361056	RNG	04	1-5	17	00	Md	-	Gn	-	170	23	4	16	5	<	960	1.0	<	3.80	83	25.2	4.7	25	.4	<	78	6.4	<
64E	843602	13	677262	6359868	RNG	04	.25-1	13	10	Md	-	Gn	-	89	14	3	14	6	<	825	1.0	<	4.10	41	15.0	3.7	30	<	<	68	6.3	<
64E	843603	13	677262	6359868	RNG	04	.25-1	13	20	Md	-	Gn	-	86	16	5	12	5	<	700	1.0	<	2.90	58	16.2	4.0	25	<	<	70	6.4	<
64E	843604	13	675209	6358809	RGT	04	.25-1	18	00	Md	-	Bk	-	120	23	<	13	5	<	2800	2.0	2	9.00	66	32.4	3.2	30	.2	<	76	6.5	<
64E	843605	13	679183	6354632	RNG	04	.25-1	9	00	Md	-	Br	-	120	23	2	18	6	<	900	1.0	<	4.60	66	30.0	3.4	25	.2	<	64	6.5	<
64E	843606	13	681618	6326071	LGD	04	pond	8	00	Md	-	BrBk	-	160	40	2	20	4	<	155	<	<	.71	66	57.4	4.2	15	.4	<	44	6.0	<
64E	843607	13	678551	6326072	LGM	04	pond	10	00	Md	-	Gn	-	170	25	<	17	15	<	720	<	2	4.60	99	56.6	10.6	45	.2	<	44	5.9	0.4
64E	843609	13	678199	6322906	LGM	04	.25-1	2	00	Lw	-	Br	-	97	20	<	19	6	<	265	<	2	2.00	83	53.8	9.8	20	.4	<	62	5.7	0.1
64E	843610	13	673223	6321628	LGD	04	.25-1	4	00	Md	-	Br	-	150	42	4	17	11	<	520	1.0	<	2.27	99	24.8	12.7	30	.4	<	78	5.9	0.17
64E	843611	13	672346	6323587	RNG	04	.25-1	4	00	Md	-	Br	Lgt	140	26	3	16	9	<	675	<	2	2.80	99	27.4	12.1	25	.4	<	88	5.9	0.12
64E	843612	13	662983	6321521	RNG	04	.25-1	3	00	Md	-	BrBk	-	130	34	<	25	5	<	145	<	2	1.13	99	40.2	2.6	10	.4	<	58	5.1	<
64E	843613	13	666486	6326239	RGT	04	.25-1	4	00	Lw	-	Br	-	190	25	3	25	11	<	450	<	2	1.90	91	42.8	4.0	30	.4	<	54	5.4	<
64E	843614	13	672439	6326024	RNG	04	.25-1	1	00	Md	-	Br	Lgt	170	38	3	20	9	<	490	1.0	<	2.50	108	51.2	5.8	30	.6	<	56	5.7	0.06
64E	843615	13	673757	6326941	LGD	04	.25-1	3	00	Md	-	Br	-	98	71	2	17	5	<	170	<	<	1.19	140	43.0	13.2	25	.4	<	72	5.9	0.18
64E	843616	13	671147	6328324	RNG	04	.25-1	3	00	Md	-	Br	-	180	47	<	13	9	<	650	<	2	6.00	75	40.4	6.8	40	.2	<	70	6.3	<
64E	843617	13	674351	6330747	LGD	04	.25-1	2	00	Md	-	BrBk	-	140	18	2	23	6	<	235	<	<	1.70	83	40.8	3.6	25	.4	<	50	5.6	0.05
64E	843618	13	665567	6337293	RMG	04	.25-1	5	00	Md	-	Gn	-	220	37	2	18	9	.2	815	<	<	1.69	71	45.2	5.5	30	.8	<	56	6.3	<
64E	843619	13	667413	6337890	RMG	04	.25-1	14	00	Md	-	Br	-	150	28	4	15	3	<	455	1.0	<	2.80	57	30.8	5.4	35	.6	<	48	6.3	0.05
64E	843620	13	674872	6337051	RMG	04	.25-1	5	00	Md	-	Br	-	240	17	<	17	8	.2	630	1.0	<	2.08	50	50.8	5.7	20	.4	<	48	6.1	0.05
64E	843622	13	679000	6336200	RGT	04	.25-1	4	10	Md	-	Br	-	180	21	3	23	5	<	115	<	<	.97	50	60.0	3.3	25	.8	<	30	5.3	<
64E	843624	13	679000	6336200	RGT	04	.25-1	4	20	Md	-	Br	-	190	22	4	23	4	<	120	<	2	1.00	43	58.8	4.0	20	.6	<	30	4.9	<
64E	843625	13	677700	6334598	RMG	04	.25-1	5	00	Md	-	Bk	-	20	19	4	25	14	.2	500	1.0	2	3.60	50	21.2	3.8	45	.4	<	82	6.4	<
64E	843626	13	680977	6333889	RMG	04	.25-1	11	00	Md	-	Br	-	140	28	<	14	6	<	500	<	2	2.29	86	28.4	2.9	30	.4	<	42	6.0	<
64E	843627	13	681000	6337500	RMG	04	.25-1	11	00	Mi	-	Bk	-	150	23	<	15	13	.2	1370	1.0	4	12.4	79	37.0	3.9	110	<	<	52	6.4	<
64E	843628	13	681216	6340606	RGT	04	.25-1	5	00	Md	-	Bk	-	70	9	<	6	3	<	435	<	2	7.70	64	64.2	2.2	25	<	<	46	6.2	<

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																									
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2
Map	ID	RS																									
64E	843600	00	1.40	7.5	43	4.4	13	<	3.6	34.0	85	2	0.2	2.5	700	77	140	10.00	2	1.2	4	0.6	6	< <2	< 18.0	4.3	
64E	843602	10	1.90	7.6	46	4.6	12	<	1.9	19.0	98	2	0.2	2.4	790	74	140	10.00	1	1.1	3	0.6	8	0.8 <2	< 17.0	4.4	
64E	843603	20	1.70	6.9	31	3.2	9	<	2.3	23.0	90	2	0.3	2.1	720	66	120	8.90	2	0.9	3	0.5	8	0.7 <2	< 16.0	3.9	
64E	843604	00	0.78	5.0	21	12.0	10	<	3.2	37.0	42	4	0.1	1.1	430	68	120	8.70	1	0.9	3	0.4	3	< <3	< 11.0	3.3	
64E	843605	00	0.74	6.4	48	5.2	11	<	2.3	38.0	39	2	0.3	1.5	370	73	130	10.00	1	1.2	3	0.6	3	0.7 <3	< 12.0	3.4	
64E	843606	00	0.38	4.8	<	0.9	9	<	1.3	66.0	10	<	0.2	0.7	230	51	91	7.20	2	0.8	2	0.4	1	< <2	< 7.5	4.7	
64E	843607	00	0.21	3.9	43	5.6	22	<	<1.0	50.0	8	2	<	<	280	67	130	8.00	<	1.0	2	0.5	2	< <2	< 6.8	11.0	
64E	843609	00	0.18	2.8	24	1.8	6	<	2.2	39.0	7	1	0.2	<	200	37	73	5.80	<	0.7	<	0.3	<	< <2	< 5.7	10.0	
64E	843610	00	1.10	6.1	35	2.2	13	<	1.8	23.0	58	1	0.2	2.2	430	50	100	8.40	<	1.0	3	0.5	4	0.7 <2	< 13.0	12.0	
64E	843611	00	1.10	6.9	37	3.2	11	<	1.7	26.0	71	1	0.2	1.6	450	73	140	11.00	1	1.5	3	0.6	4	0.7 <3	< 15.0	12.0	
64E	843612	00	0.23	3.9	<	1.3	6	<	1.1	37.0	11	3	0.1	0.7	190	31	60	4.70	1	0.5	<	0.2	1	< <2	< 5.1	2.5	
64E	843613	00	0.78	6.6	45	2.2	13	21	2.6	41.0	46	3	0.2	1.6	420	57	120	8.40	<	0.9	2	0.4	3	0.8 <2	< 12.0	4.0	
64E	843614	00	0.31	5.2	37	2.9	9	29	3.2	37.0	18	3	0.2	1.1	160	56	110	9.50	1	1.2	3	0.6	2	< <2	< 8.7	7.0	
64E	843615	00	0.26	7.0	30	1.5	6	20	2.6	53.0	13	3	0.2	0.9	180	70	140	12.00	2	1.3	4	0.6	1	< <3	< 11.0	13.0	
64E	843616	00	0.64	6.9	37	6.4	14	<	3.6	37.0	29	3	0.3	1.1	260	75	150	13.00	2	1.6	4	0.7	5	< <3	< 12.0	6.9	
64E	843617	00	0.45	3.4	43	1.8	8	<	1.1	41.0	22	3	0.2	0.8	240	59	120	10.00	1	0.8	3	0.4	3	< <2	< 7.6	3.8	
64E	843618	00	0.55	7.1	29	2.6	11	<	3.2	47.0	26	2	0.2	1.5	270	89	160	12.00	1	1.2	3	0.6	2	0.6 <3	< 12.0	5.4	
64E	843619	00	1.10	8.7	61	3.3	8	26	3.0	60.0	65	2	0.2	2.4	500	100	170	14.00	3	1.5	4	0.6	4	0.8 <3	< 18.0	5.4	
64E	843620	00	0.38	4.6	<	2.1	10	<	1.8	45.0	16	3	0.1	0.9	210	41	79	5.70	<	0.7	<	0.3	2	< <2	< 7.0	5.2	
64E	843622	10	0.66	4.8	41	1.1	9	<	2.0	58.0	25	2	0.2	0.9	300	42	77	5.40	<	<	<	0.4	3	< <4	< 6.8	3.3	
64E	843624	20	0.69	4.5	33	1.1	6	<	1.7	55.0	25	1	0.2	0.9	310	39	72	5.20	<	<	2	0.3	3	< <2	< 6.6	3.4	
64E	843625	00	1.40	7.5	47	3.2	17	<	2.5	18.0	90	3	0.3	3.5	600	63	120	8.20	2	0.9	3	0.4	4	0.8 <3	< 16.0	3.6	
64E	843626	00	0.75	4.3	32	2.0	6	<	1.0	32.0	42	2	0.1	1.0	350	50	110	8.40	1	1.1	2	0.5	3	< <2	< 8.4	2.8	
64E	843627	00	0.55	6.7	49	11.0	14	<	2.8	48.0	32	5	<	1.1	360	100	190	16.00	1	1.7	6	0.7	3	< <3	< 12.0	3.8	
64E	843628	00	0.09	2.0	<	6.0	6	<	1.7	41.0	9	2	0.1	0.5	180	31	57	5.50	<	0.8	<	0.2	2	< <3	< 5.2	2.2	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments												Waters									
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep							2	2	2	2	2	0.2	ppm	ppm	ppm	ppm	ppm	ppm	1.0	0.5	ppm	ppm	ppm	ppb	20
74A	841002	13	515976	6314834	WRQ	04	.25-1	2	00	Md	-	Br	-	64	10	<	11	4	<	120	<	2	.72	57	29.8	3.1	10	.4	<	88	6.3	0.11	
74A	841003	13	516272	6311317	PN	04	1-5	3	10	Md	-	Br	-	130	18	<	18	6	<	260	1.0	8	2.16	36	33.4	12.3	20	<	<	120	6.7	0.06	
74A	841004	13	516272	6311317	PN	04	1-5	3	20	Md	-	Br	-	130	18	<	16	6	<	240	1.0	6	1.86	21	30.4	10.6	20	.4	<	120	6.8	0.07	
74A	841005	13	513044	6312918	WRN	04	1-5	4	00	Md	-	Br	-	45	13	2	10	4	<	250	<	2	.97	<	6.8	7.0	15	.4	<	86	6.3	0.07	
74A	841006	13	511393	6314026	WRN	04	.25-1	1	00	Md	-	Br	-	45	6	2	11	3	.2	155	<	<	.61	50	38.2	8.5	10	.6	<	96	6.6	0.07	
74A	841007	13	510243	6312882	WRN	04	1-5	1	00	Md	-	Br	-	75	8	<	12	4	<	275	<	2	1.44	43	39.8	9.4	35	.4	<	92	6.8	0.07	
74A	841008	13	507781	6315021	WRN	04	.25-1	3	00	Md	-	Br	-	41	3	<	8	3	<	215	<	2	1.06	14	11.2	5.4	10	.2	<	66	6.5	0.06	
74A	841009	13	505127	6314739	WRN	04	.25-1	2	00	Md	-	Br	-	51	8	<	11	2	<	260	<	2	.81	49	41.6	5.0	20	.4	<	82	6.6	0.05	
74A	841010	13	504454	6310651	WRN	04	1-5	6	00	Md	-	Br	-	190	10	<	15	7	.2	780	1.0	2	6.60	77	30.6	7.2	35	.4	.2	64	6.5	<	
74A	841011	13	505321	6308560	WRN	04	.25-1	3	00	Md	-	Br	-	79	16	<	18	6	.2	170	<	2	.91	49	30.8	14.3	10	.6	<	72	6.2	0.05	
74A	841012	13	509142	6307846	WRN	04	.25-1	11	00	Md	-	Br	-	170	31	<	14	4	.2	680	1.0	2	1.51	182	48.2	30.7	45	1.4	<	74	6.4	0.11	
74A	841013	13	513414	6308537	WRQ	04	>5	5	00	Md	-	Br	-	100	21	<	11	4	.4	620	1.0	4	1.63	28	17.8	17.0	25	.6	<	120	6.8	<	
74A	841014	13	514799	6308412	RGM	04	.25-1	2	00	Md	-	Br	-	60	28	<	10	6	.2	610	4.0	8	26.9	70	47.8	20.1	135	<	<	120	6.5	0.05	
74A	841016	13	512634	6305440	RGM	04	1-5	7	00	Md	-	Br	-	93	28	<	14	5	<	325	<	4	1.68	70	40.6	8.4	25	.4	<	66	6.0	<	
74A	841017	13	505962	6304512	WRN	04	.25-1	15	00	Md	-	Br	-	120	21	2	11	5	<	300	1.0	2	1.65	117	45.0	22.3	50	.6	.2	86	6.8	0.07	
74A	841018	13	505642	6302306	WRN	04	.25-1	3	00	Hi	-	Br	-	130	12	<	9	5	.2	1600	1.0	2	5.00	48	47.0	7.0	30	.6	<	66	6.6	<	
74A	841019	13	508618	6303136	WPSN	04	.25-1	7	00	Md	-	Br	-	110	9	<	11	14	<	590	19.0	2	6.30	97	34.6	6.9	50	.4	.5	54	6.1	0.07	
74A	841020	13	509106	6301932	RGM	04	1-5	14	00	Md	-	Br	-	110	17	<	9	4	.2	930	5.0	2	5.50	76	41.2	10.1	40	.4	<	64	6.5	<	
74A	841022	13	511687	6300055	RGPX	04	.25-1	7	00	Md	-	Br	-	50	14	2	13	6	<	135	<	2	1.31	48	56.0	1.8	20	.8	<	38	5.9	<	
74A	841023	13	507183	6296205	RGPX	04	.25-1	7	00	Md	-	Br	-	65	16	4	13	4	.2	200	<	2	1.31	97	29.2	3.5	20	.4	<	76	6.0	<	
74A	841024	13	505066	6292382	RGPX	04	.25-1	6	00	Md	-	Gn	-	96	22	2	14	7	<	585	1.0	6	6.30	62	36.6	4.6	35	.4	<	100	6.5	<	
74A	841025	13	508412	6292643	RGPX	04	1-5	6	10	Md	-	Br	-	62	13	<	8	3	<	475	<	2	2.31	34	30.6	3.0	25	.4	<	80	6.6	<	
74A	841026	13	508412	6292643	RGPX	04	1-5	6	20	Md	-	Br	-	62	16	2	8	5	.4	550	1.0	2	2.05	62	32.4	2.9	20	.2	<	80	6.6	<	
74A	841027	13	507811	6289591	DD	04	1-5	12	00	Md	-	Br	-	150	100	3	19	8	.2	785	1.0	4	7.40	92	42.6	2.4	80	.2	<	44	6.4	<	
74A	841029	13	505656	6287082	RGPX	04	.25-1	5	00	Md	-	Br	-	130	33	2	11	5	<	315	<	<	1.80	41	59.8	1.5	45	.4	<	44	5.5	<	
74A	841030	13	503892	6281292	RGPX	04	.25-1	2	00	Md	-	Br	-	78	20	<	16	6	<	275	<	<	1.24	41	64.4	.6	20	.4	<	40	6.1	<	
74A	841031	13	501457	6284517	RGPX	04	1-5	4	00	Md	-	Gn	-	130	14	<	8	9	.2	3300	9.0	2	16.5	31	22.4	3.5	45	<	<	60	6.6	<	
74A	841032	13	502681	6287675	RGPX	04	.25-1	10	00	Md	-	Br	-	140	18	2	6	5	.2	205	<	2	.94	21	56.4	1.4	15	.4	<	56	6.3	<	
74A	841033	13	504721	6288849	RGPX	04	.25-1	1	00	Md	-	Br	-	70	12	<	7	4	<	720	<	2	2.09	15	18.4	2.5	15	<	<	62	6.5	<	
74A	841034	13	500788	6290452	WRN	04	.25-1	3	00	Md	-	Br	-	140	20	<	19	24	<	825	3.0	6	10.6	67	28.6	6.5	60	<	<	84	6.6	0.05	
74A	841035	13	502563	6293841	WPSN	04	1-5	8	00	Md	-	Br	-	40	4	<	6	19	.2	475	3.0	2	2.53	15	4.6	3.8	10	.2	<	64	6.6	0.06	
74A	841036	13	505064	6298314	WSH	04	1-5	2	00	Md	-	Br	-	190	17	<	25	11	<	700	6.0	2	6.10	67	38.0	16.0	45	.4	<	60	6.3	0.11	
74A	841037	13	501517	6298821	WRN	04	.25-1	7	00	Md	-	Br	-	98	15	<	14	4	.4	560	<	2	3.15	62	41.4	20.2	30	.6	<	62	6.6	0.06	
74A	841038	13	502671	6301990	WRN	04	1-5	2	00	Md	-	Br	-	96	17	<	8	3	<	675	1.0	2	4.90	41	48.8	6.9	30	.4	<	58	6.6	<	
74A	841039	13	501149	6304154	WRN	04	1-5	1	00	Md	-	Br	-	110	14	<	10	3	<	510	<	2	3.10	36	47.2	3.0	25	.4	<	60	6.7	<	
74A	841040	13	501536	6308436	WPSN	04	.25-1	1	00	Md	-	Gn	-	75	3	<	8	2	<	540	<	<	2.75	26	38.2	3.4	25	<	<	50	6.5	<	
74A	841042	13	500968	6310421	WRN	04	.25-1	3</																									

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																										
Element:	Units:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mg	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U	
	Detection Limit:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	
Map	ID	RS																										
74A	841002	00	0.15	2.0	<	0.7	6	<	1.6	30.0	<	2	<	0.9	<	51	80	8.30	1	0.9	<	0.4	<	<	<	6.0	3.2	
74A	841003	10	0.73	7.6	55	3.1	9	<	4.0	33.0	15	7	0.2	0.6	290	170	230	24.40	2	2.9	8	1.4	5	<	<	<	20.0	11.0
74A	841004	20	1.10	8.5	67	3.2	14	<	5.1	35.0	40	7	0.2	1.2	310	190	260	27.50	4	2.8	9	1.6	5	<	2	<	23.3	13.0
74A	841005	00	2.53	7.0	30	1.8	7	<	2.1	9.3	110	3	0.3	1.8	830	59	100	8.40	<	1.0	4	0.7	13	1.2	<	<	16.0	10.0
74A	841006	00	0.25	3.0	24	0.9	<	<	1.6	28.0	<	2	0.2	0.8	130	50	85	8.50	2	1.1	3	0.5	<	<	<	<	8.0	8.2
74A	841007	00	0.17	4.6	32	1.9	<	<	2.2	36.0	9	3	0.4	<	140	93	120	18.00	2	2.2	6	1.1	<	0.6	<	<	13.0	9.4
74A	841008	00	2.15	6.2	31	2.1	9	<	2.2	18.0	79	<	0.3	1.2	660	49	75	7.00	1	1.0	3	0.7	10	0.8	<	<	14.0	5.8
74A	841009	00	0.10	4.2	25	1.0	<	<	2.5	38.0	<	2	0.5	<	120	39	74	6.90	<	1.0	3	0.5	<	<	<	5	7.9	5.2
74A	841010	00	0.90	10.0	41	6.6	11	21	4.2	39.0	39	3	0.4	1.5	330	99	150	16.00	3	2.0	6	1.1	6	0.5	2	<	18.0	7.3
74A	841011	00	1.30	8.7	54	1.8	9	<	2.7	36.0	54	2	0.5	1.3	460	92	160	15.00	2	2.1	6	1.2	6	0.7	<	<	20.1	17.0
74A	841012	00	0.33	9.4	52	2.0	9	<	4.9	64.0	<11	5	0.5	1.2	260	252	350	42.00	4	4.6	12	2.4	3	0.8	<	<	30.1	30.3
74A	841013	00	0.44	6.4	34	1.8	6	<	2.3	32.0	23	3	<	1.0	260	130	200	19.00	2	2.2	5	1.3	3	<	<	<	15.0	18.0
74A	841014	00	0.46	18.0	78	33.8	8	<	7.9	34.0	24	7	0.2	<	190	384	710	67.40	8	7.1	20	3.9	5	0.9	<	<	37.4	23.6
74A	841016	00	0.36	4.9	36	2.1	<	<	1.8	52.0	16	3	0.2	1.1	190	79	140	10.00	1	1.2	3	0.6	<	<	11.0	9.1		
74A	841017	00	0.08	6.8	54	2.0	10	<	3.3	58.0	<13	4	1.0	<	<	329	250	59.10	6	6.3	13	2.6	1	<	<	<	12.0	23.3
74A	841018	00	0.38	4.0	<	5.4	6	<	2.9	33.0	<	2	0.3	<	370	77	130	12.00	<	1.3	3	0.7	1	<	<	<	7.5	8.4
74A	841019	00	0.27	4.2	27	5.0	20	<	21.0	26.0	22	3	0.2	0.7	170	76	150	13.00	<	1.4	4	0.7	<	0.5	1	<	11.0	6.4
74A	841020	00	0.40	5.4	36	6.3	7	29	8.0	46.0	19	3	0.2	1.1	360	87	150	15.00	2	2.1	5	0.7	2	0.7	<	<	14.0	12.0
74A	841022	00	0.59	5.5	40	2.1	13	<	4.5	66.0	22	4	0.3	0.7	230	44	88	5.50	<	0.9	2	0.4	4	<	<	<	10.0	2.1
74A	841023	00	1.40	6.4	50	2.0	6	<	1.3	31.0	66	2	0.1	1.4	560	72	130	10.00	<	1.1	3	0.4	6	0.8	<	<	12.0	3.0
74A	841024	00	0.88	6.6	53	7.3	11	<	3.5	39.0	35	7	0.1	1.0	410	100	180	13.00	<	1.5	4	0.7	5	0.6	<	<	15.0	4.2
74A	841025	10	1.20	5.9	38	3.2	5	<	1.5	25.0	39	2	0.1	0.9	480	55	100	7.90	<	1.0	3	0.5	5	0.6	<	<	10.0	2.6
74A	841026	20	1.40	7.8	29	3.9	8	27	2.2	40.0	63	2	0.2	1.5	610	73	130	11.00	2	1.5	4	0.6	6	<	<	<	13.0	3.7
74A	841027	00	0.35	13.0	44	7.3	9	<	3.3	54.0	19	2	0.2	<	220	110	190	14.00	2	1.3	4	0.6	2	<	<	<	13.0	2.6
74A	841029	00	0.17	3.4	26	2.4	13	<	2.1	60.0	<	2	0.1	0.5	190	59	120	9.10	2	0.9	3	0.3	<	<	<	<	5.9	1.8
74A	841030	00	0.10	2.3	42	1.8	12	<	2.7	53.0	<	2	0.2	<	140	27	56	4.10	<	<	0.3	<	<	<	<	3.8	1.0	
74A	841031	00	1.20	6.7	34	15.0	14	<	11.0	29.0	44	4	0.1	0.7	440	77	130	11.00	2	1.1	4	0.7	5	<	1	<	11.0	3.4
74A	841032	00	0.38	3.3	<	1.0	6	<	2.0	39.0	10	4	0.1	0.5	180	31	52	4.60	<	0.6	<	0.3	1	<	<	<	5.2	1.8
74A	841033	00	2.21	6.8	35	3.0	15	<	1.9	16.0	67	2	0.1	0.7	730	49	94	7.70	1	1.1	3	0.5	7	0.6	3	<	7.9	2.4
74A	841034	00	1.30	11.0	64	11.0	31	39	4.8	30.0	44	7	0.2	1.4	280	100	190	15.00	2	1.8	5	0.9	4	0.7	<	<	20.0	7.0
74A	841035	00	2.51	5.6	39	3.3	25	<	3.9	5.3	84	3	0.1	1.4	710	40	73	6.50	1	0.9	3	0.5	8	0.7	<	<	9.1	4.0
74A	841036	00	0.48	5.9	41	6.3	17	29	10.0	50.0	20	3	0.3	0.5	250	80	150	14.00	3	1.8	6	1.0	3	<	<	<	16.0	16.0
74A	841037	00	0.25	8.3	49	3.2	10	<	2.9	38.0	<	2	0.2	1.5	98	215	310	36.80	5	3.6	8	1.4	2	<	<	<	21.1	20.0
74A	841038	00	0.21	3.6	37	4.5	6	<	2.8	27.0	9	3	0.3	<	170	58	90	9.40	1	1.1	3	0.5	1	<	<	<	7.9	6.5
74A	841039	00	0.69	4.3	<	3.6	7	<	2.8	20.0	26	2	0.2	0.7	300	49	82	8.50	<	1.0	3	0.6	4	<	<	<	10.0	3.7
74A	841040	00	1.00	5.0	29	3.3	<	<	2.3	17.0	31	3	0.2	0.5	300	45	90	7.30	<	0.8	3	0.6	3	<	1	<	10.0	3.2
74A	841042	10	0.46	8.2	38	6.5	7	<	6.2	35.0	23	5	0.5	0.6	170	73	160	13.00	2	1.6	6	1.0	3	<	<	<	13.0	10.0
74A	841043	20	0.42	7.3	34	5.9	9	<	6.4	31.0	19	5	0.6	0.9	150	65	140	12.00	2	1.6	5	0.9	2	<	<	<	13.0	10.0
74A	841044	00	0.54	5.6	44	5.8	6	<	2.9	28.0	30	4	0.2	0.9	220	66	110	11.00	2	1.2	4	0.7	2	<	<	<	12.0	4.9

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments													Waters								
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:		Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep						Br	2	2	2	2	2	0.2	ppm	ppm	ppm	ppm	ppm	1.0	0.5	ppm	5	0.2	0.2	ppb	20	0.05
74H	841002	13	557737	6355969	PGN	04	pond	2	00	Md	-	Br	-	16	<	<	2	2	<	85	<	<	.81	21	4.8	1.4	10	<	<	120	6.6	<		
74H	841003	13	554864	6355525	WRN	04	1-5	2	10	Md	-	Br	-	80	12	2	13	3	.2	300	2.0	4	3.20	77	37.2	6.0	25	.6	<	140	6.4	0.06		
74H	841004	13	554864	6355525	WRN	04	1-5	2	20	Md	-	Br	-	81	13	<	13	4	<	330	1.0	6	4.42	56	34.6	6.8	20	.4	<	130	6.5	0.06		
74H	841005	13	551894	6355744	WRN	04	1-5	11	00	Md	-	Br	-	260	20	<	28	60	.2	4950	2.0	16	15.8	87	37.4	10.2	60	.8	<	96	6.2	0.05		
74H	841006	13	547654	6354680	WFN	04	1-5	5	00	Md	-	Br	-	120	13	<	8	9	.2	970	<	4	4.80	51	23.8	5.3	20	.2	<	90	6.0	<		
74H	841007	13	545050	6356484	WFN	04	>5	5	00	Md	-	Br	-	83	10	<	8	5	<	490	<	2	6.80	26	14.8	6.0	25	<	<	98	6.3	0.06		
74H	841008	13	541170	6353422	WFN	04	1-5	3	00	Md	-	Br	-	84	9	<	9	5	.2	340	1.0	2	3.52	36	17.2	5.6	25	.6	<	100	6.3	0.06		
74H	841009	13	539176	6355399	WRN	04	1-5	2	00	Md	-	Br	-	102	12	<	14	5	<	200	<	<	1.13	36	47.2	4.7	20	.6	<	66	6.1	<		
74H	841010	13	535243	6356673	WRN	04	>5	13	00	Md	-	Br	-	88	13	<	12	4	<	475	<	<	2.65	72	28.6	7.6	25	.2	<	66	6.3	0.06		
74H	841011	13	532365	6355472	WCN	04	pond	1	00	Md	-	Br	-	65	10	<	10	4	.2	125	<	<	.48	46	31.4	6.2	10	.4	<	94	6.2	0.07		
74H	841012	13	527557	6355573	WRN	04	pond	4	00	Lw	-	Br	Lgt	43	2	<	8	2	<	125	<	<	.41	51	25.0	2.3	10	.2	<	58	6.1	0.05		
74H	841013	13	524840	6356326	WRN	04	pond	6	00	Md	-	Br	-	22	4	<	7	2	<	145	2.0	2	1.12	21	10.4	32.3	10	<	<	72	6.8	0.06		
74H	841014	13	518915	6355336	WRN	04	pond	1	00	Md	-	Br	Lgt	60	9	<	9	3	<	285	<	<	.96	56	42.2	7.4	30	.4	<	70	6.3	0.05		
74H	841016	13	516607	6355250	WRN	04	.25-1	1	00	Md	-	Br	Lgt	79	9	<	16	7	<	215	<	<	1.13	51	41.6	6.2	20	.4	<	40	5.9	0.07		
74H	841017	13	511782	6354434	WRN	04	.25-1	2	00	Md	-	Br	-	70	10	<	14	5	<	230	<	2	2.03	49	37.4	6.8	25	<	<	46	6.3	0.07		
74H	841018	13	508416	6355448	MFB	04	1-5	3	00	Md	-	Br	-	92	10	<	7	3	<	640	2.0	2	12.2	35	24.8	2.4	20	<	<	30	6.2	<		
74H	841019	13	505462	6353698	MFB	04	.25-1	6	00	Md	-	Br	-	85	9	<	7	2	<	255	1.0	4	19.5	35	46.6	2.2	35	<	<	22	5.9	<		
74H	841020	13	502746	6354038	MFB	04	.25-1	1	00	Md	-	Br	-	130	14	<	8	3	<	215	4.0	2	9.60	54	55.0	1.8	30	.2	<	22	5.9	<		
74H	841022	13	503131	6352243	MFB	04	1-5	2	00	Md	-	Gn	-	110	18	<	12	5	<	570	3.0	2	16.2	49	47.6	2.8	45	<	<	24	6.3	<		
74H	841023	13	505502	6352616	WRN	04	1-5	3	10	Lw	-	Br	-	88	8	4	4	2	<	105	2.0	4	2.84	40	51.0	.8	15	.2	<	24	5.3	<		
74H	841024	13	505502	6352616	WRN	04	1-5	3	20	Lw	-	Br	-	83	6	2	4	2	<	95	2.0	2	2.73	40	49.6	1.3	15	.2	<	26	5.4	<		
74H	841025	13	508305	6350035	WRN	04	1-5	1	00	Md	-	Br	-	101	12	<	12	4	<	190	<	2	7.00	64	47.4	14.2	40	<	<	40	6.4	0.16		
74H	841026	13	511051	6350638	WRN	04	pond	1	00	Md	-	Br	-	54	7	<	13	5	<	120	<	<	.76	55	37.8	3.3	10	.4	<	42	5.9	0.05		
74H	841027	13	514804	6350230	WRN	04	1-5	2	00	Md	-	Br	-	55	4	<	5	3	.2	220	<	<	2.00	30	22.8	5.6	20	.2	<	46	6.0	0.07		
74H	841029	13	518591	6351923	WRN	04	1-5	3	00	Lw	-	Br	-	57	14	<	17	3	<	265	2.0	2	2.09	55	44.0	5.0	40	.4	<	34	5.8	<		
74H	841030	13	524459	6352964	WRN	04	pond	1	00	Lw	-	Br	Lgt	50	7	<	12	5	<	520	<	2	.71	51	39.6	2.0	10	.2	<	66	5.9	<		
74H	841031	13	527304	6351656	WRN	04	>5	2	00	Md	-	Br	-	77	11	<	10	4	<	270	<	2	2.14	30	26.0	7.8	10	.2	<	60	6.2	0.09		
74H	841032	13	531550	6352586	WRN	04	pond	1	00	Lw	-	Br	Lgt	55	8	<	13	6	<	405	<	2	.88	68	46.0	4.9	10	.4	<	76	6.1	<		
74H	841033	13	534189	6352399	WRN	04	pond	1	00	Lw	-	Br	-	84	18	<	10	6	<	80	<	2	1.01	34	47.0	19.8	15	.6	<	70	6.0	0.08		
74H	841034	13	536054	6351797	WRN	04	pond	4	00	Lw	-	Br	Lgt	41	14	<	8	2	.2	70	<	2	.41	115	36.2	3.6	10	.6	<	76	6.0	0.05		
74H	841035	13	542179	6351081	WFN	04	.25-1	6	00	Md	-	Br	-	97	16	<	10	5	.2	240	<	2	3.00	58	29.4	5.7	25	.6	<	150	6.1	<		
74H	841036	13	546472	6350833	WFN	04	1-5	3	00	Md	-	Br	-	62	10	<	8	6	.2	195	<	2	1.55	42	19.0	5.2	20	.4	<	100	6.1	0.06		
74H	841037	13	548446	6352809	WPF	04	.25-1	3	00	Md	-	Br	-	65	10	<	12	5	<	185	<	2	1.07	54	36.6	9.9	5	.6	<	120	6.1	0.12		
74H	841038	13	553124	6351066	PGN	04	>5	9	00	Md	-	Br	-	78	13	<	9	4	.2	500	2.0	4	2.93	79	49.6	10.0	20	.4	<	100	6.4	0.06		
74H	841039	13	556259	6350663	PBN	04	1-5	4	00	Md	-	Br	-	110	18	<	11	3	.2	230	<	4	2.20	54	63.0	2.3	25	.6	<	170	5.9	<		
74H	841040	13	558533	6352080	PG	04	pond	1	00	Lw	-	Br	Lgt	75	11	<	7	5	<	140	1.0	2	1.83	75	35.2	2.0	40	.6	<	260	5.6	<		
74H	841042	13	555463	6348096	PG	04	1-5	1	00	Md	-	Br</																						

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																												
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb	Th ppm	U ppm			
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
	Map	ID	RS																										
74H	841002	00	2.40	2.8	32	1.2	6	<	0.8	3.9	99	1	<	1.2	680	25	37	3.80	<	<	<	0.3	6	0.5	<	<	7.5	1.8	
74H	841003	10	0.18	3.1	29	4.4	<	<	3.3	29.0	12	7	0.2	0.7	<	73	120	10.00	<	1.2	4	0.6	<	<	1	<	11.0	5.8	
74H	841004	20	0.18	3.1	31	3.9	<	<	2.2	25.0	14	5	<	<	83	72	110	10.00	1	1.2	3	0.6	<	<	<	<	11.0	5.8	
74H	841005	00	0.36	6.5	42	16.0	74	29	4.4	29.0	22	15	0.1	1.5	460	150	300	19.00	<	2.4	7	1.1	3	<	2	<	20.0	11.0	
74H	841006	00	0.68	4.3	52	4.3	10	24	1.6	17.0	27	5	<	1.2	270	86	160	11.00	2	1.5	4	0.7	2	<	<	<	14.0	4.2	
74H	841007	00	1.80	5.4	33	6.4	7	<	2.0	17.0	78	3	0.2	1.4	570	74	120	10.00	<	1.4	4	0.7	5	0.6	1	<	16.0	5.6	
74H	841008	00	1.40	4.9	32	3.9	10	<	2.2	19.0	56	3	0.2	0.7	440	71	120	11.00	2	1.2	4	0.6	7	<	<	<	15.0	5.2	
74H	841009	00	0.37	4.6	31	1.7	9	<	2.6	43.0	<	3	0.3	0.8	210	85	150	10.00	2	1.3	4	0.6	<	<	1	<	12.0	4.9	
74H	841010	00	0.75	6.1	42	3.5	10	<	2.0	37.0	17	3	0.1	1.3	180	85	140	12.00	<	1.2	4	0.8	3	<	<	4	16.0	7.6	
74H	841011	00	0.17	2.5	<	0.6	6	<	1.3	18.0	<	2	<	<	96	59	80	7.60	<	1.0	<	0.4	1	<	<	<	7.6	5.5	
74H	841012	00	0.36	1.9	<	0.6	6	<	0.9	15.0	<	3	0.1	<	180	12	30	2.00	<	<	<	<	<	<	<	<	3.5	2.7	
74H	841013	00	1.40	3.3	55	1.7	<	<	2.7	20.0	67	4	0.2	1.0	470	21	50	0.87	1	0.6	2	0.7	3	0.6	1	<	7.4	38.9	
74H	841014	00	0.53	3.9	35	1.5	9	<	2.4	33.0	14	3	0.2	1.2	250	33	63	5.20	<	0.7	2	0.5	2	<	1	<	10.0	8.9	
74H	841016	00	0.22	2.8	20	1.4	6	30	2.9	37.0	<	2	0.2	0.7	130	25	45	4.40	2	0.5	<	0.4	<	<	<	6.7	6.7		
74H	841017	00	0.23	3.9	35	2.5	7	<	2.8	37.0	10	3	0.2	0.8	140	37	65	6.10	1	0.9	3	0.5	<	<	<	<	10.0	6.9	
74H	841018	00	0.58	3.8	<	12.0	7	<	4.4	19.0	28	2	0.2	1.0	200	21	37	3.20	<	0.6	<	0.4	9	<	1	3	12.0	2.1	
74H	841019	00	0.26	3.4	30	21.1	<	<	4.8	36.0	15	4	0.3	<	150	19	34	3.30	<	<	<	0.4	4	0.7	2	<	9.1	2.3	
74H	841020	00	0.15	3.2	27	10.0	<	<	9.3	50.0	<	2	0.3	0.7	110	15	23	3.30	<	0.6	<	0.3	1	<	<	<	10.0	2.1	
74H	841022	00	0.33	5.6	21	18.0	12	<	6.8	33.0	11	2	0.3	1.1	120	23	46	4.00	<	0.6	<	0.4	4	0.6	1	<	15.0	2.8	
74H	841023	10	0.26	2.4	<	3.0	<	<	5.3	29.0	8	2	0.3	1.1	120	13	21	1.80	<	<	<	0.2	3	<	1	<	5.4	1.4	
74H	841024	20	0.23	2.1	<	2.9	<	<	4.4	24.0	<	3	0.3	<	100	11	17	1.70	<	<	<	0.2	4	<	<	<	5.0	1.0	
74H	841025	00	0.40	9.0	62	7.7	7	<	3.7	34.0	24	3	0.2	0.9	78	69	88	12.00	2	1.5	6	1.2	4	<	<	<	18.0	16.0	
74H	841026	00	0.08	2.3	<	1.0	7	<	2.0	33.0	<	2	0.2	<	130	20	39	4.00	<	0.7	<	0.2	<	<	<	<	5.5	4.1	
74H	841027	00	1.30	3.5	25	2.8	6	<	2.0	18.0	53	3	0.2	1.1	350	27	52	4.30	<	0.8	<	0.4	4	0.6	<	<	8.4	6.5	
74H	841029	00	0.46	6.6	58	3.1	8	<	4.3	33.0	17	4	0.2	1.7	280	42	90	6.50	2	0.8	3	0.5	2	0.7	2	<	13.0	5.2	
74H	841030	00	0.31	2.0	21	0.8	5	<	2.2	22.0	8	3	0.1	0.7	170	18	32	3.00	<	<	<	<	<	<	<	<	5.1	2.7	
74H	841031	00	1.80	5.0	40	3.3	6	<	2.2	21.0	58	3	0.2	1.0	500	45	79	6.20	1	0.9	3	0.6	5	0.6	<	<	11.0	7.7	
74H	841032	00	0.10	3.1	<	1.0	<	24	1.8	35.0	<	2	0.1	0.9	77	50	95	6.90	<	0.8	2	0.5	<	<	<	<	9.2	4.8	
74H	841033	00	0.20	4.5	28	1.1	8	<	1.7	21.0	10	5	0.2	<	82	150	170	20.70	<	2.3	6	1.0	<	<	<	<	13.0	19.0	
74H	841034	00	0.23	2.5	<	0.4	<	<	1.4	38.0	14	3	0.2	<	110	26	43	3.30	<	<	<	0.3	<	<	5	<	6.1	3.7	
74H	841035	00	0.82	5.5	42	3.6	9	<	2.8	34.0	28	2	0.1	0.9	340	130	210	17.00	3	1.9	6	0.9	4	0.8	<	<	18.0	5.4	
74H	841036	00	1.30	4.2	35	2.0	10	<	1.6	18.0	51	3	0.2	1.3	330	64	110	8.70	<	1.0	3	0.6	6	0.5	1	<	11.0	5.6	
74H	841037	00	0.16	2.8	24	1.2	5	<	2.0	34.0	<	4	0.1	0.8	120	86	150	12.00	<	1.6	3	0.6	<	<	<	<	12.0	10.0	
74H	841038	00	0.38	3.9	34	4.3	6	24	2.7	42.0	13	6	0.2	<	180	95	140	13.00	<	1.6	4	0.7	3	<	2	<	12.0	10.0	
74H	841039	00	0.35	3.3	26	2.2	6	<	3.8	64.0	12	6	0.1	1.0	190	33	67	5.10	1	0.7	2	0.3	<	0.6	<	<	9.0	2.2	
74H	841040	00	0.53	3.3	34	2.5	<	<	2.9	33.0	18	2	0.1	<	300	53	97	9.10	2	1.1	3	0.5	<	<	<	<	10.0	2.1	
74H	841042	00	2.00	3.7	28	4.2	7	<	11.0	25.0	91	18	0.2	1.5	570	39	60	5.70	<	0.6	2	0.4	5	<	<	<	8.8	3.5	
74H	841043	00	0.58	3.8	30	4.4	<	<	2.5	28.0	28	3	0.1	0.7	240	39	75	5.70	<	0.7	2	0.4	3	<	2	<	3	11.0	2.2
74H	841044	00	2.32	4.1	30	4.1	<	<	1.8	6.2	97	2	0.1	1.4	620	52	93	7.70	1	1.1	3	0.5	7	<	<	<	11.0	3.7	
74H	841045	10	0.35	7.0	29	11.0	14	26	3.6	37.0	15	5	0.3	1.0	270	130	210	19.00	<	2.2	5	1.0	<	<	2	<	4	21.6	10.0

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data											Sample Media: Sediments														Waters							
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Variable: Units:													F-W	pH	U-W					
			Easting	Northing	Type	Age	Area	Dep				Zn ppm	Cu ppm	Pb ppm	Ni ppm	Co ppm	Ag ppm	Mn ppm	As ppm	Mo ppm	Fe pct	Hg ppb	LOI 1.0	U ppm	V ppm	Cd ppm	Sb ppm					
			Detection Limit:									2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	F-W	pH	U-W		
																											20	20	0.05			
74H	841046	13	544101	6347295	WPF	04	>5	7	20	Md	-	Br	-	140	13	<	11	6	<	1020	2.0	2	10.0	87	33.8	8.6	45	.4	<	140	6.1	0.05
74H	841047	13	542059	6347407	WFN	04	1-5	15	00	Md	-	Br	-	70	14	2	7	2	<	270	<	4	1.65	26	17.0	8.4	20	.2	<	140	6.2	<
74H	841048	13	536450	6347354	WFN	04	1-5	1	00	Md	-	Br	-	2	2	<	3	4	<	1130	<	2	3.40	35	8.8	5.5	25	<	<	82	6.4	0.05
74H	841049	13	534754	6346472	WRN	04	.25-1	2	00	Md	-	Br	-	65	8	<	7	4	<	270	<	2	2.60	52	35.8	13.0	25	.4	<	80	6.4	0.06
74H	841050	13	530734	6346924	WRN	04	1-5	4	00	Md	-	Gn	-	41	7	<	6	3	.2	145	<	2	.98	22	9.4	5.2	10	.2	<	62	6.0	<
74H	841051	13	526237	6347198	WCN	04	.25-1	2	00	Md	-	Br	-	83	10	<	13	5	.2	200	<	2	2.03	57	49.4	9.2	25	.2	<	60	6.1	0.08
74H	841052	13	523792	6348932	WRN	04	.25-1	2	00	Lw	-	Br	-	78	13	<	19	6	.2	150	<	2	1.17	57	49.6	10.8	30	.4	<	48	5.7	0.1
74H	841054	13	520240	6347424	WRN	04	1-5	2	00	Lw	-	Br	-	98	5	<	9	5	.4	685	<	2	1.95	49	56.4	4.6	15	.6	<	64	6.1	<
74H	841055	13	515672	6348378	WRN	04	1-5	2	00	Lw	-	Br	-	90	10	<	12	6	<	380	<	2	1.81	53	44.4	4.9	20	.6	<	44	5.8	<
74H	841056	13	511255	6347200	WRN	04	.25-1	1	00	Lw	-	Br	-	50	5	<	10	4	.2	235	<	2	1.34	67	42.8	11.1	25	.6	<	46	6.2	0.15
74H	841057	13	509023	6346885	WRN	04	.25-1	3	00	Md	-	Br	-	80	10	<	13	5	<	530	<	2	2.13	76	38.6	5.0	25	.4	<	42	6.3	<
74H	841058	13	506315	6346734	WRN	04	1-5	2	00	Md	-	Br	-	74	10	<	10	4	.2	225	1.0	2	3.20	58	33.8	8.0	35	.2	<	36	6.4	0.09
74H	841059	13	500869	6347980	MFB	04	.25-1	2	00	Md	-	Br	-	80	9	<	9	4	<	450	1.0	2	3.90	44	31.4	2.5	30	.4	<	30	6.3	<
74H	841060	13	500409	6345732	WRN	04	>5	8	00	Lw	-	Br	-	130	8	<	6	9	<	2150	3.0	2	19.0	49	25.6	3.0	40	<	<	28	6.3	<
74H	841062	13	506042	6342786	WRN	04	.25-1	5	00	Md	-	Br	-	90	13	<	15	7	.2	545	<	2	2.32	70	38.0	8.3	30	.4	<	36	6.2	0.11
74H	841063	13	508957	6345044	WRN	04	.25-1	2	00	Md	-	Br	-	85	12	<	11	4	<	365	<	2	5.00	56	48.8	17.0	25	.2	<	44	6.2	0.06
74H	841064	13	513083	6345446	WRN	04	1-5	6	00	Md	-	Br	-	75	7	<	11	5	<	265	<	2	2.78	56	29.2	4.0	20	.2	<	36	6.2	<
74H	841065	13	516297	6344375	WRN	04	>5	3	00	Md	-	Br	-	35	6	<	9	3	.2	260	<	2	.71	23	22.6	2.6	10	.4	<	54	6.4	<
74H	841066	13	520147	6343152	WRN	04	1-5	3	00	Md	-	Br	-	79	9	<	13	4	.4	410	<	2	2.74	42	33.6	18.4	35	.4	<	70	6.2	0.1
74H	841067	13	524224	6342731	WRN	04	1-5	3	00	Md	-	Br	-	74	9	<	12	5	.4	460	<	2	2.40	60	33.4	10.3	25	.4	<	70	6.1	0.14
74H	841068	13	527466	6343271	WRN	04	1-5	2	00	Md	-	Br	-	51	7	<	18	5	<	195	<	<	.63	56	44.4	4.9	20	.4	<	64	6.0	0.05
74H	841069	13	530041	6343358	WRN	04	1-5	4	10	Md	-	Br	-	39	8	2	8	4	.2	170	<	2	.88	19	8.6	8.0	10	.2	<	78	6.1	0.11
74H	841070	13	530041	6343358	WRN	04	1-5	4	20	Md	-	Br	-	80	8	<	12	5	.2	400	<	2	1.43	56	37.0	8.3	20	.2	<	78	6.1	0.1
74H	841071	13	558288	6347610	PG	04	1-5	2	00	Md	-	Br	-	120	26	<	21	9	.4	260	<	4	3.10	57	42.4	4.9	25	.4	<	200	5.7	<
74H	841072	13	558307	6343860	PG	04	.25-1	1	00	Lw	-	Br	-	38	4	<	3	2	<	190	<	<	.90	19	10.8	2.4	10	<	<	220	6.3	<
74H	841073	13	556144	6344308	PG	04	pond	1	00	Lw	-	Br	Lgt	140	7	<	9	5	<	270	2.0	2	5.30	67	42.8	1.6	40	<	<	110	5.4	<
74H	841074	13	553796	6345075	PBG	04	.25-1	1	00	Md	-	Br	-	44	4	<	4	3	<	970	4.0	4	4.40	19	13.0	3.3	40	<	<	260	6.3	<
74H	841075	13	549625	6344833	PBN	04	.25-1	2	00	Lw	-	Br	Lgt	91	10	<	8	3	.2	400	2.0	2	4.20	86	65.0	1.1	55	.4	<	110	5.7	<
74H	841076	13	544348	6344163	PBN	04	>5	24	00	Md	-	Br	-	200	13	<	11	18	.2	9350	2.0	4	16.9	76	32.0	12.0	65	.6	<	94	6.3	0.06
74H	841077	13	540305	6343635	WFN	04	.25-1	2	00	Md	-	Br	-	120	10	<	9	17	<	395	<	6	2.73	43	19.2	8.9	20	.2	<	160	5.7	0.1
74H	841078	13	537645	6344255	WFN	04	.25-1	2	00	Md	-	Br	-	77	9	<	10	4	<	125	<	<	1.28	52	33.0	2.8	20	.6	<	120	5.5	<
74H	841079	13	534613	6343944	WFN	04	.25-1	1	00	Lw	-	Br	-	85	12	<	12	7	.2	260	<	2	1.31	128	34.6	7.1	25	.6	<	250	5.8	0.1
74H	841080	13	530226	6340034	WRN	04	.25-1	4	00	Md	-	Br	-	120	13	<	11	6	.2	325	<	4	6.60	105	40.0	4.2	45	<	<	66	6.1	<
74H	841083	13	525379	6340708	WRN	04	1-5	7	00	Lw	-	Br	-	82	11	<	12	5	<	555	<	2	2.63	85	25.8	11.4	35	.2	<	74	6.5	0.13
74H	841084	13	522215	6339226	WRN	04	pond	1	00	Lw	-	Br	-	53	4	<	12	2	<	150	<	<	1.08	60	33.2	3.7	15	.2	<	64	6.1	<
74H	841085	13	520484	6339631	WRN	04	.25-1	3	00	Lw	-	Br	-	76	5	<	10	4	.2	410	<	<	1.24	55	41.4	3.7	15					

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																												
	Na pct 0.02	Sc ppm 0.2	Cr ppm 20	Fe pct 0.2	Co ppm 5	Ni ppm 20	As ppm 0.5	Br ppm 0.5	Rb ppm 5	Mo ppm 1	Sb ppm 0.1	Cs ppm 0.5	Ba ppm 50	La ppm 2	Ce ppm 5	Sm ppm 0.05	Eu ppm 1	Tb ppm 0.5	Yb ppm 2	Lu ppm 0.2	Hf ppm 1	Ta ppm 0.5	W ppm 1	Au ppb 2	Th ppm 0.2	U ppm 0.2			
	74H	841046	20	0.36	6.7	46	11.0	11	<	3.2	37.0	16	4	0.2	1.4	240	120	200	18.00	2	2.3	6	1.1	2	<	<	<	20.1	9.5
	74H	841047	00	1.30	6.1	48	2.1	<	28	1.6	33.0	59	5	0.2	1.8	520	110	220	16.00	<	2.1	7	1.1	7	0.6	2	5	21.9	9.4
74H	841048	00	2.00	5.1	26	3.9	<	<	1.4	9.4	70	2	0.2	1.3	500	69	110	10.00	<	1.3	4	0.7	7	0.6	<	<	13.0	5.7	
74H	841049	00	0.69	4.1	48	3.1	<	<	1.7	17.0	23	3	0.3	1.0	230	93	120	14.00	2	1.5	4	0.8	3	<	<	13.0	13.0		
74H	841050	00	2.59	7.2	48	1.8	7	<	1.5	7.9	110	2	0.2	1.7	780	59	100	7.80	<	1.0	4	0.7	13	1.1	<	<	16.0	6.1	
74H	841051	00	0.13	3.8	<	2.7	9	<	2.4	37.0	<	2	0.2	1.0	170	57	88	7.80	2	0.9	3	0.6	<	<	<	9.2	10.0		
74H	841052	00	0.21	4.9	29	1.3	6	<	2.2	30.0	11	2	0.2	0.8	190	56	110	10.00	<	1.4	4	0.7	<	<	1	<	12.0	11.0	
74H	841054	00	0.09	2.1	<	2.3	8	<	2.7	30.0	<	4	0.1	0.6	150	22	41	2.40	<	<	<	0.2	<	<	<	5.0	4.2		
74H	841055	00	0.34	4.3	24	2.3	10	<	3.4	27.0	14	3	0.2	0.9	200	31	55	5.00	1	0.7	3	0.5	<	<	1	<	8.6	4.9	
74H	841056	00	0.12	2.5	<	1.6	6	<	2.2	27.0	<	2	0.2	0.8	130	21	41	3.00	<	<	<	0.4	1	<	<	3	5.4	11.0	
74H	841057	00	0.20	4.8	30	3.2	11	<	2.6	45.0	10	2	0.1	1.2	160	36	68	6.00	1	0.8	3	0.3	<	<	2	<	10.0	6.2	
74H	841058	00	0.43	3.5	26	3.6	7	<	3.4	27.0	31	2	0.2	<	160	34	55	7.00	<	0.8	3	0.6	2	<	2	3	10.0	9.2	
74H	841059	00	0.55	4.1	46	5.4	8	<	3.3	25.0	25	2	0.2	0.7	200	24	42	4.30	<	0.7	3	0.5	7	0.7	1	<	11.0	2.6	
74H	841060	00	0.51	5.1	<	22.1	16	20	4.8	24.0	31	2	0.1	0.6	240	30	50	5.30	<	0.8	2	0.5	8	0.6	2	<	12.0	3.2	
74H	841062	00	0.19	4.6	52	3.0	10	<	1.7	39.0	9	3	0.1	<	130	45	84	7.10	<	0.9	2	0.6	1	<	<	11.0	8.5		
74H	841063	00	0.17	5.0	24	5.0	8	<	2.6	37.0	<	3	0.2	0.6	140	56	81	9.20	2	1.0	4	0.8	<	<	<	8.9	17.0		
74H	841064	00	1.10	4.9	36	3.4	<	<	2.7	24.0	46	2	0.2	1.4	380	27	48	4.00	<	0.7	<	0.4	6	<	<	<	10.0	3.9	
74H	841065	00	1.80	3.9	<	1.1	<	<	1.3	11.0	65	2	0.1	1.2	630	32	51	5.20	<	0.8	<	0.5	6	0.7	<	<	9.4	3.0	
74H	841066	00	0.53	5.6	25	3.7	8	<	2.2	27.0	27	4	0.2	1.9	290	53	79	8.00	<	1.1	4	0.7	3	<	<	12.0	18.0		
74H	841067	00	0.15	3.9	26	3.5	9	22	2.2	43.0	<	<	0.2	0.8	89	63	120	10.00	<	1.4	4	0.7	<	<	<	12.0	11.0		
74H	841068	00	0.12	3.4	26	0.7	9	<	2.7	39.0	<	3	0.2	<	96	53	83	8.00	<	0.9	2	0.4	<	<	<	9.2	4.4		
74H	841069	10	2.12	6.0	21	1.7	<	<	2.2	10.0	82	2	0.3	1.4	680	44	76	6.10	<	1.0	3	0.6	10	0.9	<	4	13.0	8.4	
74H	841070	20	0.41	4.4	39	2.4	10	<	2.8	41.0	10	2	0.3	1.0	200	67	110	9.10	1	1.2	3	0.5	2	0.6	<	13.0	10.0		
74H	841071	00	0.49	5.5	48	4.4	13	<	3.9	37.0	20	7	0.3	0.9	160	120	220	18.00	<	1.9	4	0.8	<	<	2	<	14.0	6.5	
74H	841072	00	2.28	4.0	28	1.5	<	<	1.5	8.3	100	1	0.1	1.5	610	38	71	5.70	<	0.8	3	0.4	6	<	<	10.0	2.1		
74H	841073	00	0.21	2.9	38	5.9	7	<	5.6	34.0	<	3	0.1	0.7	110	36	72	5.90	<	<	2	0.4	<	<	<	7.9	1.4		
74H	841074	00	2.44	5.8	44	6.6	<	<	7.1	9.4	110	7	0.2	1.4	680	60	99	8.50	<	1.2	4	0.6	9	0.6	3	<	14.0	3.9	
74H	841075	00	0.10	3.6	35	6.6	6	<	5.0	41.0	<	3	0.2	<	<	51	89	7.30	1	0.9	4	0.4	<	<	2	<	8.6	2.5	
74H	841076	00	0.64	6.3	37	19.0	27	<	4.4	35.0	41	6	0.2	0.9	630	200	390	28.80	<	3.1	9	1.4	4	0.6	2	<	21.9	13.0	
74H	841077	00	1.00	3.7	41	3.3	17	<	2.1	21.0	56	8	0.2	1.2	500	130	240	19.00	<	2.0	4	1.0	4	<	5	<	23.0	12.0	
74H	841078	00	0.14	2.2	<	1.6	<	20	1.3	29.0	<	4	0.6	<	110	66	120	11.00	<	1.2	<	0.4	<	<	<	9.3	2.7		
74H	841079	00	0.57	3.7	26	1.7	9	27	2.0	31.0	22	5	<	1.1	230	95	180	14.00	<	1.7	3	0.7	1	<	<	4	15.0	7.0	
74H	841082	00	0.30	4.8	54	7.3	14	22	3.1	30.0	15	4	0.3	<	110	96	160	14.00	<	1.9	4	0.7	<	<	<	13.0	4.1		
74H	841083	00	0.59	6.2	37	2.9	5	<	2.1	30.0	23	2	0.2	0.8	180	85	150	12.00	2	1.4	4	0.8	2	0.7	<	16.0	11.0		
74H	841084	00	0.07	1.8	<	1.3	6	<	1.2	24.0	7	2	<	<	32	54	5.20	<	0.6	3	0.4	<	<	<	5.4	3.3			
74H	841085	00	0.12	1.6	36	1.6	8	<	2.1	37.0	<	2	0.1	0.6	<	20	33	3.10	<	0.5	<	0.2	<	<	<	4.0	4.1		
74H	841086	00	0.09	4.7	<	1.8	6	<	1.5	22.0	10	2	0.1	<	150	75	110	13.00	2	1.3	4	0.7	1	<	<	11.0	7.1		
74H	841087	10	0.23	4.6	38	3.6	11	<	3.1	42.0	12	3	0.2	<	140	34	59	5.20	<	0.8	2	0.5	<	<	1	<	9.0	3.8	
74H	841088	20	0.24	4.2	40	3.4	9	<	3.0	38.0	12	3	0.1	<	160	31	64	5.00	<	0.7	2	0.4	1	<	<	4	8.4	3.2	
74H	841089	00	0.07	2.4	30	0.3	6	<	2.4	31.0	<	2	0.2	<	100	11	14	2.30	<	<	2	0.2	<	<	<	4.0	1.8		

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments														Waters																					
Map	ID	ZN	UTM			Rock		Lake		RS	Rlf	Cont	Colr	Susp	Detection Limit:												Variable:		Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep	ppm						ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppm	ppb	20	0.05																
74H	841090	13	505450	6340060	WRN	04	1-5	5	00	Md	-	Br	-	77	10	<	9	5	.4	290	<	2	2.14	43	70.2	5.5	20	.2	<	34	6.3	<															
74H	841091	13	500713	6339448	WRN	04	.25-1	1	00	Md	-	Br	-	52	12	<	7	2	<	95	<	2	1.20	36	49.8	19.3	70	.2	<	32	6.4	0.06															
74H	841092	13	560249	6339552	PBG	04	.25-1	3	00	Md	-	Br	-	50	18	<	8	6	.4	785	<	6	11.4	71	43.4	4.5	45	.2	<	140	6.1	<															
74H	841093	13	556272	6340520	PG	04	.25-1	1	00	Lw	-	Br	-	160	11	<	12	5	<	460	<	2	2.63	64	44.8	2.6	10	.4	<	170	6.0	<															
74H	841094	13	552734	6341858	PBG	04	1-5	2	00	Md	-	Br	-	43	2	<	2	3	.4	225	<	<	2.72	14	5.2	1.8	5	<	<	200	6.2	<															
74H	841095	13	549511	6341478	PBG	04	.25-1	3	00	Lw	-	Gn	-	150	13	<	12	6	<	32800	<	8	3.60	36	35.4	5.0	30	.4	<	230	6.3	<															
74H	841096	13	545652	6340631	PBG	04	.25-1	1	00	Md	-	Br	-	120	18	<	11	5	<	285	<	16	7.00	36	36.6	10.3	90	<	<	230	6.1	0.06															
74H	841098	13	542097	6341027	PBN	04	1-5	14	00	Md	-	Gn	-	130	22	<	11	2	<	195	1.0	8	2.35	50	41.2	21.8	20	.4	<	150	6.7	0.07															
74H	841099	13	538670	6340423	WFB	04	1-5	4	00	Md	-	Br	-	160	22	<	15	13	.2	1030	1.0	4	8.30	71	26.2	15.2	35	<	<	100	6.1	0.06															
74H	841100	13	535657	6339801	WFB	04	>5	5	00	Md	-	Br	-	65	8	<	6	5	<	605	<	4	2.02	21	13.0	8.8	15	<	<	120	6.3	0.06															
74H	841103	13	533200	6338100	WFB	04	1-5	2	00	Md	-	Br	-	110	11	<	6	4	.4	235	<	4	2.34	50	58.4	5.3	10	.2	<	210	5.9	<															
74H	841104	13	530644	6337488	WFB	04	.25-1	2	00	Lw	-	Br	-	92	13	2	11	4	.4	250	<	4	1.62	50	35.2	11.6	20	.4	<	310	6.1	0.12															
74H	841105	13	528033	6336083	WFB	04	1-5	4	00	Md	-	Br	-	150	18	<	13	9	.2	970	1.0	2	1.12	86	32.4	10.7	60	.4	<	72	6.4	0.06															
74H	841106	13	523361	6338190	WRN	04	>5	7	10	Md	-	Br	-	77	9	<	11	5	<	735	1.0	2	5.90	71	20.6	17.5	45	<	<	68	6.5	0.17															
74H	841107	13	523361	6338190	WRN	04	>5	7	20	Md	-	Br	-	79	11	<	11	8	.2	615	1.0	2	4.60	48	20.0	16.1	40	.2	<	62	6.5	0.11															
74H	841108	13	519522	6337165	WRN	04	.25-1	1	00	Md	-	Br	-	33	3	<	11	3	<	65	<	<	.31	55	35.4	11.0	15	.2	<	74	6.2	0.16															
74H	841109	13	517283	6337627	WRN	04	1-5	2	00	Md	-	Br	-	38	3	<	5	3	<	150	<	2	1.82	28	19.2	6.8	25	<	<	72	6.3	0.09															
74H	841110	13	512490	6336709	WRN	04	.25-1	4	00	Md	-	Br	-	90	7	<	10	3	<	195	<	2	1.57	55	40.6	5.0	80	.2	<	42	6.3	<															
74H	841111	13	508402	6335703	WRN	04	.25-1	4	00	Md	-	Br	-	150	9	<	19	15	.2	2150	2.0	2	9.20	76	32.8	10.3	40	.4	<	62	6.5	0.06															
74H	841112	13	505847	6335419	WRN	04	.25-1	1	00	Lw	-	Br	-	65	6	<	13	3	.2	330	<	<	.56	55	46.8	2.7	20	.2	<	46	6.1	0.05															
74H	841113	13	501349	6336227	WRN	04	1-5	4	00	Lw	-	Br	-	49	5	<	5	3	<	225	<	2	3.40	21	15.6	5.6	25	<	<	34	6.6	0.06															
74H	841114	13	501838	6333484	WRN	04	>5	4	00	Md	-	Gn	-	80	9	<	16	6	.2	475	2.0	<	3.80	41	23.4	6.0	30	<	<	34	6.4	<															
74H	841115	13	505915	6332802	WRN	04	.25-1	3	00	Md	-	Br	-	79	10	<	17	6	<	470	<	2	2.01	48	45.6	7.9	35	.4	<	40	6.1	0.05															
74H	841116	13	507754	6332054	WRN	04	1-5	9	00	Hi	-	Br	-	130	23	<	23	6	.2	440	2.0	4	13.0	93	46.0	10.2	130	<	<	48	6.4	<															
74H	841117	13	510913	6333071	WFN	04	1-5	11	00	Md	-	Br	-	99	18	<	18	6	<	415	<	4	8.00	80	42.2	14.2	80	.2	<	46	6.6	0.06															
74H	841118	13	515363	6333931	WRN	04	.25-1	1	00	Md	-	Br	-	60	6	<	11	7	.2	175	<	2	1.15	47	40.2	15.3	25	.2	<	52	6.4	0.06															
74H	841119	13	520520	6333952	WRN	04	.25-1	5	00	Md	-	Gn	-	74	9	<	13	7	<	695	<	2	2.24	93	44.4	15.3	40	.2	<	100	6.7	0.09															
74H	841120	13	522325	6334432	WRN	04	.25-1	5	00	Md	-	Br	-	74	8	<	9	3	.4	485	<	2	2.66	87	33.0	16.1	40	.2	<	66	6.6	0.11															
74H	841122	13	525629	6332832	WFN	04	.25-1	1	00	Md	-	Br	-	140	16	<	17	8	<	265	<	6	3.12	67	54.2	6.7	25	.6	<	64	5.7	<															
74H	841124	13	530695	6333986	WFN	04	pond	2	00	Lw	-	Br	-	110	14	<	10	5	<	190	<	4	1.67	53	53.8	10.7	10	.4	<	180	5.9	<															
74H	841125	13	533926	6333877	WPF	04	pond	1	00	Md	-	Br	-	52	9	<	7	5	<	120	<	2	1.07	54	33.2	6.3	10	.2	<	130	6.2	0.1															
74H	841126	13	539198	6336865	PBN	04	.25-1	33	00	Hi	-	Bk	-	140	20	<	9	20	<	5750	7.0	28	22.6	85	38.4	35.7	45	<	<	200	6.4	0.09															
74H	841127	13	540375	6337007	PBN	04	pond	11	00	Md	-	Br	-	100	11	<	8	4	<	210	<	2	.93	30	46.8	3.3	5	.6	<	120	5.9	<															
74H	841128	13	546002	6337251	PBG	04	>5	2	00	Md	-	Br	-	140	14	<	11	5	<	335	<	2	3.60	24	38.8	3.8	25	.4	<	180	5.9	<															
74H	841129	13	546959	6335807	PBG	04	.25-1	4	10	Lw	-	Br	-	210	18	<	14	9	<	665	<	2	11.8	115	34.8	2.2	60	.2	<	150	6.2	<															
74H	841130	13	546959	6335807	PBG	04	.25-1	4	20	Lw	-	Br	-	210	17	<	14	10	.2	695	1.0	2	9.90	103	35.0	2.9																					

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element:	Lake Sediment - INAA Data																											
	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mn	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U		
	Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	
	Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2	
Map	ID	RS																										
74H	841135	00	0.07	1.9	21	1.3	8	<	4.2	41.0	<	3	0.2	0.7	99	16	34	3.30	<	<	<	<	<	<	<	5.8	2.2	
74H	841136	00	1.60	6.5	37	1.4	6	<	3.1	6.9	87	1	0.3	2.8	590	39	69	5.70	<	0.8	2	0.5	13	2.2	2	<	21.4	4.0
74H	841137	00	0.92	3.9	23	1.6	<	<	3.5	17.0	40	1	0.2	1.1	350	22	45	3.30	<	<	0.3	15	0.8	<	3	16.0	2.3	
74H	841138	00	0.40	3.3	20	2.4	<	<	4.3	38.0	17	2	0.2	1.4	190	23	40	3.80	<	<	0.3	4	0.6	<	<	18.0	2.3	
74H	841139	00	1.00	4.2	35	1.6	<	<	3.6	20.0	52	2	0.2	1.7	340	30	53	4.20	<	0.7	<	0.3	8	1.2	2	<	20.0	3.0
74H	841140	00	0.06	1.7	<	1.7	<	<	3.4	24.0	<	3	0.1	0.6	<	12	25	2.30	<	<	<	2	<	<	<	11.0	1.4	
74H	841142	10	0.11	3.2	<	0.9	<	22	6.9	23.0	<	2	0.2	0.8	160	24	56	6.90	1	0.6	<	0.5	2	<	<	6	20.9	3.8
74H	841143	20	0.07	4.4	<	1.2	7	35	9.4	28.0	<10	4	0.3	<	<	26	52	6.80	1	0.8	2	0.6	<	<	<	5	23.1	4.2
74H	841144	00	0.36	3.7	<	35.8	13	<	19.0	31.0	25	8	0.2	0.8	130	23	42	4.20	<	<	0.3	4	<	<	<	14.0	2.6	
74H	841145	00	0.91	4.7	21	15.0	15	<	22.0	16.0	46	3	0.4	1.5	320	30	55	4.60	<	0.6	3	0.5	14	0.9	1	<	14.0	3.3
74H	841146	00	0.27	3.4	38	3.0	<	<	9.2	41.0	12	3	0.3	0.8	110	21	41	4.20	<	<	<	0.3	3	<	2	<	13.0	3.4
74H	841147	00	0.26	1.5	<	1.8	<	<	4.5	15.0	9	2	0.2	<	71	13	28	2.20	<	<	<	3	<	<	<	9.4	1.2	
74H	841148	00	0.11	1.8	<	3.0	6	<	6.9	27.0	<	3	0.2	<	72	9	15	2.00	<	<	<	0.2	2	<	<	7.4	1.6	
74H	841149	00	0.81	3.1	<	12.0	11	<	7.4	7.3	37	3	0.1	0.6	270	19	36	3.50	<	<	<	0.3	10	0.5	1	<	12.0	2.2
74H	841150	00	1.10	3.9	34	1.0	<	<	2.4	11.0	55	1	0.2	1.0	370	26	48	3.70	<	<	2	0.4	13	1.2	<	3	17.0	2.4
74H	841152	00	0.09	3.2	<	0.6	7	36	4.4	23.0	6	2	0.2	0.6	64	16	34	6.20	<	0.7	3	0.5	2	<	<	<	14.0	5.0
74H	841153	00	0.08	1.3	<	<	<	<	5.2	24.0	<	2	0.2	<	<	9	15	2.70	<	<	0.2	<	<	<	<	7.0	3.0	
74H	841154	00	0.65	2.1	<	0.8	<	<	2.7	17.0	28	<	0.1	0.7	210	15	26	2.20	<	<	<	9	0.6	<	<	8.6	1.4	
74H	841155	00	0.84	4.2	42	8.2	6	<	5.6	29.0	39	4	0.2	1.4	250	24	42	3.90	<	0.7	<	0.4	9	0.9	2	<	13.0	2.4
74H	841156	00	1.30	6.5	39	17.0	7	<	25.0	19.0	61	3	0.3	1.2	470	36	71	5.50	<	0.9	3	0.5	15	1.4	1	<	20.8	4.2
74H	841157	00	0.24	5.3	25	23.0	11	38	10.0	67.0	<	3	0.3	0.7	110	38	70	6.40	<	1.0	4	0.5	4	0.6	<	<	18.0	5.1
74H	841158	00	0.33	5.5	67	19.0	8	<	10.0	43.0	17	7	0.3	1.0	130	32	62	5.10	1	0.7	2	0.5	4	0.8	1	<	13.0	3.1
74H	841159	00	0.14	1.3	25	0.7	<	<	3.6	25.0	<	3	0.2	0.6	73	9	14	1.50	<	<	<	<	<	<	<	4.3	1.8	
74H	841160	00	0.33	3.1	43	4.8	12	<	7.6	34.0	20	5	0.5	1.2	170	20	42	3.40	<	<	0.4	3	0.6	<	<	8.8	3.9	
74H	841162	00	0.36	3.1	34	25.2	18	<	40.0	32.0	17	3	0.2	<	110	20	36	4.00	<	0.6	<	0.4	6	<	2	<	11.0	2.4
74H	841163	00	0.22	2.9	25	0.6	<	<	12.0	36.0	<	4	0.5	0.7	<	21	54	5.00	<	0.6	3	0.3	3	<	<	<	10.0	4.3
74H	841164	00	0.17	1.7	21	1.7	<	<	3.9	38.0	<	3	0.2	0.6	56	10	24	1.60	<	<	2	<	<	<	<	4.9	1.0	
74H	841165	10	0.25	4.4	23	18.0	10	<	21.0	40.0	20	5	0.4	1.4	150	22	49	4.10	<	0.6	2	0.4	5	<	2	<	13.0	4.2
74H	841166	20	0.31	5.5	53	15.0	9	21	22.0	47.0	15	5	0.5	1.4	150	28	54	4.60	<	0.8	2	0.4	5	0.5	<	<	15.0	4.7
74H	841167	00	0.45	4.5	<	28.5	15	<	18.0	41.0	26	8	0.3	1.2	400	28	49	4.80	<	0.8	3	0.5	5	0.6	3	<	12.0	3.8
74H	841168	00	0.71	1.7	<	12.0	8	<	5.9	7.3	32	2	0.2	0.7	260	13	19	2.00	<	<	0.2	8	<	<	<	5.0	1.1	
74H	841169	00	1.10	4.7	<	4.7	7	<	8.2	11.0	51	4	0.4	1.6	420	37	70	5.30	<	0.7	3	0.4	12	1.6	2	3	26.7	3.2
74H	841170	00	0.76	3.3	26	0.5	<	<	3.5	25.0	34	2	0.2	1.0	260	22	39	2.80	<	<	2	0.2	8	0.7	<	3	12.0	1.6
74H	841171	00	0.06	1.4	26	1.7	7	<	11.0	33.0	<	3	0.3	<	110	9	19	2.20	<	<	0.2	<	<	<	<	5.1	2.1	
74H	841172	00	0.06	1.7	<	3.1	<	<	17.0	40.0	<	4	0.4	<	<	9	16	2.20	<	0.6	<	0.2	<	<	<	5.9	2.3	
74H	841173	00	0.13	2.3	<	2.3	<	<	7.6	34.0	<	3	0.2	0.9	66	12	19	2.40	<	0.6	<	0.2	2	<	<	<	8.8	1.8
74H	841174	00	0.07	1.5	<	2.9	<	<	3.8	30.0	<	2	0.1	<	55	10	18	2.00	<	<	<	<	<	<	<	3	7.3	1.1
74H	841175	00	0.15	1.8	<	0.5	<	<	3.2	12.0	7	1	<	<	79	19	30	3.40	<	<	0.2	2	<	<	<	9.0	2.6	
74H	841176	00	0.25	7.3	32	6.7	8	<	4.5	43.0	21	1	0.2	1.5	140	28	45	4.80	<	0.8	2	0.5	2	<	<	<	18.0	7.7
74H	841177	00	0.23	5.7	32	2.3	11	<	2.9	39.0	23	1	0.2	1.1	160	29	58	4.90	<	0.8	2	0.5	1	<	<	<	13.0	7.5

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data															Sample Media: Sediments															Waters				
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W	
			Easting	Northing	Type	Age	Area	Dep						Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppb	20	0.05			
Detection Limit:															2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	F-W	pH	U-W	
74H	841178	13	554954	6401579	WRN	04	.25-1	1	00	Lw	-	Br	-	50	8	2	15	5	<	155	<	<	1.03	36	35.6	6.9	5	.2	<	80	6.7	0.1		
74H	841179	13	554827	6404731	WRN	04	1-5	2	00	Md	-	Gn	-	110	8	<	16	8	<	325	<	<	3.80	29	49.8	12.9	15	.4	<	54	6.2	0.07		
74H	841182	13	557930	6408129	WRN	04	>5	4	00	Md	-	Br	-	96	11	<	11	7	<	320	2.0	<	6.10	36	37.0	5.5	25	.4	<	52	6.4	0.05		
74H	841183	13	559118	6405820	WPSN	04	.25-1	2	10	Md	-	Br	-	62	19	<	19	7	<	210	<	<	.90	50	54.4	32.3	10	.6	<	70	6.7	0.2		
74H	841184	13	559118	6405820	WPSN	04	.25-1	2	20	Md	-	Br	-	75	15	<	21	8	<	230	<	2	1.18	43	54.2	32.3	15	.6	<	72	6.8	0.19		
74H	841185	13	558322	6402635	WRN	04	>5	2	00	Lw	-	Br	-	150	17	<	32	12	<	595	1.0	<	3.10	46	54.4	11.1	10	1.2	<	70	6.8	0.06		
74H	841186	13	554462	6399420	WRN	04	>5	5	00	Md	-	Br	-	110	23	<	34	10	<	475	1.0	<	3.70	79	40.8	11.8	15	.6	<	68	6.6	0.14		
74H	841187	13	551520	6398097	WRN	04	.25-1	2	00	Lw	-	Br	-	60	11	<	22	6	<	175	<	<	1.38	79	45.4	18.5	15	.2	<	62	6.2	0.27		
74H	841188	13	549570	6397088	WRN	04	.25-1	3	00	Md	-	Br	-	81	13	<	17	6	<	285	1.0	2	1.45	73	60.2	8.2	20	.4	<	84	6.5	0.05		
74H	841189	13	546572	6398274	WRN	04	.25-1	1	00	Lw	-	Br	-	55	4	<	7	3	<	120	1.0	<	1.13	47	29.0	3.6	15	.4	<	48	6.3	<		
74H	841190	13	539720	6399881	WRN	04	.25-1	3	00	Md	-	Br	-	45	8	<	7	3	<	140	2.0	2	1.56	67	33.0	1.5	10	.4	<	38	6.1	<		
74H	841191	13	538430	6399395	WRN	04	1-5	12	00	Md	-	Br	-	63	9	<	7	4	<	135	3.0	<	1.93	60	31.6	2.7	15	.4	<	28	6.1	<		
74H	841192	13	535036	6398569	WRN	04	1-5	6	00	Md	-	Br	-	87	11	<	14	8	<	140	7.0	4	4.40	73	60.2	3.4	40	.6	<	30	6.0	<		
74H	841193	13	531020	6397098	WPSN	04	1-5	9	00	Md	-	Br	-	30	7	<	7	4	<	300	2.0	2	2.06	47	16.0	2.3	15	.4	<	38	6.5	<		
74H	841194	13	526206	6397097	MFC	04	1-5	8	00	Md	-	Gy	-	33	8	<	8	10	<	440	5.0	<	4.00	40	12.4	3.1	25	.2	<	22	6.1	<		
74H	841195	13	524070	6393324	WPSN	04	.25-1	4	00	Md	-	Br	-	46	9	<	9	5	<	250	4.0	<	2.03	67	29.4	1.0	15	.4	<	26	5.9	<		
74H	841197	13	528156	6395133	WPSN	04	>5	2	00	Md	-	Bk	-	37	5	<	5	4	<	220	2.0	<	4.30	67	22.2	1.7	15	.4	<	34	6.3	<		
74H	841198	13	531335	6394991	WRN	04	1-5	5	00	Lw	-	Br	-	68	8	<	11	7	<	235	4.0	<	3.00	67	33.8	1.9	15	.4	<	30	6.1	<		
74H	841199	13	533825	6393142	WRN	04	1-5	6	00	Lw	-	Br	-	130	14	<	10	6	<	290	3.0	2	10.8	53	59.0	2.0	25	.4	<	28	6.2	<		
74H	841200	13	538924	6393837	WRN	04	>5	4	00	Lw	-	Br	-	160	12	<	15	15	<	930	17.0	4	27.9	67	40.4	4.0	100	.2	<	28	6.0	<		
74H	841202	13	542093	6396217	WRN	04	.25-1	2	00	Lw	-	Br	-	82	8	<	8	7	<	235	2.0	<	5.60	93	52.8	2.8	25	.4	<	32	5.8	<		
74H	841203	13	546141	6394587	WRN	04	>5	17	00	Md	-	Gn	-	140	19	<	14	11	<	565	3.0	<	7.10	113	32.8	38.4	45	.8	<	56	6.6	0.1		
74H	841204	13	549754	6393720	WRN	04	.25-1	4	10	Md	-	Br	-	67	17	<	15	6	<	405	<	<	1.46	133	42.6	10.4	25	.4	<	94	6.4	0.19		
74H	841205	13	549754	6393720	WRN	04	.25-1	4	20	Md	-	Br	-	67	18	<	15	6	<	405	<	<	1.32	133	41.8	12.0	20	.4	<	96	6.4	0.18		
74H	841206	13	551413	6394525	WRN	04	.25-1	2	00	Md	-	Br	-	110	12	<	16	7	<	280	<	<	1.62	40	58.8	13.6	15	.4	<	74	6.0	0.06		
74H	841207	13	558558	6398930	WRN	04	.25-1	1	00	Lw	-	Br	-	85	6	<	11	7	<	240	1.0	<	3.70	73	48.8	3.3	15	.4	<	72	5.9	<		
74H	841208	13	559372	6395734	WRN	04	pond	13	00	Lw	-	Br	-	80	16	<	26	12	<	1420	16.0	2	3.30	60	48.0	40.6	40	.2	<	98	6.9	<		
74H	841209	13	555033	6393729	WRN	04	.25-1	3	00	Md	-	Br	-	79	13	<	17	11	<	330	<	<	2.50	73	42.2	40.6	25	.2	<	48	5.7	0.2		
74H	841211	13	555099	6392328	WRN	04	.25-1	6	00	Md	-	Br	-	84	12	<	11	5	<	280	<	<	1.63	120	57.0	5.5	15	.4	<	50	6.0	<		
74H	841212	13	556448	6388694	WRN	04	.25-1	1	00	Lw	-	Br	-	58	12	<	18	6	<	310	<	<	1.07	80	49.4	3.3	15	.2	<	72	6.2	<		
74H	841213	13	559568	6386509	WPSN	04	pond	1	00	Md	-	Br	-	54	13	<	17	8	<	160	<	<	.80	87	41.0	2.1	25	.4	<	70	5.9	<		
74H	841214	13	557971	6383775	WG	04	1-5	8	00	Md	-	Br	-	76	16	<	13	8	<	880	<	<	2.60	67	33.0	7.1	25	.4	<	98	6.5	0.05		
74H	841215	13	554411	6383114	WPSN	04	pond	1	00	Lw	-	Br	Lgt	99	8	<	11	11	<	1700	2.0	<	2.80	94	45.6	6.5	30	.6	<	110	6.3	<		
74H	841216	13	555414	6380555	WCN	04	.25-1	1	00	Lw	-	Br	-	47	8	<	13	6	<	225	<	<	1.10	44	24.6	1.3	25	.2	<	110	6.2	<		
74H	841217	13	559681	6380320	WFN	04	.25-1	1	00	Lw	-	Br	-	89	11	2	12	8	<	155	<	<	1.34	69	56.4	8.5	20	.6	<	150	5.8	0.06		

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																											
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U		
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm			
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
Map	ID	RS																											
74H	841178	00	0.18	3.0	<	1.0	<	<	1.5	24.0	<	2	<	0.5	65	24	31	4.00	<	0.7	<	0.5	1	<	<	<	7.9	7.5	
74H	841179	00	0.25	6.4	34	3.4	10	20	4.5	44.0	21	2	0.2	1.4	170	33	59	4.90	<	0.9	3	0.6	2	<	<	<	15.0	14.0	
74H	841182	00	0.37	4.6	36	5.5	7	<	4.9	31.0	24	3	0.1	1.3	140	25	48	4.20	<	0.7	3	0.4	3	<	<	<	11.0	5.0	
74H	841183	10	0.25	5.8	35	0.9	8	21	3.2	48.0	14	4	0.2	0.9	100	39	70	5.00	1	1.0	4	0.9	1	<	<	<	16.0	30.5	
74H	841184	20	0.23	5.8	38	1.0	8	<	3.2	47.0	9	3	0.3	0.8	120	40	77	5.40	<	1.0	4	1.0	<	<	<	<	16.0	28.6	
74H	841185	00	0.68	3.3	23	2.2	10	<	3.4	43.0	21	4	0.1	0.7	220	24	44	3.00	<	<	<	0.4	4	<	<	<	10.0	11.0	
74H	841186	00	0.21	4.4	31	2.8	9	<	2.8	46.0	<	3	0.1	<	100	30	57	4.50	1	0.7	2	0.5	<	<	<	<	12.0	11.0	
74H	841187	00	0.13	5.0	32	1.4	8	29	1.7	36.0	13	3	0.1	0.8	76	43	84	6.60	<	0.9	2	0.6	<	<	<	3	14.0	18.0	
74H	841188	00	0.18	5.0	24	1.5	9	<	4.0	33.0	17	6	0.2	0.7	140	27	55	4.30	<	0.6	<	0.5	<	<	1	<	12.0	8.5	
74H	841189	00	0.28	2.3	<	1.3	<	<	3.3	25.0	16	<	0.1	<	140	17	33	2.70	1	<	<	0.2	4	<	2	<	8.2	3.4	
74H	841190	00	0.05	1.6	<	1.5	<	<	4.8	28.0	<	3	0.2	<	<	8	<	1.60	<	<	<	<	<	<	<	4.5	1.3		
74H	841191	00	0.41	2.6	26	1.9	<	<	5.0	33.0	19	2	0.2	1.3	190	19	31	3.30	<	<	<	0.3	5	0.9	<	3	12.0	2.2	
74H	841192	00	0.32	2.7	24	4.1	9	<	13.0	39.0	10	5	0.5	0.9	98	16	37	2.90	<	<	<	0.3	3	0.6	1	<	9.1	3.3	
74H	841193	00	1.10	4.2	32	2.0	6	<	4.0	19.0	41	2	0.3	1.6	390	25	46	3.90	<	0.6	<	0.3	11	1.1	2	<	13.0	2.6	
74H	841194	00	1.10	5.0	35	4.4	11	<	8.8	14.0	47	2	0.3	1.3	380	33	60	5.70	<	1.0	3	0.5	16	1.4	<	<	19.0	3.2	
74H	841195	00	0.27	1.8	32	1.9	7	<	5.5	23.0	15	2	0.2	0.7	<	11	17	2.10	<	<	<	0.2	3	<	<	<	5.0	1.3	
74H	841197	00	1.20	3.4	<	4.7	<	<	4.9	17.0	37	3	0.3	0.9	330	19	30	3.10	<	0.6	<	0.3	13	0.5	2	<	8.5	2.2	
74H	841198	00	0.48	3.1	32	3.0	8	<	8.1	33.0	23	3	0.3	1.0	190	20	43	3.30	<	<	<	5	0.7	<	<	11.0	2.2		
74H	841199	00	0.29	3.8	30	12.0	9	<	11.0	48.0	13	7	0.4	1.2	150	20	31	3.40	<	<	<	0.4	3	<	<	11.0	2.5		
74H	841200	00	0.18	6.7	43	31.3	20	35	29.0	34.0	20	6	0.3	1.3	90	33	69	6.30	1	1.0	3	0.6	5	0.9	<	<	23.3	4.0	
74H	841202	00	0.09	3.0	23	5.6	6	<	6.0	46.0	<	2	0.2	<	120	26	50	4.40	<	<	<	2	0.3	1	<	<	5	6.2	2.8
74H	841203	00	0.53	6.7	71	6.7	9	21	6.6	42.0	29	6	0.2	1.0	240	70	130	9.40	2	1.5	5	1.3	7	0.9	<	<	21.6	35.8	
74H	841204	10	0.17	3.5	36	1.6	6	<	2.8	54.0	11	3	0.2	1.1	120	48	91	7.10	<	1.0	3	0.5	<	<	<	12.0	12.0		
74H	841205	20	0.12	3.3	<	1.4	<	<	2.2	53.0	16	3	0.1	1.1	210	45	88	6.60	1	0.8	3	0.5	1	<	<	12.0	12.0		
74H	841206	00	0.17	3.7	29	1.6	10	<	3.6	36.0	7	4	0.2	0.6	140	27	50	3.80	<	0.6	<	0.5	<	<	2	3	8.4	14.0	
74H	841207	00	0.11	2.0	23	2.9	8	<	3.8	31.0	<	2	0.1	<	140	15	26	2.60	<	<	<	<	<	<	<	<	4.6	3.4	
74H	841208	00	0.38	6.6	120	4.3	18	<	24.0	120.0	36	6	0.4	2.6	320	56	68	4.90	<	1.1	2	0.9	<	0.6	<	6	13.0	44.3	
74H	841209	00	0.36	5.1	<	2.5	10	22	3.2	34.0	26	2	0.2	<	160	37	75	4.60	<	1.0	<	0.8	2	<	<	11.0	40.9		
74H	841211	00	0.08	2.9	22	1.9	<	<	2.4	50.0	<	3	<	<	190	22	38	3.90	<	<	<	0.3	<	<	4	4.8	5.1		
74H	841212	00	0.18	2.4	<	1.1	6	<	2.3	38.0	10	3	0.2	<	140	20	37	3.40	<	<	<	<	<	2	<	6.1	3.3		
74H	841213	00	0.12	3.4	27	1.1	7	<	<	39.0	13	2	<	<	87	44	87	7.70	<	1.0	<	0.4	<	<	<	9.0	2.4		
74H	841214	00	0.28	5.5	<	3.0	12	<	2.5	50.0	<11	5	0.2	<	230	85	170	13.00	<	1.5	5	0.6	<	<	4	15.0	7.8		
74H	841215	00	0.24	3.0	39	2.4	10	<	3.1	32.0	9	4	0.2	<	170	43	92	6.30	<	0.7	2	0.3	<	<	<	8.1	6.0		
74H	841216	00	1.20	5.0	32	1.6	8	<	2.0	22.0	45	2	0.2	1.5	440	38	71	5.80	<	0.9	<	0.3	3	0.7	<	<	11.0	2.7	
74H	841217	00	0.10	3.0	27	1.5	11	<	2.7	28.0	9	5	0.2	0.8	120	69	130	10.00	<	1.3	4	0.5	<	<	<	10.0	8.6		
74H	841218	00	0.07	2.6	<	1.3	9	29	1.6	32.0	<	4	<	0.8	<	98	180	17.00	<	1.8	3	0.7	<	<	<	12.0	7.4		
74H	841219	00	0.05	1.3	29	1.1	<	<	2.0	32.0	<	2	0.1	<	72	44	88	7.50	<	1.0	2	0.2	<	<	<	4.2	2.2		
74H	841220	00	0.25	3.4	46	2.2	8	<	2.3	43.0	15	5	0.1	0.6	130	95	190	15.00	<	1.7	5	0.6	<	0.6	<	<	13.0	6.0	
74H	841222	00	0.15	2.3	40	1.7	6	<	2.7	46.0	<12	2	0.2	<	150	39	90	5.60	<	1.1	<	0.3	<	<	8	7.9	3.5		
74H	841223	00	0.26	4.0	37	0.7	11	22	1.9	66.0	<13	<	0.5	<	170	100	150	11.00	<	1.3	2	1.0	<	<	<	<	5	12.0	23.9

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data														Sample Media: Sediments														Waters						
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp		Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep							Units:	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	pct	ppm	ppm	ppm	ppm	ppb	20	0.05	
														Detection Limit:	2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	F-W	pH	U-W	
74H	841224	13	517576	6317335	X	04	.25-1	1	00	Md	-	Gn	-	88	11	<	11	5	<	130	<	<	6.20	73	38.4	7.8	10	.4	<	120	6.1	0.15		
74H	841225	13	504703	6317920	WRN	04	1-5	2	00	Md	-	Br	-	53	6	<	8	4	<	235	<	<	1.37	18	23.0	2.1	10	.2	<	64	6.4	<		
74H	841226	13	509489	6319615	WRN	04	pond	2	00	Md	-	Br	-	92	8	<	11	18	<	1110	2.0	<	1.30	42	17.4	5.3	20	.2	<	70	6.5	<		
74H	841227	13	512053	6322350	WRN	04	1-5	7	00	Md	-	Br	-	77	10	<	9	7	<	395	1.0	<	2.80	67	22.6	5.0	25	.2	<	74	6.5	<		
74H	841228	13	512988	6318793	WRN	04	.25-1	1	00	Lw	-	Br	-	65	9	<	10	5	<	675	<	<	1.02	61	32.4	5.7	20	.4	<	80	6.6	0.06		
74H	841229	13	516263	6322242	WPF	04	.25-1	1	10	Md	-	Gn	-	90	23	<	19	5	<	190	<	2	.78	61	47.2	7.3	10	.2	<	96	6.3	<		
74H	841230	13	516263	6322242	WPF	04	.25-1	1	20	Md	-	Gn	-	70	12	<	10	4	<	120	<	2	.65	36	25.0	5.3	10	.2	<	96	6.4	<		
74H	841231	13	519797	6323286	WPF	04	1-5	3	00	Md	-	Br	-	110	32	<	15	8	<	325	<	2	2.60	67	29.4	12.8	40	.2	<	78	6.2	<		
74H	841232	13	521884	6322474	WPF	04	.25-1	3	00	Md	-	Br	-	150	12	<	12	12	<	980	<	<	7.50	67	41.2	9.9	50	.4	<	110	6.2	0.05		
74H	841233	13	523112	6318553	PBN	04	.25-1	5	00	Md	-	Br	-	110	25	<	16	24	<	495	<	4	6.20	67	17.0	13.1	40	.2	<	80	6.0	<0.1		
74H	841235	13	526674	6318597	RGM	04	.25-1	2	00	Md	-	Br	-	100	30	<	17	10	<	325	<	<	4.20	67	39.0	20.1	35	.2	<	200	6.1	0.15		
74H	841236	13	528995	6318543	RGPX	04	1-5	20	00	Md	-	Gn	-	180	30	<	12	20	<	2350	2.0	16	18.6	127	32.2	37.7	70	.2	<	140	6.3	0.15		
74H	841237	13	559940	6335006	PBG	04	.25-1	4	00	Lw	-	-	-	180	28	<	24	14	<	710	<	2	8.10	103	35.0	5.7	55	.4	<	140	6.5	<		
74H	841238	13	554855	6333552	PBG	04	.25-1	1	00	Lw	-	Br	Lgt	86	13	<	15	4	<	465	<	2	2.50	85	39.6	3.8	30	.4	<	160	6.4	<		
74H	841239	13	551377	6333050	PBN	04	.25-1	3	00	Md	-	Br	-	110	17	<	14	4	<	370	<	4	5.30	73	35.4	2.8	40	.2	<	160	6.3	<		
74H	841240	13	549888	6333863	PBN	04	.25-1	3	00	Md	-	Br	-	100	16	<	14	6	<	310	<	2	4.30	67	34.0	2.7	45	.2	<	150	6.0	<		
74H	841242	13	544134	6333192	PGN	04	1-5	3	00	Md	-	Br	-	68	9	<	9	10	<	615	<	<	2.80	29	10.4	3.9	15	.2	<	120	6.2	<		
74H	841243	13	540834	6333098	PGN	04	.25-1	5	00	Md	-	Br	-	100	34	<	15	10	<	450	<	2	4.80	82	32.0	5.8	30	.2	<	150	6.1	0.08		
74H	841245	13	539288	6333051	PBN	04	.25-1	6	10	Md	-	Br	-	120	30	<	17	12	<	685	1.0	4	9.30	106	38.6	4.6	60	.2	<	220	6.7	<		
74H	841246	13	539288	6333051	PBN	04	.25-1	6	20	Md	-	Br	-	130	29	<	16	13	<	690	1.0	2	10.0	100	38.8	5.2	60	.4	<	220	6.2	<		
74H	841247	13	534276	6330305	PBN	04	.25-1	7	00	Hi	-	Br	-	86	20	2	8	6	<	170	<	<	1.21	41	32.2	17.2	20	.4	<	140	6.3	<		
74H	841248	13	529371	6331266	WFB	04	.25-1	2	00	Md	-	Br	-	100	13	<	14	6	<	325	<	2	2.20	47	29.2	9.0	25	.4	<	230	6.0	0.08		
74H	841249	13	527707	6330085	WFB	04	.25-1	4	00	Md	-	Br	-	100	10	<	10	9	<	285	<	2	3.20	65	47.6	7.0	15	.4	<	120	5.8	0.05		
74H	841250	13	524566	6329806	WFB	04	1-5	3	00	Md	-	Br	-	43	2	<	3	5	<	160	<	<	3.40	24	5.8	3.8	10	.2	<	98	6.5	0.06		
74H	841251	13	520656	6329565	WRN	04	.25-1	2	00	Md	-	Gn	-	79	6	<	110	5	<	385	<	<	3.60	48	29.8	11.0	25	.4	<	110	6.6	0.1		
74H	841252	13	516893	6328744	WRN	04	.25-1	1	00	Md	-	Br	-	44	3	<	12	5	<	95	<	<	.93	61	43.6	6.8	10	.4	<	98	6.5	0.08		
74H	841253	13	513579	6328994	WRN	04	.25-1	2	00	Md	-	Br	-	62	8	<	16	7	<	215	<	<	1.58	67	38.6	10.8	20	.2	<	86	6.3	0.15		
74H	841254	13	509521	6329637	WFN	04	.25-1	2	00	Md	-	Br	-	61	12	<	19	8	<	230	<	<	1.60	73	50.8	3.7	25	.4	<	72	6.0	<		
74H	841255	13	504810	6328891	WPSN	04	1-5	22	00	Md	-	Gn	-	97	14	<	12	13	<	6500	4.0	4	22.2	61	37.0	5.2	45	.2	<	68	6.6	<		
74H	841256	13	502110	6330619	WRN	04	.25-1	1	00	Md	-	Br	-	62	8	<	16	7	<	345	<	<	1.67	61	55.2	4.0	30	.4	<	62	5.9	<		
74H	841257	13	501923	6325436	WFN	04	.25-1	2	00	Md	-	Br	-	84	13	<	10	8	<	165	<	<	4.70	67	48.0	2.6	30	.4	<	58	6.0	<		
74H	841258	13	503249	6323400	WPSN	04	1-5	2	00	Md	-	Br	-	70	5	<	7	9	<	215	<	<	5.60	30	13.4	3.7	40	.2	<	68	6.1	<		
74H	841259	13	501484	6318565	WFN	04	1-5	2	00	Md	-	Gn	-	87	13	<	13	8	<	375	1.0	2	4.80	42	32.0	4.3	20	.4	<	78	6.6	<		
74H	841260	13	506087	6322698	WRN	04	1-5	22	00	Md	-	Gn	-	130	7	3	12	9	<	865	2.0	6	11.5	119	38.0	6.7	65	.4	<	74	6.5	<		
74H	841262	13	508000	6322500	WRN	04	.25-1	6	00	Md	-	Br	-	93	9	<	15	8	<	420	1.0	2	6.90	106	51.6	9.5	70	.4	<	94	6.8	0.05		
74H	841264	13	505042	6327236	WGDB	04	.25-1	4	00	Md	-	Br	-	150	1																			

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb	Th ppm	U ppm		
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
	Map	ID	RS																									
74H	841224	00	0.13	2.8	<40	0.9	<10	<	3.2	47.0	<23	<2	0.9	<1.0	<100	58	130	8.60	4	<1.0	<4	1.0	<2	<1.0	<2	<9	10.0	11.0
74H	841225	00	1.80	4.4	23	2.4	<	<	1.7	11.0	64	1	0.2	1.3	480	30	53	3.90	<	0.5	2	0.5	5	<	<	2	8.7	2.6
74H	841226	00	1.70	4.8	35	3.9	15	<	1.9	16.0	57	<	0.2	1.0	520	58	100	7.70	<	1.1	3	0.6	4	0.7	<	<	11.0	4.8
74H	841227	00	1.40	7.6	50	3.7	6	<	2.2	28.0	50	<	0.2	1.3	350	74	130	8.80	<	1.0	4	0.7	6	<	<	4	17.0	5.0
74H	841228	00	0.85	4.7	31	1.3	7	<	1.6	26.0	31	<	0.2	<	300	46	98	6.70	<	0.9	3	0.7	5	<	<	<	12.0	5.5
74H	841229	10	0.26	4.1	<	1.1	7	<	1.3	29.0	18	<	0.2	1.4	100	130	150	15.00	<	2.2	5	0.9	1	<	<	5	14.0	6.7
74H	841230	20	ns	ns	ns	ns	ns																					
74H	841231	00	1.10	12.0	<270	5.9	<25	<160	<5.9	96.0	<110	<17	1.5	<6.4	<590	240	<200	34.00	<14	7.5	<10	3.1	<15	<2.5	<11	<43	33.0	15.0
74H	841232	00	0.20	5.0	52	8.2	13	<	3.1	50.0	<13	1	0.2	<	160	.88	180	11.00	3	1.8	4	0.9	<	<	<	<4	14.0	11.0
74H	841233	00	1.50	10.0	45	6.6	19	30	1.6	22.0	59	<	0.2	0.9	470	92	170	12.00	<	1.7	5	1.1	5	0.9	<	<	19.0	15.0
74H	841235	00	0.08	3.8	<	3.4	7	<	1.5	48.0	<12	<	0.1	0.8	<	130	230	11.00	<	1.2	3	1.1	2	<	<	<4	15.0	21.3
74H	841236	00	0.67	10.0	77	20.0	24	<25	3.4	51.0	30	5	0.2	1.7	350	222	370	19.00	<2	2.3	6	2.5	3	1.1	<	<6	29.0	38.5
74H	841237	00	0.67	7.1	53	7.9	15	<	2.5	42.0	29	<	0.1	1.1	320	110	190	12.00	2	1.5	4	0.7	2	0.5	2	<	15.0	5.5
74H	841238	00	0.15	3.4	43	2.0	7	<	2.6	47.0	<10	<	0.2	1.0	95	72	150	8.90	2	1.0	2	0.5	<	<	<	<8.8	3.9	
74H	841239	00	0.16	3.0	29	3.6	10	<	1.7	40.0	<11	2	0.1	<	110	54	120	7.20	<	0.9	<	0.4	<	<	<4	8.1	2.7	
74H	841240	00	0.14	2.9	29	3.2	7	<	1.6	35.0	<2	<	0.7	150	42	84	5.90	<	0.8	<	0.3	<	<	<	<	7.1	2.7	
74H	841242	00	2.08	5.4	38	3.1	12	<	1.4	8.3	85	2	0.1	1.6	600	70	120	10.00	<	1.3	3	0.6	8	<	1	<	11.0	3.7
74H	841243	00	0.29	5.0	<	4.5	10	<	1.6	32.0	15	6	<	0.8	140	110	190	15.00	2	1.4	3	0.6	<	<	<	12.0	6.8	
74H	841245	10	0.19	6.7	53	9.3	17	24	3.0	43.0	<	5	0.1	0.8	140	190	350	22.70	<	2.3	6	0.9	3	<	2	<	18.0	5.0
74H	841246	20	0.18	7.3	53	10.0	17	<	3.3	44.0	<11	6	0.1	1.6	170	190	350	22.60	2	2.4	7	0.7	2	0.6	<	<5	19.0	5.1
74H	841247	00	0.44	4.7	20	1.2	<	<	1.8	36.0	26	5	0.2	1.4	190	110	91	21.20	2	2.5	6	1.1	1	0.5	<	5	10.0	16.0
74H	841248	00	0.58	4.6	36	2.3	<	32	1.5	60.0	17	7	0.2	0.8	210	160	260	27.30	2	3.0	5	1.0	3	<	<	<5	24.8	14.0
74H	841249	00	0.09	2.6	<	2.7	7	<	1.3	42.0	<	5	0.1	<	<	100	170	14.00	1	1.6	4	0.7	<	<	<	11.0	7.2	
74H	841250	00	2.42	7.0	85	7.1	7	<	1.8	7.8	90	<	0.2	1.4	600	69	110	10.00	<	1.0	4	0.6	12	1.4	<	<	23.2	3.7
74H	841251	00	0.37	4.6	38	3.7	5	<	1.9	20.0	17	2	0.2	0.7	160	93	150	15.00	<	1.8	4	0.9	2	<	2	4	13.0	11.0
74H	841252	00	0.13	3.2	33	0.8	<	<	1.7	23.0	<3	0.3	0.8	<	96	120	14.00	<	1.3	3	0.6	<	<	<	<	10.0	5.9	
74H	841253	00	0.24	4.9	22	1.9	6	<	2.0	41.0	8	2	0.2	<	160	85	150	12.00	3	1.5	5	0.8	2	0.5	<	<	13.0	12.0
74H	841254	00	0.12	5.0	40	1.7	9	<	2.2	45.0	9	3	0.2	<	130	72	140	12.00	2	1.3	3	0.7	<	<	<	12.0	3.6	
74H	841255	00	0.39	8.5	29	27.4	17	<	5.7	40.0	25	6	0.2	1.1	1900	99	160	15.00	1	1.6	6	1.0	3	<	<	<	16.0	4.9
74H	841256	00	0.10	4.5	39	1.7	5	<	2.4	46.0	6	2	0.2	0.8	62	41	83	7.20	<	0.9	3	0.5	<	<	1	<	8.4	4.2
74H	841257	00	0.14	3.7	32	4.4	6	<	2.1	28.0	<4	4	0.1	0.8	150	58	110	10.00	<	1.1	4	0.6	<	<	<	<	9.5	4.0
74H	841258	00	2.00	6.4	46	7.8	10	<	1.1	17.0	73	3	0.2	0.7	610	72	130	12.00	<	1.5	5	0.7	5	<	<	<	16.0	4.1
74H	841259	00	1.10	5.2	51	5.5	8	20	3.7	26.0	38	3	0.2	1.0	340	46	81	8.60	<	1.0	3	0.6	5	<	<	<	14.0	4.2
74H	841260	00	0.58	8.9	54	11.0	11	<	5.1	58.0	23	5	0.3	1.2	280	120	220	18.00	2	2.3	6	1.1	3	<	<	<	19.0	7.3
74H	841262	00	0.22	8.9	33	6.1	<	<	3.2	49.0	<5	5	0.4	<	89	180	290	26.00	3	3.0	7	1.4	2	<	2	<	18.0	9.0
74H	841264	00	1.00	11.0	58	13.0	31	21	3.1	32.0	43	5	0.2	1.6	490	120	230	17.00	1	2.2	6	1.2	4	0.6	<	<	22.2	7.0
74H	841265	10	0.39	5.9	46	3.5	8	22	0.9	37.0	8	4	0.1	<	220	120	250	22.80	2	3.2	9	1.5	2	<	<	<	22.3	15.0
74H	841266	20	0.38	5.2	34	3.1	11	<	1.2	33.0	12	3	0.1	0.6	150	110	210	20.90	2	2.9	7	1.2	2	0.6	<	<	21.5	14.0
74H	841267	00	0.28	9.0	60	28.8	14	36	5.0	49.0	15	13	0.6	<	95	160	240	23.00	3	2.9	8	1.6	4	0.6	<2	<4	21.1	14.0
74H	841268	00	0.21	3.8	<	3.6	6	<	1.9	34.0	10	4	0.3	0.8	110	72	120	12.00	1	1.5	4	0.6	1	<	<	<	10.0	8.5

</

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data													Sample Media: Sediments																		Waters																
Map	ID	ZN	UTM			Rock	Lake	Type	Age	Area	Dep	RS	Rlf	Cont	Colr	Susp	Detection Limit:												Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Units:												ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	1.0	0.5	ppm	ppm	ppm	ppm	F-ppb	pH	ppb									
74H	841269	13	519339	6326672	WFB	04	.25-1	4	00	Md	-	Br	-	56	9	<	10	4	<	110	<	<	.89	65	43.8	1.3	10	.4	<	110	6.4	<															
74H	841270	13	524202	6327393	WFB	04	.25-1	2	00	Md	-	Br	-	64	10	<	11	4	<	95	<	<	1.63	58	52.4	3.2	15	.4	<	180	5.8	<															
74H	841271	13	528008	6325756	X	04	.25-1	5	00	Md	-	Br	-	13	17	<	10	10	<	400	1.0	6	4.70	128	41.4	13.7	35	.6	<	130	6.4	0.11															
74H	841272	13	529971	6326733	PBN	04	1-5	17	00	Md	-	Br	-	160	23	<	14	15	<	5000	25.7	18	2.80	71	33.0	14.6	75	.2	1.4	150	6.8	0.05															
74H	841273	13	533205	6325197	RGM	04	.25-1	3	00	Md	-	Br	-	110	29	<	19	11	<	270	<	2	4.10	71	43.8	3.0	45	.2	<	72	6.1	<															
74H	841274	13	539175	6325805	RGM	04	.25-1	3	00	Lw	-	Br	-	87	38	<	19	10	<	315	<	<	1.79	84	40.2	24.1	30	.4	<	62	5.9	0.25															
74H	841275	13	539164	6328428	PBN	04	.25-1	1	00	Md	-	Br	-	130	21	<	8	7	<	405	1.0	<	10.4	65	52.8	6.6	100	.2	<	140	6.4	<															
74H	841276	13	540529	6329583	PBN	04	.25-1	4	00	Lw	-	Br	-	140	32	<	13	17	<	640	2.0	14	17.9	65	35.2	19.5	110	.2	<	78	6.6	<															
74H	841277	13	544044	6330282	PBN	04	1-5	11	00	Md	-	Br	-	180	23	<	8	14	<	1520	4.0	8	22.7	84	33.4	7.3	60	.2	<	130	6.5	<															
74H	841278	13	547721	6329447	PBN	04	.25-1	7	00	Lw	-	Br	-	130	43	<	18	12	<	660	<	2	9.00	100	37.4	6.4	45	.4	<	94	6.6	<															
74H	841279	13	553242	6328876	PGN	04	1-5	4	00	Md	-	Br	-	63	25	<	15	11	<	765	2.0	2	2.40	27	3.4	5.8	20	<	<	96	6.5	<															
74H	841280	13	555112	6328669	PGN	04	.25-1	2	00	Lw	-	Br	Lgt	120	20	<	9	8	<	475	1.0	<	3.50	93	32.2	2.5	35	.6	<	70	6.0	<															
74H	841282	13	558768	6329044	PGN	04	.25-1	1	00	Lw	-	Br	Lgt	49	14	<	8	5	<	220	<	<	.87	93	38.6	2.7	10	.2	<	100	6.3	<															
74H	841283	13	557946	6326439	PGN	04	1-5	6	10	Md	-	Br	-	210	62	<	27	21	<	3000	1.0	12	7.80	73	29.0	14.8	55	1.0	<	72	6.5	<															
74H	841284	13	557946	6326439	PGN	04	1-5	6	20	Md	-	Br	-	140	35	2	16	15	<	1950	2.0	8	5.50	53	13.6	8.5	40	.4	<	74	6.7	0.06															
74H	841285	13	554347	6326535	PBNG	04	.25-1	6	00	Md	-	Br	-	230	49	<	21	25	<	1600	1.0	10	7.00	53	35.2	21.1	55	1.0	<	88	6.6	0.05															
74H	841286	13	552256	6325723	PBNG	04	.25-1	1	00	Lw	-	Br	-	95	19	<	11	5	<	205	<	8	2.40	67	40.4	28.9	30	.4	<	210	6.3	0.33															
74H	841287	13	549824	6327037	PBNG	04	1-5	17	00	Md	-	Br	-	200	48	<	18	25	<	3950	3.0	20	33.0	103	35.4	21.1	95	.2	<	110	6.7	0.06															
74H	841289	13	544199	6325838	RGPX	04	.25-1	1	00	Lw	-	Br	-	100	25	<	13	10	<	575	1.0	<	5.60	65	21.8	13.3	45	.2	<	120	6.6	0.08															
74H	841290	13	542087	6326090	RGPX	04	.25-1	2	00	Md	-	Br	-	120	25	<	15	7	<	190	<	2	1.45	77	42.0	39.8	20	.4	<	74	5.6	0.5															
74H	841291	13	533127	6322727	RGPX	04	1-5	11	00	Md	-	Br	-	210	36	<	15	31	<	2660	1.0	12	18.2	97	34.0	29.2	65	.6	<	94	6.4	0.1															
74H	841292	13	530228	6322092	RGM	04	.25-1	5	00	Md	-	Br	-	110	26	<	13	12	<	330	<	2	5.20	116	39.8	4.1	60	.4	<	120	6.2	<															
74H	841293	13	526727	6320826	PBNG	04	.25-1	2	00	Md	-	Br	-	130	38	<	18	14	<	525	<	2	7.70	84	45.4	5.3	70	.2	<	92	6.3	<															
74H	841294	13	534611	6318215	RGPX	04	1-5	13	00	Md	-	Br	-	130	31	2	14	10	<	700	<	<	5.00	84	28.4	12.9	35	.4	<	110	6.3	<															
74H	841295	13	536641	6320790	RGPX	04	.25-1	4	00	Md	-	Br	-	73	77	4	16	30	.2	435	4.0	6	9.60	103	34.6	<	90	<	<	180	6.7	0.05															
74H	841296	13	538684	6320010	RGPX	04	.25-1	3	00	Lw	-	Br	-	100	41	<	13	10	<	230	<	<	1.02	77	57.4	29.9	10	.2	<	100	6.0	0.1															
74H	841297	13	540819	6320561	RGPX	04	pond	2	00	Md	-	Br	Lgt	90	18	<	11	6	<	125	<	2	3.80	84	43.0	9.5	35	.2	<	120	6.1	1.0															
74H	841298	13	539976	6322603	RGPX	04	.25-1	3	00	Md	-	Br	-	120	17	<	12	15	<	710	<	<	4.80	39	17.8	27.5	25	.2	<	150	6.7	0.13															
74H	841299	13	544249	6322674	RGPX	04	.25-1	5	00	Md	-	Gn	-	120	23	<	13	7	<	345	<	<	4.50	77	38.2	6.8	25	.4	<	160	6.2	<															
74H	841300	13	547459	6323538	RGPX	04	.25-1	6	00	Md	-	Gn	-	120	18	<	12	8	<	360	<	<	5.20	84	31.8	7.4	20	.2	<	150	6.1	0.05															
74H	841302	13	545761	6320505	RGPX	04	pond	3	00	Md	-	Br	-	73	18	<	14	8	<	265	<	<	1.00	52	37.6	7.9	20	.2	<	98	6.3	<															
74H	841303	13	548103	6319547	RGPX	04	.25-1	3	10	Md	-	Br	-	100	14	<	5	8	<	390	3.0	<	5.40	45	23.2	4.2	25	<	<	98	5.9	<															
74H	841304	13	548103	6319547	RGPX	04	.25-1	3	20	Md	-	Br	-	120	13	<	8	7	<	400	4.0	<	6.50	26	11.4	3.7	25	.2	<	96	6.2	<															
74H	841305	13	552187	6318636	RGPX	04	.25-1	10	00	Md	-	Br	-	92	27	<	14	6	<	185	9.0	<	1.42	87	47.2	4.3	20	.4	<	64	6.1	<															
74H	841306	13	553618	6321708	RGPX	04	.25-1	5	00	Md	-	Br	-	100	27	<	11	10	<	310	<	<	3.50	93	44.6	5.7																					

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element:	Lake Sediment - INAA Data																												
	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U			
	Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm			
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2			
Map	ID	RS																											
74H	841269	00	0.06	1.8	<	0.8	<	<	1.7	38.0	<	2	0.3	<	57	33	49	5.00	<	0.6	<	0.3	<	<	<	4.7	1.6		
74H	841270	00	0.09	2.8	28	1.6	<	<	2.0	25.0	9	3	0.1	0.7	130	75	140	11.00	<	1.2	3	0.5	<	<	<	8.4	2.8		
74H	841271	00	0.20	5.3	46	4.1	12	<	3.7	62.0	<	6	0.2	<	110	170	260	23.30	2	2.6	7	1.4	<	<	<	18.0	14.0		
74H	841272	00	0.35	9.2	30	33.2	17	<	36.0	50.0	24	18	0.9	1.4	330	331	629	45.20	3	4.8	15	2.3	3	<	3	29.3	17.0		
74H	841273	00	0.35	6.3	45	4.1	13	<	1.9	53.0	14	4	<	1.3	130	93	160	12.00	2	1.0	3	0.5	2	<	<	12.0	2.4		
74H	841274	00	0.26	5.3	43	2.0	13	20	1.5	49.0	<	5	<	0.7	180	86	170	11.00	<	1.3	3	0.8	2	<	<	<	10.0	28.2	
74H	841275	00	0.21	10.0	73	11.0	8	<	4.3	77.0	<11	6	0.1	1.0	100	308	518	32.90	4	3.3	8	1.4	<	<	<	25.5	27.1		
74H	841276	00	0.90	12.0	81	18.0	17	20	5.5	54.0	40	14	0.2	1.2	280	270	410	37.20	3	3.8	11	2.1	5	0.6	<	<	25.4	19.0	
74H	841277	00	0.38	7.7	29	21.8	15	<	5.4	39.0	23	9	0.2	1.4	210	180	330	20.30	2	2.2	6	1.0	3	<	<	<	19.0	6.2	
74H	841278	00	0.50	9.4	67	11.0	18	<	3.1	70.0	17	7	0.2	0.9	250	218	360	24.60	4	2.2	5	1.0	3	0.6	<2	<4	25.4	10.0	
74H	841279	00	2.44	6.9	31	3.4	13	<	3.1	25.0	110	6	0.2	1.9	800	66	110	8.80	1	1.3	4	0.7	11	0.9	2	<	15.0	6.5	
74H	841280	00	1.00	5.2	34	3.2	10	<	2.0	32.0	36	3	0.1	0.7	330	54	98	7.30	1	0.8	2	0.4	4	0.5	<	<	7.8	2.2	
74H	841282	00	0.13	1.5	<	0.7	<	<	1.4	24.0	<	2	0.1	<	82	36	63	4.50	<	<	<	<	<	<	<	<	4.6	1.7	
74H	841283	10	0.46	10.0	61	6.8	23	<	3.0	39.0	19	14	0.1	0.8	380	251	450	30.70	3	3.2	8	1.3	2	0.7	<2	<4	27.9	16.0	
74H	841284	20	1.60	8.5	41	5.7	20	23	2.6	20.0	68	10	0.2	2.0	610	150	270	18.00	2	2.1	5	1.0	9	0.7	2	<	20.0	10.0	
74H	841285	00	0.71	10.0	68	6.4	15	<	2.9	62.0	36	14	0.2	1.6	360	190	330	24.40	2	2.7	7	1.2	3	0.7	<2	6	23.9	24.6	
74H	841286	00	0.10	2.1	26	2.0	7	<	1.5	44.0	<	9	0.4	<	120	65	100	7.90	<	1.0	<	0.6	<	<	<	2	<	7.3	32.7
74H	841287	00	0.38	18.0	90	46.3	35	<21	6.3	63.0	30	26	0.2	<	300	403	691	49.80	5	4.9	12	2.2	4	0.6	<3	<6	42.4	28.4	
74H	841289	00	1.10	8.2	54	4.9	12	<	2.9	31.0	54	4	0.1	1.8	400	140	260	19.00	2	2.2	5	0.9	6	0.6	<	<	21.7	15.0	
74H	841290	00	0.24	3.6	33	1.6	<	<	1.7	44.0	10	5	0.2	0.7	140	69	140	8.50	1	1.2	2	0.9	1	<	<	<	10.0	47.9	
74H	841291	00	0.41	12.0	68	22.7	47	<	4.6	47.0	14	12	0.1	1.2	360	238	430	27.30	3	3.0	9	1.8	3	0.5	<3	<5	28.4	40.1	
74H	841292	00	0.27	5.2	44	5.1	14	<	2.5	50.0	12	3	0.1	<	170	140	240	15.00	2	1.5	4	0.6	<	<	<	<	14.0	5.6	
74H	841293	00	0.12	6.8	38	6.4	16	<	2.1	41.0	12	4	<	0.6	170	130	230	15.00	2	1.4	2	0.4	2	<	<	<	17.0	4.8	
74H	841294	00	0.63	8.7	55	4.7	9	<	2.5	47.0	27	3	0.1	1.3	330	212	360	24.90	3	2.1	5	1.0	4	<	<	<	25.2	15.0	
74H	841295	00	0.23	12.0	67	7.8	24	<	5.6	42.0	<14	11	0.2	<	150	698	784	105.00	12	8.6	16	3.2	2	<	<3	<6	36.4	41.3	
74H	841296	00	0.36	4.4	21	1.1	9	<	1.3	35.0	19	4	0.1	<	190	53	94	8.00	1	0.8	3	0.8	3	<	<	<	7.6	28.7	
74H	841297	00	0.12	3.1	27	2.9	6	<	1.5	34.0	<	6	0.1	<	160	51	96	7.50	1	0.7	3	0.6	1	<	<	<	6.2	10.0	
74H	841298	00	1.90	7.0	44	5.1	19	<	2.8	27.0	76	3	0.2	1.3	610	77	130	9.20	1	1.0	4	0.9	7	0.7	2	<	16.0	31.2	
74H	841299	00	0.60	4.8	26	3.9	9	<	2.3	42.0	27	4	0.1	1.0	240	68	120	8.80	1	1.0	3	0.5	3	0.6	<	<	11.0	7.1	
74H	841300	00	1.00	5.7	33	5.3	11	22	2.7	39.0	40	5	0.2	1.0	370	81	140	10.00	2	1.2	4	0.6	5	0.8	<	<	13.0	7.6	
74H	841302	00	0.29	4.2	28	1.0	5	<	1.5	42.0	12	1	0.1	<	230	73	130	13.00	1	1.2	2	0.5	2	<	<	<	10.0	8.1	
74H	841303	10	1.00	4.0	28	6.0	10	<	5.5	27.0	40	4	<	0.7	380	60	110	8.80	<	1.0	3	0.5	3	<	<	<	10.0	4.4	
74H	841304	20	1.80	2.8	22	11.0	11	<	10.0	12.0	99	5	0.2	0.9	630	39	73	6.00	<	0.8	2	0.3	2	<	1	<	7.0	3.1	
74H	841305	00	0.45	4.4	34	1.5	9	23	1.4	53.0	14	1	<	1.3	220	74	130	12.00	1	1.1	3	0.6	2	<	<	<	10.0	4.4	
74H	841306	00	0.21	4.3	28	3.4	7	<	2.0	46.0	10	2	0.1	<	130	89	150	11.00	2	1.2	3	0.5	1	<	<	<	8.7	6.0	
74H	841307	00	0.51	7.4	47	8.5	11	<	1.7	32.0	25	6	0.1	1.7	250	120	210	16.00	3	1.7	5	0.8	3	<	<2	<	14.0	8.4	
74H	841308	00	0.36	7.0	54	5.3	13	37	2.2	59.0	18	4	<	1.0	360	180	350	23.30	3	2.1	6	1.0	1	<	<2	<4	15.0	6.3	
74H	841309	00	0.75	6.1	30	3.4	8	<	1.7	32.0	34	2	<	0.8	350	150	270	20.00	3	2.1	5	0.8	3	<	<	<	15.0	3.6	
74H	841310	00	0.23	4.3	47	2.6	6	<	1.4	43.0	8	2	0.1	0.6	200	110	200	16.00	1	1.6	4	0.6	2	<	2	<	11.0	3.4	
74H	841311	00	1.40	6.2	48	11.0	13	<	7.1	31.0	64	3	0.2	1.5	870	89	140	12.00	2	1.4	4	0.8	5	0.7	<	<	18.0	5.6	

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data											Sample Media: Sediments																Waters						
Map	ID	ZN	UTM		Rock			Lake			Cont	Colr	Susp	Variable:	Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep	RS	Rlf				ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	10	1.0	0.5	ppm	5	ppm	0.2	0.2	ppb	20
Detection Limit:											2	2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	0.2	0.2	ppb	20	0.05			
74H	841312	13	555137	6359251	WRN	04	1-5	7	00	Md	-	Br	-	180	16	<	12	17	<	1750	3.0	12	18.0	80	32.6	14.6	55	.2	<	160	6.3	0.06	
74H	841313	13	553181	6357860	WPF	04	.25-1	3	00	Md	-	Br	-	52	10	<	12	6	<	185	<	<	.76	53	34.2	3.3	10	.2	<	280	5.9	<	
74H	841314	13	547839	6357960	WFN	04	.25-1	4	00	Lw	-	Br	-	130	12	<	9	7	<	385	<	2	6.10	71	51.8	6.9	30	.2	<	150	5.5	<	
74H	841315	13	544052	6359246	WPF	04	.25-1	1	00	Md	-	Br	-	54	6	<	6	4	<	260	<	<	2.00	58	38.2	3.6	5	.2	<	200	6.2	<	
74H	841316	13	540998	6357070	WRN	04	1-5	3	00	Md	-	Br	-	100	9	<	11	6	<	225	<	<	1.38	45	34.8	6.3	10	.6	<	86	5.8	0.06	
74H	841317	13	539186	6360162	WRN	04	.25-1	3	00	Md	-	Br	-	70	12	<	15	4	<	255	<	<	.91	52	32.2	8.3	5	.4	<	82	6.3	0.06	
74H	841318	13	537161	6361235	WCN	04	1-5	4	00	Md	-	Gn	-	100	12	<	12	7	<	525	<	<	5.00	52	34.2	5.2	20	.2	<	90	6.3	<	
74H	841319	13	535126	6358252	WRN	04	.25-1	2	00	Md	-	Br	-	88	11	<	15	7	<	290	<	<	2.90	52	37.8	7.7	20	.2	<	100	6.3	0.07	
74H	841322	13	530932	6359774	WRN	04	1-5	1	00	Md	-	Br	-	83	8	<	13	7	<	210	<	<	1.33	45	37.6	6.4	15	.4	<	70	6.0	0.06	
74H	841323	13	527347	6359182	WRN	04	.25-1	20	00	Md	-	Bk	-	110	20	<	13	23	<	3550	9.0	16	21.8	58	32.4	21.2	70	<	.4	68	6.9	<	
74H	841324	13	523362	6357941	WRN	04	1-5	1	00	Lw	-	Br	-	100	11	<	12	6	<	225	<	2	4.70	39	43.8	2.8	35	.2	<	54	6.0	<	
74H	841325	13	520015	6358815	WRN	04	pond	1	00	Lw	-	Br	-	93	7	<	11	7	<	275	<	2	3.00	58	40.0	5.6	30	.4	<	58	6.7	0.05	
74H	841326	13	515216	6357706	WRN	04	.25-1	11	10	Md	-	Br	-	140	17	<	11	5	<	750	1.0	2	4.40	103	38.8	6.5	25	.8	<	48	6.3	0.06	
74H	841327	13	515216	6357706	WRN	04	.25-1	11	20	Md	-	Br	-	120	17	<	12	6	<	755	1.0	<	4.10	90	40.6	8.3	25	.6	<	46	6.4	0.06	
74H	841328	13	511543	6359489	MFB	04	1-5	2	00	Lw	-	Br	-	120	11	<	13	9	<	595	4.0	<	10.5	58	43.0	5.1	25	.4	<	36	6.3	<	
74H	841330	13	508222	6360496	MFB	04	.25-1	5	00	Md	-	Br	-	60	7	<	5	5	<	165	1.0	<	7.30	26	28.2	2.5	20	.2	<	26	6.1	<	
74H	841331	13	507944	6359248	MFB	04	.25-1	3	00	Md	-	-	-	13	2	<	4	3	<	55	1.0	<	1.00	13	2.2	1.8	5	<	<	26	6.2	<	
74H	841332	13	504659	6358046	MFB	04	.25-1	1	00	Md	-	Br	-	66	23	<	19	8	<	160	<	<	1.35	52	36.6	1.5	15	.2	<	24	6.1	<	
74H	841333	13	500692	6357422	WRN	04	1-5	6	00	Md	-	Bk	-	140	22	<	24	17	<	495	2.0	<	1.40	77	45.0	2.9	80	.2	<	22	6.2	<	
74H	841334	13	501902	6362811	MFB	04	.25-1	2	00	Md	-	Br	-	74	27	<	13	9	<	200	3.0	<	2.50	39	34.8	1.8	130	.2	<	24	6.4	<	
74H	841335	13	503686	6364730	DD	04	.25-1	3	00	Lw	-	Br	-	100	25	<	12	10	<	165	<	<	1.80	52	60.0	1.0	25	.8	<	<	5.5	<	
74H	841336	13	502621	6366097	DD	04	.25-1	3	00	Md	-	Br	-	100	23	<	13	9	<	440	1.0	<	7.00	65	37.2	1.7	35	.4	<	<	6.3	<	
74H	841337	13	504875	6367871	WPSN	04	.25-1	5	00	Md	-	Br	-	80	23	<	11	5	<	205	<	<	1.18	65	42.6	2.5	25	.8	<	<	6.1	<	
74H	841338	13	503424	6368467	DD	04	1-5	9	00	Md	-	Br	-	83	17	<	13	10	<	545	3.0	<	3.60	58	27.0	2.4	25	.4	<	26	6.2	<	
74H	841339	13	501637	6372170	WPSN	04	.25-1	6	00	Md	-	Br	-	82	7	<	5	4	<	65	<	<	.60	19	53.4	.8	10	.6	<	<	5.8	<	
74H	841340	13	504873	6375511	WPSN	04	1-5	7	00	Md	-	Br	-	20	<	<	<	3	<	45	<	<	.49	13	6.4	.7	5	.2	<	24	6.2	<	
74H	841342	13	506724	6372350	WRN	04	1-5	7	00	Md	-	Gn	-	200	13	<	8	10	<	1290	4.0	2	18.6	39	41.2	1.7	35	.4	<	24	6.3	<	
74H	841343	13	510989	6369809	WRN	04	.25-1	6	10	Md	-	Gn	-	95	12	<	9	8	<	365	7.0	2	19.2	45	41.6	2.8	75	<	<	24	6.5	<	
74H	841344	13	510989	6369809	WRN	04	.25-1	6	20	Md	-	Gn	-	95	13	<	9	10	<	395	6.0	2	17.0	45	44.6	2.9	65	<	<	24	6.3	<	
74H	841345	13	510001	6367720	WRN	04	.25-1	6	00	Md	-	Gn	-	95	9	<	7	13	<	925	13.0	4	25.3	45	31.2	3.1	35	<	<	24	6.4	<	
74H	841346	13	509343	6366286	WRN	04	1-5	22	00	Md	-	Br	-	130	11	<	8	13	<	880	6.0	<	15.6	58	24.2	2.1	35	.2	<	24	6.5	<	
74H	841347	13	513783	6365624	WRN	04	>5	1	00	Md	-	Br	-	23	2	5	2	3	<	115	<	<	1.23	19	8.6	1.3	5	<	.7	30	6.3	<	
74H	841348	13	511124	6362551	WRN	04	pond	1	00	Md	-	Br	-	110	11	2	9	10	<	965	4.0	<	14.3	65	45.2	4.2	30	.4	<	28	6.3	<	
74H	841349	13	514915	6362022	WRN	04	pond	4	00	Lw	-	Br	Lgt	95	10	<	13	5	<	315	1.0	<	1.66	65	42.0	2.8	40	.6	<	28	6.0	<	
74H	841350	13	519084	6363512	WRN	04	.25-1	1	00	Lw	-	Br	-	100	13	<	18	8	<	295	<	<	1.22	67	53.4	4.6	20	.6	<	34	5.8	<	
74H	841351	13	522293	6361187	WRN	04	.25-1	1	00	Lw	-	Br	-	95	10	<	9	6	<	385													

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																										
Element:	Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U		
Units:	pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm			
Detection Limit:	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
Map	ID	RS																										
74H	841312	00	0.27	6.1	43	16.0	17	<	3.1	32.0	16	10	0.1	0.9	190	150	260	19.00	1	2.3	7	1.3	1	<	2	<	20.8	13.0
74H	841313	00	0.14	2.4	<	0.7	<	<	1.3	26.0	10	3	0.2	<	70	64	120	7.50	<	0.9	2	0.4	<	<	<	<	9.3	3.3
74H	841314	00	0.09	2.7	30	4.8	9	24	2.1	48.0	<	3	0.4	0.6	76	90	170	13.00	1	1.5	4	0.8	<	<	<	<	12.0	6.3
74H	841315	00	0.11	1.6	<	1.3	<	<	1.4	27.0	<	2	<	<	100	29	45	4.20	<	<	<	0.3	<	<	<	2	4.9	3.4
74H	841316	00	0.82	4.0	30	1.6	7	<	1.7	23.0	34	2	0.2	0.7	260	58	100	8.00	1	0.9	3	0.5	4	<	<	<	10.0	6.2
74H	841317	00	0.33	3.4	30	0.9	<	<	1.2	25.0	11	3	0.2	0.7	160	54	91	7.90	<	1.0	4	0.5	2	<	<	<	10.0	7.9
74H	841318	00	0.31	4.5	24	4.5	7	20	2.9	32.0	14	4	0.1	0.8	110	46	82	6.20	<	1.1	2	0.4	2	<	<	<	11.0	5.2
74H	841319	00	0.46	5.9	55	3.1	13	22	2.7	48.0	19	2	0.2	1.9	190	79	150	11.00	2	1.5	4	0.7	2	<	<	<	16.0	9.5
74H	841322	00	0.69	4.6	42	1.7	8	<	2.9	31.0	26	2	0.2	1.0	290	41	68	5.50	1	0.8	3	0.4	3	<	<	<	10.0	7.7
74H	841323	00	0.56	4.5	59	20.2	22	<	10.0	43.0	35	12	0.4	1.6	380	73	80	13.00	1	1.7	5	1.0	2	0.5	<	<	12.0	21.2
74H	841324	00	0.34	4.4	41	4.0	10	<	3.4	34.0	18	2	0.2	1.0	170	32	61	6.50	1	1.0	3	0.5	3	0.5	<	<	10.0	4.2
74H	841325	00	0.42	3.7	42	2.8	6	<	2.4	29.0	20	2	0.2	<	220	36	69	5.60	2	0.7	3	0.4	3	<	<	<	10.0	5.4
74H	841326	10	0.15	5.9	42	4.4	6	28	4.5	56.0	20	3	0.3	1.1	220	49	88	8.50	2	1.1	4	0.7	2	<	3	<	12.0	9.3
74H	841327	20	0.31	5.4	47	3.6	7	<	3.2	49.0	14	3	0.2	1.0	210	42	83	7.30	<	1.0	3	0.6	2	<	<	<	11.0	8.5
74H	841328	00	0.48	6.2	56	11.0	9	<	7.3	34.0	29	2	0.3	1.6	250	31	58	5.40	1	0.9	4	0.5	6	0.7	<	4	17.0	5.1
74H	841330	00	0.54	4.2	<	7.8	<	<	2.8	26.0	24	2	0.3	0.8	170	23	45	4.70	<	0.7	3	0.5	11	0.7	<	<	11.0	2.6
74H	841331	00	0.68	2.6	<	1.2	<	<	2.4	3.4	30	<	0.2	0.7	200	19	31	2.80	<	<	0.3	12	0.7	<	<	<	11.0	1.8
74H	841332	00	0.08	8.6	<	1.4	8	<	3.1	27.0	<	2	0.2	<	100	10	25	3.00	<	0.6	2	0.3	1	<	<	<	12.0	1.6
74H	841333	00	0.25	10.0	28	13.0	18	28	5.9	42.0	13	2	0.1	<	130	21	37	3.90	1	0.6	2	0.4	4	<	<	<	9.2	2.3
74H	841334	00	0.25	6.4	40	2.0	8	25	7.2	30.0	10	3	0.2	<	81	12	21	2.20	<	<	0.3	2	<	<	3	6.6	1.9	
74H	841335	00	0.07	3.8	<	1.6	9	<	2.4	39.0	<	1	0.2	<	140	6	14	2.20	<	<	0.2	<	<	<	<	4.0	1.0	
74H	841336	00	0.13	5.9	<	6.6	9	<	4.4	35.0	<	2	0.1	0.7	76	13	29	3.30	<	<	0.2	3	<	<	<	9.5	1.4	
74H	841337	00	0.10	4.3	22	1.3	<	<	1.8	42.0	<	1	0.1	0.5	130	15	21	2.70	<	<	0.2	<	<	<	<	5.1	2.1	
74H	841338	00	0.81	4.7	<	3.4	9	<	5.5	23.0	33	2	0.2	0.7	300	24	41	5.00	<	0.7	<	0.4	10	0.7	<	<	16.0	2.1
74H	841339	00	0.47	2.7	30	0.8	<	<	2.8	45.0	20	<	0.2	0.9	200	14	25	1.90	<	<	<	6	<	1	<	5.5	1.0	
74H	841340	00	0.83	1.1	<	0.6	<	<	1.2	4.4	26	<	0.1	0.5	190	8	15	1.00	<	<	<	6	<	<	<	3.7	0.5	
74H	841342	00	0.40	4.0	<	20.0	13	<	7.8	45.0	18	3	0.2	1.0	250	20	33	3.00	<	<	0.3	3	<	2	<	7.3	1.5	
74H	841343	10	0.29	2.8	55	20.0	9	<	11.0	46.0	9	3	0.2	<	140	16	28	3.70	<	0.5	<	0.3	3	<	<	<	7.8	2.8
74H	841344	20	0.36	3.4	22	19.0	9	<	10.0	50.0	15	3	0.3	0.8	140	20	34	3.80	<	0.6	2	0.5	4	<	2	<	8.6	2.9
74H	841345	00	0.28	2.9	<	28.7	14	<	16.0	33.0	13	5	0.1	0.7	130	25	37	5.40	<	0.7	3	0.5	3	<	<	<	7.4	3.3
74H	841346	00	0.62	4.1	22	15.0	12	<	8.0	25.0	28	3	0.2	0.8	230	20	42	3.80	<	0.5	2	0.4	7	0.6	2	<	11.0	1.7
74H	841347	00	1.00	2.1	<	1.3	<	<	1.4	5.6	37	<	0.7	0.5	300	13	22	1.70	<	<	<	7	<	1	<	6.4	1.4	
74H	841348	00	0.29	4.8	24	14.0	10	<	6.6	31.0	18	2	0.3	1.4	160	27	48	4.50	<	0.6	2	0.5	6	0.5	<	<	14.0	3.7
74H	841349	00	0.09	2.7	27	1.6	<	<	2.8	38.0	<	2	0.1	0.9	76	14	27	2.90	<	0.5	<	0.2	<	<	<	5.4	3.2	
74H	841350	00	0.13	3.1	24	1.1	9	<	2.3	35.0	11	2	0.2	0.8	160	27	54	4.20	<	0.6	3	0.3	<	<	<	6.5	4.1	
74H	841351	00	0.21	4.0	31	3.6	9	<	3.3	60.0	<	2	0.2	1.6	180	24	42	3.50	<	<	2	0.4	2	<	<	3	5.8	5.7
74H	841352	00	2.00	6.7	48	1.7	6	<	1.4	26.0	84	1	0.2	2.3	570	34	58	4.40	1	<	2	0.4	8	1.0	<	<	12.0	2.4
74H	841353	00	0.40	2.3	<	0.8	<	<	1.9	30.0	22	4	0.1	<	140	14	26	1.70	<	<	0.3	2	<	<	<	4.0	6.2	
74H	841354	00	0.77	4.7	28	2.7	10	<	1.6	29.0	32	2	0.2	1.3	300	43	88	6.00	1	0.8	3	0.4	3	<	<	<	11.0	5.1
74H	841355	00	0.29	4.5	22	2.5	8	<	3.1	41.0	9	4	0.2	0.7	140	57	96	5.90	<	0.7	2	0.5	1	<	<	<	10.0	6.5

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments												Waters								
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Variable: Zn Cu Pb Ni Co Ag Mn As Mo Fe Hg LOI U V Cd Sb F-W pH U-W												20	0.05					
			Easting	Northing	Type	Age	Area	Dep						2	2	2	2	2	0.2	ppm	ppm	ppm	ppm	pct	ppb	10	1.0	ppm	ppm	ppm	ppm	
74H	841357	13	545461	6360687	WFN	04	.25-1	1	00	Lw	-	Br	-	130	17	<	14	7	<	305	<	2	1.87	58	46.8	10.9	30	.6	<	140	6.0	<
74H	841358	13	549504	6361579	WFN	04	.25-1	2	00	Md	-	Gn	-	95	17	<	15	7	<	225	<	<	2.39	58	42.6	9.5	20	.4	<	140	6.0	<
74H	841359	13	551610	6361308	WFN	04	.25-1	2	00	Md	-	Br	-	71	12	<	13	6	<	265	<	<	1.17	59	33.0	5.2	15	.4	<	130	5.9	0.05
74H	841360	13	554742	6362688	WFN	04	pond	2	00	Md	-	Br	-	80	14	<	11	8	<	190	<	<	2.90	74	43.2	4.9	20	.4	<	120	5.7	<
74H	841362	13	559177	6361256	WRN	04	pond	1	00	Lw	-	Br	-	42	5	<	6	5	<	545	2.0	<	1.07	59	42.0	.5	<	.2	<	190	6.5	<
74H	841363	13	559150	6365770	WFN	04	.25-1	1	00	Md	-	Br	-	60	8	<	5	5	<	260	<	<	.95	52	35.4	1.5	<	.4	<	150	6.1	<
74H	841365	13	554869	6365987	WFN	04	pond	2	00	Md	-	Br	-	95	14	<	10	12	<	310	<	2	4.30	81	46.4	4.5	25	.4	<	110	5.9	<
74H	841366	13	552885	6366296	WFN	04	.25-1	1	00	Md	-	Br	-	70	10	<	11	5	<	210	<	<	1.72	52	30.2	6.2	20	.2	<	150	6.0	0.06
74H	841367	13	549214	6366888	WFN	04	>5	15	00	Md	-	Gn	-	90	13	5	11	6	<	655	1.0	<	4.30	44	12.0	7.1	25	.2	<	120	6.3	<
74H	841368	13	545234	6366729	WRN	04	.25-1	1	00	Lw	-	Br	-	62	6	<	11	6	<	225	<	<	1.14	50	27.0	2.8	15	.4	<	160	6.3	<
74H	841369	13	540747	6365271	WCN	04	pond	1	10	Md	-	Br	-	56	7	<	15	4	<	205	<	<	1.17	57	42.8	6.0	15	.4	<	86	5.9	<
74H	841370	13	540747	6365271	WCN	04	pond	1	20	Md	-	Br	-	57	7	<	13	5	<	200	<	<	1.10	57	43.6	6.8	10	.2	<	86	6.0	<
74H	841371	13	532542	6366080	WG	04	.25-1	2	00	Md	-	Br	-	82	9	<	10	6	<	185	<	<	1.75	50	46.8	3.2	15	.2	<	130	6.0	<
74H	841372	13	529532	6367036	WRN	04	.25-1	1	00	Lw	-	Br	-	74	5	<	8	6	<	210	<	<	1.40	36	27.2	6.2	20	.4	<	64	6.2	0.05
74H	841373	13	525559	6366273	WRN	04	.25-1	1	00	Md	-	Br	-	58	9	<	11	4	<	235	1.0	<	1.62	64	50.2	8.9	25	.4	<	64	6.3	0.06
74H	841374	13	521658	6364274	WRN	04	.25-1	3	00	Md	-	Gn	-	86	10	<	6	4	<	140	<	<	.92	29	23.6	4.4	10	.4	<	40	6.4	<
74H	841375	13	520420	6366704	WRN	04	.25-1	5	00	Md	-	Br	-	100	14	<	19	9	<	255	<	<	1.90	93	45.8	28.5	20	.6	<	40	6.0	0.25
74H	841376	13	517259	6366502	WRN	04	.25-1	1	00	Md	-	Br	-	66	7	<	14	5	<	130	<	<	1.53	57	32.4	7.5	20	.2	<	44	6.0	0.08
74H	841377	13	513263	6371417	WRN	04	pond	3	00	Lw	-	Br	-	250	6	<	9	9	<	150	<	<	.86	33	79.4	.8	15	1.2	<	<	4.9	<
74H	841378	13	509774	6376544	WRN	04	1-5	5	00	Md	-	Gn	-	89	4	<	4	8	.2	420	2.0	<	7.00	36	40.6	1.6	35	<	<	26	6.1	<
74H	841379	13	510508	6378831	WRN	04	1-5	6	00	Lw	-	Gn	-	120	5	<	9	9	.4	775	2.0	4	13.6	42	41.0	2.0	45	.2	<	26	6.2	<
74H	841380	13	511047	6383072	WRN	04	pond	2	00	Md	-	Gn	-	75	5	2	6	2	<	45	<	<	.22	18	59.6	.8	10	.4	.3	<	4.8	<
74H	841382	13	513463	6379721	WRN	04	.25-1	18	00	Hi	-	Br	-	81	5	<	2	2	.2	225	1.0	2	.93	33	46.2	.8	15	.4	.2	<	6.1	<
74H	841383	13	516204	6379597	WPSN	04	.25-1	6	10	Md	-	Gn	-	130	6	<	6	20	<	4200	11.0	<	23.1	48	31.8	2.7	75	<	<	34	6.1	<
74H	841384	13	516204	6379597	WPSN	04	.25-1	6	20	Md	-	Gn	-	120	5	<	7	16	<	3150	8.0	<	19.3	42	24.4	2.3	60	<	<	34	6.0	<
74H	841385	13	513915	6376251	WPSN	04	.25-1	11	00	Md	-	Gn	-	95	5	<	5	5	.6	135	2.0	<	1.62	30	28.8	3.1	35	.4	<	24	6.2	<
74H	841386	13	515823	6376171	WRN	04	.25-1	9	00	Md	-	Gn	-	95	5	<	6	15	<	1380	5.0	2	8.40	73	38.8	1.7	40	.2	<	32	6.3	<
74H	841387	13	516032	6373326	WRN	04	.25-1	2	00	Lw	-	Gn	-	52	2	<	4	2	<	55	1.0	<	2.76	24	25.2	1.2	20	.2	<	34	6.0	<
74H	841388	13	519765	6373401	WRN	04	1-5	6	00	Md	-	Gn	-	33	3	<	4	3	<	145	2.0	<	3.90	24	15.0	1.7	15	<	<	34	6.1	<
74H	841389	13	521277	6370704	WRN	04	1-5	3	00	Md	-	Br	-	140	10	<	13	7	<	395	1.0	2	4.60	61	39.4	12.3	20	.2	<	42	6.0	0.07
74H	841390	13	524795	6369773	WRN	04	.25-1	1	00	Md	-	Br	-	37	4	<	7	2	.2	50	<	<	6.70	48	38.2	48.8	20	.2	<	74	6.4	0.32
74H	841391	13	528300	6369524	WRN	04	1-5	4	00	Md	-	Gn	-	83	9	<	11	6	<	330	<	<	2.12	61	30.2	11.0	20	.2	<	66	6.3	0.08
74H	841392	13	530498	6370476	WRN	04	.25-1	4	00	Md	-	Br	-	43	4	<	11	5	<	265	<	2	1.00	61	38.4	53.2	15	.2	<	90	6.8	0.25
74H	841394	13	534697	6369540	WRN	04	.25-1	3	00	Md	-	Br	-	79	4	<	8	5	<	300	<	2	3.00	42	49.4	2.9	15	.5	<	64	5.7	<
74H	841395	13	539320	6369821	WRN	04	pond	1	00	Lw	-	Br	-	45	3	<	10	5	<	205	<	<	1.67	82	43.6	2.8	30	.2	<	100	6.0	<
74H	841396	13	540547	6369766	WG	04	pond	1	00	Lw	-	Br	Lgt	74	5	<	14	7	<	325	<	2	1.26	67	47.0	3.2	20	.2	<	82	5.8	<
74H	841397	13	545470	6369557	WRN	04	1-5	1	00	Lw	-	Br	-	53	3	<	12	6	.2	155	<	2	.68	52	33.8	5.5	10	.2	<	110	6.3	<
74H	841																															

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																									
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2
Map	ID	RS																									
74H	841357 00	0.18	3.8	39	1.9	11	25	1.8	47.0	<	7	0.1	<	160	83	150	13.00	2	1.5	4	0.7	2	<	<	<	13.0	11.0
74H	841358 00	0.12	2.9	<	1.9	8	<	1.6	29.0	8	5	0.2	<	110	62	100	8.80	<	1.0	3	0.5	<	<	2	3	10.0	10.0
74H	841359 00	0.31	3.2	23	1.2	6	<	1.5	27.0	11	3	<	<	190	88	160	12.00	<	1.4	4	0.6	1	<	<	<	12.0	4.9
74H	841360 00	0.08	3.4	<	2.4	6	<	1.5	32.0	<	3	<	<	120	120	210	13.00	<	1.5	4	0.6	<	<	<	5	16.0	4.4
74H	841362 00	0.04	1.0	<	1.1	<	<	4.6	39.0	<	2	0.2	<	120	7	15	1.50	<	<	<	<	<	<	<	<	2.0	0.6
74H	841363 00	0.13	1.6	<	0.8	6	<	1.4	26.0	<	2	<	<	81	26	40	3.40	<	<	<	0.2	1	<	<	<	4.4	1.2
74H	841365 00	0.08	2.9	<	4.0	11	<	2.3	41.0	<	5	0.2	<	150	70	120	9.30	<	1.2	3	0.6	<	<	<	<	10.0	4.1
74H	841366 00	0.48	4.3	<	2.2	5	<	2.3	30.0	23	4	0.2	0.9	220	90	150	13.00	<	1.5	3	0.6	3	<	<	4	14.0	8.5
74H	841367 00	1.80	7.9	51	4.6	8	<	2.8	22.0	84	4	0.3	1.9	680	88	150	12.00	<	1.6	5	0.7	8	1.0	2	<	20.2	7.7
74H	841368 00	0.60	2.9	25	1.2	<	<	2.0	20.0	29	2	0.2	0.8	230	29	53	4.60	<	0.7	<	0.3	3	<	2	<	7.4	2.7
74H	841369 10	0.05	2.8	<	1.2	9	<	1.6	36.0	<	3	0.2	<	120	63	100	8.00	1	0.8	2	0.4	<	<	<	<	10.0	7.1
74H	841370 20	0.05	2.5	27	1.0	<	<	1.5	29.0	<	2	<	<	120	50	90	6.50	<	0.8	<	0.4	<	<	<	<	8.0	5.7
74H	841371 00	0.11	2.5	38	1.9	6	<	1.4	41.0	8	3	0.1	0.8	70	29	52	3.80	<	<	<	0.3	<	<	<	<	6.2	3.2
74H	841372 00	1.70	4.6	45	2.0	7	<	2.5	24.0	61	2	0.2	1.5	470	34	59	4.60	<	0.7	2	0.5	9	<	2	<	11.0	7.6
74H	841373 00	0.21	2.7	25	1.6	5	<	3.4	38.0	<	2	0.2	0.6	110	25	40	3.20	<	0.5	<	0.4	<	<	<	<	6.2	8.3
74H	841374 00	1.40	4.7	32	1.2	8	<	2.0	27.0	58	3	0.3	1.3	410	34	53	6.20	<	0.8	3	0.6	6	0.6	<	<	9.2	6.0
74H	841375 00	0.27	5.5	<	2.4	9	<	3.9	59.0	18	2	0.2	1.7	170	40	86	5.20	<	0.9	4	0.8	2	<	<	<	16.0	30.1
74H	841376 00	0.44	4.3	23	2.0	6	<	2.7	31.0	28	2	0.2	1.1	220	25	46	4.20	1	0.6	<	0.5	4	<	<	<	11.0	8.6
74H	841377 00	0.11	2.1	22	1.0	9	<	3.4	40.0	6	2	0.2	1.0	110	9	20	1.20	<	<	<	<	<	<	<	3	3.8	0.7
74H	841378 00	0.77	3.7	22	9.1	11	<	6.2	39.0	21	3	0.2	0.7	230	22	43	3.30	<	0.5	<	0.3	8	<	1	<	7.6	1.6
74H	841379 00	0.47	3.9	<	16.0	8	<	6.5	34.0	20	4	0.2	1.2	140	23	43	3.30	<	<	<	0.3	5	<	<	<	7.1	1.7
74H	841380 00	0.20	1.5	<	0.2	<	<	1.7	21.0	9	2	0.1	0.6	130	7	13	0.94	<	<	<	<	1	<	<	<	2.7	0.6
74H	841382 00	0.10	1.0	<	0.9	<	<	3.1	39.0	<	4	0.3	<	73	7	8	1.10	<	<	<	<	2	<	<	2	2.8	0.7
74H	841383 10	0.23	3.2	<	29.0	29	<	17.0	23.0	22	2	0.2	0.5	280	24	41	4.80	<	0.7	<	0.4	3	<	2	<	9.5	2.4
74H	841384 20	0.42	3.3	<	25.5	24	23	13.0	18.0	20	3	0.1	<	210	24	40	4.60	<	0.6	<	0.4	6	<	3	<	9.0	2.5
74H	841385 00	0.34	3.4	<	2.0	<	<	4.8	27.0	13	3	0.2	0.8	140	29	64	6.20	<	0.8	3	0.4	4	<	<	<	9.4	3.3
74H	841386 00	0.19	2.0	<	7.5	14	<	6.7	27.0	11	2	0.1	0.6	140	14	33	2.80	<	<	<	<	3	<	2	<	7.7	1.4
74H	841387 00	0.31	1.5	<	2.9	<	<	2.0	16.0	13	2	0.2	<	94	7	16	1.60	<	<	<	<	3	<	<	<	3.4	1.2
74H	841388 00	1.10	3.8	24	5.5	<	<	5.9	15.0	43	1	0.3	0.7	360	24	45	3.60	<	0.6	3	0.4	14	1.1	<	<	14.0	2.3
74H	841389 00	0.26	4.8	27	5.5	11	<	4.0	46.0	8	2	0.3	0.6	150	34	73	5.20	<	0.8	2	0.6	3	0.5	<	<	17.0	12.0
74H	841390 00	0.11	2.9	21	0.8	<	<	2.8	24.0	9	<	0.3	<	41	67	4.60	2	0.9	3	0.9	1	<	2	<	7.6	48.0	
74H	841391 00	0.63	4.9	25	2.8	6	<	2.7	33.0	29	3	0.2	1.0	210	46	83	6.90	<	1.0	3	0.7	4	<	1	<	13.0	11.0
74H	841393 00	0.10	4.3	<	1.1	<	<	2.5	32.0	14	1	0.3	1.2	120	54	85	6.30	1	1.3	3	1.1	<	<	<	<	10.0	48.6
74H	841394 00	0.40	3.5	34	3.3	7	<	3.5	35.0	20	3	0.2	0.8	180	18	36	2.60	<	<	<	0.2	3	<	2	<	6.4	3.4
74H	841395 00	0.30	3.3	28	2.1	6	<	1.9	30.0	14	2	0.2	0.6	130	27	51	4.20	<	0.7	<	0.4	1	<	<	7.8	2.7	
74H	841396 00	0.43	2.7	30	1.5	7	23	2.9	36.0	19	2	0.2	0.6	160	27	55	3.80	<	<	<	0.3	2	<	<	<	8.3	3.5
74H	841397 00	0.92	4.2	23	1.0	10	<	2.0	25.0	38	2	0.2	0.7	300	49	79	6.70	1	0.9	3	0.4	4	<	<	<	11.0	6.4
74H	841398 00	0.16	3.0	37	1.2	6	<	3.6	38.0	<	4	0.2	<	170	31	54	4.30	<	0.5	<	0.3	<	<	<	5	6.8	2.7
74H	841399 00	1.20	3.8	33	1.4	<	<	2.7	23.0	53	4	0.2	0.8	370	41	67	6.40	<	0.9	2	0.5	6	<	<	3	11.0	4.9
74H	841400 00	0.22	3.3	22	1.4	6	<	2.3	55.0	17	4	0.3	0.7	130	95	160	13.00	<	1.6	3	0.7	2	<	<	<	14.0	9.2

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Field Data												Sample Media: Sediments														Waters																		
Map	ID	ZN	UTM		Rock		Lake		RS	Rlf	Cont	Colr	Susp	Detection Limit:												Zn	Cu	Pb	Ni	Co	Ag	Mn	As	Mo	Fe	Hg	LOI	U	V	Cd	Sb	F-W	pH	U-W
			Easting	Northing	Type	Age	Area	Dep						ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	pct	ppb	10	1.0	0.5	5	ppm	ppm	ppm	ppm	ppb	20	0.05										
74H	841402	13	550906	6373271	WPSN	04	.25-1	9	00	Md	-	Gn	-	120	9	<	9	6	<	540	<	4	3.10	85	29.0	7.1	15	.2	<	170	6.1	<												
74H	841403	13	547604	6373985	WRN	04	.25-1	1	00	Lw	-	Br	-	110	3	<	10	6	<	375	<	2	1.95	58	30.6	2.1	10	.2	<	100	6.4	<												
74H	841405	13	544854	6372364	WRN	04	1-5	1	00	Md	-	Br	-	44	7	<	13	5	<	135	<	<	.83	45	34.8	5.6	10	.2	<	110	6.2	0.06												
74H	841406	13	541927	6373346	WRN	04	.25-1	6	00	Md	-	Br	-	75	10	<	12	7	<	160	<	2	1.60	42	29.8	2.7	15	.2	<	44	5.7	<												
74H	841407	13	537736	6373238	WRN	04	.25-1	1	00	Md	-	Br	-	78	7	<	10	6	.2	300	1.0	<	2.20	49	49.4	5.0	20	.2	<	78	6.2	<												
74H	841408	13	534765	6373889	WRN	04	pond	2	10	Lw	-	Br	Lgt	49	9	<	7	3	<	210	1.0	<	1.14	64	29.6	17.5	20	.2	<	94	6.6	0.08												
74H	841409	13	534765	6373889	WRN	04	pond	2	20	Lw	-	Br	Lgt	57	8	<	7	4	<	200	1.0	<	1.15	67	30.6	16.0	15	.2	<	94	6.5	0.08												
74H	841410	13	529992	6372366	WCN	04	.25-1	1	00	Md	-	Br	-	50	10	<	17	4	.6	115	<	2	.47	67	60.8	11.0	15	.2	<	50	5.9	0.1												
74H	841411	13	525438	6372824	WCN	04	.25-1	1	00	Md	-	Br	-	72	11	<	12	5	.2	245	<	<	2.30	67	41.6	23.4	45	.2	<	64	6.2	0.14												
74H	841412	13	523411	6372248	WRN	04	.25-1	3	00	Lw	-	Br	-	75	12	<	14	7	<	170	2.0	2	2.80	61	38.4	9.1	20	.2	<	48	6.0	0.09												
74H	841413	13	519566	6377438	MFB	04	.25-1	2	00	Lw	-	Bk	-	91	7	<	7	6	<	680	3.0	<	14.1	61	36.4	2.8	30	<	<	42	6.2	<												
74H	841414	13	521184	6379350	MFB	04	.25-1	5	00	Lw	-	Bk	-	120	7	<	7	8	<	830	3.0	<	15.3	73	32.6	3.5	35	<	<	40	6.1	<												
74H	841415	13	516297	6384443	WRN	04	pond	9	00	Hi	-	Gn	-	71	7	<	3	2	<	200	<	<	.51	42	46.0	<	15	.2	<	26	5.6	<												
74H	841416	13	517528	6385998	WRN	04	>5	10	00	Md	-	Gn	-	68	5	<	6	6	<	605	3.0	<	6.40	42	27.6	1.5	25	<	<	30	6.0	<												
74H	841417	13	520388	6390084	WRN	04	1-5	6	00	Md	-	Br	-	60	5	<	5	5	<	355	2.0	2	2.80	55	29.0	1.3	30	<	<	38	6.0	<												
74H	841418	13	522828	6390909	WPSN	04	1-5	21	00	Md	-	Bk	-	120	14	<	10	7	<	1590	4.0	20	12.0	73	37.4	3.8	45	.4	<	38	6.1	<												
74H	841419	13	526978	6392386	WRN	04	1-5	6	00	Md	-	Gn	-	18	3	<	<	2	.4	130	1.0	<	1.22	15	3.2	1.2	10	<	<	34	6.0	<												
74H	841420	13	530159	6391525	WRN	04	1-5	7	00	Md	-	Gn	-	67	5	<	5	3	<	205	1.0	2	1.12	37	49.2	1.3	15	.2	<	34	6.1	<												
74H	841422	13	531319	6386943	WRN	04	1-5	5	00	Md	-	Gn	-	100	10	<	9	4	.4	485	5.0	6	5.70	55	44.4	2.4	25	.4	.2	36	5.9	<												
74H	841423	13	525353	6387666	WRN	04	pond	1	00	Lw	-	Br	Lgt	170	6	<	12	5	.2	120	3.0	<	2.20	110	55.8	1.3	10	.8	<	26	5.0	<												
74H	841424	13	523455	6385880	WRN	04	>5	6	00	Md	-	Gn	-	57	6	<	6	6	<	475	4.0	2	3.60	40	20.4	1.2	25	.2	.2	28	5.9	<												
74H	841425	13	520286	6386697	WPSN	04	>5	15	00	Md	-	Gn	-	130	11	<	9	11	<	2300	6.0	4	15.0	55	33.2	2.9	75	.2	.2	28	5.9	<												
74H	841426	13	520331	6383411	WRN	04	.25-1	8	00	Md	-	Gn	-	17	2	<	<	2	.2	55	<	<	.54	18	5.8	<	<	<	<	22	5.7	<												
74H	841427	13	523695	6383315	WRN	04	1-5	6	00	Lw	-	Gn	-	72	7	<	8	8	<	1420	7.0	2	9.50	30	21.4	2.3	30	.2	.2	28	6.0	<												
74H	841428	13	523447	6379730	MFB	04	.25-1	4	10	Lw	-	Gn	-	110	11	<	8	6	<	660	4.0	2	15.9	73	38.0	3.7	50	<	<	40	6.2	<												
74H	841429	13	523447	6379730	MFB	04	.25-1	4	20	Lw	-	Gn	-	95	9	<	8	8	<	600	3.0	2	16.2	73	38.0	4.0	50	<	<	38	6.4	<												
74H	841430	13	523636	6377469	MFB	04	pond	1	00	Lw	-	Br	-	90	8	<	6	3	.2	50	1.0	<	1.26	48	47.6	1.2	10	.6	<	<	4.8	<												
74H	841432	13	525905	6377880	MFB	04	pond	4	00	Lw	-	Gn	-	95	11	<	7	3	<	80	<	<	2.23	61	65.0	1.4	25	.4	<	<	4.9	<												
74H	841433	13	527358	6379869	MFB	04	1-5	4	00	Lw	-	Gn	-	88	10	<	9	5	<	325	3.0	<	10.8	73	33.0	4.3	55	<	<	38	6.2	<												
74H	841434	13	528135	6382647	MFB	04	.25-1	2	00	Lw	-	Br	-	47	7	<	5	9	<	200	4.0	<	5.90	30	18.0	2.4	50	<	<	30	6.0	<												
74H	841435	13	531344	6384001	MFB	04	.25-1	1	00	Lw	-	Br	-	115	9	<	7	3	<	70	1.0	<	.84	49	66.4	1.3	15	.6	<	22	5.3	<												
74H	841436	13	534211	6384611	WRN	04	pond	1	00	Lw	-	Br	-	78	7	<	10	7	.2	115	<	<	1.07	64	40.6	35.6	25	.2	<	40	6.6	0.2												
74H	841437	13	534111	6380141	WRN	04	.25-1	2	00	Md	-	Gn	-	85	8	<	9	4	<	350	<	<	1.69	48	52.6	35.1	25	.2	<	72	6.7	0.23												
74H	841438	13	530521	6378410	WRN	04	pond	3	00	Md	-	Br	-	73	5	<	9	5	<	235	1.0	2	1.23	61	32.6	65.2	25	.2	<	72	6.6	0.34												
74H	841439	13	531534	6377456	WRN	04	.25-1	2	00	Md	-	Br	-	47	6	<	5	5	<	165	<	2	1.07	61	42.8	128.	40	.2	<	80	6.9	1.1												
74H	841440	13	533469	6376765	WRN	04	.25-1	1	00	Md	-	Br	-	48	6	<	7	4	<	175	1.0	2	2.04	26	16.2	33.1	30	<	<	84	6.6	0.34												
74H	841442	13	538009	6																																								

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Element: Units: Detection Limit:	Lake Sediment - INAA Data																											
	Na pct	Sc ppm	Cr ppm	Fe pct	Co ppm	Ni ppm	As ppm	Br ppm	Rb ppm	Mo ppm	Sb ppm	Cs ppm	Ba ppm	La ppm	Ce ppm	Sm ppm	Eu ppm	Tb ppm	Yb ppm	Lu ppm	Hf ppm	Ta ppm	W ppm	Au ppb	Th ppm	U ppm		
	0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.2	1	0.5	1	2	0.2	0.2		
	Map	ID	RS																									
74H	841402	00	0.37	3.9	<	3.4	8	21	2.1	30.0	20	4	0.2	0.7	190	57	110	9.30	<	1.1	3	0.5	1	<	<	11.0	7.0	
74H	841403	00	0.34	2.5	29	2.0	7	<	1.9	16.0	19	3	0.1	0.6	200	25	45	3.60	<	<	<	0.3	1	<	<	5.6	2.3	
74H	841405	00	0.72	3.8	28	1.2	<	<	2.3	27.0	34	1	0.2	1.1	220	44	72	6.20	<	0.9	2	0.4	3	<	<	10.0	6.0	
74H	841406	00	1.50	6.6	45	2.4	9	<	1.8	38.0	74	2	0.2	2.2	420	33	58	4.40	<	0.7	3	0.4	6	0.9	2	<	11.0	2.4
74H	841407	00	0.34	3.0	25	2.6	6	<	3.9	39.0	19	3	0.2	0.9	170	24	42	3.40	<	<	<	0.3	2	<	<	7.5	5.0	
74H	841408	10	0.51	3.7	29	1.3	<	<	2.8	27.0	26	1	0.3	0.9	210	28	45	2.80	<	<	2	0.4	3	<	<	8.4	17.0	
74H	841409	20	0.50	3.3	23	1.5	<	<	2.3	26.0	18	2	0.2	1.2	180	25	44	2.90	<	0.6	<	0.4	4	0.5	<	7.9	15.0	
74H	841410	00	0.07	7.9	36	0.7	<	<	2.5	38.0	16	<	0.3	1.3	130	33	55	8.00	2	1.3	4	0.8	<	<	<	15.0	12.0	
74H	841411	00	0.33	4.9	35	2.8	6	<	2.3	33.0	12	2	0.3	1.0	160	54	90	7.00	2	1.1	4	0.8	3	<	<	11.0	22.8	
74H	841412	00	0.10	3.2	20	3.7	7	<	5.2	29.0	7	3	0.2	0.7	72	25	51	4.30	<	0.8	2	0.4	1	<	<	11.0	10.0	
74H	841413	00	0.46	4.8	33	17.0	9	<	6.4	31.0	30	2	0.2	1.3	190	26	48	4.20	<	0.6	2	0.4	6	0.6	2	<	13.0	3.7
74H	841414	00	0.46	5.1	22	19.0	11	<	6.4	32.0	28	3	0.2	1.8	210	26	46	4.40	<	0.7	2	0.4	5	0.6	<	<	13.0	3.7
74H	841415	00	0.18	1.3	30	0.8	<	<	4.7	57.0	<	6	0.5	1.0	170	9	15	1.10	<	<	<	<	<	<	<	3.6	0.7	
74H	841416	00	0.65	3.2	<	7.1	6	<	5.3	30.0	27	2	0.2	1.0	240	20	38	3.10	<	<	<	0.3	8	<	<	8.6	1.8	
74H	841417	00	0.19	1.7	<	3.0	<	<	3.5	23.0	7	2	0.2	0.5	130	12	22	2.40	<	<	<	2	<	3	<	4.0	1.2	
74H	841418	00	0.46	3.8	21	14.0	11	<	10.0	46.0	23	21	0.3	0.6	250	23	41	3.80	<	<	2	0.3	5	<	5	<	9.2	3.4
74H	841419	00	0.70	1.9	<	1.6	<	<	4.0	4.3	33	2	0.2	0.6	250	13	25	2.30	<	<	<	0.2	11	0.7	<	<	9.2	1.6
74H	841420	00	0.30	1.9	<	1.3	<	<	4.3	25.0	15	3	0.2	0.7	110	12	18	1.70	<	<	<	<	3	<	<	5.1	1.2	
74H	841422	00	0.72	4.9	28	6.8	6	<	12.0	41.0	32	5	0.3	1.3	200	28	48	3.80	<	0.6	<	0.4	6	0.8	2	<	15.0	2.2
74H	841423	00	0.13	1.1	<	2.5	<	<	5.5	26.0	5	1	0.2	0.6	90	8	16	1.80	<	<	<	<	2	<	<	5	4.6	1.4
74H	841424	00	0.90	3.8	22	5.1	9	<	7.8	29.0	35	3	0.2	0.9	310	25	49	3.70	<	<	<	0.3	10	<	<	<	10.0	2.0
74H	841425	00	0.36	4.2	<	18.0	14	<	10.0	34.0	16	5	0.3	<	250	26	49	4.30	<	0.5	2	0.3	5	<	<	8.2	2.3	
74H	841426	00	0.57	0.9	<	0.7	<	<	1.7	6.3	21	<	<	0.5	170	9	18	1.10	<	<	<	<	3	<	<	4.2	0.7	
74H	841427	00	0.87	3.8	20	13.0	12	<	12.0	24.0	33	5	0.3	1.1	310	27	46	4.00	1	<	<	0.4	8	<	<	<	10.0	2.2
74H	841428	10	0.39	4.9	<	19.0	11	<	7.0	34.0	24	2	0.2	1.1	190	27	46	4.10	<	0.5	2	0.4	4	<	<	12.0	3.8	
74H	841429	20	0.42	5.7	25	21.5	12	<	8.3	39.0	23	2	0.2	1.7	160	27	46	4.70	<	0.6	3	0.5	5	<	5	<	14.0	4.0
74H	841430	00	0.56	2.4	<	1.4	<	<	3.2	22.0	20	2	0.2	0.9	220	11	20	1.50	<	<	<	9	<	<	7.1	0.9		
74H	841432	00	0.25	2.5	<	2.7	<	<	2.9	57.0	8	2	0.2	0.9	140	12	29	1.80	<	<	<	1	<	<	4.6	1.9		
74H	841433	00	0.65	4.3	32	13.0	7	<	6.4	32.0	26	3	0.2	1.3	200	23	41	3.80	<	0.6	2	0.4	7	<	<	11.0	4.6	
74H	841434	00	1.10	5.0	25	9.2	14	<	9.3	20.0	41	2	0.3	1.0	310	33	65	5.80	1	1.0	3	0.6	9	<	<	12.0	3.3	
74H	841435	00	0.29	2.5	27	1.0	<	<	3.7	26.0	8	1	0.2	0.6	130	11	21	1.70	<	<	<	0.2	5	<	<	6.0	1.1	
74H	841436	00	0.04	3.3	28	1.0	7	<	1.7	15.0	<	3	0.1	<	97	36	62	5.40	<	1.0	4	0.8	<	<	<	8.2	32.6	
74H	841437	00	0.26	3.2	27	2.3	5	<	2.9	56.0	11	1	0.3	0.7	180	39	59	4.30	1	1.0	4	1.0	2	<	<	7.9	39.1	
74H	841438	00	0.36	2.9	32	1.4	6	<	4.7	31.0	15	<	0.6	0.9	190	23	48	<3.20	<	0.5	<	0.9	4	0.6	<	9.4	75.5	
74H	841439	00	0.16	3.9	23	1.3	7	<	4.0	47.0	10	<	0.8	0.8	87	44	92	<5.90	<	1.1	4	2.0	2	<	3	4	10.0	142.0
74H	841440	00	1.30	5.2	33	2.9	6	<	2.8	21.0	49	2	0.2	1.2	440	40	79	4.20	<	0.9	4	0.9	10	0.8	4	<	13.0	36.2
74H	841442	00	0.39	2.9	27	1.3	<	<	2.7	34.0	13	2	0.1	0.7	190	20	42	1.20	<	<	0.5	3	<	1	<	6.3	27.8	
74H	841443	00	2.07	6.7	44	5.8	11	<	2.3	7.9	100	1	0.2	2.3	650	38	68	5.50	<	0.8	3	0.5	10	1.1	<	<	14.0	6.2
74H	841444	00	1.10	5.8	37	4.9	7	<	2.8	21.0	56	2	0.2	1.5	390	36	67	5.00	<	0.6	2	0.4	5	0.7	<	<	12.0	6.9
74H	841445	10	0.43	3.3	<	1.4	6	<	2.2	24.0	18	2	0.2	0.8	160	35	62	3.70	<	<	0.3	3	<	<	7.1	4.7		

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Map	Field Data											Sample Media: Sediments														Waters											
	ID	ZN	UTM		Rock		Lake		Rlf	Cont	Colr	Susp	Variable: Zn Cu Pb Ni Co Ag Mn As Mo Fe Hg LOI U V Cd Sb														F-W	pH	U-W								
			Easting	Northing	Type	Age	Area	Dep						ppm	ppm	pct	ppb	10	1.0	0.5	5	ppm	ppm	0.2	0.2	20	0.05										
															2	2	2	2	2	0.2	5	1	2	0.02	10	1.0	0.5	5	ppm	ppm	0.2	0.2	20	0.05			
74H	841446	13	547461	6376023	WRN	04	1-5	1	20	Lw	-	Br	-	88	8	<	9	6	<	120	<	<	1.04	22	63.4	5.0	10	.4	<	60	6.3	<					
74H	841447	13	550607	6376868	WRN	04	.25-1	2	00	Md	-	Br	-	41	6	<	11	6	<	230	<	<	1.60	44	24.4	5.8	20	<	<	140	6.4	0.05					
74H	841448	13	558442	6370163	WFN	04	.25-1	3	00	Md	-	Br	-	60	8	<	7	6	<	270	<	2	2.20	61	30.8	3.0	20	<	<	160	6.5	<					
74H	841449	13	552254	6380041	WRN	04	1-5	3	00	Md	-	Br	-	66	10	<	13	7	<	405	<	2	2.50	48	32.2	6.6	25	<	<	130	6.1	0.05					
74H	841451	13	547723	6378646	WRN	04	.25-1	1	00	Lw	-	Br	-	58	7	<	12	7	<	245	<	<	1.14	52	39.2	4.4	20	.2	<	78	6.2	<					
74H	841452	13	544708	6379024	WRN	04	1-5	6	00	Md	-	Gn	-	75	7	<	12	9	<	945	1.0	<	6.70	44	24.2	6.6	30	<	<	64	6.5	<					
74H	841453	13	542563	6379893	WRN	04	1-5	16	00	Md	-	Gn	-	84	10	<	7	7	.2	1050	2.0	2	10.2	83	26.4	18.8	55	<	<	76	6.6	0.11					
74H	841454	13	537889	6379752	WRN	04	.25-1	2	00	Md	-	Br	-	90	11	<	7	6	.4	415	<	<	3.10	39	51.0	6.7	15	.2	<	44	6.0	<					
74H	841455	13	539370	6383555	WRN	04	.25-1	3	00	Md	-	Br	-	70	6	<	4	6	.6	155	2.0	10	6.90	44	52.0	77.9	75	<	.2	72	6.9	0.22					
74H	841456	13	536974	6386047	WRN	04	.25-1	10	00	Md	-	Br	-	88	12	<	9	3	<	285	<	4	1.68	87	52.6	63.4	25	.4	<	32	6.5	0.5					
74H	841457	13	533453	6388474	MFB	04	.25-1	2	00	Lw	-	Br	-	87	5	<	3	5	<	180	2.0	<	1.70	30	36.4	1.1	20	.2	<	24	5.8	<					
74H	841458	13	534230	6391296	MFB	04	.25-1	3	00	Lw	-	Br	-	160	8	<	5	9	<	475	13.0	4	21.8	65	53.2	1.5	45	<	.2	32	5.9	<					
74H	841459	13	538439	6391366	WRN	04	.25-1	1	00	Lw	-	Br	-	120	4	<	7	12	<	1700	10.0	2	16.5	52	44.6	1.9	45	.2	.2	30	6.1	<					
74H	841460	13	540925	6391593	WRN	04	.25-1	3	00	Md	-	Br	-	104	12	<	13	6	<	185	<	4	1.57	48	68.4	61.1	15	.2	<	38	6.0	0.23					
74H	841462	13	544041	6391668	WRN	04	.25-1	3	10	Md	-	Br	-	36	10	<	11	5	<	120	<	<	1.12	52	22.2	27.1	15	<	<	70	6.6	0.36					
74H	841463	13	544041	6391668	WRN	04	.25-1	3	20	Md	-	Br	-	37	10	<	10	4	<	100	<	<	.90	57	22.6	23.8	20	.2	<	72	6.6	0.35					
74H	841464	13	543042	6388960	WRN	04	.25-1	6	00	Md	-	Br	-	31	7	<	5	4	<	150	<	2	.75	24	32.6	30.3	15	.2	<	52	6.5	0.05					
74H	841465	13	544495	6387141	WRN	04	1-5	8	00	Md	-	Br	-	30	5	<	7	3	.2	195	1.0	<	2.25	22	11.6	12.0	10	<	<	58	6.5	<					
74H	841466	13	542181	6383719	WRN	04	1-5	22	00	Md	-	Gn	-	64	5	<	7	4	<	445	2.0	<	4.10	56	25.6	5.5	20	<	<	28	6.3	<					
74H	841467	13	544570	6384404	WRN	04	.25-1	3	00	Lw	-	Gn	-	85	7	<	7	9	<	470	3.0	2	17.2	70	36.4	4.1	60	<	<	62	6.4	<					
74H	841468	13	547528	6384255	WRN	04	pond	1	00	Lw	-	Br	Lgt	87	6	<	10	9	.4	295	1.0	<	2.10	65	55.6	1.9	25	.2	<	58	6.4	<					
74H	841469	13	550673	6385375	WRN	04	.25-1	6	00	Hi	-	Gn	-	28	11	<	4	5	.2	1350	36.0	4	27.0	35	36.0	10.0	60	<	.6	180	7.1	<					
74H	841470	13	549502	6386022	WRN	04	.25-1	4	00	Md	-	Br	-	59	9	<	11	8	.2	260	<	2	2.40	44	22.8	4.5	30	<	<	56	6.4	<					
74H	841471	13	551353	6389011	WRN	04	.25-1	4	00	Md	-	Br	-	103	11	<	12	8	<	945	1.0	2	3.40	65	46.2	7.6	30	.2	<	66	6.4	<					
74H	841472	13	548768	6390765	WRN	04	>5	16	00	Lw	-	Gn	-	62	8	<	10	6	<	295	1.0	<	1.39	44	16.0	10.1	20	<	<	62	6.5	<					
74H	841473	13	552753	6392063	WRN	04	1-5	2	00	Md	-	Br	-	83	8	<	9	8	<	410	1.0	6	6.40	44	33.8	8.6	45	<	<	62	6.0	<					

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

		Lake Sediment - INAA Data																										
Element:		Na	Sc	Cr	Fe	Co	Ni	As	Br	Rb	Mo	Sb	Cs	Ba	La	Ce	Sm	Eu	Tb	Yb	Lu	Hf	Ta	W	Au	Th	U	
Units:		pct	ppm	ppm	pct	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	
Detection Limit:		0.02	0.2	20	0.2	5	20	0.5	0.5	5	1	0.1	0.5	50	2	5	0.05	1	0.5	2	0.5	1	0.2	1	0.5	2	0.2	0.2
Map	ID	RS																										
74H	841446	20	0.48	3.3	27	1.4	7	<	1.8	24.0	18	2	0.2	1.0	160	37	68	4.10	<	<	0.4	2	<	<	<	7.6	4.9	
74H	841447	00	0.41	3.3	21	1.6	6	<	1.5	22.0	20	2	0.1	0.8	120	36	62	5.60	<	0.7	<	0.4	2	<	<	<	8.2	5.6
74H	841448	00	0.21	3.0	<	2.5	7	<	2.6	36.0	14	4	0.2	0.7	100	43	84	6.20	<	0.7	3	0.4	1	<	3	<	8.0	3.3
74H	841449	00	0.27	3.6	39	2.7	9	<	2.5	33.0	20	3	<	0.8	180	42	66	5.90	<	0.8	2	0.4	2	<	<	<	9.1	6.0
74H	841451	00	0.44	2.5	20	1.2	8	<	2.0	27.0	23	2	0.1	0.6	140	24	45	3.60	<	0.6	<	0.3	2	<	<	<	6.5	3.8
74H	841452	00	0.93	6.3	40	7.4	10	<	2.6	22.0	46	2	0.2	2.0	390	39	72	5.50	1	0.8	<	0.5	4	0.6	<	<	12.0	6.0
74H	841453	00	0.74	5.5	45	10.0	11	<	4.7	32.0	43	3	0.2	1.4	320	39	69	5.10	<	0.8	3	0.7	5	0.5	2	<	13.0	17.0
74H	841454	00	0.23	2.2	<	3.3	7	<	2.2	42.0	7	3	<	0.6	150	15	23	1.90	<	<	0.2	2	<	<	<	4.1	7.0	
74H	841455	00	0.28	3.4	48	7.5	<	<	6.4	40.0	19	8	0.6	<	74	36	68	1.00	<	0.9	3	1.3	3	<	9	<	6.5	77.4
74H	841456	00	0.09	3.1	29	1.5	<	<	2.6	61.0	<	3	0.2	0.6	100	34	61	4.20	1	1.1	3	1.1	1	<	<	<	5.7	62.6
74H	841457	00	0.56	2.1	<	2.0	5	<	6.6	36.0	20	<	0.2	0.6	250	13	27	2.80	<	<	<	0.2	6	<	<	<	7.3	1.5
74H	841458	00	0.11	3.3	<	25.6	10	<	21.0	50.0	11	7	0.2	<	100	14	22	2.50	<	<	<	0.3	2	<	<	2	7.4	1.3
74H	841459	00	0.39	5.2	36	23.3	19	23	17.0	23.0	26	3	0.2	1.5	200	27	57	4.40	<	<	2	0.4	4	0.5	<2	4	12.0	2.5
74H	841460	00	0.12	4.0	<	1.5	7	22	3.4	33.0	14	3	0.2	0.6	170	31	72	0.67	<	0.7	4	1.0	1	<	<	<	8.7	57.8
74H	841462	10	0.47	4.3	31	1.4	<	<	2.3	22.0	28	2	0.2	1.6	160	55	82	9.40	1	1.6	5	0.9	5	0.8	<	<	15.0	27.8
74H	841463	20	0.41	3.8	33	1.1	5	<	2.1	21.0	26	2	0.2	0.9	170	50	71	8.20	<	1.4	4	0.9	4	<	<	<	13.0	25.0
74H	841464	00	0.27	3.3	22	1.0	<	<	3.3	41.0	15	2	0.3	0.6	130	38	48	5.30	<	0.9	3	0.8	3	<	<	<	9.3	33.0
74H	841465	00	1.30	4.9	35	3.4	5	<	2.8	17.0	61	1	0.2	1.2	400	35	63	4.20	<	0.8	3	0.5	14	1.2	<	<	15.0	14.0
74H	841466	00	0.65	3.9	24	5.3	6	<	4.8	30.0	23	1	0.3	1.3	290	21	39	3.20	<	<	0.3	6	<	<	<	8.4	5.7	
74H	841467	00	0.43	4.7	45	20.4	10	<	6.2	31.0	24	3	0.2	0.9	220	24	50	4.30	<	0.6	2	0.5	4	<	4	<	9.2	4.1
74H	841468	00	0.20	2.5	32	2.3	13	<	5.2	38.0	10	2	0.1	0.8	160	16	28	2.60	<	<	<	0.2	1	<	<	<	5.3	2.3
74H	841469	00	0.04	2.9	<	37.7	<	<	50.6	63.0	<	4	0.1	<	79	54	71	6.00	<	0.8	2	0.4	<	<	4	<	7.6	11.0
74H	841470	00	0.90	5.5	38	2.6	9	<	2.4	22.0	55	2	0.1	1.4	290	35	62	5.20	<	0.7	<	0.4	5	0.5	<	<	12.0	4.3
74H	841471	00	0.34	4.7	36	3.4	10	<	4.2	46.0	15	4	0.4	0.6	170	31	61	4.60	<	0.7	<	0.4	3	<	<	<	10.0	7.2
74H	841472	00	1.20	5.4	45	1.9	5	<	3.1	22.0	62	2	0.2	1.7	420	34	62	4.40	<	0.7	2	0.4	8	1.0	<	<	14.0	10.0
74H	841473	00	1.00	6.5	42	7.4	9	21	4.2	37.0	59	5	0.1	1.7	400	40	73	5.60	1	0.8	3	0.5	5	0.6	3	<	13.0	9.4

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Summary Statistics for Total Data Set

Variable Units Detection Limit Analytical Method	Zn ppm 2 AAS	Cu ppm 2 AAS	Pb ppm 2 AAS	Ni ppm 2 AAS	Co ppm 2 AAS	Ag ppm 0.2 AAS	Mn ppm 5 AAS	As ppm 1 AAS	Mo ppm 2 AAS	Fe pct 0.02 AAS	Hg ppb 10 AAS	LOI pct 1.0 GRA	U ppm 0.5 NADNC	V ppm 5 AAS	Cd ppm 0.2 AAS	Sb ppm 0.2 AAS	F-W ppb 20 ISE	pH GCM	U-W ppb 0.05 LIF
Number of Values	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	
Values >= D.L.	1177	1161	89	1159	1127	296	1178	178	304	1178	1170	1178	1170	1134	907	26	1164	1178	
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Mean	96.56	14.24	1.39	10.98	7.46	0.1430	720.36	1.22	2.87	3.77	61.65	35.74	7.04	27.41	0.2974	0.1047	105.58	6.18	
Standard Deviation	44.77	9.39	2.16	6.29	4.67	0.0982	2536.45	2.34	3.33	4.41	44.25	14.83	9.29	16.82	0.1872	0.0490	70.79	0.3536	
Skewness	1.23	2.83	21.57	7.24	2.88	3.36	17.66	7.12	3.94	2.91	14.87	-0.1071	6.03	2.21	1.35	19.00	2.37	-0.9500	
Excess Kurtosis	2.28	15.79	563.40	106.00	17.68	14.58	389.69	70.90	21.50	9.95	361.14	-0.1778	56.10	8.51	3.05	445.04	10.45	2.84	
Coef. of Var. %	46.37	65.94	154.99	57.29	62.61	68.68	352.11	192.07	115.91	117.15	71.78	41.49	132.00	61.37	62.96	46.80	67.05	5.72	
Std Error of the Mean	1.30	0.2736	0.0628	0.1833	0.1361	0.0029	73.90	0.0681	0.0970	0.1286	1.29	0.4321	0.2706	0.4901	0.0055	0.0014	2.06	0.0103	
Lower 95% limit on Mean	94.00	13.70	1.27	10.63	7.19	0.1373	575.37	1.08	2.68	3.52	59.12	34.90	6.50	26.45	0.2867	0.1019	101.53	6.16	
Upper 95% limit on Mean	99.12	14.78	1.51	11.34	7.73	0.1486	865.35	1.35	3.06	4.02	64.17	36.59	7.57	28.37	0.3081	0.1075	109.62	6.20	
Geometric Statistics																			
Mean	86.80	11.94	1.19	9.78	6.42	0.1259	371.89	0.7570	2.05	2.45	54.52	31.43	4.79	23.23	0.2455	0.1022	87.16	6.17	
Log10 Mean	1.94	1.08	0.0759	0.9904	0.8075	-0.9000	2.57	-0.1209	0.3110	0.3886	1.74	1.50	0.6800	1.37	-0.6100	-0.9907	1.94	0.7904	
Log10 S.D.	0.2094	0.2621	0.1812	0.2177	0.2351	0.1907	0.3985	0.3247	0.3194	0.3853	0.2152	0.2540	0.3584	0.2580	0.2734	0.0696	0.2760	0.0258	
Log10 Std. Error of Mean	0.0061	0.0076	0.0053	0.0063	0.0069	0.0056	0.0116	0.0095	0.0093	0.0112	0.0063	0.0074	0.0104	0.0075	0.0080	0.0020	0.0080	0.0008	
Lower 95% limit on Mean	84.44	11.54	1.16	9.50	6.22	0.1228	352.89	0.7253	1.96	2.33	53.00	30.40	4.57	22.45	0.2368	0.1012	84.05	6.15	
Upper 95% limit on Mean	89.23	12.36	1.22	10.06	6.62	0.1291	391.92	0.7900	2.13	2.57	56.09	32.50	5.02	24.03	0.2545	0.1031	90.39	6.19	
Percentiles																			
Min Value	2.00	1.00	1.00	1.00	1.00	0.1000	20.00	0.5000	1.00	0.1600	5.00	1.20	0.2500	2.50	0.1000	0.1000	10.00	3.70	
25th Xtile	67.00	8.00	1.00	8.00	5.00	0.1000	210.00	0.5000	1.00	1.26	41.00	27.00	2.90	15.00	0.2000	0.1000	62.00	6.00	
50th Xtile	88.00	12.00	1.00	10.00	6.00	0.1000	330.00	0.5000	2.00	2.23	58.00	36.60	4.60	25.00	0.2000	0.1000	88.00	6.20	
75th Xtile	120.00	18.00	1.00	13.00	9.00	0.1000	580.00	1.00	4.00	4.30	73.00	45.40	7.20	35.00	0.4000	0.1000	130.00	6.40	
80th Xtile	130.00	19.00	1.00	14.00	10.00	0.2000	670.00	1.00	4.00	4.80	79.00	47.80	8.30	35.00	0.4000	0.1000	140.00	6.50	
90th Xtile	150.00	24.00	2.00	17.00	13.00	0.2000	1110.00	2.00	6.00	8.40	94.00	53.80	12.50	45.00	0.6000	0.1000	190.00	6.60	
95th Xtile	180.00	30.00	3.00	19.00	15.00	0.4000	1950.00	4.00	8.00	13.60	108.00	59.20	20.20	60.00	0.6000	0.1000	240.00	6.70	
98th Xtile	230.00	38.00	4.00	23.00	22.00	0.4000	4000.00	9.00	14.00	19.00	131.00	64.60	35.10	75.00	0.8000	0.2000	310.00	6.80	
99th Xtile	240.00	45.00	5.00	26.00	25.00	0.6000	5900.00	13.00	18.00	23.10	156.00	66.40	48.80	95.00	0.8000	0.2000	360.00	6.90	
Max Value	320.00	100.00	62.00	111.00	60.00	1.0000	65000	36.00	34.00	33.00	1190.00	96.40	128.00	140.00	1.40	1.40	740.00	7.10	

Summary Statistics for Total Data Set

Variable Units Detection Limit Analytical Method	Na pct 0.02 INA	Sc ppm 0.2 INA	Cr ppm 20 INA	Fe pct 0.2 INA	Co ppm 5 INA	Ni ppm 20 INA	As ppm 0.5 INA	Br ppm 0.5 INA	Rb ppm 5 INA	Mo ppm 1 INA	Sb ppm 0.1 INA	Cs ppm 0.5 INA	Ba ppm 50 INA
Number of Values	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178
Values >= D.L.	1176	1178	850	1177	986	140	1168	1178	936	1072	1036	902	1153
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0
Mean	0.6840	4.71	28.61	4.67	10.06	12.11	3.07	31.67	32.73	4.02	0.1702	1.09	293.80
Standard Deviation	0.6383	2.15	17.28	5.42	6.17	5.53	3.44	13.81	33.18	3.33	0.1046	0.7863	219.36
Skewness	1.22	1.11	4.54	3.06	2.38	2.72	6.46	0.7276	1.33	3.11	3.58	1.47	1.49
Excess Kurtosis	0.4895	2.89	68.14	11.53	13.62	7.44	59.42	2.51	1.10	14.34	30.84	2.86	3.02
Coef. of Var. %	93.31	45.60	60.41	116.01	61.35	45.69	112.03	43.61	101.38	82.81	61.44	72.18	74.66
Std Error of the Mean	0.0186	0.0626	0.5035	0.1579	0.1799	0.1612	0.1001	0.4025	0.9669	0.0969	0.0030	0.0229	6.39
Lower 95% limit on Mean	0.6475	4.59	27.62	4.36	9.71	11.79	2.87	30.88	30.84	3.83	0.1642	1.04	281.27
Upper 95% limit on Mean	0.7205	4.83	29.59	4.98	10.42	12.42	3.26	32.46	34.63	4.21	0.1762	1.13	306.34
Geometric Statistics													
Mean	0.4316	4.24	24.23	3.10	8.45	11.35	2.42	28.20	17.64	3.15	0.1457	0.8382	225.98
Log10 Mean	-0.3649	0.6273	1.38	0.4909	0.9267	1.05	0.3837	1.45	1.25	0.4988	-0.8367	-0.0767	2.35
Log10 S.D.	0.4393	0.2060	0.2601	0.3756	0.2690	0.1386	0.2650	0.2306	0.5366	0.3013	0.2471	0.3290	0.3243
Log10 Std. Error of Mean	0.0128	0.0060	0.0076	0.0109	0.0078	0.0040	0.0077	0.0067	0.0156	0.0088	0.0072	0.0096	0.0094
Lower 95% limit on Mean	0.4073	4.13	23.42	2.95	8.15	11.14	2.34	27.35	16.43	3.03	0.1410	0.8027	216.53
Upper 95% limit on Mean	0.4573	4.36	25.08	3.25	8.75	11.56	2.51	29.06	18.93	3.28	0.1505	0.8753	235.83
Percentiles													
Min Value	0.0100	0.6000	10.00	0.1000	2.50	10.00	0.2500	3.00	2.50	0.5000	0.0500	0.2500	25.00
25th Xtile	0.2000	3.10	10.00	1.70	6.00	10.00	1.70	23.00	8.00	2.00	0.1000	0.6000	140.00
50th Xtile	0.4000	4.40	28.00	2.90	9.00	10.00	2.30	31.00	20.00	3.00	0.2000	0.9000	220.00
75th Xtile	1.00	5.90	37.00	5.10	12.00	10.00	3.10	39.00	47.00	5.00	0.2000	1.40	390.00
80th Xtile	1.20	6.30	40.00	5.90	13.00	10.00	3.50	42.00	58.00	5.00	0.2000	1.60	460.00
90th Xtile	1.80	7.60	47.00	11.00	17.00	21.00	5.00	48.00	85.00	7.00	0.3000	2.10	630.00
95th Xtile	2.00	8.60	54.00	17.00	21.00	25.00	7.40	55.00	99.00	10.00	0.3000	2.50	740.00
98th Xtile	2.40	10.00	66.00	23.30	27.00	29.00	12.00	63.00	120.00	14.00	0.4000	3.20	890.00
99th Xtile	2.50	11.00	71.00	28.50	32.00	33.00	21.00	66.00	130.00	18.00	0.5000	3.70	920.00
Max Value	2.70	18.00	320.00	46.30	74.00	52.00	50.60	120.00	180.00	30.00	1.50	5.30	1900.00

Summary Statistics for Total Data Set

Variable Units Detection Limit Analytical Method	La ppm 2 INA	Ce ppm 5 INA	Sm ppm 0.05 INA	Eu ppm 1 INA	Tb ppm 0.5 INA	Yb ppm 2 INA	Lu ppm 0.2 INA	Hf ppm 1 INA	Ta ppm 0.5 INA	W ppm 1 INA	Au ppb 2 INA	Th ppm 0.2 INA	U ppm 0.2 INA
Number of Values	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178	1178
Values >= D.L.	1178	1176	1176	261	976	704	1131	750	337	215	186	1178	1178
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0
Mean	66.64	113.16	8.28	0.9919	1.09	3.08	0.6237	3.04	0.4231	0.8960	1.56	11.36	7.19
Standard Deviation	51.31	81.14	6.85	0.8682	0.7836	2.11	0.4486	2.67	0.2790	0.8216	1.49	5.24	9.49
Skewness	3.47	2.57	4.75	3.76	3.18	2.50	3.74	1.36	1.59	3.10	3.71	1.40	5.91
Excess Kurtosis	25.43	12.03	44.35	29.28	18.83	12.65	23.79	2.09	2.32	14.98	20.77	4.41	55.49
Coef. of Var. %	76.99	71.70	82.69	87.53	71.97	68.74	71.93	87.81	65.95	91.70	95.17	46.12	132.01
Std Error of the Mean	1.49	2.36	0.1995	0.0253	0.0228	0.0616	0.0131	0.0778	0.0081	0.0239	0.0433	0.1527	0.2766
Lower 95% Limit on Mean	63.71	108.52	7.89	0.9423	1.04	2.96	0.5980	2.89	0.4071	0.8490	1.48	11.06	6.65
Upper 95% Limit on Mean	69.57	117.80	8.67	1.04	1.13	3.20	0.6493	3.19	0.4390	0.9430	1.65	11.66	7.73
Geometric Statistics													
Mean	53.05	91.13	6.63	0.7851	0.8831	2.51	0.5202	1.98	0.3588	0.7074	1.26	10.25	4.90
Log10 Mean	1.72	1.96	0.8217	-0.1051	-0.0540	0.3997	-0.2838	0.2963	-0.4452	-0.1503	0.1013	1.01	0.6901
Log10 S.D.	0.2982	0.2953	0.2952	0.2711	0.2895	0.2811	0.2623	0.4294	0.2327	0.2620	0.2360	0.2018	0.3508
Log10 Std. Error of Mean	0.0087	0.0086	0.0086	0.0079	0.0084	0.0082	0.0076	0.0125	0.0068	0.0076	0.0069	0.0059	0.0102
Lower 95% limit on Mean	51.01	87.65	6.38	0.7576	0.8500	2.42	0.5026	1.87	0.3479	0.6835	1.22	9.98	4.68
Upper 95% limit on Mean	55.17	94.74	6.90	0.8136	0.9173	2.60	0.5385	2.09	0.3699	0.7323	1.30	10.53	5.13
Percentiles													
Min Value	6.00	2.50	0.0250	0.5000	0.2500	1.00	0.1000	0.5000	0.2500	0.5000	1.00	1.60	0.4000
25th Xtile	33.00	58.00	4.30	0.5000	0.6000	1.00	0.4000	0.5000	0.2500	0.5000	1.00	7.60	2.80
50th Xtile	54.00	93.00	6.50	0.5000	0.9000	3.00	0.5000	2.00	0.2500	0.5000	1.00	11.00	4.50
75th Xtile	81.00	140.00	10.00	1.00	1.30	4.00	0.7000	4.00	0.6000	1.00	1.00	14.00	7.40
80th Xtile	90.00	150.00	11.00	2.00	1.40	4.00	0.8000	5.00	0.7000	1.00	1.00	15.00	8.80
90th Xtile	120.00	200.00	15.00	2.00	1.90	5.00	1.00	7.00	0.9000	2.00	3.00	18.00	13.00
95th Xtile	150.00	250.00	19.00	2.00	2.30	7.00	1.30	8.00	1.00	2.00	5.00	20.20	21.30
98th Xtile	218.00	350.00	27.30	3.00	3.20	8.00	1.90	10.00	1.20	3.00	6.00	24.80	38.50
99th Xtile	267.00	414.00	35.70	4.00	4.30	11.00	2.50	12.00	1.20	4.00	7.00	29.00	48.00
Max Value	698.00	784.00	105.00	12.00	8.60	21.00	5.20	16.00	2.20	9.00	18.00	47.50	142.00

Statistics per Variable

Variable - Antimony [Sb]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	26	2	0	1	3	1	0	0	0	0	0	1	2	16
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.10	0.11	-	0.16	0.10	0.10	-	-	-	-	-	0.10	0.11	0.11
------	------	------	---	------	------	------	---	---	---	---	---	------	------	------

Standard Deviation	0.05	0.025	-	0.29	0.021	0.017	-	-	-	-	-	0	0.045	0.056
--------------------	------	-------	---	------	-------	-------	---	---	---	---	---	---	-------	-------

Skewness	19.00	3.38	-	3.82	7.75	5.23	-	-	-	-	-	0	8.07	7.62
----------	-------	------	---	------	------	------	---	---	---	---	---	---	------	------

Excess Kurtosis	445.04	9.71	-	13.29	63.77	26.18	-	-	-	-	-	0	66.33	66.90
-----------------	--------	------	---	-------	-------	-------	---	---	---	---	---	---	-------	-------

Coef. of Var. %	46.80	23.46	-	176.18	20.07	16.90	-	-	-	-	-	9.62	42.79	50.59
-----------------	-------	-------	---	--------	-------	-------	---	---	---	---	---	------	-------	-------

Std. Error of the Mean	0.00	0	-	0.065	0	0	-	-	-	-	-	0	0	0
------------------------	------	---	---	-------	---	---	---	---	---	---	---	---	---	---

N	X	Cum %	Lower 95% limit on Mean	0.10	0.097	-	0.029	0.099	0.097	-	-	-	0.099	0.096	0.10
---	---	-------	-------------------------	------	-------	---	-------	-------	-------	---	---	---	-------	-------	------

			Upper 95% limit on Mean	0.11	0.12	-	0.30	0.11	0.11	-	-	-	0.10	0.12	0.12
--	--	--	-------------------------	------	------	---	------	------	------	---	---	---	------	------	------

ppm															
-----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

0.02-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

0.05-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

0.10-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

0.20-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

0.50-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

1.00-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

2.00-	.														
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--

+-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

0	10	20	30	40	50	60	70	80	90	100	%			
---	----	----	----	----	----	----	----	----	----	-----	---	--	--	--

Percentage of Values

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Antimony [Sb]

Number of Values - 1178

Units - ppm

Detection Limit - 0.1

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1036	30	57	19	112	29	45	102	12	54	21	91	79	268
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.17	0.23	0.13	0.19	0.15	0.15	0.14	0.14	0.11	0.12	0.15	0.16	0.17	0.22
Standard Deviation	0.10	0.081	0.065	0.17	0.084	0.073	0.067	0.059	0.061	0.066	0.071	0.084	0.075	0.12
Skewness	3.58	0.81	0.42	3.23	0.65	0.87	0.39	0.14	0.53	0.67	0.46	1.47	0.62	2.37
Excess Kurtosis	30.84	2.34	-0.86	10.43	-0.30	1.60	-0.85	-1.11	-1.39	-0.56	-0.84	5.57	0.35	9.79
Coef. of Var. %	61.44	35.83	48.84	90.87	55.62	48.45	48.23	41.07	54.69	53.54	46.97	53.13	42.89	54.38
Std. Error of the Mean	0.00	0.015	0	0.039	0	0.013	0	0	0.014	0	0.015	0	0	0

N	%	Cum %	Lower 95% limit on Mean	0.16	0.20	0.12	0.11	0.14	0.13	0.12	0.13	0.081	0.11	0.12
Upper 95% limit on Mean	0.18	0.26	0.15	0.27	0.16	0.18	0.16	0.16	0.14	0.14	0.18	0.18	0.19	0.23

			Geometric Statistics											
--	--	--	----------------------	--	--	--	--	--	--	--	--	--	--	--

Mean	0.15	0.21	0.12	0.16	0.13	0.13	0.12	0.13	0.096	0.11	0.14	0.14	0.16	0.19
Log10 Mean	-0.84	-0.67	-0.93	-0.80	-0.89	-0.87	-0.92	-0.88	-1.02	-0.97	-0.87	-0.86	-0.80	-0.72
Log10 S.D.	0.25	0.18	0.23	0.25	0.26	0.23	0.23	0.20	0.24	0.24	0.22	0.24	0.20	0.22

Log10 Std. Error of Mean	0.01	0.032	0.027	0.056	0.022	0.039	0.031	0.019	0.057	0.028	0.045	0.024	0.022	0.013
--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Lower 95% limit on Mean	0.14	0.18	0.10	0.12	0.12	0.11	0.11	0.12	0.073	0.093	0.11	0.12	0.14	0.18
Upper 95% limit on Mean	0.15	0.25	0.13	0.21	0.14	0.16	0.14	0.14	0.13	0.12	0.17	0.15	0.18	0.20

Percentiles														
Min Value	0.05	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
25th Xtile	0.10	0.20	0.10	0.10	0.10	0.10	0.10	0.050	0.10	0.050	0.050	0.10	0.10	0.20

50th Xtile	0.20	0.20	0.10	0.20	0.10	0.20	0.10	0.10	0.10	0.10	0.10	0.10	0.20	0.20
75th Xtile	0.20	0.30	0.20	0.20	0.20	0.20	0.20	0.10	0.20	0.20	0.20	0.20	0.20	0.20

80th Xtile	0.20	0.30	0.20	0.20	0.20	0.20	0.10	0.20	0.20	0.20	0.20	0.20	0.20	0.30
90th Xtile	0.30	0.30	0.20	0.20	0.30	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.30
95th Xtile	0.30	0.30	0.20	0.20	0.30	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.30	0.40

80th Xtile	0.20	0.30	0.20	0.20	0.20	0.20	0.10	0.20	0.20	0.20	0.20	0.20	0.20	0.30
90th Xtile	0.30	0.30	0.20	0.20	0.30	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.30
95th Xtile	0.30	0.30	0.20	0.20	0.30	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.30

98th Xtile	0.40	0.50	0.30	0.90	0.30	0.40	0.20	0.20	0.20	0.30	0.30	0.30	0.40	0.60
99th Xtile	0.50	0.50	0.30	0.90	0.40	0.40	0.20	0.30	0.20	0.30	0.30	0.40	0.40	0.70
Max Value	1.50	0.50	0.30	0.90	0.40	0.40	0.20	0.30	0.20	0.30	0.30	0.60	0.40	1.00

* Summary statistics not calculated for rock units with less than ten values.

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

Statistics per Variable

Variable - Arsenic [As]

Number of Values - 1178

Units - ppm

Detection Limit - 1

Analytical Method - AAS

					All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN																	
					Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276																
					Number of Values >= D.L.	178	17	6	6	13	4	3	8	0	4	3	10	23	66																
					Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
ppm 0.1- . 0.2- . 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- . +-----+-----+-----+-----+-----+ 0 10 20 30 40 50 60 70 80 90 100 %	800 67.9 67.9 200 17.0 84.9 70 5.9 90.8 68 5.8 96.6 22 1.9 98.5 15 1.3 99.7 3 0.3 100.0																																	
Geometric Statistics																																			
Mean																																			
Standard Deviation																																			
Skewness																																			
Excess Kurtosis																																			
Coef. of Var. %																																			
N % Cum % Std. Error of the Mean																																			
Lower 95% limit on Mean																																			
Upper 95% limit on Mean																																			
Percentiles																																			
Min Value																																			
25th Xtile																																			
50th Xtile																																			
75th Xtile																																			
80th Xtile																																			
90th Xtile																																			
95th Xtile																																			
98th Xtile																																			
99th Xtile																																			
Max Value																																			
Percentage of Values																																			

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Arsenic [As]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1168	31	70	20	138	32	53	112	18	73	23	105	81	275
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	3.07	7.46	2.25	5.03	2.49	2.41	2.06	2.25	2.03	1.98	2.35	2.36	4.13	4.06
Standard Deviation	3.44	5.97	1.16	7.49	2.52	1.31	0.63	1.20	0.53	0.72	1.32	1.21	4.50	4.87
Skewness	6.46	1.75	1.45	3.51	5.06	1.49	0.18	3.93	-0.43	1.91	1.73	2.42	2.55	5.78

Excess Kurtosis	59.42	2.04	3.04	11.67	29.86	3.22	0.42	23.48	-1.35	6.13	2.32	8.85	6.06	42.65
Coef. of Var. %	112.03	80.06	51.54	148.99	101.14	54.22	30.63	53.61	26.19	36.05	56.12	51.17	108.94	120.03
Std. Error of the Mean	0.10	1.07	0.14	1.67	0.21	0.23	0.086	0.11	0.13	0.084	0.27	0.12	0.50	0.29

Lower 95% limit on Mean	2.87	5.27	1.97	1.52	2.07	1.95	1.89	2.02	1.76	1.82	1.78	2.13	3.14	3.48
Upper 95% limit on Mean	3.26	9.65	2.52	8.53	2.92	2.87	2.24	2.47	2.29	2.15	2.92	2.59	5.12	4.64

N % Cum %

10 0.8 0.8

Geometric Statistics													
----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

Mean	2.42	5.96	2.00	3.42	2.03	2.08	1.94	2.06	1.95	1.88	2.10	2.12	2.92	3.11
Log10 Mean	0.38	0.78	0.30	0.53	0.31	0.32	0.29	0.31	0.29	0.27	0.32	0.33	0.47	0.49
Log10 S.D.	0.27	0.28	0.21	0.32	0.25	0.26	0.17	0.17	0.13	0.14	0.20	0.20	0.34	0.27

Log10 Std. Error of Mean	0.01	0.050	0.025	0.071	0.021	0.045	0.023	0.016	0.030	0.016	0.041	0.020	0.037	0.017
Lower 95% limit on Mean	2.34	4.71	1.78	2.43	1.85	1.69	1.75	1.91	1.69	1.74	1.72	1.94	2.47	2.89
Upper 95% limit on Mean	2.51	7.54	2.24	4.82	2.23	2.57	2.17	2.21	2.26	2.03	2.56	2.32	3.46	3.36

* Summary statistics not calculated for rock units with less than ten values.

Percentage of Values

0 10 20 30 40 50 60 70 80 90 100 %

Statistics per Variable

Variable - Barium [Ba]

Number of Values - 1178

Units - ppm

Detection Limit - 50

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN				
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276			
				Number of Values >= D.L.	1153	30	70	19	139	32	54	112	18	73	23	104	80	266			
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
ppm 10- .				Mean	293.80	174.29	336.84	287.75	298.28	291.36	336.07	406.34	312.28	453.60	515.22	253.86	314.87	228.37			
				Standard Deviation	219.36	84.13	223.44	186.76	218.70	229.07	219.54	232.85	260.75	271.95	259.19	205.70	261.65	163.48			
				Skewness	1.49	1.21	0.82	0.84	0.96	1.12	0.78	0.77	1.10	0.68	0.13	1.71	2.96	1.66			
				Excess Kurtosis	3.02	2.77	-0.41	-0.46	-0.37	0.045	-0.60	-0.34	-0.31	-0.60	-1.56	3.00	14.24	2.96			
				Coef. of Var. %	74.66	48.27	66.33	64.90	73.32	78.62	65.33	57.30	83.50	59.95	50.31	81.03	83.10	71.59			
				Std. Error of the Mean	6.39	15.11	26.71	41.76	18.55	39.88	29.88	22.00	61.46	31.83	54.05	19.98	28.89	9.84			
				N	%	Cum %	Lower 95% limit on Mean	281.27	143.43	283.56	200.34	261.60	210.11	276.16	362.73	182.60	390.15	403.13	214.24	257.36	208.99
							Upper 95% limit on Mean	306.34	205.15	390.13	375.16	334.96	372.62	395.99	449.94	441.96	517.06	627.31	293.48	372.37	247.74
				Geometric Statistics																	
				25	2.1	2.1	Mean	225.98	154.47	268.71	229.13	230.17	.216.78	270.81	344.77	234.36	374.96	445.72	192.62	241.57	181.22
50- .				Log10 Mean	2.35	2.19	2.43	2.36	2.36	2.34	2.43	2.54	2.37	2.57	2.65	2.28	2.38	2.26			
				Log10 S.D.	0.32	0.23	0.30	0.33	0.31	0.35	0.29	0.25	0.33	0.28	0.25	0.32	0.33	0.31			
				126	10.7	12.8	Log10 Std. Error of Mean	0.01	0.042	0.036	0.074	0.027	0.061	0.040	0.024	0.077	0.033	0.052	0.031	0.036	0.018
				406	34.5	47.3	Lower 95% limit on Mean	216.53	126.83	227.69	160.27	203.87	162.57	225.22	309.14	161.00	322.74	346.93	166.83	204.91	166.69
200- .				Upper 95% limit on Mean	235.83	188.14	317.12	327.58	259.86	289.06	325.63	384.50	341.16	435.63	572.65	222.40	284.80	197.01			
				Percentiles																	
				192	16.3	99.7	Min Value	25.00	25.00	61.00	25.00	65.00	25.00	100.00	120.00	95.00	83.00	150.00	25.00	25.00	25.00
				4	0.3	100.0	25th Xtile	140.00	110.00	150.00	150.00	120.00	130.00	130.00	210.00	120.00	230.00	280.00	120.00	140.00	130.00
500- .				50th Xtile	220.00	170.00	270.00	240.00	210.00	200.00	260.00	350.00	170.00	380.00	500.00	160.00	250.00	170.00			
				75th Xtile	390.00	210.00	500.00	330.00	440.00	340.00	560.00	550.00	420.00	680.00	770.00	350.00	400.00	290.00			
				80th Xtile	460.00	220.00	540.00	420.00	540.00	490.00	560.00	610.00	490.00	740.00	790.00	370.00	490.00	320.00			
				90th Xtile	630.00	250.00	680.00	620.00	680.00	680.00	610.00	770.00	820.00	870.00	830.00	520.00	630.00	460.00			
1000- .				95th Xtile	740.00	310.00	740.00	630.00	730.00	800.00	610.00	840.00	890.00	980.00	850.00	690.00	660.00	560.00			
				98th Xtile	890.00	470.00	890.00	690.00	800.00	870.00	610.00	920.00	890.00	1000.00	960.00	820.00	910.00	680.00			
				99th Xtile	920.00	470.00	920.00	690.00	810.00	870.00	610.00	970.00	890.00	1200.00	960.00	960.00	1900.00	840.00			
				Max Value	1900.00	470.00	920.00	690.00	910.00	870.00	610.00	1100.00	890.00	1200.00	960.00	1100.00	1900.00	900.00			
0 10 20 30 40 50 60 70 80 90 100 %																					
Percentage of Values																					

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Bromine [Br]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	31.67	31.85	31.70	42.16	29.67	31.26	31.27	32.21	33.39	30.04	26.74	31.07	25.81	31.69
Standard Deviation	13.81	12.38	15.07	18.06	13.29	12.19	14.34	14.91	10.18	13.75	11.23	11.49	12.79	13.56

Skewness	0.73	0.65	0.29	0.019	0.39	-0.37	0.072	0.14	0.14	0.084	0.072	0.57	0.062	1.93
Excess Kurtosis	2.51	1.06	-0.068	-0.51	0.44	0.94	-0.36	-0.62	-0.18	-0.68	-1.24	1.39	-1.11	9.61

Coef. of Var. %	43.61	38.86	47.53	42.84	44.79	38.99	45.87	46.29	30.48	45.77	41.98	36.97	49.57	42.79
Std. Error of the Mean	0.40	2.22	1.80	4.04	1.13	2.12	1.95	1.41	2.40	1.61	2.34	1.12	1.41	0.82

N	%	Cum %	Lower 95% limit on Mean	30.88	27.31	28.11	33.71	27.44	26.94	27.36	29.42	28.33	26.83	21.88	28.86	23.00	30.09
			Upper 95% limit on Mean	32.46	36.39	35.29	50.61	31.90	35.59	35.18	35.00	38.45	33.25	31.59	33.29	28.62	33.30

			Geometric Statistics														
			Mean	28.20	28.98	27.36	37.12	26.06	27.36	27.10	27.90	31.75	26.13	24.24	28.66	21.92	28.98

			Log10 Mean	1.45	1.46	1.44	1.57	1.42	1.44	1.43	1.45	1.50	1.42	1.38	1.46	1.34	1.46
			Log10 S.D.	0.23	0.22	0.26	0.26	0.25	0.27	0.26	0.26	0.15	0.26	0.21	0.19	0.27	0.19

			Log10 Std. Error of Mean	0.01	0.040	0.031	0.058	0.021	0.048	0.036	0.025	0.035	0.030	0.043	0.019	0.030	0.012
			Lower 95% limit on Mean	27.35	24.04	23.70	28.10	23.69	21.86	23.00	24.92	26.77	22.76	19.75	26.33	19.07	27.48
			Upper 95% limit on Mean	29.06	34.94	31.60	49.03	28.67	34.25	31.94	31.23	37.67	29.99	29.74	31.21	25.19	30.55

			Percentiles
--	--	--	-------------

			Min Value	3.00	3.40	6.40	6.20	3.10	3.90	11.00	3.00	12.00	4.20	10.00	4.60	4.30	4.30
--	--	--	-----------	------	------	------	------	------	------	-------	------	-------	------	-------	------	------	------

			25th Xtile	23.00	25.00	22.00	35.00	21.00	27.00	16.00	21.00	27.00	20.00	15.00	24.00	16.00	24.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			50th Xtile	31.00	32.00	32.00	40.00	30.00	32.00	24.00	32.00	33.00	30.00	28.00	29.00	26.00	31.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			75th Xtile	39.00	36.00	40.00	50.00	37.00	35.00	30.00	42.00	39.00	41.00	37.00	38.00	37.00	38.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			80th Xtile	42.00	36.00	43.00	54.00	40.00	39.00	30.00	46.00	42.00	43.00	37.00	40.00	39.00	39.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			90th Xtile	48.00	50.00	49.00	65.00	46.00	42.00	32.00	51.00	46.00	46.00	41.00	46.00	43.00	46.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			95th Xtile	55.00	57.00	58.00	70.00	51.00	53.00	32.00	59.00	56.00	50.00	41.00	48.00	46.00	56.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			98th Xtile	63.00	67.00	66.00	77.00	64.00	62.00	32.00	64.00	56.00	58.00	49.00	55.00	49.00	60.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			99th Xtile	66.00	67.00	75.00	77.00	66.00	62.00	32.00	66.00	56.00	65.00	49.00	58.00	50.00	64.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			Max Value	120.00	67.00	75.00	77.00	75.00	62.00	32.00	67.00	56.00	65.00	49.00	76.00	50.00	120.00
--	--	--	-----------	--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------

* Summary statistics not calculated for rock units with less than ten values.

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

Statistics per Variable

Variable - Cadmium [Cd]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	907	17	51	17	103	26	33	89	18	61	14	86	55	216
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.30	0.21	0.30	0.29	0.29	0.32	0.25	0.29	0.31	0.30	0.27	0.31	0.29	0.30
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Standard Deviation	0.19	0.14	0.18	0.17	0.18	0.21	0.16	0.18	0.14	0.17	0.17	0.19	0.22	0.19
--------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Skewness	1.35	1.46	0.49	0.65	0.97	1.28	0.79	1.14	0.77	0.87	0.47	0.93	1.66	1.80
----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Excess Kurtosis	3.05	1.20	-0.63	-0.96	0.30	1.70	-0.65	1.52	-0.77	0.32	-1.18	0.60	3.53	5.77
-----------------	------	------	-------	-------	------	------	-------	------	-------	------	-------	------	------	------

Coef. of Var. %	62.96	69.56	58.56	56.59	63.51	65.95	65.82	60.33	45.31	55.99	63.92	60.11	74.74	65.51
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Std. Error of the Mean	0.01	0.026	0.021	0.037	0.016	0.037	0.022	0.017	0.033	0.020	0.035	0.018	0.024	0.012
------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

N	%	Cum %	Lower 95% limit on Mean	0.29	0.15	0.26	0.22	0.26	0.24	0.21	0.26	0.24	0.26	0.19
---	---	-------	-------------------------	------	------	------	------	------	------	------	------	------	------	------

Upper 95% limit on Mean	0.31	0.26	0.34	0.37	0.32	0.39	0.29	0.33	0.38	0.34	0.34	0.35	0.34	0.32
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

ppm	0.02-	.												
-----	-------	---	--	--	--	--	--	--	--	--	--	--	--	--

0.05-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

0.10-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

0.20-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

0.50-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

1.00-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

2.00-	.													
-------	---	--	--	--	--	--	--	--	--	--	--	--	--	--

+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+
---	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

0	10	20	30	40	50	60	70	80	90	100	%			
---	----	----	----	----	----	----	----	----	----	-----	---	--	--	--

Percentage of Values														
----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Geometric Statistics														
----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

271	23.0	23.0	Mean	0.25	0.17	0.25	0.25	0.24	0.26	0.20	0.25	0.28	0.26	0.21
-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------

389	33.0	56.0	Log10 Mean	-0.61	-0.77	-0.61	-0.60	-0.63	-0.59	-0.69	-0.61	-0.55	-0.59	-0.67
-----	------	------	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

377	32.0	88.0	Log10 S.D.	0.27	0.25	0.29	0.25	0.28	0.29	0.29	0.26	0.18	0.25	0.30
-----	------	------	------------	------	------	------	------	------	------	------	------	------	------	------

135	11.5	99.5	Log10 Std. Error of Mean	0.01	0.046	0.034	0.056	0.024	0.050	0.039	0.025	0.043	0.043	0.029
-----	------	------	--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

6	0.5	100.0	Lower 95% limit on Mean	0.24	0.14	0.21	0.19	0.21	0.21	0.17	0.22	0.23	0.22
---	-----	-------	-------------------------	------	------	------	------	------	------	------	------	------	------

			Upper 95% limit on Mean	0.25	0.21	0.29	0.33	0.26	0.33	0.24	0.28	0.35	0.29
--	--	--	-------------------------	------	------	------	------	------	------	------	------	------	------

Percentiles														
-------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Min Value	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.20	0.10	0.10	0.10	0.10
-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

25th Xtile	0.20	0.10	0.10	0.20	0.10	0.20	0.10	0.20	0.20	0.20	0.20	0.20	0.20	0.20
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

50th Xtile	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

75th Xtile	0.40	0.20	0.40	0.40	0.40	0.40	0.40	0.20	0.40	0.40	0.40	0.40	0.40	0.40
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

80th Xtile	0.40	0.20	0.40	0.40	0.40	0.40	0.40	0.20	0.40	0.40	0.40	0.40	0.40	0.40
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

90th Xtile	0.60	0.40	0.60	0.60	0.60	0.60	0.60	0.40	0.60	0.60	0.60	0.60	0.60	0.60
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

95th Xtile	0.60	0.60	0.60	0.60	0.60	0.60	0.80	0.40	0.60	0.60	0.60	0.60	0.60	0.60
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

98th Xtile	0.80	0.60	0.60	0.60	0.80	1.00	0.40	0.80	0.60	0.80	0.60	0.80	0.60	0.80
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

99th Xtile	0.80	0.60	0.80	0.60	0.80	1.00	0.40	0.80	0.60	0.80	0.60	0.80	0.60	0.80
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Max Value	1.40	0.60	0.80	0.60	0.80	1.00	0.40	1.00	0.60	0.80	0.60	0.80	0.60	1.00
-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Cerium [Ce]

Number of Values - 1178

Units - ppm

Detection Limit - 5

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1176	31	70	20	139	33	54	112	18	73	23	106	82	275
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	113.16	36.39	139.99	234.50	145.42	147.55	154.94	131.88	124.89	108.34	110.57	107.72	69.34	73.59
------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------

Standard Deviation	81.14	15.83	54.98	170.38	74.82	98.45	62.45	91.86	67.23	43.17	32.10	57.42	38.05	57.56
--------------------	-------	-------	-------	--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Skewness	2.57	0.52	1.04	0.71	1.10	1.56	1.00	3.87	2.25	1.10	-0.075	0.85	1.81	2.88
----------	------	------	------	------	------	------	------	------	------	------	--------	------	------	------

Excess Kurtosis	12.03	-0.56	1.44	-0.77	1.36	1.97	1.62	21.93	5.47	2.23	-1.05	0.50	5.09	11.82
-----------------	-------	-------	------	-------	------	------	------	-------	------	------	-------	------	------	-------

Coef. of Var. %	71.70	43.49	39.28	72.66	51.45	66.73	40.31	69.66	53.83	39.85	29.04	53.30	54.87	78.22
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

N	%	Cum %												
---	---	-------	--	--	--	--	--	--	--	--	--	--	--	--

Std. Error of the Mean	2.36	2.84	6.57	38.10	6.35	17.14	8.50	8.68	15.85	5.05	6.69	5.58	4.20	3.46
------------------------	------	------	------	-------	------	-------	------	------	-------	------	------	------	------	------

Lower 95% limit on Mean	108.52	30.58	126.87	154.76	132.87	112.62	137.90	114.68	91.46	98.27	96.68	96.66	60.98	66.76
-------------------------	--------	-------	--------	--------	--------	--------	--------	--------	-------	-------	-------	-------	-------	-------

Upper 95% limit on Mean	117.80	42.19	153.10	314.24	157.97	182.47	171.99	149.09	158.32	118.42	124.45	118.78	77.70	80.41
-------------------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------

2	0.2	0.2
---	-----	-----

Geometric Statistics

1	0.1	0.3	Mean	91.13	33.04	130.27	180.08	127.91	123.22	143.20	113.33	113.43	100.44	105.69	92.80	60.92	59.17
---	-----	-----	------	-------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------	-------

10	.	.	Log10 Mean	1.96	1.52	2.11	2.26	2.11	2.09	2.16	2.05	2.05	2.00	2.02	1.97	1.78	1.77
----	---	---	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

20	.	.	Log10 S.D.	0.30	0.20	0.17	0.33	0.23	0.26	0.18	0.23	0.19	0.17	0.14	0.25	0.22	0.29
----	---	---	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

50	.	.	Log10 Std. Error of Mean	0.01	0.036	0.020	0.074	0.019	0.045	0.024	0.022	0.044	0.020	0.029	0.024	0.025	0.017
----	---	---	--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

188	16.0	18.4	Lower 95% limit on Mean	87.65	27.92	118.91	126.36	117.25	99.55	128.07	102.49	91.77	91.57	92.13	83.13	54.40	54.71
-----	------	------	-------------------------	-------	-------	--------	--------	--------	-------	--------	--------	-------	-------	-------	-------	-------	-------

409	34.7	53.1	Upper 95% limit on Mean	94.74	39.09	142.72	256.66	139.53	152.53	160.11	125.31	140.20	110.18	121.24	103.60	68.23	63.99
-----	------	------	-------------------------	-------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------

Percentiles															
-------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Min Value	2.50	13.00	44.00	65.00	27.00	37.00	63.00	14.00	51.00	34.00	53.00	15.00	15.00	2.50
-----------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

25th Xtile	58.00	23.00	100.00	89.00	93.00	96.00	110.00	82.00	93.00	78.00	87.00	59.00	45.00	42.00
------------	-------	-------	--------	-------	-------	-------	--------	-------	-------	-------	-------	-------	-------	-------

50th Xtile	93.00	34.00	130.00	160.00	127.00	126.00	113.00	120.00	102.00	104.00	110.00	96.00	61.00	59.00
------------	-------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------	-------

75th Xtile	140.00	46.00	180.00	360.00	190.00	163.00	132.00	147.00	142.00	138.00	140.00	141.00	87.00	83.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------

80th Xtile	150.00	46.00	182.00	370.00	206.00	190.00	132.00	160.00	148.00	140.00	140.00	150.00	91.00	91.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	-------	-------

90th Xtile	200.00	58.00	220.00	410.00	240.00	296.00	261.00	200.00	173.00	156.00	147.00	180.00	118.00	130.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

95th Xtile	250.00	70.00	231.00	518.00	297.00	414.00	261.00	270.00	360.00	175.00	158.00	220.00	131.00	170.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

98th Xtile	350.00	71.00	247.00	629.00	352.00	450.00	261.00	370.00	360.00	235.00	170.00	240.00	170.00	260.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

99th Xtile	414.00	71.00	350.00	629.00	370.00	450.00	261.00	430.00	360.00	278.00	170.00	250.00	250.00	310.00
------------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

Max Value	784.00	71.00	350.00	629.00	440.00	450.00	261.00	784.00	360.00	278.00	170.00	307.00	250.00	470.00
-----------	--------	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

* Summary statistics not calculated for rock units with less than ten values.



Statistics per Variable

Variable - Cesium [Cs]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	902	26	61	17	110	23	46	86	11	58	23	75	65	204
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	1.09	0.87	1.30	1.00	1.30	0.90	1.65	1.36	0.99	1.22	1.60	0.87	1.02	0.90
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Standard Deviation	0.79	0.40	0.87	0.50	0.95	0.59	1.25	0.96	0.85	0.77	0.84	0.60	0.64	0.55
--------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Skewness	1.47	0.22	1.06	0.53	1.13	0.58	1.17	0.83	0.89	0.97	0.71	1.29	0.99	0.85
----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Excess Kurtosis	2.86	-0.59	0.50	0.28	0.83	-0.70	0.52	0.20	-0.68	1.14	-0.61	2.33	0.63	0.59
-----------------	------	-------	------	------	------	-------	------	------	-------	------	-------	------	------	------

Coef. of Var. %	72.18	46.74	67.13	49.70	73.30	64.89	76.06	70.89	85.72	63.43	52.76	68.07	62.89	61.26
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Std. Error of the Mean	0.02	0.073	0.10	0.11	0.081	0.10	0.17	0.091	0.20	0.090	0.18	0.058	0.071	0.033
------------------------	------	-------	------	------	-------	------	------	-------	------	-------	------	-------	-------	-------

N	%	Cum %	Lower 95% limit on Mean	1.04	0.72	1.09	0.77	1.14	0.69	1.31	1.18	0.57	1.04	1.23
---	---	-------	-------------------------	------	------	------	------	------	------	------	------	------	------	------

Upper 95% limit on Mean	1.13	1.01	1.50	1.24	1.46	1.11	1.99	1.54	1.42	1.40	1.97	0.99	1.17	0.97
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

ppm	0.1-	.												
-----	------	---	--	--	--	--	--	--	--	--	--	--	--	--

0.2-	.	□												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

0.5-	.	□												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

1.0-	.	□												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

2.0-	.	□												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

5.0-	.	□												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

10.0-	.	□												
-------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+	-----+
---	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

0	10	20	30	40	50	60	70	80	90	100	%			
---	----	----	----	----	----	----	----	----	----	-----	---	--	--	--

Percentage of Values	276	23.4	23.4											
----------------------	-----	------	------	--	--	--	--	--	--	--	--	--	--	--

Geometric Statistics	413	35.1	58.5											
----------------------	-----	------	------	--	--	--	--	--	--	--	--	--	--	--

Mean	0.84	0.76	1.03	0.86	0.98	0.71	1.24	1.01	0.69	0.97	1.40	0.69	0.83	0.73
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Log10 Mean	-0.08	-0.12	0.012	-0.063	-0.011	-0.15	0.094	0	-0.16	-0.014	0.15	-0.16	-0.080	-0.14
------------	-------	-------	-------	--------	--------	-------	-------	---	-------	--------	------	-------	--------	-------

Log10 S.D.	0.33	0.25	0.31	0.27	0.35	0.32	0.34	0.37	0.39	0.32	0.23	0.32	0.30	0.30
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Log10 Std. Error of Mean	0.01	0.045	0.037	0.060	0.030	0.056	0.046	0.035	0.091	0.037	0.048	0.031	0.033	0.018
--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Lower 95% limit on Mean	0.80	0.61	0.87	0.65	0.85	0.54	1.00	0.86	0.45	0.82	1.11	0.60	0.72	0.67
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Upper 95% limit on Mean	0.88	0.93	1.22	1.15	1.12	0.92	1.54	1.18	1.08	1.15	1.76	0.79	0.97	0.79
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Percentiles	127	10.8	99.9											
-------------	-----	------	------	--	--	--	--	--	--	--	--	--	--	--

Min Value	1	0.1	100.0											
-----------	---	-----	-------	--	--	--	--	--	--	--	--	--	--	--

25th Xtile	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.60	0.25	0.25	0.25
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

50th Xtile	0.60	0.60	0.70	0.70	0.60	0.25	0.60	0.60	0.25	0.70	0.90	0.25	0.60	0.50
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

75th Xtile	0.90	0.80	1.10	0.90	1.10	0.80	0.90	1.20	0.70	1.00	1.50	0.80	0.80	0.80
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

80th Xtile	1.40	1.20	1.80	1.40	1.70	1.20	2.30	2.00	1.50	1.60	2.30	1.20	1.40	1.20
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

90th Xtile	2.10	1.30	2.50	1.40	2.70	1.60	3.30	2.60	2.60	2.20	2.60	1.60	1.90	1.70
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

95th Xtile	2.50	1.60	3.20	1.60	3.50	2.00	3.30	3.10	2.80	2.40	3.30	1.90	2.30	1.90
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

98th Xtile	3.20	1.80	3.80	2.30	4.00	2.30	3.30	3.70	2.80	3.30	3.50	2.50	2.80	2.30
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

99th Xtile	3.70	1.80	3.80	2.30	4.10	2.30	3.30	3.90	2.80	4.00	3.50	3.00	3.00	2.40
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Max Value	5.30	1.80	3.80	2.30	4.10	2.30	3.30	4.70	2.80	4.00	3.50	3.20	3.00	2.70
-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Chromium [Cr]

Number of Values - 1178

Units - ppm

Detection Limit - 20

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	850	18	59	17	94	23	41	91	11	59	21	70	52	199
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	28.61	23.52	36.54	36.35	26.53	26.55	30.15	32.61	28.00	29.14	33.70	25.95	23.50	28.37
------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Standard Deviation	17.28	13.39	36.95	19.07	13.88	13.15	15.00	15.51	18.82	12.76	10.65	14.22	11.69	15.71
--------------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Skewness	4.54	0.55	6.42	0.91	0.36	0.24	0.15	0.24	0.75	0.36	-0.73	0.56	0.19	1.25
----------	------	------	------	------	------	------	------	------	------	------	-------	------	------	------

Excess Kurtosis	68.14	-0.80	46.56	-0.043	-0.89	-0.42	-0.98	-0.45	-0.46	-0.034	-0.32	-0.095	-1.19	4.09
-----------------	-------	-------	-------	--------	-------	-------	-------	-------	-------	--------	-------	--------	-------	------

Coef. of Var. %	60.41	56.94	101.11	52.47	52.32	49.55	49.77	47.56	67.22	43.79	31.60	54.79	49.73	55.37
-----------------	-------	-------	--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Std. Error of the Mean	0.50	2.41	4.42	4.27	1.18	2.29	2.04	1.47	4.44	1.49	2.22	1.38	1.29	0.95
------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

N	%	Cum %	Lower 95% limit on Mean	27.62	18.60	27.73	27.42	24.20	21.88	26.05	29.70	18.64	26.16	29.09	23.21	20.93	26.51
			Upper 95% limit on Mean	29.59	28.43	45.35	45.28	28.85	31.21	34.24	35.51	37.36	32.11	38.30	28.69	26.07	30.23

ppm	2-	.	Geometric Statistics														
-----	----	---	----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

	314	26.7	26.7	Mean	24.23	19.88	29.97	31.86	22.65	22.91	25.85	28.29	22.31	26.01	31.43	21.92	20.36	24.17
--	-----	------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	10-	.	□	Log10 Mean	1.38	1.30	1.48	1.50	1.36	1.36	1.41	1.45	1.35	1.42	1.50	1.34	1.31	1.38
--	-----	---	---	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

	20-	.	□	Log10 S.D.	0.26	0.26	0.26	0.24	0.26	0.25	0.26	0.25	0.25	0.31	0.22	0.19	0.26	0.24	0.26
--	-----	---	---	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

	50-	.	□	Log10 Std. Error of Mean	0.01	0.047	0.031	0.053	0.022	0.044	0.036	0.024	0.073	0.026	0.039	0.026	0.027	0.015
--	-----	---	---	--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	100-	.	□	Lower 95% limit on Mean	23.42	15.94	26.00	24.69	20.51	18.60	21.94	25.39	15.66	23.07	26.14	19.50	17.99	22.53
--	------	---	---	-------------------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	200-	.	□	Upper 95% limit on Mean	25.08	24.79	34.53	41.12	25.01	28.21	30.45	31.53	31.79	29.32	37.79	24.65	23.04	25.92
--	------	---	---	-------------------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	500-	.	□	83	7.0	99.8	Percentiles										
--	------	---	---	----	-----	------	-------------	--	--	--	--	--	--	--	--	--	--

	100-	.	□	Min Value	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
--	------	---	---	-----------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	200-	.	□	25th Xtile	10.00	10.00	26.00	26.00	10.00	10.00	10.00	22.00	10.00	24.00	28.00	10.00	10.00
--	------	---	---	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	500-	.	□	50th Xtile	28.00	22.00	32.00	30.00	25.00	31.00	24.00	33.00	25.00	28.00	36.00	27.00	24.00	27.00
--	------	---	---	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	80th Xtile	37.00	33.00	41.00	41.00	37.00	34.00	24.00	44.00	40.00	36.00	43.00	37.00	34.00	40.00
--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	90th Xtile	40.00	35.00	44.00	45.00	38.00	36.00	24.00	46.00	40.00	39.00	43.00	37.00	34.00	40.00
--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	95th Xtile	47.00	42.00	49.00	67.00	46.00	38.00	57.00	53.00	66.00	45.00	46.00	45.00	39.00	48.00
--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	Max Value	54.00	46.00	56.00	73.00	51.00	48.00	57.00	56.00	69.00	53.00	46.00	51.00	41.00	55.00
--	-----------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	98th Xtile	66.00	56.00	77.00	81.00	55.00	61.00	57.00	67.00	69.00	61.00	48.00	62.00	46.00	63.00
--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	99th Xtile	71.00	56.00	320.00	81.00	59.00	61.00	57.00	68.00	69.00	63.00	48.00	66.00	48.00	71.00
--	------------	-------	-------	--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

	Max Value	320.00	56.00	320.00	81.00	60.00	61.00	57.00	77.00	69.00	63.00	48.00	69.00	48.00	120.00
--	-----------	--------	-------	--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------

* Summary statistics not calculated for rock units with less than ten values.

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

Statistics per Variable

Variable - Cobalt [Co]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1127	28	69	19	133	30	52	110	18	73	23	101	81	252
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	7.46	5.00	8.24	9.75	7.55	6.94	8.96	8.91	9.00	9.73	10.26	7.31	6.83	5.90
Standard Deviation	4.67	2.28	3.68	6.50	3.83	3.97	4.49	4.55	3.88	6.17	6.50	4.95	3.78	4.59

Skewness	2.88	0.46	0.54	0.60	1.09	1.31	1.44	2.14	1.32	1.69	1.61	2.75	1.86	6.61
Excess Kurtosis	17.68	-1.10	-0.59	-0.97	1.66	2.40	2.88	7.30	1.17	2.63	1.82	8.98	4.20	69.12

Coef. of Var. %	62.61	45.61	44.70	66.63	50.75	57.18	50.08	51.07	43.12	63.43	63.38	67.65	55.40	77.83
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

N	X	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean
0.14	0.41	0.44	1.45	0.32	0.69
7.19	4.16	7.36	6.71	6.90	5.53
7.73	5.84	9.12	12.79	8.19	8.35
				10.19	9.76
				10.93	11.17
				13.07	8.26
					7.66

2	0.2	0.2	Geometric Statistics											
Mean	6.42	4.50	7.42	7.73	6.64	5.97	7.97	8.00	8.37	8.33	8.88	6.29	6.05	5.05

Log10 Mean	0.81	0.65	0.87	0.89	0.82	0.78	0.90	0.90	0.90	0.92	0.92	0.95	0.80	0.78	0.70
Log10 S.D.	0.24	0.21	0.21	0.31	0.23	0.25	0.22	0.20	0.20	0.16	0.23	0.23	0.23	0.21	0.23

402	34.1	38.5	Log10 Std. Error of Mean											
0.01	0.037	0.025	0.070	0.019	0.043	0.030	0.019	0.039	0.039	0.027	0.047	0.022	0.023	0.014

Lower 95% limit on Mean	6.22	3.78	6.63	5.51	6.08	4.88	6.95	7.34	6.93	7.35	7.09	5.69	5.44	4.74
Upper 95% limit on Mean	6.62	5.36	8.31	10.85	7.25	7.30	9.15	8.73	10.10	9.44	11.11	6.96	6.72	5.38

534	45.3	83.8	Upper 95% limit on Mean

165	14.0	97.8	Percentiles
Min Value	1.00	2.00	2.00

25th Xtile	5.00	3.00	5.00
50th Xtile	6.00	5.00	7.00

75th Xtile	9.00	6.00	11.00
80th Xtile	10.00	7.00	12.00

90th Xtile	13.00	9.00	14.00
95th Xtile	15.00	9.00	15.00

98th Xtile	22.00	9.00	16.00
99th Xtile	25.00	9.00	18.00

Max Value	60.00	9.00	18.00
		24.00	22.00


		21.00	26.00
		31.00	20.00

		20.00	22.00
		24.00	17.00

		30.00	24.00
		22.00	14.00

		33.00	22.00
		33.00	60.00

* Summary statistics not calculated for rock units with less than ten values.



Percentage of Values

Statistics per Variable

Variable - Cobalt [Co]

Number of Values - 1178

Units - ppm

Detection Limit - 5

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN	
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Values >= D.L.	986	19	67	16	121	30	50	106	17	71	23	89	65	192
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ppm 1- .				Mean	10.06	6.95	12.06	11.55	10.48	10.17	12.55	12.31	11.22	13.17	15.04	9.63	9.33	7.49
				Standard Deviation	6.17	3.90	4.87	7.66	5.22	4.18	6.71	5.96	4.40	7.60	8.63	6.44	5.42	5.85
				Skewness	2.38	0.12	0.45	0.41	0.80	0.42	1.49	2.02	0.47	1.89	1.51	2.42	1.35	5.80
				Excess Kurtosis	13.62	-1.47	-0.12	-1.13	1.44	1.07	2.76	8.71	-0.84	4.09	1.55	7.94	2.94	59.53
				Coef. of Var. %	61.35	56.13	40.40	66.29	49.78	41.07	53.49	48.44	39.21	57.70	57.38	66.89	58.09	77.99
				Std. Error of the Mean	0.18	0.70	0.58	1.71	0.44	0.73	0.91	0.56	1.04	0.89	1.80	0.63	0.60	0.35
				N	9.71	5.52	10.90	7.97	9.60	8.69	10.71	11.19	9.03	11.40	11.31	8.39	8.14	6.80
				%	Cum %	Lower 95% limit on Mean												
					9.71	5.52	10.90	7.97	9.60	8.69	10.71	11.19	9.03	11.40	11.31	8.39	8.14	6.80
					Upper 95% limit on Mean	10.42	8.38	13.23	15.13	11.35	11.65	14.38	13.42	13.41	14.94	18.78	10.87	10.52
2- . □ . <<<<<< 5- . □ 10- . □ 20- . □ 50- . □ 100- . □				Geometric Statistics														
				Mean	8.45	5.74	10.99	8.87	9.05	9.16	10.98	11.07	10.42	11.58	13.28	8.09	7.84	6.15
				Log10 Mean	0.93	0.76	1.04	0.95	0.96	0.96	1.04	1.04	1.02	1.06	1.12	0.91	0.89	0.79
				Log10 S.D.	0.27	0.29	0.20	0.35	0.26	0.22	0.24	0.21	0.17	0.22	0.21	0.26	0.27	0.27
				Log10 Std. Error of Mean	0.01	0.052	0.024	0.078	0.022	0.039	0.032	0.020	0.041	0.025	0.044	0.025	0.030	0.016
				Lower 95% limit on Mean	8.15	4.50	9.82	6.08	8.20	7.64	9.46	10.13	8.54	10.32	10.75	7.21	6.83	5.71
				Upper 95% limit on Mean	8.75	7.33	12.29	12.92	9.99	10.98	12.73	12.10	12.72	13.00	16.40	9.07	9.00	6.63
				Percentiles														
				Min Value	2.50	2.50	2.50	2.50	2.50	2.50	2.50	2.50	5.00	2.50	6.00	2.50	2.50	2.50
				25th Xtile	6.00	2.50	9.00	6.00	7.00	8.00	9.00	9.00	7.00	8.00	10.00	6.00	6.00	2.50
				50th Xtile	9.00	7.00	11.00	8.00	10.00	10.00	10.00	12.00	10.00	11.00	11.00	9.00	9.00	7.00
0 10 20 30 40 50 60 70 80 90 100 % Percentage of Values				75th Xtile	12.00	11.00	16.00	17.00	13.00	12.00	26.00	14.00	16.00	15.00	20.00	11.00	11.00	9.00
				80th Xtile	13.00	11.00	16.00	17.00	14.00	13.00	26.00	16.00	16.00	17.00	21.00	11.00	13.00	10.00
				90th Xtile	17.00	12.00	18.00	19.00	18.00	15.00	36.00	19.00	16.00	24.00	21.00	17.00	15.00	12.00
				95th Xtile	21.00	13.00	21.00	25.00	21.00	15.00	36.00	23.00	21.00	32.00	38.00	23.00	17.00	15.00
				98th Xtile	27.00	14.00	22.00	27.00	23.00	23.00	36.00	24.00	21.00	32.00	38.00	29.00	29.00	19.00
				99th Xtile	32.00	14.00	26.00	27.00	23.00	23.00	36.00	27.00	21.00	46.00	38.00	34.00	29.00	22.00
				Max Value	74.00	14.00	26.00	27.00	32.00	23.00	36.00	47.00	21.00	46.00	38.00	43.00	29.00	74.00

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Copper [Cu]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1161	30	69	20	138	32	52	112	18	73	23	104	79	271
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	14.24	9.77	19.13	18.95	15.79	17.15	19.37	18.13	17.33	15.90	19.13	11.18	9.43	9.20
Standard Deviation	9.39	5.11	13.50	9.21	7.99	11.11	13.01	9.72	7.34	6.28	8.74	4.13	4.59	4.18
Skewness	2.83	1.73	2.98	0.68	0.77	1.93	1.76	2.36	1.08	0.37	0.88	0.43	0.83	1.24

Excess Kurtosis	15.79	3.13	13.73	0.28	0.83	5.62	3.60	10.73	1.04	-0.28	-0.38	0.58	1.04	3.10
Coef. of Var. %	65.94	52.28	70.58	48.59	50.63	64.80	67.17	53.64	42.35	39.49	45.69	36.91	48.68	45.42

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean											
0.2-	.	.	0.27	0.92	1.61	2.06	0.68	1.93	1.77	0.92	1.73	0.74	1.82	0.40	0.51	0.25
0.5-	.	.	13.70	7.90	15.91	14.64	14.45	13.21	15.82	16.30	13.68	14.44	15.35	10.38	8.42	8.70
1.0-	.	.	14.78	11.65	22.35	23.26	17.13	21.09	22.92	19.95	20.98	17.37	22.91	11.97	10.44	9.69

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean									
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean								
---	---	-------	------------------------	-------------------------	-------------------------	--	--	--	--	--	--	--	--

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Europium [Eu]

Number of Values - 1178

Units - ppm

Detection Limit - 1

Analytical Method - INA

			All Units*																									
			MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN													
ppm	0.1-	.	Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276											
			Number of Values >= D.L.	261	0	30	8	37	9	17	39	5	16	5	12	2	38											
			Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0											
			Mean	0.99	-	1.30	1.65	1.03	1.15	1.07	1.29	1.14	1.01	1.02	0.73	0.57	0.83											
			Standard Deviation	0.87	-	0.78	1.35	0.70	1.11	0.71	1.30	0.94	0.57	0.57	0.52	0.26	0.72											
			Skewness	3.76	-	0.44	0.68	1.05	2.62	0.75	5.06	1.60	0.83	0.78	2.30	4.46	3.28											
			Excess Kurtosis	29.28	-	-1.07	-1.24	-0.12	8.22	-0.92	37.86	2.11	-0.78	-0.89	4.39	20.79	14.61											
			Coef. of Var. %	87.53	-	60.16	81.73	67.92	96.78	66.09	100.73	82.21	56.34	56.14	71.17	45.45	86.24											
			Std. Error of the Mean	0.03	-	0.093	0.30	0.059	0.19	0.097	0.12	0.22	0.067	0.12	0.050	0.028	0.043											
	N	%	Cum %	Lower 95% limit on Mean	0.94	-	1.11	1.02	0.91	0.76	0.88	1.05	0.67	0.88	0.77	0.63	0.51	0.75										
				Upper 95% limit on Mean	1.04	-	1.49	2.28	1.15	1.55	1.27	1.54	1.60	1.15	1.27	0.83	0.62	0.92										
	0.2-	.				Geometric Statistics																						
	0.5-	.				713	60.5	60.5	Mean	0.79	-	1.06	1.18	0.84	0.87	0.87	0.98	0.89	0.88	0.89	0.63	0.54	0.68					
	1.0-	.				204	17.3	77.8	Log10 Mean	-0.11	-	0.027	0.072	-0.075	-0.062	-0.058	-0	-0.050	-0.058	-0.052	-0.20	-0.27	-0.17					
	2.0-	.				210	17.8	95.7	Log10 S.D.	0.27	-	0.28	0.37	0.27	0.30	0.28	0.31	0.30	0.23	0.23	0.21	0.12	0.24					
	5.0-	.				46	3.9	99.6	Log10 Std. Error of Mean	0.01	-	0.034	0.082	0.023	0.053	0.038	0.029	0.070	0.027	0.049	0.020	0.013	0.014					
	10.0-	.				4	0.3	99.9	Lower 95% limit on Mean	0.76	-	0.91	0.79	0.76	0.68	0.74	0.86	0.63	0.77	0.70	0.57	0.51	0.64					
	20.0-	.				1	0.1	100.0	Upper 95% limit on Mean	0.81	-	1.24	1.75	0.93	1.11	1.04	1.12	1.25	0.99	1.12	0.69	0.57	0.73					
	0	10	20	30	40	50	60	70	80	90	100	%	Percentiles															
													Min Value	0.50	-	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
													25th Xtile	0.50	-	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
													50th Xtile	0.50	-	1.00	1.00	0.50	0.50	0.50	1.00	0.50	1.00	1.00	0.50	0.50	0.50	0.50
													75th Xtile	1.00	-	2.00	3.00	2.00	2.00	1.00	2.00	2.00	1.00	1.00	0.50	0.50	0.50	1.00
													80th Xtile	2.00	-	2.00	3.00	2.00	2.00	1.00	2.00	2.00	2.00	2.00	2.00	1.00	0.50	1.00
													90th Xtile	2.00	-	2.00	4.00	2.00	2.00	1.00	2.00	2.00	2.00	2.00	2.00	2.00	0.50	2.00
													95th Xtile	2.00	-	3.00	4.00	2.00	3.00	1.00	3.00	4.00	2.00	2.00	2.00	2.00	1.00	2.00
													98th Xtile	3.00	-	3.00	4.00	3.00	6.00	1.00	3.00	4.00	2.00	2.00	2.00	2.00	2.00	3.00
													99th Xtile	4.00	-	3.00	4.00	3.00	6.00	1.00	3.00	4.00	2.00	2.00	2.00	2.00	2.00	4.00
													Max Value	12.00	-	3.00	4.00	3.00	6.00	1.00	12.00	4.00	2.00	2.00	2.00	3.00	2.00	6.00

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Fluoride [F-W]

Number of Values - 1178

Units - ppb

Detection Limit - 20

Analytical Method - ISE

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN				
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276			
				Number of Values >= D.L.	1164	29	70	20	139	33	53	111	18	73	23	106	79	271			
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
ppb 2- . 5- . 10- . 20- . 50- . 100- . 200- . 500- . 1000- .				Mean	105.58	33.55	142.26	135.60	170.94	151.27	114.59	101.68	107.11	71.84	64.78	120.32	85.22	66.90			
				Standard Deviation	70.79	13.13	74.01	40.73	93.24	64.11	50.51	43.35	51.37	17.98	19.54	70.71	59.59	35.37			
				Skewness	2.37	0.73	0.81	0.42	1.36	0.86	1.28	1.90	1.12	0.18	1.68	6.39	1.90	1.14			
				Excess Kurtosis	10.45	0.68	0.35	-0.85	2.47	0.17	3.68	8.09	0.85	0.20	3.12	52.91	5.35	1.81			
				Coef. of Var. %	67.05	39.14	52.03	30.04	54.55	42.38	44.08	42.63	47.96	25.03	30.16	58.77	69.93	52.87			
				N	%	Cum %	Std. Error of the Mean	2.06	2.36	8.85	9.11	7.91	11.16	6.87	4.10	12.11	2.10	4.07	6.87	6.58	2.13
				Lower 95% limit on Mean	101.53	28.73	124.61	116.54	155.30	128.53	100.81	93.56	81.56	67.64	56.33	106.70	72.12	62.71			
				Upper 95% limit on Mean	109.62	38.36	159.91	154.66	186.57	174.01	128.38	109.80	132.66	76.03	73.23	133.94	98.32	71.09			
				14	1.2	1.2	Geometric Statistics														
				Mean	87.16	30.98	123.95	129.89	149.04	139.18	103.13	93.43	97.22	69.47	62.50	110.83	67.74	58.11			
				Log10 Mean	1.94	1.49	2.09	2.11	2.17	2.14	2.01	1.97	1.99	1.84	1.80	2.04	1.83	1.76			
				Log10 S.D.	0.28	0.18	0.24	0.13	0.23	0.18	0.22	0.19	0.19	0.12	0.11	0.16	0.31	0.24			
				189	16.0	17.2	Log10 Std. Error of Mean	0.01	0.033	0.028	0.029	0.020	0.031	0.030	0.018	0.046	0.014	0.024	0.016	0.035	0.014
				Lower 95% limit on Mean	84.05	26.51	108.93	112.75	136.34	120.14	89.67	86.18	77.89	65.24	55.78	103.19	57.83	54.42			
				517	43.9	61.1	Upper 95% limit on Mean	90.39	36.21	141.05	149.64	162.92	161.24	118.61	101.30	121.34	73.97	70.04	119.04	79.35	62.04
				364	30.9	92.0	Percentiles														
				Min Value	10.00	10.00	36.00	78.00	26.00	66.00	110.00	10.00	48.00	30.00	40.00	38.00	10.00	10.00			
				25th Xtile	62.00	24.00	84.00	96.00	98.00	100.00	120.00	70.00	68.00	60.00	54.00	90.00	40.00	38.00			
				50th Xtile	88.00	32.00	130.00	130.00	150.00	140.00	130.00	96.00	82.00	72.00	62.00	110.00	74.00	64.00			
				75th Xtile	130.00	40.00	190.00	150.00	220.00	190.00	170.00	120.00	140.00	82.00	68.00	140.00	110.00	84.00			
				80th Xtile	140.00	42.00	200.00	160.00	240.00	200.00	170.00	130.00	140.00	84.00	74.00	140.00	110.00	90.00			
				90th Xtile	190.00	50.00	230.00	200.00	290.00	230.00	240.00	150.00	180.00	96.00	88.00	160.00	140.00	110.00			
				95th Xtile	240.00	66.00	260.00	200.00	350.00	280.00	240.00	180.00	250.00	110.00	98.00	180.00	170.00	130.00			
				98th Xtile	310.00	68.00	350.00	220.00	450.00	330.00	240.00	190.00	250.00	110.00	130.00	210.00	290.00	170.00			
				99th Xtile	360.00	68.00	370.00	220.00	530.00	330.00	240.00	200.00	250.00	120.00	130.00	250.00	350.00	180.00			
				Max Value	740.00	68.00	370.00	220.00	550.00	330.00	240.00	350.00	250.00	120.00	130.00	740.00	350.00	220.00			
Percentage of Values				* Summary statistics not calculated for rock units with less than ten values.																	
0 10 20 30 40 50 60 70 80 90 100 %																					

* Summary statistics not calculated for
rock units with less than ten values.

Statistics per Variable

Variable - Gold [Au]

Number of Values - 1178

Units - ppb

Detection Limit - 2

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	186	3	9	2	28	4	17	15	2	8	1	25	14	40
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	1.56	1.23	1.41	1.30	1.81	1.42	2.30	1.35	1.28	1.33	1.17	1.84	1.49	1.53
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Standard Deviation	1.49	0.72	1.22	0.98	1.81	1.28	2.19	0.94	0.83	0.94	0.83	1.69	1.22	1.65
--------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Skewness	3.71	2.82	3.13	2.94	2.32	3.06	1.55	2.66	2.45	2.74	4.19	2.09	3.54	5.58
----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Excess Kurtosis	20.77	6.66	9.42	7.68	4.98	9.16	1.56	6.57	4.60	6.34	16.26	3.71	16.14	43.22
-----------------	-------	------	------	------	------	------	------	------	------	------	-------	------	-------	-------

Coef. of Var. %	95.17	58.49	86.38	75.29	99.95	89.56	95.57	69.49	64.68	71.01	71.05	91.62	81.98	108.06
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------

Std. Error of the Mean	0.04	0.13	0.15	0.22	0.15	0.22	0.30	0.089	0.19	0.11	0.17	0.16	0.13	0.099
------------------------	------	------	------	------	------	------	------	-------	------	------	------	------	------	-------

N	%	Cum %	Lower 95% limit on Mean	1.48	0.96	1.12	0.84	1.51	0.97	1.70	1.17	0.87	1.11	0.81
---	---	-------	-------------------------	------	------	------	------	------	------	------	------	------	------	------

			Upper 95% limit on Mean	1.65	1.49	1.71	1.76	2.12	1.88	2.90	1.52	1.69	1.55	1.53
--	--	--	-------------------------	------	------	------	------	------	------	------	------	------	------	------

ppb	0.2-	.												
-----	------	---	--	--	--	--	--	--	--	--	--	--	--	--

0.5-	.	.												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

1.0-	.	.												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

2.0-	.	.												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

5.0-	.	.												
------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

10.0-	.	.												
-------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

20.0-	.	.												
-------	---	---	--	--	--	--	--	--	--	--	--	--	--	--

+	-	-	-	-	-	-	-	-	-	-	-	-	-	-
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

0	10	20	30	40	50	60	70	80	90	100	%			
---	----	----	----	----	----	----	----	----	----	-----	---	--	--	--

Percentage of Values														
----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

80th Xtile	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

90th Xtile	3.00	1.00	3.00	1.00	5.00	3.00	6.00	3.00	3.00	3.00	1.00	4.00	3.00	3.00
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

95th Xtile	5.00	3.00	4.00	3.00	6.00	4.00	6.00	4.00	4.00	4.00	1.00	6.00	3.00	4.00
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

98th Xtile	6.00	4.00	6.00	5.00	8.00	7.00	6.00	4.00	4.00	4.00	5.00	5.00	7.00	5.00
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

99th Xtile	7.00	4.00	7.00	5.00	9.00	7.00	6.00	4.00	4.00	4.00	5.00	5.00	8.00	9.00
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Max Value	18.00	4.00	7.00	5.00	10.00	7.00	6.00	4.00	4.00	4.00	5.00	5.00	8.00	9.00
-----------	-------	------	------	------	-------	------	------	------	------	------	------	------	------	------

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Hafnium [Hf]

Number of Values - 1178

Units - ppm

Detection Limit - 1

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN						
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276					
				Number of Values >= D.L.	750	24	44	13	86	23	37	83	8	57	21	54	53	173					
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
ppm 0.1- .				Mean	3.04	5.16	3.11	2.70	2.75	3.23	3.16	3.49	2.11	3.34	4.46	2.34	3.91	3.06					
				Standard Deviation	2.67	3.81	2.62	2.01	2.31	2.62	2.35	2.43	2.32	2.23	2.69	2.17	3.52	2.84					
				Skewness	1.36	0.62	0.79	0.46	1.19	0.99	0.75	0.49	1.37	0.69	0.25	1.15	1.10	1.52					
				Excess Kurtosis	2.09	-0.41	-0.49	-0.94	1.22	0.45	-0.25	-0.82	0.62	-0.30	-1.53	0.32	0.55	2.54					
				Coef. of Var. %	87.81	73.79	84.03	74.41	83.99	81.07	74.58	69.61	110.06	66.75	60.41	92.59	90.12	92.86					
				Std. Error of the Mean	0.08	0.68	0.31	0.45	0.20	0.46	0.32	0.23	0.55	0.26	0.56	0.21	0.39	0.17					
				N	297	25.2	25.2	Cum %	Lower 95% limit on Mean	2.89	3.76	2.49	1.76	2.36	2.30	2.51	3.04	0.96	2.82	3.29	1.92	3.13	2.72
				%					Upper 95% limit on Mean	3.19	6.56	3.74	3.64	3.14	4.16	3.80	3.95	3.27	3.86	5.62	2.76	4.68	3.40
				Geometric Statistics																			
				Mean	1.98	3.50	2.01	1.86	1.85	2.20	2.24	2.50	1.27	2.54	3.55	1.50	2.38	1.94					
0.5- .				Log10 Mean	0.30	0.54	0.30	0.27	0.27	0.34	0.35	0.40	0.11	0.40	0.55	0.18	0.38	0.29					
				Log10 S.D.	0.43	0.45	0.44	0.42	0.41	0.42	0.40	0.40	0.44	0.36	0.33	0.42	0.48	0.44					
				Log10 Std. Error of Mean	0.01	0.081	0.053	0.095	0.035	0.073	0.054	0.038	0.10	0.042	0.069	0.041	0.052	0.027					
				Lower 95% limit on Mean	1.87	2.39	1.58	1.18	1.58	1.56	1.74	2.11	0.77	2.10	2.56	1.25	1.87	1.72					
				Upper 95% limit on Mean	2.09	5.11	2.56	2.94	2.17	3.10	2.87	2.97	2.11	3.07	4.93	1.81	3.03	2.18					
				Percentiles																			
				Min Value	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50					
				25th Xtile	0.50	2.00	0.50	0.50	0.50	1.00	0.50	1.00	0.50	2.00	2.00	0.50	1.00	0.50					
				50th Xtile	2.00	4.00	2.00	3.00	2.00	3.00	3.00	3.00	1.00	3.00	4.00	2.00	3.00	2.00					
				75th Xtile	4.00	9.00	5.00	4.00	4.00	4.00	4.00	5.00	3.00	5.00	7.00	4.00	6.00	4.00					
				80th Xtile	5.00	9.00	6.00	4.00	5.00	5.00	4.00	6.00	3.00	6.00	8.00	4.00	6.00	5.00					
				90th Xtile	7.00	9.00	7.00	5.00	6.00	7.00	6.00	7.00	7.00	6.00	8.00	6.00	8.00	7.00					
				95th Xtile	8.00	12.00	8.00	6.00	7.00	8.00	6.00	8.00	8.00	7.00	8.00	7.00	12.00	8.00					
				98th Xtile	10.00	15.00	9.00	7.00	9.00	11.00	6.00	8.00	8.00	8.00	9.00	8.00	13.00	11.00					
				99th Xtile	12.00	15.00	10.00	7.00	11.00	11.00	6.00	8.00	8.00	10.00	9.00	8.00	14.00	14.00					
				Max Value	16.00	15.00	10.00	7.00	11.00	11.00	6.00	10.00	8.00	10.00	9.00	8.00	14.00	15.00					
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+																							
0 10 20 30 40 50 60 70 80 90 100 %																							
Percentage of Values																							

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Iron [Fe]

Number of Values - 1178

Units - pct

Detection Limit - 0.02

Analytical Method - AAS

			All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN	
			Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
			Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
			Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
pct 0.05- . 0.10- . 0.20- . 0.50- . 1.00- . 2.00- . 5.00- . 10.00- . 20.00- . 50.00- .	N % Cum % 17 1.4 1.7 150 12.7 14.4 357 30.3 44.7 428 36.3 81.1 131 11.1 92.2 72 6.1 98.3 20 1.7 100.0		Mean	3.77	7.13	3.67	7.84	3.33	4.16	3.96	3.18	1.88	3.00	4.58	3.75	4.44	3.58
			Standard Deviation	4.41	6.56	2.90	6.98	3.25	4.94	3.89	3.15	1.15	2.92	5.08	4.58	5.69	4.87
			Skewness	2.91	0.62	1.98	0.98	3.10	3.13	2.09	2.92	0.93	2.31	2.03	3.19	2.37	2.84
			Excess Kurtosis	9.95	-1.03	3.88	-0.42	12.87	11.14	3.94	10.28	0.20	5.41	3.21	12.17	5.50	8.17
			Coef. of Var. %	117.15	91.91	79.09	89.01	97.58	118.76	98.20	98.99	61.00	97.43	110.88	122.01	128.30	136.08
			Std. Error of the Mean	0.13	1.18	0.35	1.56	0.28	0.86	0.53	0.30	0.27	0.34	1.06	0.44	0.63	0.29
			Lower 95% limit on Mean	3.52	4.73	2.97	4.58	2.79	2.41	2.90	2.59	1.31	2.32	2.38	2.87	3.19	3.00
			Upper 95% limit on Mean	4.02	9.54	4.36	11.11	3.88	5.92	5.03	3.77	2.45	3.68	6.78	4.63	5.69	4.16
			3 0.3 0.3														
			Geometric Statistics														
			Mean	2.45	3.85	2.89	5.25	2.43	2.74	2.73	2.33	1.58	2.20	3.05	2.42	2.54	2.11
			Log10 Mean	0.39	0.59	0.46	0.72	0.39	0.44	0.44	0.37	0.20	0.34	0.48	0.38	0.40	0.32
			Log10 S.D.	0.39	0.56	0.29	0.42	0.34	0.40	0.39	0.33	0.27	0.32	0.38	0.39	0.44	0.41
			Log10 Std. Error of Mean	0.01	0.10	0.035	0.093	0.029	0.070	0.053	0.031	0.063	0.037	0.080	0.037	0.049	0.025
			Lower 95% limit on Mean	2.33	2.39	2.46	3.34	2.13	1.98	2.13	2.02	1.16	1.86	2.08	2.04	2.03	1.88
			Upper 95% limit on Mean	2.57	6.19	3.40	8.23	2.77	3.81	3.49	2.68	2.15	2.61	4.47	2.87	3.17	2.36
			Percentiles														
			Min Value	0.16	0.16	0.75	0.93	0.30	0.18	1.00	0.41	0.58	0.69	0.67	0.42	0.49	0.22
			25th Xtile	1.26	1.26	1.69	2.35	1.33	1.67	4.57	1.36	1.08	1.26	1.77	1.23	1.06	1.07
			50th Xtile	2.23	3.90	2.80	4.30	2.50	2.93	6.24	2.17	1.38	1.81	3.10	2.39	2.23	1.70
			75th Xtile	4.30	12.60	4.30	9.80	4.10	4.00	7.19	3.90	2.70	3.50	4.60	4.20	4.80	3.60
			80th Xtile	4.80	14.10	4.60	10.40	4.50	4.80	7.19	4.40	2.80	4.50	4.80	4.40	5.60	4.40
			90th Xtile	8.40	15.90	6.80	17.90	6.30	9.50	13.70	5.80	3.40	5.40	11.30	7.45	11.50	7.10
			95th Xtile	13.60	19.50	11.40	22.60	9.80	11.70	13.70	8.80	4.90	9.20	17.10	12.40	16.80	16.50
			98th Xtile	19.00	21.80	12.90	22.70	13.70	27.00	13.70	16.50	4.90	13.40	20.70	16.80	23.10	21.80
			99th Xtile	23.10	21.80	14.80	22.70	18.80	27.00	13.70	18.20	4.90	15.30	20.70	24.30	29.20	25.30
			Max Value	33.00	21.80	14.80	22.70	23.20	27.00	13.70	18.60	4.90	15.30	20.70	29.60	29.20	27.90

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Iron [Fe]

Number of Values - 1178

Units - pct

Detection Limit - 0.2

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1177	30	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	4.67	9.09	4.62	9.78	4.38	5.08	5.33	3.85	2.83	3.78	5.87	4.40	5.50	4.28
Standard Deviation	5.42	8.04	3.62	8.90	4.16	6.21	4.95	3.50	2.08	3.31	6.14	5.48	7.16	5.73
Skewness	3.06	0.50	2.78	1.06	2.84	3.74	1.99	2.95	1.49	2.36	1.97	3.25	2.44	3.00

Excess Kurtosis	11.53	-1.25	9.77	0.12	10.10	15.53	3.48	10.68	1.89	5.84	2.81	12.22	5.58	9.68
Coef. of Var. %	116.01	88.53	78.33	90.98	95.11	122.09	92.93	90.81	73.65	87.48	104.65	124.41	130.16	133.79

N	%	Cum %	Std. Error of the Mean	0.16	1.44	0.43	1.99	0.35	1.08	0.67	0.33	0.49	0.39	1.28	0.53	0.79	0.34
---	---	-------	------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Lower 95% limit on Mean	4.36	6.14	3.76	5.62	3.68	2.88	3.98	3.20	1.79	3.01	3.21	3.35	3.93	3.60
Upper 95% limit on Mean	4.98	12.04	5.48	13.94	5.08	7.29	6.68	4.51	3.86	4.56	8.52	5.46	7.07	4.96

1	0.1	0.1	Geometric Statistics											
---	-----	-----	----------------------	--	--	--	--	--	--	--	--	--	--	--

2	0.2	0.3	Mean	3.10	4.80	3.77	6.38	3.20	3.49	3.82	2.98	2.28	2.96	4.08	2.88	3.22	2.59
			Log10 Mean	0.49	0.68	0.58	0.80	0.51	0.54	0.58	0.47	0.36	0.47	0.61	0.46	0.51	0.41

15	1.3	1.5	Log10 S.D.	0.38	0.60	0.27	0.43	0.34	0.37	0.36	0.30	0.29	0.28	0.36	0.37	0.42	0.40
----	-----	-----	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			Log10 Std. Error of Mean	0.01	0.11	0.032	0.097	0.029	0.065	0.049	0.028	0.067	0.033	0.075	0.036	0.047	0.024
--	--	--	--------------------------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

77	6.5	8.1	Lower 95% limit on Mean	2.95	2.89	3.26	4.00	2.81	2.58	3.05	2.62	1.65	2.54	2.84	2.45	2.60	2.32
			Upper 95% limit on Mean	3.25	7.96	4.37	10.17	3.66	4.72	4.79	3.38	3.17	3.45	5.84	3.40	3.98	2.90

301	25.6	33.6	Percentiles													
-----	------	------	-------------	--	--	--	--	--	--	--	--	--	--	--	--	--

			Min Value	0.10	0.10	1.00	1.20	0.30	0.40	1.20	0.50	0.80	1.00	1.10	0.50	0.60	0.20
--	--	--	-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			25th Xtile	1.70	1.40	2.40	2.90	1.90	2.20	5.60	1.80	1.50	1.80	2.30	1.60	1.50	1.40
--	--	--	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			50th Xtile	2.90	7.80	3.80	6.60	3.30	3.90	8.30	2.80	1.60	2.50	4.40	2.50	2.70	2.30
--	--	--	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			75th Xtile	5.10	17.00	5.30	11.00	5.20	4.50	8.40	4.70	3.60	4.30	5.80	4.60	5.20	4.10
--	--	--	------------	------	-------	------	-------	------	------	------	------	------	------	------	------	------	------

			80th Xtile	5.90	18.00	5.60	18.00	6.00	5.90	8.40	5.20	4.60	5.70	6.20	5.00	6.10	5.40
--	--	--	------------	------	-------	------	-------	------	------	------	------	------	------	------	------	------	------

			90th Xtile	11.00	20.00	7.60	21.80	8.10	11.00	20.90	7.30	5.10	6.50	14.00	8.50	14.00	10.00
--	--	--	------------	-------	-------	------	-------	------	-------	-------	------	------	------	-------	------	-------	-------

			95th Xtile	17.00	23.00	13.00	23.20	13.00	12.00	20.90	10.00	9.10	12.00	23.00	17.00	23.30	19.00
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	------	-------	-------	-------	-------	-------

			98th Xtile	23.30	25.60	15.00	33.20	20.10	35.90	20.90	15.00	9.10	16.00	23.50	22.20	29.00	25.20
			99th Xtile	28.50	25.60	23.40	33.20	24.70	35.90	20.90	20.00	9.10	18.00	23.50	27.30	35.80	28.80
			Max Value	46.30	25.60	23.40	33.20	26.80	35.90	20.90	22.70	9.10	18.00	23.50	35.60	35.80	37.70

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Lanthanum [La]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - IIA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN							
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276						
				Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276						
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0						
ppm 2- . 5- . 10- . 20- . 50- . 100- . 200- . 500- . 1000- .				Mean	66.64	19.61	82.10	144.50	85.17	90.64	90.52	78.02	75.33	62.88	62.96	61.60	39.88	44.08						
				Standard Deviation	51.31	8.33	31.56	102.73	45.52	64.79	37.04	70.18	42.51	23.86	18.20	33.85	20.70	39.61						
				Skewness	3.47	0.41	0.84	0.45	1.47	1.67	1.13	6.39	2.36	1.23	0.053	1.11	1.34	3.44						
				Excess Kurtosis	25.43	-0.75	0.11	-1.38	3.24	2.22	2.42	52.00	5.92	3.73	-0.86	1.77	2.08	16.30						
				Coef. of Var. %	76.99	42.45	38.44	71.09	53.45	71.49	40.92	89.96	56.43	37.95	28.90	54.95	51.91	89.86						
				N	1.49	1.50	3.77	22.97	3.86	11.28	5.04	6.63	10.02	2.79	3.79	3.29	2.29	2.38						
				%																				
				Cum %																				
				Std. Error of the Mean																				
				Lower 95% limit on Mean	63.71	16.56	74.57	96.42	77.53	67.65	80.41	64.88	54.19	57.31	55.09	55.08	35.33	39.38						
				Upper 95% limit on Mean	69.57	22.67	89.63	192.58	92.80	113.62	100.63	91.16	96.47	68.44	70.83	68.12	44.43	48.77						
				22	1.9	1.9																		
				Geometric Statistics																				
				Mean	53.05	17.84	76.59	108.93	74.70	74.43	83.50	65.64	67.97	58.71	60.27	52.87	35.26	34.30						
				Log10 Mean	1.72	1.25	1.88	2.04	1.87	1.87	1.92	1.82	1.83	1.77	1.78	1.72	1.55	1.54						
				Log10 S.D.	0.30	0.20	0.16	0.35	0.23	0.27	0.18	0.24	0.19	0.16	0.13	0.25	0.22	0.30						
				430	36.5	44.5	Log10 Std. Error of Mean	0.01	0.036	0.019	0.078	0.019	0.047	0.024	0.023	0.045	0.019	0.028	0.024	0.024	0.018			
				Lower 95% limit on Mean	51.01	15.09	70.03	74.75	68.46	59.72	74.57	59.23	54.64	53.75	52.69	47.31	31.56	31.64						
				Upper 95% limit on Mean	55.17	21.10	83.76	158.73	81.51	92.77	93.50	72.74	84.56	64.13	68.93	59.10	39.40	37.19						
				□	130	11.0	97.6																	
				Percentiles																				
				Min Value	6.00	6.00	28.00	33.00	19.00	25.00	32.00	9.00	29.00	19.00	31.00	7.00	8.00	7.00						
				25th Xtile	33.00	12.00	58.00	51.00	53.00	52.00	58.00	47.00	51.00	47.00	50.00	35.00	26.00	23.00						
				50th Xtile	54.00	19.00	75.00	93.00	75.00	73.00	58.00	67.00	64.00	59.00	63.00	56.00	36.00	34.00						
				75th Xtile	81.00	26.00	100.00	213.00	110.00	100.00	73.00	86.00	81.00	80.00	77.00	82.00	45.00	49.00						
				80th Xtile	90.00	26.00	110.00	218.00	120.00	110.00	73.00	93.00	84.00	82.00	77.00	88.00	55.00	56.00						
				90th Xtile	120.00	31.00	130.00	301.00	140.00	180.00	120.00	110.00	110.00	86.00	82.00	98.00	72.00	85.00						
				95th Xtile	150.00	36.00	140.00	308.00	170.00	251.00	120.00	150.00	226.00	100.00	97.00	130.00	81.00	100.00						
				Max Value	698.00	38.00	180.00	331.00	278.00	297.00	120.00	698.00	226.00	170.00	97.00	200.00	120.00	329.00						
				Percentage of Values																				
				0	10	20	30	40	50	60	70	80	90	100	%									

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Lead [Pb]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	89	0	6	0	17	1	14	14	0	6	9	6	2	6
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	1.39	-	1.37	-	1.49	1.09	1.96	1.47	-	1.29	2.09	1.80	1.50	1.12
Standard Deviation	2.16	-	0.76	-	1.02	0.52	1.68	0.90	-	0.75	1.12	5.94	3.43	0.45
Skewness	21.57	-	2.16	-	2.61	5.23	2.51	1.95	-	2.93	0.39	9.80	8.58	4.89
Excess Kurtosis	563.40	-	3.98	-	7.70	26.18	7.87	3.02	-	8.87	-1.42	96.19	73.32	29.22
Coef. of Var. %	154.99	-	55.76	-	68.29	47.87	85.68	61.09	-	58.57	53.89	329.92	228.61	39.97

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean
0.06	-	0.091	-	0.086	0.091
0.06	-	1.19	-	1.32	0.91
0.06	-	1.55	-	1.66	1.28
0.06	-	-	-	2.42	1.64
0.06	-	-	-	-	1.46
0.06	-	-	-	-	2.57
0.06	-	-	-	-	2.95
0.06	-	-	-	-	2.25
0.06	-	-	-	-	1.17
0.06	-	-	-	-	1.60
0.06	-	-	-	-	0.66
0.06	-	-	-	-	0.75
0.06	-	-	-	-	1.07

ppm	0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
-----	------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

0.2-	.	0.5-	.	1.0-	.	2.0-	.	5.0-	.	10.0-	.	20.0-	.	50.0-	.	100.0-
------	---	------	---	------	---	------	---	------	---	-------	---	-------	---	-------	---	--------

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Loss-On-Ignition [LOI]

Number of Values - 1178

Units - pct

Detection Limit - 1.0

Analytical Method - GRA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	35.74	38.32	36.18	36.66	35.78	35.89	36.35	34.75	38.90	31.81	26.33	34.97	31.21	36.79
Standard Deviation	14.83	13.77	14.89	14.07	15.69	17.43	17.15	16.94	15.46	18.16	14.31	13.47	14.55	13.29

Skewness	-0.11	-0.22	-0.36	-0.012	-0.35	-0.20	-0.15	0.21	-0.52	0.65	0.18	0.037	-0.18	-0.12
Excess Kurtosis	-0.18	0.26	-0.61	0.18	-0.68	-0.26	-1.02	-0.88	-1.11	0.72	-1.29	0.47	-0.87	0.066

Coef. of Var. %	41.49	35.93	41.15	38.39	43.86	48.58	47.18	48.76	39.73	57.09	54.34	38.53	46.62	36.12
Std. Error of the Mean	0.43	2.47	1.78	3.15	1.33	3.04	2.33	1.60	3.64	2.13	2.98	1.31	1.61	0.80

N	%	Cum %	Lower 95% Limit on Mean	34.90	33.27	32.63	30.07	33.15	29.71	31.67	31.58	31.21	27.58	20.14	32.38	28.01	35.21
			Upper 95% limit on Mean	36.59	43.37	39.73	43.25	38.41	42.08	41.03	37.92	46.59	36.05	32.52	37.57	34.41	38.36

Geometric Statistics

2	0.2	0.2	Mean	31.43	34.27	31.90	33.00	30.65	28.81	30.82	29.93	34.87	25.55	22.06	31.32	26.44	33.62
			Log10 Mean	1.50	1.53	1.50	1.52	1.49	1.46	1.49	1.48	1.54	1.41	1.34	1.50	1.42	1.53

19	1.6	1.8	Log10 S.D.	0.25	0.26	0.25	0.24	0.28	0.36	0.29	0.26	0.23	0.33	0.28	0.24	0.29	0.21
			Log10 Std. Error of Mean	0.01	0.047	0.030	0.053	0.024	0.063	0.039	0.024	0.055	0.039	0.059	0.023	0.032	0.013

52	4.4	6.2	Lower 95% limit on Mean	30.40	27.41	27.84	25.53	27.49	21.46	25.71	26.77	26.73	21.36	16.65	28.14	22.83	31.76
			Upper 95% limit on Mean	32.50	42.84	36.56	42.66	34.18	38.66	36.94	33.46	45.50	30.56	29.21	34.86	30.61	35.58

127	10.8	17.0	Percentiles														
			Min Value	1.20	2.20	5.20	5.20	3.00	3.20	17.40	4.80	9.80	1.20	7.00	2.00	2.80	3.20

			25th Xtile	27.00	31.40	28.20	32.20	25.20	29.20	22.00	21.60	25.20	17.40	13.00	28.60	19.40	29.20
			50th Xtile	36.60	36.60	38.80	35.20	38.00	38.60	29.20	33.80	39.80	32.40	27.40	35.40	32.40	37.80

			75th Xtile	45.40	47.60	46.60	40.80	46.40	45.20	35.40	47.20	50.80	41.60	36.40	42.20	40.80	45.80
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			80th Xtile	47.80	47.60	48.00	41.20	49.80	48.60	35.40	49.80	52.40	44.00	40.20	45.40	42.80	47.40
			90th Xtile	53.80	54.00	53.40	52.80	53.80	54.40	36.40	58.20	57.20	53.80	49.00	51.80	51.60	52.60

			95th Xtile	59.20	65.00	57.80	63.00	60.00	65.60	36.40	64.40	59.00	64.20	49.60	56.40	53.40	58.80
--	--	--	------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			98th Xtile	64.60	66.40	60.40	65.00	63.40	74.20	36.40	65.60	59.00	67.60	51.20	63.60	54.60	64.60
			99th Xtile	66.40	66.40	68.40	65.00	64.60	74.20	36.40	66.40	59.00	96.40	51.20	70.40	59.60	68.40

			Max Value	96.40	66.40	68.40	65.00	70.60	74.20	36.40	77.00	59.00	96.40	51.20	73.80	59.60	79.40
--	--	--	-----------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

* Summary statistics not calculated for rock units with less than ten values.

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

Statistics per Variable

Variable - Lutetium [Lu]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1131	25	70	20	137	32	54	109	18	72	23	103	79	251
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.62	0.32	0.64	1.03	0.68	0.72	0.80	0.56	0.48	0.50	0.54	0.72	0.57	0.54
Standard Deviation	0.45	0.15	0.24	0.71	0.34	0.53	0.37	0.39	0.20	0.20	0.13	0.65	0.45	0.36

Skewness	3.74	-0.20	1.89	0.72	1.95	2.81	1.25	4.15	1.38	0.99	-0.60	4.45	2.60	2.05
Excess Kurtosis	23.79	-1.18	6.39	-0.86	7.39	9.73	1.19	22.65	2.58	2.23	0.84	25.10	7.54	6.72

Coef. of Var. %	71.93	45.78	37.02	69.09	49.71	73.88	46.19	69.43	42.20	38.98	23.55	91.21	78.70	67.45
N	%	Cum %	Std. Error of the Mean											

Lower 95% limit on Mean	0.60	0.27	0.58	0.70	0.62	0.53	0.70	0.49	0.38	0.46	0.48	0.59	0.47	0.50
Upper 95% limit on Mean	0.65	0.38	0.70	1.36	0.74	0.91	0.90	0.63	0.58	0.55	0.59	0.84	0.66	0.58

ppm	0.02-	0.05-	0.10-	0.20-	0.50-	1.00-	2.00-	5.00-	10.00-					
-----	-------	-------	-------	-------	-------	-------	-------	-------	--------	--	--	--	--	--

	47	4.0	4.0	Geometric Statistics										
				Mean	0.52	0.28	0.61	0.81	0.61	0.60	0.73	0.49	0.44	0.46

				Log10 Mean	-0.28	-0.55	-0.22	-0.090	-0.22	-0.22	-0.14	-0.31	-0.35	-0.33
				Log10 S.D.	0.26	0.26	0.14	0.31	0.21	0.26	0.18	0.22	0.18	0.18

				543	46.1	54.0	Log10 Std. Error of Mean							

					543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

						543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

							543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

								543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

									543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

										543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

											543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

												543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

													543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

														543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

															543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

																543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

																	543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

																		543	46.1	54.0	Log10 Std. Error of Mean	0.01	0.046	0.017	0.070	0.018	0.045

* Summary statistics not calculated for rock units with less than ten values.

National Geochemical Reconnaissance Lake Sediment and Water Geochemical Data. Saskatchewan 1988, GSC OF-1643, NGR-108-1988, NTS 64E, 74A, 74H

Statistics per Variable

Variable - Mercury [Hg]

Number of Values - 1178

Units - ppb

Detection Limit - 10

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN			
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276		
				Number of Values >= D.L.	1170	31	70	20	138	32	54	111	18	72	23	106	81	273		
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
ppb 1- . 2- . . . 5- . 10- . . . 20- . . . 50- . . . 100- . 200- . 500- . 1000- . 2000- .	N 1 . 2 . 5 . 10- . 46 . 20- . 409 . 635 . 75 . 4 . 80th Xtile 90th Xtile 95th Xtile 98th Xtile 99th Xtile Max Value	%	Cum %	Mean	61.65	86.74	68.67	64.45	62.92	57.70	65.61	66.09	80.11	62.59	67.22	65.89	48.35	52.92		
				Standard Deviation	44.25	205.59	35.50	22.78	28.06	23.38	30.95	33.69	35.91	24.47	30.28	45.56	22.68	22.90		
				Skewness	14.87	4.98	1.50	-0.26	0.83	-0.24	2.61	1.57	2.00	-0.015	0.19	5.14	0.39	1.25		
				Excess Kurtosis	361.14	23.75	3.75	-0.37	1.64	-0.99	11.32	5.28	4.12	-0.41	-1.15	36.48	-0.20	3.81		
				Coef. of Var. %	71.78	237.02	51.69	35.34	44.60	40.52	47.17	50.97	44.83	39.09	45.05	69.15	46.91	43.27		
				Std. Error of the Mean	1.29	36.93	4.24	5.09	2.38	4.07	4.21	3.18	8.46	2.86	6.31	4.43	2.50	1.38		
				Lower 95% limit on Mean	59.12	11.34	60.21	53.79	58.21	49.40	57.16	59.78	62.25	56.88	54.12	57.11	43.37	50.21		
				Upper 95% limit on Mean	64.17	162.14	77.14	75.11	67.63	65.99	74.06	72.40	97.97	68.30	80.31	74.66	53.34	55.63		
				2 0.2 0.2																
				Geometric Statistics																
. . 10- . . . 20- . . . 50- . . . 100- . 200- . 500- . 1000- . 2000- .	6 0.5 0.7 46 3.9 4.6 409 34.7 39.3 635 53.9 93.2 75 6.4 99.6 4 0.3 99.9 80th Xtile 90th Xtile 95th Xtile 98th Xtile 99th Xtile Max Value	%	Cum %	Mean	54.52	51.22	60.66	59.27	56.40	51.68	60.24	58.33	74.72	56.36	60.15	58.07	42.42	48.09		
				Log10 Mean	1.74	1.71	1.78	1.77	1.75	1.71	1.78	1.77	1.87	1.75	1.78	1.76	1.63	1.68		
				Log10 S.D.	0.22	0.31	0.22	0.21	0.22	0.23	0.18	0.23	0.16	0.23	0.22	0.21	0.24	0.20		
				Log10 Std. Error of Mean	0.01	0.056	0.027	0.046	0.018	0.040	0.024	0.021	0.037	0.027	0.045	0.020	0.026	0.012		
				Lower 95% limit on Mean	53.00	39.32	53.67	47.51	51.88	42.86	53.87	52.92	62.45	49.86	48.43	53.02	37.57	45.54		
				Upper 95% limit on Mean	56.09	66.72	68.56	73.95	61.31	62.32	67.36	64.29	89.41	63.70	74.70	63.61	47.89	50.79		
				Percentiles																
				Min Value	5.00	13.00	14.00	13.00	10.00	10.00	36.00	10.00	45.00	5.00	26.00	14.00	10.00	5.00		
				25th Xtile	41.00	35.00	48.00	50.00	42.00	41.00	62.00	41.00	55.00	50.00	37.00	46.00	30.00	40.00		
				50th Xtile	58.00	49.00	63.00	65.00	61.00	60.00	69.00	60.00	70.00	60.00	66.00	58.00	50.00	50.00		
				75th Xtile	73.00	65.00	80.00	76.00	76.00	75.00	76.00	84.00	86.00	80.00	87.00	73.00	61.00	63.00		
				80th Xtile	79.00	73.00	87.00	84.00	80.00	80.00	76.00	88.00	102.00	84.00	99.00	80.00	64.00	67.00		
				90th Xtile	94.00	76.00	103.00	86.00	100.00	86.00	97.00	103.00	117.00	94.00	103.00	95.00	76.00	80.00		
				95th Xtile	108.00	90.00	140.00	100.00	113.00	93.00	97.00	126.00	200.00	103.00	108.00	128.00	88.00	93.00		
				98th Xtile	131.00	1190.00	156.00	106.00	127.00	97.00	97.00	147.00	200.00	112.00	131.00	169.00	104.00	115.00		
				99th Xtile	156.00	1190.00	222.00	106.00	160.00	97.00	97.00	160.00	200.00	116.00	131.00	188.00	110.00	120.00		
				Max Value	1190.00	1190.00	222.00	106.00	176.00	97.00	97.00	241.00	200.00	116.00	131.00	430.00	110.00	182.00		
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+																				
0 10 20 30 40 50 60 70 80 90 100 %																				
Percentage of Values																				

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Manganese [Mn]

Number of Values - 1178

Units - ppm

Detection Limit - 5

Analytical Method - AAS

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	720.36	321.29	1127.50	1577.00	936.83	636.36	823.98	710.00	596.39	839.59	873.48	697.69	849.76	517.52
Standard Deviation	2536.45	269.25	4013.55	2445.08	5487.36	1071.24	1800.52	1004.02	547.15	1407.50	612.92	1540.82	1734.15	1988.15

Skewness	17.66	0.83	7.12	1.93	11.39	3.79	5.81	4.72	2.47	5.03	1.09	5.60	5.31	15.14			
N	%	Cum %	Excess Kurtosis	389.69	-0.43	52.59	2.78	129.82	14.74	35.90	27.23	6.11	30.63	0.83	37.62	33.24	239.74
Coef. of Var. %	352.11	83.80	355.97	155.05	585.73	168.34	218.52	141.41	91.74	167.64	70.17	220.85	204.08	384.17			

Std. Error of the Mean	73.90	48.36	479.71	546.74	465.43	186.48	245.02	94.87	128.96	164.74	127.80	149.66	191.50	119.67
Lower 95% limit on Mean	575.37	222.54	170.38	432.68	16.47	256.36	332.57	521.98	324.27	511.17	608.42	400.92	468.65	281.88
Upper 95% limit on Mean	865.35	420.04	2084.62	2721.32	1857.20	1016.37	1315.39	898.02	868.50	1168.01	1138.54	994.46	1230.87	753.15

1	0.1	0.1	Upper 95% limit on Mean	865.35	420.04	2084.62	2721.32	1857.20	1016.37	1315.39	898.02	868.50	1168.01	1138.54	994.46	1230.87	753.15
---	-----	-----	-------------------------	--------	--------	---------	---------	---------	---------	---------	--------	--------	---------	---------	--------	---------	--------

14	1.2	1.3	Geometric Statistics	Mean	371.89	209.24	474.80	690.92	357.71	359.67	433.77	475.12	469.85	496.30	680.55	350.41	405.97	290.62
----	-----	-----	----------------------	------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

43	3.7	4.9	Log10 Mean	2.57	2.32	2.68	2.84	2.55	2.56	2.64	2.68	2.67	2.70	2.83	2.54	2.61	2.46
Log10 S.D.	0.40	0.45	0.38	0.53	0.37	0.43	0.44	0.34	0.28	0.39	0.33	0.41	0.47	0.36			

204	17.3	22.2	Log10 Std. Error of Mean	0.01	0.082	0.046	0.12	0.032	0.074	0.060	0.032	0.066	0.046	0.069	0.039	0.052	0.022
-----	------	------	--------------------------	------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Lower 95% limit on Mean	352.89	142.57	384.87	391.90	309.53	253.57	329.37	410.16	340.39	402.71	489.56	292.77	319.77	263.38
-------------------------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

Upper 95% limit on Mean	558	47.4	69.6	391.92	307.09	585.74	1218.10	413.39	510.15	571.27	550.38	648.55	611.65	946.04	419.39	515.40	320.67
-------------------------	-----	------	------	--------	--------	--------	---------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

222	18.8	88.5	Percentiles	Min Value	20.00	20.00	120.00	170.00	50.00	50.00	120.00	120.00	190.00	100.00	140.00	80.00	40.00	40.00
-----	------	------	-------------	-----------	-------	-------	--------	--------	-------	-------	--------	--------	--------	--------	--------	-------	-------	-------

79	6.7	95.2	25th Xtile	210.00	100.00	260.00	260.00	210.00	220.00	380.00	270.00	300.00	280.00	380.00	200.00	220.00	170.00
----	-----	------	------------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

40	3.4	98.6	50th Xtile	330.00	200.00	390.00	400.00	320.00	380.00	680.00	440.00	380.00	440.00	820.00	280.00	320.00	280.00
----	-----	------	------------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

10	0.8	99.4	75th Xtile	580.00	570.00	710.00	1070.00	480.00	540.00	950.00	620.00	740.00	700.00	1240.00	450.00	710.00	470.00
----	-----	------	------------	--------	--------	--------	---------	--------	--------	--------	--------	--------	--------	---------	--------	--------	--------

4	0.3	99.7	80th Xtile	670.00	600.00	780.00	1520.00	560.00	590.00	950.00	730.00	820.00	940.00	1240.00	560.00	980.00	530.00
---	-----	------	------------	--------	--------	--------	---------	--------	--------	--------	--------	--------	--------	---------	--------	--------	--------

2	0.2	99.9	90th Xtile	1110.00	680.00	940.00	5000.00	1050.00	1100.00	13000	1200.00	1020.00	1850.00	1700.00	1130.00	1660.00	780.00
---	-----	------	------------	---------	--------	--------	---------	---------	---------	-------	---------	---------	---------	---------	---------	---------	--------

1	0.1	100.0	95th Xtile	1950.00	830.00	1150.00	5750.00	1750.00	3000.00	13000	2350.00	2550.00	3150.00	1800.00	3500.00	2350.00	1110.00
---	-----	-------	------------	---------	--------	---------	---------	---------	---------	-------	---------	---------	---------	---------	---------	---------	---------

Max Value	65000	1020.00	32800	9350.00	64900	5850.00	13000	8000.00	2550.00	10700	2650.00	13000	13500	32500			
-----------	-------	---------	-------	---------	-------	---------	-------	---------	---------	-------	---------	-------	-------	-------	--	--	--

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

* Summary statistics not calculated for
rock units with less than ten values.

Statistics per Variable

Variable - Molybdenum [Mo]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN		
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276	
				Number of Values >= D.L.	304	3	26	10	59	10	19	13	4	19	3	45	19	34	
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
ppm 0.2- . 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- .	N 435 439 156 110 32 6	%	Cum %	Mean	2.87	1.81	3.31	5.60	4.14	2.94	3.48	1.98	2.22	2.38	2.22	4.13	2.61	1.95	
				Standard Deviation	3.33	1.40	2.57	6.93	4.75	2.84	3.36	2.02	1.06	1.65	2.04	4.92	2.88	1.85	
				Skewness	3.94	2.94	2.29	1.96	3.32	2.07	1.41	4.48	0.70	1.35	2.62	3.02	3.30	4.67	
				Excess Kurtosis	21.50	9.79	7.03	3.14	14.48	3.72	0.93	24.30	-0.85	1.10	6.72	9.94	14.65	27.85	
				Coef. of Var. %	115.91	77.53	77.49	123.77	114.88	96.58	96.44	101.80	47.71	69.09	92.18	119.17	110.33	94.59	
				Std. Error of the Mean	0.10	0.25	0.31	1.55	0.40	0.49	0.46	0.19	0.25	0.19	0.43	0.48	0.32	0.11	
				N	2.68	1.29	2.70	2.36	3.34	1.93	2.57	1.60	1.69	2.00	1.33	3.18	1.98	1.73	
				%	Upper 95% limit on Mean	3.06	2.32	3.93	8.84	4.93	3.95	4.40	2.36	2.75	2.77	3.10	5.08	3.24	2.17
				Cum %	Lower 95% limit on Mean	2.68	1.29	2.70	2.36	3.34	1.93	2.57	1.60	1.69	2.00	1.33	3.18	1.98	1.73
				Geometric Statistics															
				Mean	2.05	1.53	2.68	3.34	2.80	2.16	2.36	1.59	2.00	1.95	1.77	2.76	1.87	1.60	
				Log10 Mean	0.31	0.18	0.43	0.52	0.45	0.34	0.37	0.20	0.30	0.29	0.25	0.44	0.27	0.20	
				Log10 S.D.	0.32	0.23	0.27	0.43	0.36	0.32	0.37	0.25	0.21	0.27	0.27	0.36	0.32	0.24	
				Log10 Std. Error of Mean	0.01	0.041	0.033	0.096	0.031	0.056	0.051	0.024	0.049	0.031	0.055	0.035	0.035	0.015	
				Lower 95% limit on Mean	1.96	1.26	2.30	2.10	2.43	1.66	1.87	1.43	1.58	1.69	1.36	2.35	1.59	1.49	
				Upper 95% limit on Mean	2.13	1.86	3.11	5.30	3.22	2.81	2.99	1.77	2.53	2.26	2.30	3.24	2.20	1.70	
				Percentiles															
				Min Value	1.00	1.00	1.00	1.00	1.00	1.00	2.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	
				25th Xtile	1.00	1.00	2.00	2.00	1.00	4.00	1.00	2.00	1.00	2.00	1.00	2.00	1.00	1.00	
				50th Xtile	2.00	1.00	2.00	2.00	2.00	6.00	1.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	
				75th Xtile	4.00	2.00	4.00	4.00	4.00	8.00	2.00	2.00	4.00	2.00	4.00	2.00	4.00	2.00	
				80th Xtile	4.00	2.00	4.00	8.00	6.00	4.00	8.00	2.00	4.00	4.00	2.00	6.00	4.00	2.00	
				90th Xtile	6.00	2.00	6.00	14.00	10.00	6.00	14.00	4.00	4.00	4.00	4.00	8.00	6.00	4.00	
				95th Xtile	8.00	4.00	8.00	18.00	12.00	12.00	14.00	4.00	4.00	6.00	6.00	12.00	8.00	4.00	
				98th Xtile	14.00	8.00	10.00	28.00	18.00	12.00	14.00	8.00	4.00	6.00	10.00	24.00	10.00	8.00	
				99th Xtile	18.00	8.00	16.00	28.00	28.00	12.00	14.00	12.00	4.00	8.00	10.00	26.00	20.00	12.00	
				Max Value	34.00	8.00	16.00	28.00	34.00	12.00	14.00	16.00	4.00	8.00	10.00	28.00	20.00	16.00	
				Percentage of Values	0	10	20	30	40	50	60	70	80	90	100				

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Molybdenum [Mo]

Number of Values - 1178

Units - ppm

Detection Limit - 1

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN					
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276				
				Number of Values >= D.L.	1072	27	65	19	134	30	53	97	16	61	20	105	72	245				
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0				
ppm 0.1- . 0.2- . 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- .	N 41 65 301 559 158 46 8	%	Cum %	Mean	4.02	2.69	4.54	6.43	5.31	4.52	5.12	2.89	2.33	3.08	2.98	5.55	3.96	2.99				
					3.33	1.75	2.77	6.30	4.42	3.00	3.64	1.82	0.77	1.70	2.11	4.68	3.17	1.89				
					3.11	1.85	1.12	1.75	2.49	1.53	1.30	2.48	0.16	0.67	1.79	2.88	2.53	2.79				
					14.34	4.02	1.28	2.44	8.65	2.40	0.88	8.89	-0.54	0.057	3.12	9.11	9.06	12.17				
					82.81	64.96	61.06	98.09	83.25	66.47	67.14	62.92	32.87	55.38	70.95	84.45	80.19	63.35				
					N	%	Cum %	Std. Error of the Mean	0.10	0.31	0.33	1.41	0.37	0.52	0.47	0.17	0.18	0.20	0.44	0.46	0.35	0.11
								Lower 95% limit on Mean	3.83	2.05	3.88	3.48	4.56	3.45	4.18	2.55	1.95	2.68	2.06	4.64	3.26	2.76
								Upper 95% limit on Mean	4.21	3.34	5.20	9.37	6.05	5.58	6.06	3.23	2.71	3.47	3.89	6.45	4.65	3.21
Geometric Statistics																						
Mean																						
Log10 Mean																						
Log10 S.D.																						
Log10 Std. Error of Mean																						
Lower 95% limit on Mean																						
Upper 95% limit on Mean																						
Percentiles																						
Min Value																						
25th Xtile																						
50th Xtile																						
75th Xtile																						
80th Xtile																						
90th Xtile																						
95th Xtile																						
98th Xtile																						
99th Xtile																						
Max Value																						
0 10 20 30 40 50 60 70 80 90 100 %																						
Percentage of Values																						
98th Xtile																						
99th Xtile																						
Max Value																						

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Nickel [Ni]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN		
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276	
				Number of Values >= D.L.	1159	31	69	20	137	32	50	112	18	73	23	104	80	271	
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
ppm 0.2-. 0.5-. 1.0-. 2.0-. 5.0-. 10.0-. 20.0-. 50.0-. 100.0-. 200.0-. +-----+-----+-----+-----+-----+-----+	N 0.2-. 0.5-. 1.0-. 2.0-. 5.0-. 10.0-. 20.0-. 50.0-. 100.0-. 200.0-. +-----+-----+-----+-----+-----+-----+	%	Cum %	Mean	10.98	8.58	12.24	10.85	10.58	9.55	10.04	12.79	12.78	12.62	14.39	9.25	9.24	10.81	
				Standard Deviation	6.29	3.79	6.06	3.94	4.64	4.66	4.79	10.14	3.98	4.12	4.89	3.49	5.69	7.62	
				Skewness	7.24	1.09	1.71	0.023	0.26	1.41	0.21	8.12	0.45	0.78	0.24	0.52	4.23	8.26	
				Excess Kurtosis	106.00	0.70	5.61	-0.84	-0.43	3.67	-0.070	75.66	0.22	1.41	-0.71	0.99	26.71	101.92	
				Coef. of Var. %	57.29	44.20	49.47	36.29	43.81	48.79	47.76	79.25	31.14	32.64	33.96	37.76	61.54	70.52	
				Std. Error of the Mean	0.18	0.68	0.72	0.88	0.39	0.81	0.65	0.96	0.94	0.48	1.02	0.34	0.63	0.46	
				Lower 95% limit on Mean	10.63	7.19	10.80	9.01	9.81	7.89	8.73	10.90	10.80	11.66	12.28	8.57	7.99	9.90	
				Upper 95% limit on Mean	11.34	9.97	13.69	12.69	11.36	11.20	11.35	14.69	14.76	13.58	16.50	9.92	10.49	11.71	
				9 0.8 0.8															
				Geometric Statistics															
.0 .1 .2 .5 .10 .20 .50 .100 .200 +-----+-----+-----+-----+-----+-----+	10 0.8 1.6 115 9.8 11.4 467 39.6 51.0 537 45.6 96.6 38 3.2 99.8 2 0.2 100.0 0 10 20 30 40 50 60 70 80 90 100 %	%	Cum %	Mean	9.78	7.87	10.92	10.05	9.40	8.51	8.52	11.53	12.16	11.95	13.54	8.49	8.09	9.48	
				Log10 Mean	0.99	0.90	1.04	1.00	0.97	0.93	0.93	1.06	1.09	1.08	1.13	0.93	0.91	0.98	
				Log10 S.D.	0.22	0.18	0.22	0.19	0.23	0.22	0.29	0.17	0.15	0.15	0.16	0.20	0.23	0.22	
				Log10 Std. Error of Mean	0.01	0.033	0.026	0.042	0.020	0.038	0.039	0.016	0.034	0.017	0.034	0.019	0.026	0.013	
				Lower 95% limit on Mean	9.50	6.75	9.69	8.22	8.59	7.11	7.10	10.71	10.30	11.04	11.54	7.78	7.19	8.92	
				Upper 95% limit on Mean	10.06	9.18	12.30	12.30	10.28	10.19	10.23	12.41	14.37	12.94	15.90	9.27	9.11	10.08	
				Percentiles															
				Min Value	1.00	3.00	2.00	3.00	1.00	2.00	5.00	5.00	5.00	4.00	5.00	1.00	1.00	1.00	
				25th Xtile	8.00	6.00	9.00	8.00	7.00	6.00	7.00	9.00	10.00	10.00	11.00	7.00	6.00	7.00	
				50th Xtile	10.00	7.00	11.00	11.00	10.00	9.00	9.00	11.00	13.00	13.00	12.00	15.00	9.00	9.00	10.00
				75th Xtile	13.00	11.00	15.00	14.00	14.00	12.00	11.00	14.00	14.00	14.00	18.00	11.00	11.00	12.00	
				80th Xtile	14.00	11.00	16.00	14.00	15.00	13.00	11.00	15.00	15.00	15.00	20.00	12.00	11.00	13.00	
				90th Xtile	17.00	13.00	18.00	16.00	17.00	15.00	11.00	17.00	20.00	18.00	21.00	13.00	13.00	16.00	
				95th Xtile	19.00	18.00	22.00	17.00	18.00	15.00	11.00	19.00	22.00	19.00	21.00	15.00	15.00	19.00	
				98th Xtile	23.00	19.00	26.00	18.00	21.00	27.00	11.00	23.00	22.00	25.00	25.00	18.00	21.00	24.00	
				99th Xtile	26.00	19.00	41.00	18.00	21.00	27.00	11.00	28.00	22.00	26.00	25.00	19.00	49.00	32.00	
				Max Value	111.00	19.00	41.00	18.00	24.00	27.00	11.00	111.00	22.00	26.00	25.00	21.00	49.00	110.00	

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Nickel [Ni]

Number of Values - 1178

Units - ppm

Detection Limit - 20

Analytical Method - INA

				ALL UNITS*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN	
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Values >= D.L.	140	2	10	4	21	3	10	17	6	11	4	10	5	22
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ppm 2- . 5- . 10- . 20- . 50- . 100- .	N 1011 27 139 1 0 10 20 30 40 50 60 70 80 90 100 %	%	Cum %	Mean	12.11	11.39	13.23	13.40	12.46	11.39	13.69	12.80	15.06	12.03	12.57	11.88	10.93	11.43
				Standard Deviation	5.53	5.63	7.63	6.29	5.69	3.85	7.42	6.47	7.70	4.90	5.85	4.78	3.92	4.64
				Skewness	2.72	3.86	2.86	1.35	2.15	2.31	1.71	2.21	0.94	1.99	1.77	2.27	4.55	3.45
				Excess Kurtosis	7.44	14.27	9.30	0.29	3.57	3.62	1.48	4.00	-0.72	2.15	1.46	3.67	21.81	12.08
				Coef. of Var. %	45.69	49.40	57.64	46.97	45.66	33.77	54.23	50.50	51.12	40.71	46.52	40.28	35.92	40.62
				Std. Error of the Mean	0.16	1.01	0.91	1.61	0.48	0.67	1.01	0.61	1.81	0.57	1.22	0.46	0.43	0.28
				Lower 95% limit on Mean	11.79	9.32	11.41	10.45	11.51	10.03	11.66	11.59	11.23	10.88	10.04	10.96	10.06	10.88
				Upper 95% limit on Mean	12.42	13.45	15.05	16.35	13.41	12.76	15.71	14.01	18.88	13.17	15.09	12.80	11.79	11.98
				Geometric Statistics														
				Mean	11.35	10.75	12.01	12.36	11.62	10.97	12.37	11.79	13.56	11.37	11.69	11.26	10.57	10.90
				Log10 Mean	1.05	1.03	1.08	1.09	1.07	1.04	1.09	1.07	1.13	1.06	1.07	1.05	1.02	1.04
				Log10 S.D.	0.14	0.12	0.17	0.17	0.15	0.11	0.18	0.16	0.20	0.13	0.15	0.13	0.097	0.12
				Log10 Std. Error of Mean	0.00	0.022	0.020	0.037	0.012	0.019	0.024	0.015	0.046	0.016	0.032	0.013	0.011	0
				Lower 95% limit on Mean	11.14	9.68	10.95	10.33	10.98	10.02	11.05	11.01	10.83	10.58	10.04	10.63	10.06	10.56
				Upper 95% limit on Mean	11.56	11.94	13.18	14.80	12.30	12.00	13.85	12.63	16.96	12.21	13.62	11.92	11.10	11.25
				Percentiles														
				Min Value	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	
				25th Xtile	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	
				50th Xtile	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	
				75th Xtile	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	23.00	10.00	10.00	10.00	10.00	
				80th Xtile	10.00	10.00	10.00	20.00	10.00	10.00	10.00	24.00	10.00	10.00	10.00	10.00	10.00	
				90th Xtile	21.00	10.00	21.00	22.00	22.00	20.00	10.00	23.00	26.00	22.00	24.00	20.00	10.00	10.00
				95th Xtile	25.00	25.00	26.00	24.00	26.00	21.00	10.00	28.00	33.00	25.00	25.00	24.00	21.00	22.00
				98th Xtile	29.00	38.00	39.00	30.00	30.00	24.00	10.00	32.00	33.00	26.00	29.00	27.00	26.00	29.00
				99th Xtile	33.00	38.00	52.00	30.00	34.00	24.00	10.00	37.00	33.00	26.00	29.00	28.00	36.00	35.00
				Max Value	52.00	38.00	52.00	30.00	35.00	24.00	10.00	39.00	33.00	26.00	29.00	29.00	36.00	39.00

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - pH [pH]

Number of Values - 1178

Units -

Detection Limit -

Analytical Method - GCM

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	6.18	5.95	6.27	6.34	6.13	6.25	5.94	6.25	6.34	6.24	6.23	6.07	6.17	6.26
Standard Deviation	0.35	0.39	0.30	0.30	0.35	0.33	0.51	0.31	0.39	0.30	0.35	0.35	0.34	0.34

Skewness	-0.95	-1.51	-0.12	-0.43	-0.17	-0.50	-1.73	-0.84	-0.54	-1.22	-1.49	-0.67	-0.89	-0.79
Excess Kurtosis	2.84	1.81	0.18	-0.88	-0.39	-0.036	4.97	0.60	-0.66	1.91	2.33	0.69	2.18	1.81

Coef. of Var. %	5.72	6.48	4.75	4.78	5.65	5.25	8.63	4.97	6.10	4.87	5.61	5.72	5.44	5.48
N	%	Cum %												

Std. Error of the Mean	0.01	0.069	0.036	0.068	0.029	0.057	0.070	0.029	0.091	0.036	0.073	0.034	0.037	0.021	
1	0.1	0.1	Lower 95% limit on Mean	6.16	5.81	6.20	6.19	6.07	6.13	5.80	6.19	6.15	6.17	6.08	6.01

Upper 95% limit on Mean	6.20	6.09	6.34	6.48	6.18	6.36	6.08	6.31	6.54	6.31	6.38	6.14	6.24	6.30
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Geometric Statistics														
Mean	6.17	5.94	6.26	6.33	6.12	6.24	5.91	6.24	6.33	6.23	6.22	6.06	6.16	6.25

Log10 Mean	0.79	0.77	0.80	0.80	0.79	0.80	0.77	0.80	0.80	0.79	0.79	0.78	0.79	0.80
Log10 S.D.	0.03	0.030	0.021	0.021	0.025	0.023	0.042	0.022	0.027	0.022	0.026	0.025	0.024	0.024

Log10 Std. Error of Mean	0.00	0	0	0	0	0	0	0	0	0	0	0	0	0
--------------------------	------	---	---	---	---	---	---	---	---	---	---	---	---	---

Lower 95% limit on Mean	6.15	5.79	6.19	6.19	6.06	6.12	5.76	6.18	6.14	6.16	6.06	5.99	6.08	6.20
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Upper 95% limit on Mean	6.19	6.09	6.33	6.47	6.17	6.36	6.07	6.30	6.53	6.30	6.38	6.13	6.24	6.29
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Percentiles														
Min Value	3.70	4.80	5.50	5.70	5.20	5.40	5.60	5.20	5.50	5.20	5.10	4.90	5.00	4.80

25th Xtile	6.00	5.80	6.10	6.00	5.90	6.00	5.80	6.10	6.20	6.10	6.00	5.90	6.00	6.10
50th Xtile	6.20	6.10	6.30	6.30	6.10	6.20	6.00	6.30	6.40	6.30	6.30	6.10	6.20	6.30

75th Xtile	6.40	6.20	6.50	6.60	6.40	6.50	6.10	6.50	6.60	6.40	6.40	6.30	6.40	6.50
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

80th Xtile	6.50	6.20	6.50	6.60	6.40	6.50	6.10	6.50	6.70	6.40	6.50	6.40	6.40	6.50
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

90th Xtile	6.60	6.30	6.60	6.70	6.60	6.60	6.20	6.60	6.80	6.60	6.50	6.50	6.50	6.60
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

95th Xtile	6.70	6.30	6.70	6.70	6.70	6.70	6.20	6.70	6.90	6.60	6.60	6.60	6.60	6.80
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

98th Xtile	6.80	6.40	6.90	6.80	6.80	6.90	6.20	6.70	6.90	6.70	6.70	6.60	6.70	6.90
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

99th Xtile	6.90	6.40	7.10	6.80	6.80	6.90	6.20	6.70	6.90	6.80	6.70	6.70	6.70	7.10
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Max Value	7.10	6.40	7.10	6.80	6.90	6.90	6.20	6.80	6.90	6.80	6.70	6.80	6.70	7.10
-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Rubidium [Rb]

Number of Values - 1178

Units - ppm

Detection Limit - 5

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN		
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276	
				Number of Values >= D.L.	936	24	54	13	101	26	48	96	12	66	23	81	77	216	
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
ppm 1- .				Mean	32.73	19.69	37.31	25.42	38.79	31.80	48.93	45.21	29.44	45.71	59.35	27.99	35.97	24.13	
				Standard Deviation	33.18	14.17	37.20	26.82	41.59	34.36	45.30	37.28	34.32	34.27	39.16	31.13	29.76	23.37	
				Skewness	1.33	0.63	0.88	1.26	0.99	1.19	0.97	0.61	0.87	0.56	0.43	1.77	1.09	1.50	
				Excess Kurtosis	1.10	0.24	-0.55	0.72	-0.41	-0.019	0.11	-0.80	-0.91	-0.53	-1.32	3.12	0.30	1.96	
				Coef. of Var. %	101.38	71.94	99.69	105.50	107.22	108.03	92.58	82.48	116.57	74.98	65.99	111.23	82.74	96.85	
				Std. Error of the Mean	0.97	2.54	4.45	6.00	3.53	5.98	6.16	3.52	8.09	4.01	8.17	3.02	3.29	1.41	
				N	30.84	14.50	28.44	12.87	31.82	19.62	36.56	38.22	12.37	37.71	42.41	21.99	29.43	21.36	
				%	Cum %	Lower 95% limit on Mean	30.84	14.50	28.44	12.87	31.82	19.62	36.56	38.22	12.37	37.71	42.41	21.99	
					Upper 95% limit on Mean	34.63	24.89	46.19	37.98	45.77	43.99	61.29	52.19	46.51	53.70	76.28	33.98	42.51	26.90
2- . .<<<<<< 5- . 10- . 20- . 50- . 100- . 200- .				Geometric Statistics															
				242	20.5	20.5													
				Mean	17.64	13.41	18.57	12.96	17.53	16.58	27.37	26.47	12.60	29.69	46.45	14.77	24.53	14.33	
				Log10 Mean	1.25	1.13	1.27	1.11	1.24	1.22	1.44	1.42	1.10	1.47	1.67	1.17	1.39	1.16	
				Log10 S.D.	0.54	0.45	0.59	0.58	0.62	0.55	0.54	0.53	0.62	0.48	0.33	0.53	0.42	0.49	
				Log10 Std. Error of Mean	0.02	0.080	0.070	0.13	0.052	0.095	0.074	0.051	0.15	0.056	0.068	0.052	0.046	0.029	
				243	20.6	50.8													
				Lower 95% limit on Mean	16.43	9.19	13.46	6.95	13.81	10.60	19.48	21.02	6.16	22.94	33.56	11.67	19.86	12.55	
				Upper 95% limit on Mean	18.93	19.57	25.62	24.16	22.26	25.94	38.46	33.34	25.76	38.44	64.28	18.70	30.30	16.36	
				301	25.6	76.3													
0 10 20 30 40 50 60 70 80 90 100 %				Percentiles															
				231	19.6	95.9													
				Min Value	2.50	2.50	2.50	2.50	2.50	2.50	6.00	2.50	2.50	2.50	11.00	2.50	2.50	2.50	
				25th Xtile	8.00	8.00	7.00	2.50	2.50	8.00	9.00	13.00	2.50	14.00	23.00	8.00	14.00	8.00	
				50th Xtile	20.00	20.00	19.00	19.00	19.00	17.00	42.00	34.00	10.00	39.00	42.00	15.00	25.00	17.00	
				75th Xtile	47.00	28.00	62.00	28.00	67.00	36.00	71.00	78.00	49.00	74.00	88.00	38.00	51.00	33.00	
				80th Xtile	58.00	29.00	76.00	40.00	85.00	64.00	71.00	87.00	69.00	81.00	98.00	49.00	63.00	40.00	
				90th Xtile	85.00	36.00	95.00	59.00	110.00	99.00	95.00	95.00	93.00	93.00	120.00	70.00	86.00	57.00	
				95th Xtile	99.00	41.00	110.00	80.00	130.00	110.00	95.00	110.00	98.00	99.00	130.00	89.00	93.00	75.00	
				98th Xtile	120.00	61.00	120.00	97.00	130.00	110.00	95.00	130.00	98.00	110.00	130.00	130.00	110.00	84.00	
				99th Xtile	130.00	61.00	130.00	97.00	140.00	110.00	95.00	140.00	98.00	150.00	130.00	140.00	130.00	110.00	
				Max Value	180.00	61.00	130.00	97.00	140.00	110.00	95.00	140.00	98.00	150.00	130.00	150.00	130.00	110.00	
Percentage of Values			* Summary statistics not calculated for rock units with less than ten values.																

Statistics per Variable

Variable - Samarium [Sm]

Number of Values - 1178

Units - ppm

Detection Limit - 0.05

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1176	31	70	20	139	33	54	112	18	73	23	106	82	274
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	8.28	3.37	9.45	19.08	10.05	10.74	9.10	9.09	7.08	6.66	7.38	8.11	5.48	6.37
------	------	------	------	-------	-------	-------	------	------	------	------	------	------	------	------

Standard Deviation	6.85	1.35	4.07	13.55	5.49	7.76	3.69	10.20	3.45	2.06	2.17	4.70	3.17	6.31
--------------------	------	------	------	-------	------	------	------	-------	------	------	------	------	------	------

Skewness	4.75	0.30	1.37	0.49	1.28	1.69	1.41	7.53	2.11	0.31	0.021	1.15	2.59	4.14
----------	------	------	------	------	------	------	------	------	------	------	-------	------	------	------

Excess Kurtosis	44.35	-0.62	2.40	-1.32	1.53	2.40	2.87	67.05	5.09	0.050	-1.31	1.81	9.86	24.20
-----------------	-------	-------	------	-------	------	------	------	-------	------	-------	-------	------	------	-------

Coef. of Var. %	82.69	40.15	43.06	70.97	54.64	72.24	40.49	112.18	48.73	31.00	29.39	58.02	57.96	99.04
-----------------	-------	-------	-------	-------	-------	-------	-------	--------	-------	-------	-------	-------	-------	-------

Std. Error of the Mean	0.20	0.24	0.49	3.03	0.47	1.35	0.50	0.96	0.81	0.24	0.45	0.46	0.35	0.38
------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

N	%	Cum %	2	0.2	0.2	Lower 95% limit on Mean	7.89	2.87	8.48	12.75	9.13	7.99	8.10	7.18	5.37	6.18	6.44	7.20	4.78	5.62
---	---	-------	---	-----	-----	-------------------------	------	------	------	-------	------	------	------	------	------	------	------	------	------	------

						Upper 95% limit on Mean	8.67	3.86	10.43	25.42	10.97	13.49	10.11	11.00	8.80	7.14	8.32	9.01	6.17	7.12
--	--	--	--	--	--	-------------------------	------	------	-------	-------	-------	-------	-------	-------	------	------	------	------	------	------

Geometric Statistics														
----------------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Mean	6.63	3.08	8.72	14.50	8.79	8.78	8.46	7.39	6.52	6.32	7.06	6.86	4.84	4.73
------	------	------	------	-------	------	------	------	------	------	------	------	------	------	------

Log10 Mean	0.82	0.49	0.94	1.16	0.94	0.94	0.93	0.87	0.81	0.80	0.85	0.84	0.69	0.68
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Log10 S.D.	0.30	0.19	0.17	0.34	0.22	0.27	0.17	0.25	0.17	0.15	0.14	0.26	0.21	0.36
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Log10 Std. Error of Mean	0.01	0.035	0.021	0.076	0.019	0.047	0.023	0.024	0.041	0.017	0.028	0.025	0.023	0.021
--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

N	%	Cum %	6	0.5	0.7	Lower 95% limit on Mean	6.38	2.61	7.93	10.03	8.06	7.04	7.62	6.64	5.33	5.85	6.16	6.11	4.35	4.30
---	---	-------	---	-----	-----	-------------------------	------	------	------	-------	------	------	------	------	------	------	------	------	------	------

						Upper 95% limit on Mean	6.90	3.63	9.59	20.95	9.59	10.96	9.40	8.23	7.96	6.84	8.08	7.70	5.39	5.22
--	--	--	--	--	--	-------------------------	------	------	------	-------	------	-------	------	------	------	------	------	------	------	------

			36	3.1	3.7																
--	--	--	----	-----	-----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Percentiles														
-------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Min Value	0.03	0.94	3.20	5.00	2.20	3.10	3.90	1.20	2.90	2.00	3.70	1.20	1.00	0.025
-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------

25th Xtile	4.30	2.20	6.70	7.20	6.00	5.70	6.20	5.20	4.90	5.40	5.70	4.30	3.80	3.30
------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

50th Xtile	6.50	3.30	8.40	12.00	8.50	8.90	7.10	7.50	6.00	6.50	7.30	7.10	4.60	4.60
------------	------	------	------	-------	------	------	------	------	------	------	------	------	------	------

75th Xtile	10.00	4.20	12.00	28.80	13.00	13.00	7.80	10.00	8.20	8.00	10.00	11.00	6.30	7.00
------------	-------	------	-------	-------	-------	-------	------	-------	------	------	-------	-------	------	------

N	%	Cum %	195	16.6	95.7															
---	---	-------	-----	------	------	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

						80th Xtile	11.00	4.30	12.00	32.90	15.00	15.00	7.80	10.00	8.30	8.40	10.00	12.00	6.90	8.00
--	--	--	--	--	--	------------	-------	------	-------	-------	-------	-------	------	-------	------	------	-------	-------	------	------

						90th Xtile	15.00	5.40	14.00	37.20	18.00	18.00	12.00	13.00	9.10	9.30	10.00	14.00	8.80	12.00
--	--	--	--	--	--	------------	-------	------	-------	-------	-------	-------	-------	-------	------	------	-------	-------	------	-------

						95th Xtile	19.00	5.80	17.00	41.20	21.40	30.70	12.00	19.00	19.00	10.00	10.00	17.00	11.00	16.00
--	--	--	--	--	--	------------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

						Max Value	105.00	6.40	25.20	45.20	31.10	35.70	12.00	105.00	19.00	13.00	11.00	27.90	22.80	59.10
--	--	--	--	--	--	-----------	--------	------	-------	-------	-------	-------	-------	--------	-------	-------	-------	-------	-------	-------

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Scandium [Sc]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN	
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ppm 0.2- . 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- .	N 7 82 657 419	%	Cum %	Mean	4.71	3.85	5.45	6.18	4.71	4.69	5.22	5.60	4.75	5.28	6.18	3.90	4.12	4.22
				Standard Deviation	2.15	1.76	1.80	2.80	1.94	1.86	1.93	2.29	2.33	1.76	1.79	1.86	1.40	2.00
				Skewness	1.11	0.53	0.40	0.47	0.57	0.67	0.36	0.35	0.45	0.15	-0.12	1.03	0.60	1.26
				Excess Kurtosis	2.89	-0.18	-0.35	-1.16	0.45	0.39	-0.98	-0.33	-1.08	-0.55	-1.22	1.61	0.53	3.10
				Coef. of Var. %	45.60	45.74	32.98	45.23	41.16	39.71	36.99	40.90	49.10	33.37	28.96	47.58	34.05	47.37
				Std. Error of the Mean	0.06	0.32	0.21	0.63	0.16	0.32	0.26	0.22	0.55	0.21	0.37	0.18	0.15	0.12
				Lower 95% limit on Mean	4.59	3.20	5.02	4.88	4.39	4.03	4.69	5.17	3.59	4.87	5.41	3.54	3.81	3.98
				Upper 95% limit on Mean	4.83	4.49	5.87	7.49	5.04	5.35	5.75	6.03	5.91	5.70	6.96	4.26	4.43	4.45
				Geometric Statistics														
				Mean	4.24	3.44	5.15	5.60	4.29	4.33	4.86	5.09	4.21	4.97	5.91	3.48	3.88	3.78
.	Log10 Mean	0.63	0.54	0.71	0.75	0.63	0.64	0.69	0.71	0.62	0.70	0.77	0.54	0.59	0.58
				Log10 S.D.	0.21	0.22	0.15	0.20	0.20	0.18	0.17	0.20	0.23	0.16	0.14	0.22	0.16	0.21
				Log10 Std. Error of Mean	0.01	0.039	0.018	0.045	0.017	0.032	0.023	0.019	0.053	0.019	0.029	0.021	0.017	0.013
				Lower 95% limit on Mean	4.13	2.86	4.74	4.52	3.98	3.73	4.38	4.67	3.25	4.56	5.16	3.16	3.58	3.57
				Upper 95% limit on Mean	4.36	4.13	5.59	6.95	4.63	5.03	5.40	5.55	5.45	5.41	6.78	3.83	4.20	4.00
				Percentiles														
				Min Value	0.60	1.20	2.40	2.90	1.00	1.50	2.00	0.90	1.60	2.00	3.00	0.60	1.10	0.90
				25th Xtile	3.10	2.50	3.90	3.60	3.30	3.40	3.30	3.80	2.80	4.10	4.50	2.60	3.20	2.90
				50th Xtile	4.40	3.80	5.40	5.70	4.60	4.70	5.40	5.60	3.90	5.00	6.40	3.50	4.00	4.00
				75th Xtile	5.90	5.00	6.50	7.70	5.70	5.40	5.80	6.90	6.00	6.60	7.60	5.00	4.70	5.00
				80th Xtile	6.30	5.10	6.80	9.20	6.20	5.90	5.80	7.50	6.30	7.00	7.70	5.20	5.10	5.60
				90th Xtile	7.60	6.20	7.90	10.00	7.60	7.00	7.60	8.60	8.70	7.50	8.70	6.30	6.00	6.60
				95th Xtile	8.60	6.50	8.60	10.00	8.30	8.00	7.60	9.30	9.30	8.20	8.90	7.20	6.50	8.20
				98th Xtile	10.00	8.60	10.00	12.00	8.60	10.00	7.60	10.00	9.30	8.50	9.00	7.90	7.70	9.40
				99th Xtile	11.00	8.60	10.00	12.00	8.90	10.00	7.60	12.00	9.30	10.00	9.00	10.00	8.50	10.00
				Max Value	18.00	8.60	10.00	12.00	12.00	10.00	7.60	12.00	9.30	10.00	9.00	11.00	8.50	15.00

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Silver [Ag]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN					
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276				
				Number of Values >= D.L.	296	7	18	4	36	15	17	27	7	28	6	15	15	67				
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0				
ppm 0.02- . 0.05- . 0.10- . 0.20- . 0.50- . 1.00- .	N 882 212 68 16	%	Cum % 74.9 18.0 5.8 1.4	Mean	0.14	0.14	0.15	0.13	0.16	0.18	0.17	0.14	0.14	0.15	0.13	0.13	0.13	0.14				
				Standard Deviation	0.10	0.080	0.11	0.073	0.12	0.14	0.17	0.090	0.050	0.082	0.045	0.087	0.077	0.076				
				Skewness	3.36	2.37	2.52	2.58	2.28	2.70	3.34	2.72	0.42	1.81	1.02	4.59	3.90	2.45				
				Excess Kurtosis	14.58	4.89	5.93	6.37	4.50	8.32	11.95	7.72	-1.92	2.91	-1.00	21.71	17.68	5.52				
				Coef. of Var. %	68.68	58.89	74.36	56.36	75.60	78.33	97.30	63.85	36.12	53.82	35.61	69.62	60.46	56.05				
				Std. Error of the Mean	0.00	0.014	0.013	0.016	0.010	0.025	0.023	0	0.012	0	0	0	0	0				
				Lower 95% limit on Mean	0.14	0.11	0.12	0.096	0.14	0.13	0.13	0.12	0.11	0.13	0.11	0.11	0.11	0.13				
				Upper 95% limit on Mean	0.15	0.16	0.18	0.16	0.18	0.23	0.22	0.16	0.16	0.17	0.15	0.14	0.15	0.14				
				Geometric Statistics																		
				Mean	0.13	0.12	0.13	0.12	0.13	0.15	0.14	0.12	0.13	0.14	0.12	0.11	0.12	0.12				
<<<<<<<<<<<<<<<<<<<				Log10 Mean	-0.90	-0.91	-0.89	-0.92	-0.88	-0.82	-0.86	-0.90	-0.88	-0.86	-0.92	-0.94	-0.93	-0.91				
.				Log10 S.D.	0.19	0.18	0.21	0.17	0.22	0.24	0.25	0.19	0.15	0.19	0.14	0.16	0.16	0.17				
.				Log10 Std. Error of Mean	0.01	0.032	0.025	0.037	0.019	0.041	0.033	0.018	0.036	0.022	0.028	0.015	0.018	0.010				
.				Lower 95% limit on Mean	0.12	0.11	0.12	0.099	0.12	0.13	0.12	0.12	0.11	0.12	0.10	0.11	0.11	0.12				
.				Upper 95% limit on Mean	0.13	0.14	0.15	0.14	0.14	0.18	0.16	0.14	0.16	0.15	0.14	0.12	0.13	0.13				
.				Percentiles																		
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+				Min Value	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10			
0 10 20 30 40 50 60 70 80 90 100 %				25th Xtile	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10			
Percentage of Values				50th Xtile	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10			
				75th Xtile	0.10	0.10	0.20	0.10	0.20	0.20	0.10	0.10	0.20	0.20	0.20	0.10	0.10	0.10	0.10			
				80th Xtile	0.20	0.20	0.20	0.10	0.20	0.20	0.10	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20			
				90th Xtile	0.20	0.20	0.20	0.20	0.40	0.40	0.10	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20			
				95th Xtile	0.40	0.40	0.40	0.20	0.40	0.40	0.10	0.40	0.20	0.40	0.20	0.20	0.20	0.20	0.40			
				98th Xtile	0.40	0.40	0.60	0.40	0.60	0.80	0.10	0.40	0.20	0.40	0.20	0.20	0.60	0.40	0.40			
				99th Xtile	0.60	0.40	0.60	0.40	0.60	0.80	0.10	0.40	0.20	0.40	0.20	0.20	0.60	0.60	0.40			
				Max Value	1.00	0.40	0.60	0.40	0.60	0.80	0.10	0.60	0.20	0.40	0.20	0.20	0.60	0.60	0.40			

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Sodium [Na]

Number of Values - 1178

Units - pct

Detection Limit - 0.02

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1176	31	70	20	139	33	54	112	18	73	23	105	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.68	0.42	0.81	0.59	0.74	0.74	0.83	0.92	0.64	0.98	1.13	0.59	0.76	0.55
Standard Deviation	0.64	0.29	0.74	0.58	0.72	0.76	0.68	0.68	0.72	0.74	0.71	0.61	0.63	0.53

Skewness	1.22	1.07	0.87	1.61	1.02	1.15	0.70	0.59	1.23	0.75	0.18	1.43	0.95	1.66
Excess Kurtosis	0.49	1.05	-0.68	1.77	-0.21	-0.11	-0.91	-0.94	0.14	-0.55	-1.67	1.19	-0.22	2.32
Coef. of Var. %	93.31	69.11	90.98	98.11	97.25	101.96	82.31	73.86	112.71	75.49	62.62	102.49	82.84	96.53

N	%	Cum %	Std. Error of the Mean	Lower 95% limit on Mean	Upper 95% limit on Mean
0.02	.	.	0.02	0.053	0.088
2	0.2	0.2	0.65	0.32	0.63
			0.72	0.53	0.99
			0.86	0.86	1.01
			1.01	1.01	1.04
			0.99	0.99	1.15
			1.15	1.43	0.71
			0.71	0.90	0.61

10	0.8	1.0	Geometric Statistics																
			Mean																
0.05	.	.	0.43	0.33	0.51	0.40	0.42	0.43	0.55	0.65	0.35	0.69	0.88	0.35	0.53	0.36			
0.10	.	.	95	8.1	9.1	Log10 Mean													
0.20	.	.	95	8.1	9.1	-0.36	-0.49	-0.29	-0.40	-0.37	-0.37	-0.26	-0.19	-0.45	-0.16	-0.054	-0.45	-0.28	-0.44
0.50	.	.	95	8.1	9.1	Log10 S.D.													
1.00	.	.	95	8.1	9.1	0.44	0.35	0.44	0.39	0.49	0.49	0.42	0.40	0.49	0.40	0.33	0.47	0.39	0.41
2.00	.	.	95	8.1	9.1	Log10 Std. Error of Mean													
5.00	.	.	95	8.1	9.1	0.01	0.062	0.053	0.088	0.042	0.085	0.057	0.038	0.11	0.047	0.069	0.045	0.043	0.024

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	Log10 Mean													
0.10	.	.	95	8.1	9.1	-0.36	-0.49	-0.29	-0.40	-0.37	-0.37	-0.26	-0.19	-0.45	-0.16	-0.054	-0.45	-0.28	-0.44
0.20	.	.	95	8.1	9.1	Log10 S.D.													
0.50	.	.	95	8.1	9.1	0.44	0.35	0.44	0.39	0.49	0.49	0.42	0.40	0.49	0.40	0.33	0.47	0.39	0.41
1.00	.	.	95	8.1	9.1	Log10 Std. Error of Mean													
2.00	.	.	95	8.1	9.1	0.01	0.062	0.053	0.088	0.042	0.085	0.057	0.038	0.11	0.047	0.069	0.045	0.043	0.024
5.00	.	.	95	8.1	9.1	Lower 95% limit on Mean													

10	0.8	1.0	Geometric Statistics																			
0.05	.	.	95	8.1	9.1	Lower 95% limit on Mean																
0.10	.	.	95	8.1	9.1	0.41	0.24	0.40	0.26	0.35	0.29	0.42	0.55	0.20	0.56	0.63	0.29	0.43	0.32			
0.20	.	.	95	8.1	9.1	Upper 95% limit on Mean																
0.50	.	.	95	8.1	9.1	375	31.8	56.4	0.46	0.44	0.65	0.62	0.51	0.64	0.72	0.77	0.62	0.86	1.23	0.43	0.64	0.40

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	Upper 95% limit on Mean													
0.10	.	.	95	8.1	9.1	0.46	0.44	0.65	0.62	0.51	0.64	0.72	0.77	0.62	0.86	1.23	0.43	0.64	0.40
0.20	.	.	95	8.1	9.1	Percentiles													
0.50	.	.	95	8.1	9.1	Min Value													

10	0.8	1.0	Geometric Statistics																		
0.05	.	.	95	8.1	9.1	Min Value															
0.10	.	.	95	8.1	9.1	234	19.9	76.2	0.01	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.20	0	0.10	0	
0.20	.	.	95	8.1	9.1	211	17.9	94.1	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.40	0.50	0.10	0.30	0.20
0.50	.	.	95	8.1	9.1	69	5.9	100.0	0.40	0.40	0.40	0.40	0.40	0.40	0.70	0.70	0.80	1.10	0.30	0.40	0.30

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	75th Xtile													
0.10	.	.	95	8.1	9.1	1.00	0.60	1.40	0.60	1.20	0.90	1.20	1.40	0.90	1.40	1.90	1.10	0.80	1.10
0.20	.	.	95	8.1	9.1	80th Xtile													
0.50	.	.	95	8.1	9.1	1.20	0.60	1.50	0.60	1.40	1.20	1.60	1.00	1.60	1.90	1.90	1.00	1.20	0.90

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	90th Xtile													
0.10	.	.	95	8.1	9.1	1.80	0.70	2.00	1.50	2.00	2.20	1.40	2.00	1.90	2.30	2.10	1.50	1.90	1.30
0.20	.	.	95	8.1	9.1	95th Xtile													
0.50	.	.	95	8.1	9.1	2.00	1.10	2.30	1.60	2.30	2.40	1.40	2.20	2.40	2.50	2.10	2.00	2.00	1.70

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	98th Xtile													
0.10	.	.	95	8.1	9.1	2.40	1.30	2.40	2.30	2.50	2.40	1.40	2.30	2.40	2.60	2.20	2.10	2.10	2.10
0.20	.	.	95	8.1	9.1	99th Xtile													
0.50	.	.	95	8.1	9.1	2.50	1.30	2.50	2.30	2.50	2.40	1.40	2.40	2.40	2.70	2.20	2.30	2.50	2.50

10	0.8	1.0	Geometric Statistics																
0.05	.	.	95	8.1	9.1	Max Value													
0.10	.	.	95	8.1	9.1	2.70	1.30	2.50	2.30	2.60	2.40	1.40	2.50	2.40	2.70	2.20	2.60	2.50	2.60
0.20	.	.	95	8.1	9.1	Percentile													
0.50	.	.	95	8.1	9.1	Min Value													

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Tantalum [Ta]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - INA

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN						
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276					
				Number of Values >= D.L.	337	14	24	6	41	7	22	53	6	28	10	18	21	62					
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
ppm 0.1- . 0.2- . 0.5- . 1.0- . 2.0- . 5.0- .	N 841 289 47 1 0 10 20 30 40 50 60 70 80 90 100 %	% 71.4 24.5 4.0 0.1 100.0 Percentage of Values	Geometric Statistics Log10 Std. Error of Mean Lower 95% limit on Mean Upper 95% limit on Mean Percentiles Min Value 25th Xtile 50th Xtile 75th Xtile 80th Xtile 90th Xtile 95th Xtile 98th Xtile 99th Xtile Max Value	Mean	0.42	0.47	0.45	0.39	0.44	0.38	0.50	0.53	0.45	0.48	0.53	0.35	0.44	0.39					
				Standard Deviation	0.28	0.29	0.29	0.21	0.29	0.23	0.35	0.32	0.28	0.29	0.33	0.22	0.34	0.24					
				Skewness	1.59	1.20	1.14	1.01	1.27	1.55	1.08	0.56	0.92	1.04	0.58	2.23	2.60	1.66					
				Excess Kurtosis	2.32	1.15	0.024	-0.46	0.25	1.52	0.036	-1.15	-0.63	0.55	-1.27	4.43	8.50	1.75					
				Coef. of Var. %	65.95	61.32	64.90	54.56	66.93	59.25	69.63	59.74	62.72	60.21	62.18	62.57	78.05	63.11					
				Std. Error of the Mean	0.01	0.052	0.035	0.048	0.025	0.039	0.048	0.030	0.066	0.034	0.068	0.021	0.038	0.015					
				N	841	71.4	71.4	Cum %	Lower 95% limit on Mean	0.41	0.37	0.38	0.29	0.39	0.30	0.41	0.47	0.31	0.41	0.38	0.31	0.36	0.36
				%					Upper 95% limit on Mean	0.44	0.58	0.52	0.49	0.49	0.46	0.60	0.59	0.59	0.55	0.67	0.39	0.51	0.42

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Terbium [Tb]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	976	15	69	20	127	27	52	98	15	64	22	87	65	191
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	1.09	0.49	1.24	2.14	1.31	1.35	1.28	1.07	0.92	0.90	1.05	1.13	0.83	0.86
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Standard Deviation	0.78	0.26	0.46	1.38	0.67	1.01	0.45	0.87	0.52	0.31	0.27	0.63	0.51	0.72
--------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Skewness	3.18	0.48	0.82	0.59	1.04	1.55	0.44	5.82	1.03	-0.22	-0.57	1.15	1.85	3.33
----------	------	------	------	------	------	------	------	------	------	-------	-------	------	------	------

Excess Kurtosis	18.83	-1.18	0.28	-1.11	1.48	2.67	0.74	46.77	1.37	-0.24	-0.79	3.14	5.35	17.10
-----------------	-------	-------	------	-------	------	------	------	-------	------	-------	-------	------	------	-------

Coef. of Var. %	71.97	53.01	36.58	64.61	51.45	74.75	34.76	81.91	56.02	34.27	25.77	56.23	61.39	84.10
-----------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Std. Error of the Mean	0.02	0.047	0.054	0.31	0.057	0.18	0.061	0.083	0.12	0.036	0.057	0.062	0.056	0.043
------------------------	------	-------	-------	------	-------	------	-------	-------	------	-------	-------	-------	-------	-------

N	%	Cum %	Lower 95% Limit on Mean	1.04	0.39	1.14	1.49	1.20	0.99	1.16	0.90	0.66	0.83	0.93
---	---	-------	-------------------------	------	------	------	------	------	------	------	------	------	------	------

			Upper 95% Limit on Mean	1.13	0.58	1.35	2.79	1.42	1.70	1.40	1.23	1.18	0.98	1.17
--	--	--	-------------------------	------	------	------	------	------	------	------	------	------	------	------

				ppm	0.1-									
--	--	--	--	-----	------	--	--	--	--	--	--	--	--	--

				0.2-										
--	--	--	--	------	--	--	--	--	--	--	--	--	--	--

				0.5-										
--	--	--	--	------	--	--	--	--	--	--	--	--	--	--

				1.0-										
--	--	--	--	------	--	--	--	--	--	--	--	--	--	--

				2.0-										
--	--	--	--	------	--	--	--	--	--	--	--	--	--	--

				5.0-										
--	--	--	--	------	--	--	--	--	--	--	--	--	--	--

				10.0-										
--	--	--	--	-------	--	--	--	--	--	--	--	--	--	--

					Geometric Statistics									
--	--	--	--	--	----------------------	--	--	--	--	--	--	--	--	--

					Mean	0.88	0.42	1.17	1.74	1.14	1.02	1.20	0.88	0.78
--	--	--	--	--	------	------	------	------	------	------	------	------	------	------

					Log10 Mean	-0.05	-0.37	0.067	0.24	0.055	0	0.078	-0.053	-0.11
--	--	--	--	--	------------	-------	-------	-------	------	-------	---	-------	--------	-------

					Log10 S.D.	0.29	0.24	0.16	0.29	0.25	0.35	0.17	0.27	0.27
--	--	--	--	--	------------	------	------	------	------	------	------	------	------	------

					Log10 Std. Error of Mean	0.01	0.042	0.019	0.066	0.021	0.061	0.024	0.025	0.064
--	--	--	--	--	--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------

					Lower 95% limit on Mean	0.85	0.35	1.07	1.26	1.03	0.77	1.07	0.79	0.57
--	--	--	--	--	-------------------------	------	------	------	------	------	------	------	------	------

					Upper 95% limit on Mean	0.92	0.52	1.27	2.38	1.25	1.36	1.33	0.99	1.07
--	--	--	--	--	-------------------------	------	------	------	------	------	------	------	------	------

						Percentiles								
--	--	--	--	--	--	-------------	--	--	--	--	--	--	--	--

						Min Value	0.25	0.25	0.50	0.70	0.25	0.25	0.25	0.25
--	--	--	--	--	--	-----------	------	------	------	------	------	------	------	------

						25th Xtile	0.60	0.25	0.90	0.90	0.80	1.10	0.70	0.60
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						50th Xtile	0.90	0.50	1.10	1.70	1.20	1.20	1.30	1.00
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						75th Xtile	1.30	0.70	1.50	3.10	1.60	1.60	1.50	1.20
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						80th Xtile	1.40	0.70	1.60	3.30	1.90	1.70	1.50	1.30
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						90th Xtile	1.90	0.90	1.90	4.00	2.10	2.40	1.90	1.60
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						95th Xtile	2.30	1.00	2.10	4.70	2.60	3.60	1.90	2.10
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						98th Xtile	3.20	1.00	2.50	4.80	3.40	4.80	1.90	2.30
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						99th Xtile	4.30	1.00	2.60	4.80	3.50	4.80	1.90	3.00
--	--	--	--	--	--	------------	------	------	------	------	------	------	------	------

						Max Value	8.60	1.00	2.60	4.80	3.70	4.80	1.90	8.60
--	--	--	--	--	--	-----------	------	------	------	------	------	------	------	------

* Summary statistics not calculated for rock units with less than ten values.

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

Statistics per Variable

Variable - Thorium [Th]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - INA

			All Units*														
			MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN		
			Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
			Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
			Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
			Mean	11.36	10.40	11.59	16.01	11.92	11.56	13.98	11.47	9.18	9.99	11.62	11.50	10.54	10.40
			Standard Deviation	5.24	4.21	3.61	7.31	4.85	5.14	4.69	5.58	4.14	3.67	4.19	5.53	4.09	4.67
			Skewness	1.40	0.52	0.18	0.28	0.44	1.05	0.31	1.32	0.46	0.60	0.20	0.80	1.13	1.26
			Excess Kurtosis	4.41	-0.42	-0.26	-1.39	0.48	1.18	-1.08	3.32	-1.25	0.47	-1.28	0.78	2.29	3.47
			Coef. of Var. %	46.12	40.48	31.15	45.65	40.63	44.49	33.56	48.59	45.05	36.70	36.03	48.03	38.78	44.89
			Std. Error of the Mean	0.15	0.76	0.43	1.63	0.41	0.90	0.64	0.53	0.98	0.43	0.87	0.54	0.45	0.28
			N	%	Cum %	Lower 95% limit on Mean	11.06	8.86	10.73	12.59	11.11	9.74	12.70	10.43	7.13	9.13	9.81
						Upper 95% limit on Mean	11.66	11.95	12.45	19.43	12.74	13.39	15.26	12.52	11.24	10.84	13.43
			Geometric Statistics														
			Mean	10.25	9.58	11.00	14.38	10.83	10.55	13.20	10.22	8.33	9.32	10.87	10.15	9.82	9.43
			Log10 Mean	1.01	0.98	1.04	1.16	1.03	1.02	1.12	1.01	0.92	0.97	1.04	1.01	0.99	0.97
			Log10 S.D.	0.20	0.18	0.15	0.21	0.20	0.19	0.15	0.22	0.20	0.17	0.17	0.23	0.17	0.20
			Log10 Std. Error of Mean	0.01	0.033	0.018	0.047	0.017	0.033	0.021	0.021	0.047	0.020	0.035	0.023	0.018	0.012
			Lower 95% limit on Mean	9.98	8.20	10.14	11.45	10.01	9.02	12.00	9.30	6.62	8.52	9.21	9.15	9.03	8.93
			Upper 95% limit on Mean	10.53	11.18	11.92	18.06	11.72	12.33	14.51	11.22	10.47	10.20	12.82	11.24	10.68	9.95
			Percentiles														
			Min Value	1.60	4.10	4.90	6.30	2.50	3.90	5.40	1.90	3.50	3.60	5.10	1.60	3.70	2.00
			25th Xtile	7.60	7.00	8.80	9.00	8.70	8.10	10.00	7.90	5.90	7.50	8.00	7.20	7.90	7.30
			50th Xtile	11.00	11.00	12.00	16.00	12.00	11.00	13.00	10.00	7.10	10.00	11.00	11.00	10.00	10.00
			75th Xtile	14.00	13.00	14.00	20.00	15.00	14.00	18.00	14.00	12.00	12.00	15.00	14.00	13.00	13.00
			80th Xtile	15.00	13.00	14.00	21.90	16.00	15.00	18.00	15.00	14.00	13.00	17.00	15.00	13.00	13.00
			90th Xtile	18.00	17.00	15.00	25.40	19.00	19.00	19.00	17.00	16.00	14.00	17.00	19.00	16.00	16.00
			95th Xtile	20.20	18.00	18.00	27.10	20.00	20.00	19.00	19.00	17.00	16.00	18.00	21.90	16.00	20.00
			98th Xtile	24.80	20.80	19.00	29.30	22.40	27.90	19.00	28.40	17.00	19.00	19.00	26.70	22.30	21.10
			99th Xtile	29.00	20.80	21.50	29.30	24.60	27.90	19.00	29.00	17.00	22.20	19.00	27.00	26.70	23.30
			Max Value	47.50	20.80	21.50	29.30	29.90	27.90	19.00	36.40	17.00	22.20	19.00	30.20	26.70	35.90

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Tungsten [W]

Number of Values - 1178

Units - ppm

Detection Limit - 1

Analytical Method - INA

			All Units*															
			MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN			
ppm	0.1-	.	Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276	
			Number of Values >= D.L.	215	4	17	7	25	7	14	17	2	6	1	28	18	50	
			Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
			Mean	0.90	0.76	1.01	1.08	0.90	0.89	0.96	0.81	0.69	0.66	0.59	1.11	0.98	0.90	
			Standard Deviation	0.82	0.51	0.91	0.83	0.77	0.69	0.64	0.63	0.49	0.43	0.33	1.13	0.82	0.87	
			Skewness	3.10	1.74	1.69	0.82	2.42	1.46	0.87	2.32	2.07	2.54	3.64	2.43	2.17	4.05	
			Excess Kurtosis	14.98	1.44	1.92	-0.96	6.72	0.83	-1.09	5.73	2.66	5.04	12.62	7.06	5.77	27.55	
			Coef. of Var. %	91.70	67.85	89.60	77.35	86.45	77.55	66.79	78.47	70.45	64.02	55.40	101.91	83.73	96.02	
			Std. Error of the Mean	0.02	0.092	0.11	0.19	0.066	0.12	0.088	0.060	0.12	0.050	0.068	0.11	0.091	0.052	
	N	%	Cum %	Lower 95% limit on Mean	0.85	0.57	0.80	0.69	0.77	0.65	0.79	0.69	0.45	0.57	0.45	0.89	0.80	
				Upper 95% limit on Mean	0.94	0.95	1.23	1.46	1.03	1.14	1.14	0.93	0.94	0.76	0.73	1.33	1.16	1.01
			Geometric Statistics															
				Mean	0.71	0.65	0.77	0.83	0.71	0.72	0.79	0.67	0.61	0.59	0.55	0.81	0.78	0.71
				Log10 Mean	-0.15	-0.18	-0.11	-0.082	-0.15	-0.14	-0.10	-0.17	-0.22	-0.23	-0.26	-0.094	-0.11	-0.15
				Log10 S.D.	0.26	0.22	0.30	0.31	0.26	0.26	0.26	0.23	0.20	0.18	0.14	0.32	0.27	0.26
				Log10 Std. Error of Mean	0.01	0.039	0.035	0.069	0.022	0.046	0.036	0.022	0.047	0.021	0.029	0.031	0.030	0.016
				Lower 95% limit on Mean	0.68	0.55	0.65	0.59	0.65	0.58	0.67	0.61	0.48	0.54	0.48	0.70	0.68	0.66
				Upper 95% limit on Mean	0.73	0.78	0.90	1.16	0.79	0.90	0.94	0.74	0.76	0.65	0.63	0.93	0.89	0.77
			Percentiles															
				Min Value	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	
				25th Xtile	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	
				50th Xtile	0.50	0.50	0.50	0.50	0.50	0.50	2.00	0.50	0.50	0.50	0.50	0.50	0.50	
				75th Xtile	1.00	1.00	1.00	2.00	1.00	1.00	2.00	1.00	0.50	0.50	0.50	2.00	1.00	1.00
				80th Xtile	1.00	1.00	2.00	2.00	1.00	2.00	2.00	1.00	0.50	0.50	0.50	2.00	2.00	1.00
				90th Xtile	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	1.00	0.50	2.00	2.00	2.00
				95th Xtile	2.00	2.00	3.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	1.00	4.00	2.00	2.00
				98th Xtile	3.00	2.00	4.00	3.00	3.00	3.00	2.00	2.00	2.00	2.00	2.00	4.00	3.00	3.00
				99th Xtile	4.00	2.00	4.00	3.00	4.00	3.00	2.00	3.00	2.00	2.00	2.00	5.00	5.00	4.00
				Max Value	9.00	2.00	4.00	3.00	5.00	3.00	2.00	4.00	2.00	2.00	2.00	7.00	5.00	9.00

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Uranium [U]

Number of Values - 1178

Units - ppm

Detection Limit - 0.2

Analytical Method - INA

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	7.19	2.70	4.95	9.73	5.34	5.63	8.58	5.63	3.76	6.11	6.24	8.37	6.85	9.47
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Standard Deviation	9.49	1.23	2.85	8.70	3.41	5.12	7.08	8.24	2.60	5.63	2.71	12.76	9.80	13.71
--------------------	------	------	------	------	------	------	------	------	------	------	------	-------	------	-------

Skewness	5.91	0.49	2.63	1.23	1.98	2.74	1.69	3.60	1.73	3.42	0.56	5.61	3.84	4.97
----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Excess Kurtosis	55.49	-0.96	9.86	0.79	6.10	8.73	2.39	12.75	2.99	15.48	-0.30	37.86	16.29	35.39
-----------------	-------	-------	------	------	------	------	------	-------	------	-------	-------	-------	-------	-------

Coef. of Var. %	132.01	45.63	57.59	89.38	63.77	90.82	82.50	146.46	69.11	92.13	43.37	152.53	143.10	144.76
-----------------	--------	-------	-------	-------	-------	-------	-------	--------	-------	-------	-------	--------	--------	--------

N	%	Cum %												
---	---	-------	--	--	--	--	--	--	--	--	--	--	--	--

Std. Error of the Mean	0.28	0.22	0.34	1.94	0.29	0.89	0.96	0.78	0.61	0.66	0.56	1.24	1.08	0.83
------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Lower 95% limit on Mean	6.65	2.25	4.27	5.66	4.77	3.82	6.65	4.08	2.47	4.80	5.07	5.91	4.69	7.85
-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Upper 95% limit on Mean	7.73	3.15	5.62	13.80	5.91	7.45	10.51	7.17	5.05	7.43	7.41	10.83	9.00	11.10
-------------------------	------	------	------	-------	------	------	-------	------	------	------	------	-------	------	-------

4	0.3	0.3												
---	-----	-----	--	--	--	--	--	--	--	--	--	--	--	--

			Geometric Statistics											
--	--	--	----------------------	--	--	--	--	--	--	--	--	--	--	--

19	1.6	2.0	Mean	4.90	2.43	4.41	6.79	4.45	4.38	6.57	3.58	3.14	4.75	5.65	5.53	4.40	5.76
----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			Log10 Mean	0.69	0.39	0.64	0.83	0.65	0.64	0.82	0.55	0.50	0.68	0.75	0.74	0.64	0.76
--	--	--	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

111	9.4	11.4	Log10 S.D.	0.35	0.21	0.20	0.38	0.27	0.29	0.31	0.36	0.26	0.29	0.21	0.36	0.36	0.41
-----	-----	------	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			Log10 Std. Error of Mean	0.01	0.037	0.024	0.085	0.023	0.051	0.042	0.034	0.062	0.034	0.044	0.035	0.040	0.025
--	--	--	--------------------------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

510	43.3	54.7	Lower 95% limit on Mean	4.68	2.04	3.95	4.52	4.01	3.45	5.40	3.06	2.33	4.05	4.59	4.72	3.66	5.15
-----	------	------	-------------------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			Upper 95% limit on Mean	5.13	2.89	4.92	10.21	4.94	5.57	7.98	4.19	4.24	5.56	6.96	6.48	5.28	6.44
--	--	--	-------------------------	------	------	------	-------	------	------	------	------	------	------	------	------	------	------

357	30.3	85.0														
-----	------	------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

			Percentiles													
--	--	--	-------------	--	--	--	--	--	--	--	--	--	--	--	--	--

			Min Value	0.40	0.90	1.50	2.20	0.80	1.60	5.70	0.40	1.20	0.90	1.50	0.50	0.50	0.60
--	--	--	-----------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			25th Xtile	2.80	1.80	3.40	2.70	2.90	2.60	6.00	2.20	1.80	3.10	4.40	3.50	2.50	3.20
--	--	--	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

			50th Xtile	4.50	2.40	4.00	5.30	4.90	4.40	17.00	3.40	3.20	4.40	5.90	5.60	3.70	5.70
--	--	--	------------	------	------	------	------	------	------	-------	------	------	------	------	------	------	------

			75th Xtile	7.40	3.70	5.90	15.00	6.80	6.50	24.70	4.60	4.50	7.90	7.30	8.70	6.40	10.00
--	--	--	------------	------	------	------	-------	------	------	-------	------	------	------	------	------	------	-------

			80th Xtile	8.80	3.80	6.00	16.00	7.10	7.30	24.70	5.70	4.60	8.20	8.80	9.10	7.00	11.00
--	--	--	------------	------	------	------	-------	------	------	-------	------	------	------	------	------	------	-------

			90th Xtile	13.00	4.60	7.80	19.00	8.90	10.00	28.60	8.40	7.40	10.00	10.00	12.00	15.00	18.00
--	--	--	------------	-------	------	------	-------	------	-------	-------	------	------	-------	-------	-------	-------	-------

			95th Xtile	21.30	5.10	11.00	23.10	11.00	16.00	28.60	28.70	12.00	13.00	12.00	21.70	23.00	35.80
--	--	--	------------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			98th Xtile	38.50	5.10	11.00	34.40	18.00	28.00	28.60	40.10	12.00	22.60	12.00	45.50	54.60	48.60
--	--	--	------------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			99th Xtile	48.00	5.10	20.10	34.40	18.00	28.00	28.60	41.30	12.00	39.30	12.00	57.00	61.30	75.50
--	--	--	------------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

			Max Value	142.00	5.10	20.10	34.40	22.50	28.00	28.60	47.90	12.00	39.30	12.00	110.00	61.30	142.00
--	--	--	-----------	--------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------	-------	--------

+-----+-----+-----+-----+-----+-----+-----+

0 10 20 30 40 50 60 70 80 90 100 %

Percentage of Values

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Uranium [U]

Number of Values - 1178

Units - ppm

Detection Limit - 0.5

Analytical Method - NADNC

			All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN		
		Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276		
		Number of Values >= D.L.	1170	31	69	20	138	33	54	109	18	73	23	106	82	273		
		Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
ppm 0.1- . 0.2- . . . 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- . 100.0- . 200.0- .		Mean	7.04	2.35	4.78	9.32	5.33	5.46	8.63	5.02	3.91	5.89	6.28	8.57	6.85	9.22		
		Standard Deviation	9.29	1.04	2.82	8.80	3.61	4.94	6.87	6.54	2.80	4.98	2.70	14.14	9.78	13.07		
		Skewness	6.03	0.85	2.75	1.43	2.23	2.70	1.66	3.74	1.84	2.83	0.48	6.04	3.73	4.59		
		Excess Kurtosis	56.10	0.015	11.10	1.51	7.53	8.36	2.42	14.53	3.47	10.07	-0.47	43.02	15.25	29.31		
		N	132.00	44.44	58.87	94.37	67.81	90.44	79.59	130.46	71.55	84.49	42.96	164.93	142.82	141.72		
		%																
		Cum %																
		Coef. of Var. %																
		Std. Error of the Mean																
		Lower 95% limit on Mean																
		Upper 95% limit on Mean																
8 0.7 0.7			Geometric Statistics															
23 2.0 2.6			Mean	4.79	2.14	4.17	6.32	4.34	4.27	6.69	3.34	3.25	4.66	5.69	5.60	4.37	5.60	
117 9.9 12.6			Log10 Mean	0.68	0.33	0.62	0.80	0.64	0.63	0.83	0.52	0.51	0.67	0.76	0.75	0.64	0.75	
496 42.1 54.7			Log10 S.D.	0.36	0.19	0.24	0.40	0.29	0.29	0.31	0.38	0.26	0.29	0.21	0.35	0.36	0.42	
348 29.5 84.2			Log10 Std. Error of Mean	0.01	0.034	0.029	0.089	0.025	0.050	0.042	0.035	0.062	0.034	0.044	0.034	0.040	0.025	
122 10.4 94.6			Percentiles															
53 4.5 99.1			Min Value	0.25	0.80	0.25	1.10	0.25	1.40	6.00	0.25	1.40	0.80	1.50	0.70	0.70	0.25	
9 0.8 99.8			25th Xtile	2.90	1.50	3.30	2.80	2.90	2.70	6.30	2.20	1.90	3.20	4.50	3.40	2.60	3.00	
2 0.2 100.0			50th Xtile	4.60	2.30	4.10	5.20	4.90	4.10	17.60	3.40	3.20	4.10	5.80	5.70	3.80	5.60	
80th Xtile			75th Xtile	7.20	2.80	5.40	13.10	6.90	5.80	24.10	4.80	4.70	6.90	8.30	8.30	6.50	10.00	
98th Xtile			90th Xtile	12.50	3.70	7.00	19.50	8.50	10.90	25.30	7.90	7.40	10.30	9.90	11.40	15.00	18.80	
99th Xtile			95th Xtile	20.20	4.40	10.40	21.80	10.90	14.80	25.30	13.30	13.00	13.40	11.60	22.60	24.70	33.10	
Max Value				128.00	5.10	20.10	35.70	24.50	26.90	25.30	39.80	13.00	31.70	12.10	125.00	60.00	128.00	
0 10 20 30 40 50 60 70 80 90 100 %			Percentage of Values															

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Uranium in Water [U-W]

Number of Values - 1178

Units - ppb

Detection Limit - 0.05

Analytical Method - LIF

	All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN
--	------------	-----	-----	-----	----	-----	------	------	------	-----	-----	-----	------	-----

Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
Number of Values >= D.L.	396	0	15	7	47	9	26	18	3	24	8	44	26	120
Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Mean	0.05	-	0.031	0.040	0.040	0.037	0.058	0.045	0.031	0.046	0.043	0.068	0.050	0.063
Standard Deviation	0.07	-	0.013	0.024	0.028	0.026	0.049	0.10	0.016	0.042	0.031	0.12	0.058	0.091
Skewness	7.63	-	1.63	1.21	2.53	2.82	1.61	7.82	2.06	3.03	1.60	4.66	4.26	6.56
Excess Kurtosis	81.62	-	1.12	0.13	7.49	9.01	1.65	65.52	2.99	12.02	1.45	22.88	22.30	62.48
Coef. of Var. %	144.08	-	41.19	59.57	69.21	69.12	85.00	230.58	49.72	90.52	72.31	174.22	117.21	144.95
Std. Error of the Mean	0.00	-	0	0	0	0	0	0	0	0	0	0.011	0	0

N	%	Cum %	Lower 95% limit on Mean	0.05	-	0.028	0.029	0.036	0.028	0.044	0.025	0.024	0.037	0.030	0.045	0.037	0.052
			Upper 95% limit on Mean	0.05	-	0.035	0.051	0.045	0.046	0.071	0.064	0.039	0.056	0.057	0.090	0.062	0.074

ppb

0.01 - .

0.02 - .

0.05 - .

0.10 - .

0.20 - .

0.50 - .

1.00 - .

2.00 - .

Geometric Statistics

Mean	0.04	-	0.030	0.035	0.035	0.032	0.044	0.031	0.029	0.037	0.036	0.042	0.037	0.043
------	------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Log10 Mean	-1.43	-	-1.53	-1.45	-1.46	-1.49	-1.35	-1.51	-1.54	-1.43	-1.44	-1.37	-1.43	-1.37
------------	-------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Log10 S.D.	0.28	-	0.14	0.22	0.22	0.20	0.30	0.25	0.16	0.26	0.24	0.34	0.28	0.32
------------	------	---	------	------	------	------	------	------	------	------	------	------	------	------

Log10 Std. Error of Mean	0.01	-	0.017	0.049	0.018	0.035	0.041	0.023	0.037	0.031	0.051	0.033	0.031	0.019
--------------------------	------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Lower 95% limit on Mean	0.04	-	0.027	0.028	0.032	0.027	0.037	0.027	0.024	0.032	0.028	0.036	0.032	0.039
-------------------------	------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Upper 95% limit on Mean	0.04	-	0.032	0.044	0.038	0.038	0.053	0.034	0.035	0.042	0.046	0.049	0.043	0.047
-------------------------	------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Percentiles														
-------------	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Min Value	0.03	-	0.025	0.025	0.025	0.025	0.060	0.025	0.025	0.025	0.025	0.025	0.025	0.025
-----------	------	---	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

25th Xtile	0.03	-	0.025	0.025	0.025	0.025	0.11	0.025	0.025	0.025	0.025	0.025	0.025	0.025
------------	------	---	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------

50th Xtile	0.03	-	0.025	0.025	0.025	0.025	0.13	0.025	0.025	0.025	0.025	0.025	0.025	0.025
------------	------	---	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------

75th Xtile	0.05	-	0.025	0.050	0.050	0.050	0.15	0.025	0.025	0.060	0.060	0.060	0.060	0.060
------------	------	---	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------

80th Xtile	0.06	-	0.050	0.060	0.060	0.050	0.15	0.025	0.025	0.060	0.060	0.060	0.070	0.080
------------	------	---	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------

90th Xtile	0.10	-	0.050	0.070	0.070	0.060	0.21	0.050	0.060	0.10	0.090	0.11	0.10	0.11
------------	------	---	-------	-------	-------	-------	------	-------	-------	------	-------	------	------	------

95th Xtile	0.13	-	0.060	0.090	0.10	0.080	0.21	0.10	0.080	0.11	0.12	0.18	0.10	0.20
------------	------	---	-------	-------	------	-------	------	------	-------	------	------	------	------	------

98th Xtile	0.25	-	0.070	0.10	0.15	0.15	0.21	0.15	0.080	0.18	0.13	0.60	0.26	0.34
------------	------	---	-------	------	------	------	------	------	-------	------	------	------	------	------

99th Xtile	0.34	-	0.070	0.10	0.16	0.15	0.21	0.50	0.080	0.28	0.13	0.70	0.43	0.38
------------	------	---	-------	------	------	------	------	------	-------	------	------	------	------	------

Max Value	1.10	-	0.070	0.10	0.18	0.15	0.21	1.00	0.080	0.28	0.13	0.80	0.43	1.10
-----------	------	---	-------	------	------	------	------	------	-------	------	------	------	------	------

* Summary statistics not calculated for rock units with less than ten values.

0 10 20 30 40 50 60 70 80 90 100 %
Percentage of Values

Statistics per Variable

Variable - Vanadium [V]

Number of Values - 1178

Units - ppm

Detection Limit - 5

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGPX	RGT	RNG	WFN	WPSN	WRN	
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Values >= D.L.	1134	30	66	19	128	33	53	112	17	71	23	100	78	267
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ppm 1- .				Mean	27.41	32.42	26.64	45.00	23.63	27.58	31.16	28.71	25.28	29.04	33.70	25.31	25.06	25.74
				Standard Deviation	16.82	23.77	13.95	27.86	13.23	12.57	17.58	12.13	12.66	12.21	19.84	13.19	15.90	17.67
				Skewness	2.21	2.24	1.51	0.72	1.19	0.70	2.76	1.66	0.45	0.80	1.36	1.46	1.84	2.21
				Excess Kurtosis	8.51	6.57	4.68	-0.21	2.61	-0.44	12.74	5.54	-0.41	1.48	1.74	3.71	4.63	6.99
				Coef. of Var. %	61.37	73.31	52.38	61.92	55.96	45.58	56.43	42.26	50.07	42.04	58.88	52.13	63.44	68.64
				Std. Error of the Mean	0.49	4.27	1.67	6.23	1.12	2.19	2.39	1.15	2.98	1.43	4.14	1.28	1.76	1.06
				N % Cum %	26.45	23.70	23.32	31.96	21.41	23.12	26.36	26.43	18.98	26.19	25.12	22.77	21.57	23.65
				Lower 95% limit on Mean	26.45	23.70	23.32	31.96	21.41	23.12	26.36	26.43	18.98	26.19	25.12	22.77	21.57	23.65
				Upper 95% limit on Mean	28.37	41.14	29.97	58.04	25.85	32.03	35.96	30.98	31.57	31.89	42.28	27.85	28.56	27.84
				Geometric Statistics														
2- . .00 5- . .00000 10- . .000000000 20- . .00000000000 50- . .00000000000 100- . .00000000000 200- .				Mean	23.23	26.33	23.14	36.02	20.01	24.93	27.10	26.49	21.92	26.27	28.95	21.98	21.06	21.33
				Log10 Mean	1.37	1.42	1.36	1.56	1.30	1.40	1.43	1.42	1.34	1.42	1.46	1.34	1.32	1.33
				Log10 S.D.	0.26	0.29	0.25	0.33	0.27	0.20	0.25	0.18	0.26	0.21	0.25	0.25	0.26	0.27
				Log10 Std. Error of Mean	0.01	0.052	0.030	0.074	0.023	0.035	0.034	0.017	0.061	0.025	0.052	0.024	0.029	0.016
				Lower 95% limit on Mean	22.45	20.66	20.18	25.27	18.05	21.16	23.16	24.55	16.32	23.44	22.61	19.68	18.44	19.83
				Upper 95% limit on Mean	24.03	33.55	26.52	51.34	22.18	29.37	31.71	28.58	29.44	37.07	24.56	24.04	22.94	
				Percentiles														
				Min Value	2.50	5.00	5.00	5.00	5.00	10.00	15.00	10.00	5.00	5.00	10.00	2.50	5.00	2.50
				25th Xtile	15.00	20.00	20.00	20.00	15.00	20.00	25.00	20.00	15.00	25.00	25.00	20.00	15.00	15.00
				50th Xtile	25.00	25.00	25.00	40.00	20.00	25.00	30.00	25.00	25.00	30.00	30.00	25.00	20.00	20.00
0 10 20 30 40 50 60 70 80 90 100 %				75th Xtile	35.00	45.00	35.00	60.00	30.00	35.00	35.00	35.00	35.00	35.00	35.00	30.00	30.00	30.00
				80th Xtile	35.00	45.00	35.00	60.00	35.00	35.00	35.00	35.00	35.00	35.00	50.00	35.00	35.00	35.00
				90th Xtile	45.00	55.00	40.00	75.00	40.00	50.00	35.00	45.00	40.00	45.00	60.00	40.00	45.00	45.00
				95th Xtile	60.00	65.00	55.00	100.00	45.00	55.00	35.00	45.00	55.00	50.00	65.00	45.00	50.00	65.00
				98th Xtile	75.00	130.00	60.00	110.00	60.00	55.00	35.00	65.00	55.00	65.00	95.00	65.00	75.00	75.00
				99th Xtile	95.00	130.00	90.00	110.00	75.00	55.00	35.00	70.00	55.00	70.00	95.00	75.00	95.00	100.00
				Max Value	140.00	130.00	90.00	110.00	80.00	55.00	35.00	90.00	55.00	70.00	95.00	80.00	95.00	130.00
				Percentage of Values														

* Summary statistics not calculated for rock units with less than ten values.

Statistics per Variable

Variable - Ytterbium [Yb]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - INA

			All Units*		MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGX	RGT	RNG	WFN	WPSN	WRN			
			Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276			
			Number of Values >= D.L.	704	6	51	14	107	23	48	68	10	39	16	71	41	122			
			Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
			Mean	3.08	1.61	3.34	5.70	3.63	3.52	3.91	2.88	2.44	2.45	2.70	3.32	2.62	2.53			
			Standard Deviation	2.11	0.95	1.34	4.17	1.84	2.27	1.55	1.90	1.04	1.08	0.97	2.02	1.75	1.83			
			Skewness	2.50	1.24	0.55	0.64	0.89	1.31	0.66	3.24	0.29	0.024	-0.53	1.61	1.32	2.05			
			Excess Kurtosis	12.65	0.21	0.84	-0.68	1.29	1.94	0.55	18.80	-0.12	-1.06	-0.80	5.81	1.89	6.63			
			Coef. of Var. %	68.74	59.20	40.07	73.14	50.60	64.45	39.54	65.95	42.61	44.07	36.13	60.88	66.91	72.17			
			Std. Error of the Mean	0.06	0.17	0.16	0.93	0.16	0.39	0.21	0.18	0.25	0.13	0.20	0.20	0.19	0.11			
			N	%	Cum %	Lower 95% limit on Mean	2.96	1.26	3.02	3.75	3.32	2.71	3.49	2.53	1.93	2.20	2.27	2.93	2.24	2.32
						Upper 95% limit on Mean	3.20	1.96	3.66	7.65	3.94	4.32	4.33	3.24	2.96	2.70	3.12	3.71	3.01	2.75
						Geometric Statistics														
						Mean	2.51	1.41	3.06	4.12	3.16	2.87	3.59	2.43	2.21	2.18	2.47	2.75	2.13	2.04
						Log10 Mean	0.40	0.15	0.49	0.62	0.50	0.46	0.55	0.39	0.34	0.34	0.39	0.44	0.33	0.31
						Log10 S.D.	0.28	0.22	0.20	0.39	0.25	0.29	0.19	0.26	0.21	0.22	0.20	0.28	0.28	0.28
						Log10 Std. Error of Mean	0.01	0.039	0.023	0.088	0.021	0.051	0.026	0.024	0.050	0.026	0.042	0.027	0.031	0.017
						Lower 95% limit on Mean	2.42	1.17	2.74	2.70	2.87	2.27	3.18	2.18	1.73	1.93	2.02	2.43	1.85	1.89
						Upper 95% limit on Mean	2.60	1.69	3.40	6.29	3.47	3.65	4.05	2.72	2.82	2.46	3.02	3.12	2.46	2.21
						Percentiles														
						Min Value	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	
						25th Xtile	1.00	1.00	2.00	2.00	3.00	2.00	4.00	2.00	2.00	1.00	2.00	2.00	1.00	1.00
						50th Xtile	3.00	1.00	3.00	5.00	3.00	3.00	4.00	3.00	3.00	3.00	3.00	3.00	2.00	2.00
						75th Xtile	4.00	2.00	4.00	8.00	4.00	4.00	5.00	4.00	3.00	3.00	3.00	4.00	3.00	3.00
						80th Xtile	4.00	2.00	4.00	9.00	5.00	5.00	5.00	4.00	3.00	3.00	3.00	5.00	4.00	4.00
						90th Xtile	5.00	3.00	5.00	11.00	6.00	6.00	7.00	4.00	3.00	4.00	4.00	6.00	4.00	5.00
						95th Xtile	7.00	4.00	6.00	13.00	7.00	8.00	7.00	5.00	5.00	4.00	4.00	7.00	6.00	6.00
						98th Xtile	8.00	4.00	6.00	15.00	8.00	11.00	7.00	7.00	5.00	4.00	4.00	8.00	8.00	8.00
						99th Xtile	11.00	4.00	8.00	15.00	9.00	11.00	7.00	9.00	5.00	5.00	4.00	8.00	9.00	10.00
						Max Value	21.00	4.00	8.00	15.00	11.00	11.00	7.00	16.00	5.00	5.00	4.00	14.00	9.00	13.00
			Percentage of Values																	
			0	10	20	30	40	50	60	70	80	90	100	%						

* Summary statistics not calculated for
rock units with less than ten values.

Statistics per Variable

Variable - Zinc [Zn]

Number of Values - 1178

Units - ppm

Detection Limit - 2

Analytical Method - AAS

				All Units*	MFB	PBG	PBN	PG	PGN	PGPX	RGPX	RGpx	RGT	RNG	WFN	WPSN	WRN	
				Number of Values	1178	31	70	20	139	33	54	112	18	73	23	106	82	276
				Number of Values >= D.L.	1177	31	70	20	139	33	54	112	18	73	23	105	82	276
				Number of Missing Values	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ppm 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- . 100.0- . 200.0- . 500.0- .	N 0.5- . 1.0- . 2.0- . 5.0- . 10.0- . 20.0- . 50.0- . 100.0- . 200.0- . 500.0- .	%	Cum %	Mean	96.56	85.94	114.14	116.20	113.61	92.45	106.02	100.96	87.11	92.52	99.74	96.63	83.80	79.85
				Standard Deviation	44.77	29.59	44.20	37.07	57.36	47.26	36.94	41.43	23.63	40.62	40.13	46.48	36.39	35.73
				Skewness	1.23	-0.076	0.82	0.37	1.23	1.38	0.100	1.16	-0.029	0.85	0.69	1.26	0.34	1.59
				Excess Kurtosis	2.28	0.36	0.75	-0.22	1.55	1.74	0.15	1.88	-1.03	0.37	-0.56	1.76	-0.59	4.52
				Coef. of Var. %	46.37	34.43	38.72	31.91	50.49	51.12	34.85	41.03	27.13	43.91	40.23	48.10	43.43	44.74
				Std. Error of the Mean	1.30	5.31	5.28	8.29	4.87	8.23	5.03	3.91	5.57	4.75	8.37	4.51	4.02	2.15
				Lower 95% limit on Mean	94.00	75.08	103.60	98.85	103.99	75.69	95.94	93.21	75.36	83.04	82.39	87.68	75.81	75.61
				Upper 95% limit on Mean	99.12	96.79	124.68	133.55	123.23	109.22	116.10	108.72	98.86	102.00	117.09	105.58	91.80	84.08
				1 0.1 0.1														
				Geometric Statistics														
10 0.8 0.9 127 10.8 11.7	10 0.8 0.9 127 10.8 11.7	10 0.8 0.9 127 10.8 11.7	10 0.8 0.9 127 10.8 11.7	Mean	86.80	79.26	105.99	110.32	100.67	82.32	98.24	92.89	83.86	84.02	92.48	85.35	75.35	72.91
				Log10 Mean	1.94	1.90	2.03	2.04	2.00	1.92	1.99	1.97	1.92	1.92	1.97	1.93	1.88	1.86
				Log10 S.D.	0.21	0.20	0.17	0.15	0.22	0.22	0.19	0.19	0.13	0.20	0.17	0.25	0.21	0.19
				Log10 Std. Error of Mean	0.01	0.036	0.021	0.033	0.019	0.038	0.026	0.018	0.030	0.023	0.036	0.024	0.023	0.011
				Lower 95% limit on Mean	84.44	66.80	96.45	94.00	92.51	68.90	87.27	85.74	72.55	75.56	77.82	76.41	67.69	69.28
				Upper 95% limit on Mean	89.23	94.03	116.46	129.47	109.55	98.34	110.59	100.63	96.94	93.42	109.91	95.34	83.87	76.73
				Percentiles														
				Min Value	2.00	13.00	39.00	45.00	25.00	16.00	71.00	16.00	49.00	23.00	40.00	2.00	20.00	17.00
				25th Xtile	67.00	67.00	84.00	91.00	78.00	63.00	100.00	73.00	72.00	69.00	70.00	68.00	53.00	55.00
				50th Xtile	88.00	88.00	110.00	110.00	100.00	78.00	120.00	93.00	85.00	85.00	89.00	85.00	80.00	76.00
				75th Xtile	120.00	110.00	140.00	130.00	140.00	110.00	140.00	120.00	110.00	110.00	130.00	110.00	110.00	95.00
+-----+ 0 10 20 30 40 50 60 70 80 90 100 %	Percentage of Values			80th Xtile	130.00	110.00	140.00	140.00	150.00	120.00	140.00	130.00	110.00	120.00	130.00	120.00	120.00	100.00
				90th Xtile	150.00	120.00	160.00	160.00	200.00	160.00	180.00	150.00	120.00	150.00	170.00	160.00	130.00	120.00
				95th Xtile	180.00	130.00	210.00	180.00	240.00	210.00	180.00	200.00	130.00	180.00	170.00	190.00	140.00	150.00
				98th Xtile	230.00	160.00	240.00	200.00	280.00	240.00	180.00	210.00	130.00	190.00	190.00	240.00	170.00	180.00
				99th Xtile	240.00	160.00	250.00	200.00	290.00	240.00	180.00	240.00	130.00	210.00	190.00	240.00	180.00	220.00
				Max Value	320.00	160.00	250.00	200.00	320.00	240.00	180.00	240.00	130.00	210.00	190.00	250.00	180.00	260.00

* Summary statistics not calculated for rock units with less than ten values.