

1:20 000  
Scale 1:20 000 - Echelle 1:20 000

1:5 Kilometers  
0 1 2 Kilometers

Imperial Metals  
BRITISH COLUMBIA / COLOMBIE-BRITANNIQUE  
IMPERIAL METALS MOUNT POLLEY MINE / RÉGION DE LA MINE MOUNT POLLEY DE LA SOCIÉTÉ IMPERIAL METALS  
MAGNETIC ANOMALY MAP (RESIDUAL TOTAL FIELD)  
CARTE DES ANOMALES MAGNÉTIQUES (CHAMP RÉSIDUEL TOTAL)

OPEN FILE  
DOSSIER PUBLIC  
4619  
COLOMBIE-BRITANNIQUE / BRITISH COLUMBIA  
2004  
RÉVISÉ ET AJOUTÉ

Données de provenance  
Les données de provenance  
ont été vérifiées et sont  
correctes. Les données de  
provenance ont été  
vérifiées et sont correctes.  
Les données de provenance  
ont été vérifiées et sont  
correctes. Les données de  
provenance ont été  
vérifiées et sont correctes.

PUBLISHED 2004 / RÉVISÉ 2004  
DOSSIER PUBLIC  
2004-10  
IMPERIAL METALS  
MOUNT POLLEY MINE  
2004

This map was compiled from data acquired in the area of the Imperial Metals Mount Polley Mine, British Columbia, by the Geological Survey of Canada, as part of the magnetic anomaly mapping program. The survey was completed between September 25 and 26, 2003, using an automatic ADONIS/ADONIS system.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.


The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.

The magnetic data were recorded at a 1.5 second sample rate, 200 channels, using a 1000 Hz bandwidth. The data were corrected for magnetic declination and converted to a common datum (1980). The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate. The data were then processed using a 1000 Hz bandwidth, 200 channels, and a 1.5 second sample rate.



Imperial Metals  
BRITISH COLUMBIA / COLOMBIE-BRITANNIQUE  
IMPERIAL METALS MOUNT POLLEY MINE / RÉGION DE LA MINE MOUNT POLLEY DE LA SOCIÉTÉ IMPERIAL METALS  
MAGNETIC ANOMALY MAP (RESIDUAL TOTAL FIELD)  
CARTE DES ANOMALES MAGNÉTIQUES (CHAMP RÉSIDUEL TOTAL)