

**PETER LAKE AND WOLLASTON LAKE AREAS, SASKATCHEWAN**

In 2004, Fugro Airborne Surveys completed a multi-sensor airborne geophysical survey of the Peter Lake and Wollaston Lake areas, Saskatchewan, for the Geological Survey of Canada and Saskatchewan Industry and Resources. The purpose of the survey was to obtain quantitative gamma-ray spectrometric and aeromagnetic data. The survey was flown over two seasons, from August 31 to September 25, 2003 and July 15 to September 30, 2004 using Geoscan Grand Carver 300-S aircraft.

**Gamma-ray Spectrometric Data**

The airborne gamma-ray measurements were made with an Elicon CR800 gamma-ray spectrometer using 1024 x 1024 x 400 mm NaI(Tl) crystals. The main detector array consisted of twelve crystals (total volume 50.4 m<sup>3</sup>). Three crystals (total volume 12.0 m<sup>3</sup>) shielded by the main array, were used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by <sup>40</sup>K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (<sup>214</sup>Pb for uranium and <sup>214</sup>Pb for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are:

Potassium (40K)	1370 - 1570 keV
Uranium (238U)	1060 - 1580 keV
Thorium (232Th)	2410 - 2810 keV

Gamma-ray spectra were recorded at one-second intervals at a planned beam clearance of 125 m and an air speed of 210 km/h. Noise Adjusted Singular Value Decomposition (NASVD) analysis was carried out on the full spectrum 256 channel data to reduce statistical noise in the windowed data. During processing, the spectra were energy calibrated, and counts were accumulated in the windows described above. Counts from the radon detector were removed in a 1800 - 1890 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, and for background activity from cosmic radiation. The radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations of altitude from the planned beam clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium 90.5 cps/%  
Uranium 11.4 cps/ppm  
Thorium 5.7 cps/ppm

Corrected data were filtered and interpolated to a 100 m grid for the 1:250 000 scale maps and a 50 m grid for the 1:50 000 scale maps. The results of an airborne gamma-ray spectrometry survey represent the average surface concentrations that are influenced by varying amounts of stragor, overburden, vegetation cover, soil moisture and surface water. As a result the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in microgray per hour was produced from measured counts between 400 and 2810 keV.

**Magnetic Data**

The Grand Carver aircraft was equipped with a Scintrex CS-2 cesium vapour magnetometer mounted in a slingshot to the rear of the aircraft. The system recorded readings every 0.1 seconds with a noise level of less than 0.01 nT. Magnetic interference caused by aircraft maneuvers were compensated using a MAG-ACDC magnetic compensation. Ground stations were recorded using a Fugro CF-1 cesium vapour magnetometer.

After editing the raw data, low-pass filtered digital readings were subtracted from each unfiltered aeromagnetic reading. The intersections of traverses and control lines were identified and the difference in the magnetic values was computed, analyzed and manually verified to obtain the leveling network. The International Geomagnetic Reference Field was calculated and removed using a fixed date (2004.05.15) and an altitude of 545 m for each data point. The corrected magnetic data was resampled to a 100 m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

**Positional Data**



The 400 m spaced survey lines were oriented southeast - northwest and 4000 m spaced control lines were oriented southwest - northeast. Survey and control line positions and elevations were pre-processed using S.S. Sprock's Drone software. Positional data were recorded using a Novatel ProPak NR6010 GPS ground station data were combined with airplane GPS data to produce differentially corrected positional data with an accuracy of 2 to 5 m.

**Data Presentation**

Colour levels and contours were calculated for each grid and combined with map surround information to create postscript plot files, which were plotted using Fugro's HP DesignJet colour plotters.


**PLANIMETRIC SYMBOLS**

Topographic Contour	.....
Railway	.....
Power Line	.....
Discharge	.....
Roads	.....
Flight Lines, Rowal	.....



This airborne geophysical survey and the production of this map were funded by the Government of Saskatchewan's Mineral Exploration Incentive Program.

**GEOPHYSICAL SERIES - 64E/4 - ROBSON LAKE  
SASKATCHEWAN  
NATURAL AIR ABSORBED DOSE RATE MAP**



UNIVERSITY OF TORONTO LIBRARY  
North American Datum 1983  
© Her Majesty the Queen in Right of Canada 2005  
Digitized topographic base information provided by Saskatchewan Industry and Resources.

<b>OPEN FILE DOSSIER PUBLIC 4849</b>	Open file are products that have not gone through the GSC formal publication process.	<b>SASKATCHEWAN INDUSTRY and RESOURCES</b>
<b>2005</b>	Les documents non publiés ne sont pas soumis au processus officiel de publication de la GSC.	<b>OPEN FILE 2005-3</b>
<b>SHEET 1 OF 10 FEUILLE 1 OF 10</b>		<b>SHEET 1 OF 10</b>

**NATURAL AIR ABSORBED DOSE RATE MAP  
ROBSON LAKE  
SASKATCHEWAN  
NTS 64E/4**



MAP LOCATION - LOCALISATION DE LA CARTE

Recommended citation:  
Ford, K.L., Cameron, J.M., Dumore, R., Pothin, J., Shives, R.B.K., Delaney, G., and Blomson, W.  
2005. Geophysical Series 64E/4. Robson Lake, Saskatchewan.  
Geological Survey of Canada Open File 4849.  
Saskatchewan Industry and Resources Open File 2005-3  
Scale 1:50 000