

PETER LAKE and WOLLASTON LAKE AREAS, SASKATCHEWAN

In 2004, Fugro Airborne Surveys completed a multi-sensor airborne geophysical survey of the Peter Lake and Wollaston Lake areas, Saskatchewan, for the Geological Survey of Canada and Saskatchewan Industry and Resources. The purpose of the survey was to obtain quantitative gamma-ray spectrometric and aeromagnetic data. The survey was flown over two seasons, from August 31 to September 29, 2003 and July 15 to September 30, 2004 using Casper Grand Caravan 208-B aircraft C-50CA.

Gamma-ray Spectrometric Data

The airborne gamma-ray measurements were made with an Elicor/Ortec GR202 gamma-ray spectrometer using 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of twelve crystals (total volume 50.4 litres). Three crystals (total volume 12.6 litres) shielded by the main array, were used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least-squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by ⁴⁰K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (214Bi for uranium and 208Tl for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are:

Potassium (40K)	1370 - 1570 keV
Uranium (238U)	1860 - 1960 keV
Thorium (232Th)	2410 - 2510 keV

Gamma-ray spectra were recorded at one-second intervals at a planned terrain clearance of 125 m and an air speed of 210 km/h. Noise Adjusted Singular Value Decomposition (NASVD) analysis was carried out on the full spectrum 256 channel data to reduce statistical noise in the windows used. During processing, the spectra were energy calibrated, and counts were accumulated into the windows described above. Counts from the radon detectors were recorded in a 1860 - 1960 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, and for background activity from cosmic radiation, the radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for special scattering in the ground, air and detectors. Corrections for deviations of altitude from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium	90.5 cps/m
Uranium	11.4 cps/m
Thorium	1.7 cps/m

Corrected data were filtered and interpolated to a 100 m grid for the 1:250 000 scale maps and to a 50 m grid for the 1:50 000 scale maps. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of terrain, vegetation, soil moisture and surface water. As a result the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in nanograys per hour was calculated from measured counts between 400 and 2610 keV.

Magnetic Data

The Grand Caravan aircraft was equipped with a Schriener CS-2 cesium vapour magnetic sensor mounted in a slinger to the rear of the aircraft. The system recorded readings every 0.1 seconds with a noise level of less than 0.01 nT. Magnetic interference caused by aircraft maneuvers were compensated using an RMS AADCII Magnetic compensator. Diurnal variations were recorded using a Fugro CF-1 cesium vapour magnetometer.

After editing the survey data, low pass filtered diurnal readings were subtracted from each unfiltered aeromagnetic reading. The intersections of traverse and control lines were determined and the differences in the magnetic values were computed, analyzed and manually verified to obtain the leveling network. The International Geomagnetic Field was calculated and removed using a field date (20040815) and an altitude of 545 m for each data point. The corrected magnetic data was interpolated to a 100 m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

Positional Data

The 400 m spaced survey lines were oriented southeast - northwest and 4000 m spaced control lines were oriented southwest - northeast. Survey and control line positions and elevations were pre-planned using G.S.C. Smooth Drapage software. Positional data were recorded using a Novatel ProPak 4901/101. GPS ground station data were combined with airborne GPS data to produce differentially corrected positional data with an accuracy of 2 to 5 m.

Data Presentation

Colour levels and contours were calculated for each grid and combined with map ground information to create postscript plot files, which were plotted using Fugro's HP Designist colour plotters.

PLANIMETRIC SYMBOLS


- Topographic Contour
- Railway
- Power lines
- Drainage
- Roads
- Flight lines, 95/340

Positional Data

NATIONAL TOPOGRAPHICAL SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX

Recommended citation:
Ford, K.L., Carson, J.M., Dumont, R., Poirier, J., Shives, R.B.K., Delaney, G., and Slimmon, W.
2005. Geophysical Series - NTS 64L/2 - Fidler Bay, Saskatchewan.
Geological Survey of Canada Open file 4867.
Saskatchewan Industry and Resources Open file 2005-21
Scale 1:50 000


This airborne geophysical survey and the production of this map were funded by the Government of Saskatchewan's Mineral Exploration Incentive Program



**GEOPHYSICAL SERIES - 64L/2 - FIDLER BAY
SASKATCHEWAN**

URANIUM / POTASSIUM MAP

Scale 1:50 000 - Échelle 1/50 000



**OPEN FILE
DOSSIER PUBLIC
4867**

2005

SHEET 6 OF 10
FEUILLE 6 OF 10

Open file are products that have not gone through the GSC formal publication process.

Les documents publics sont des produits qui n'ont pas été soumis au processus officiel de publication de la GSC.

**SASKATCHEWAN
INDUSTRY and
RESOURCES**

**OPEN FILE
2005-21**

SHEET 6 OF 10

URANIUM / POTASSIUM MAP

**FIDLER BAY
SASKATCHEWAN**

NTS 64L/2



Universal Transverse Mercator Projection
NAD83 / UTM zone 19W
Système de coordonnées géographiques universelles
© Her Majesty the Queen in Right of Canada 2005 © Sa Majesté la Reine du chef du Canada 2005
Digital topographic base information provided by Saskatchewan Industry and Resources.