

In 2004 and 2005, Sander Geophysics Limited completed four multi-sensor airborne geophysical surveys in the Nahanni River area of the Northwest Territories for Parks Canada (Prairie Creek, Caribou River and Flat River) and the Government of the Northwest Territories (Sekwi Range). The Geological Survey of Canada provided survey supervision and quality control. The purpose of the survey was to obtain quantitative gamma-ray spectrometric and aeromagnetic data. The survey was flown over two seasons, from August 26 to October 3, 2004 and the second phase from August 13 to August 20, 2005 using the SGL Asar 330 B helicopter, C-GSGH.

**Gamma-ray Spectrometer Data**  
The airborne gamma-ray measurements were made with an Exploranium GR620 gamma-ray spectrometer using nine 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of eight crystals (total volume 33.6 litres). One crystal (total volume 4.2 litres), shielded by the main array, was used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium ( $^{40}\text{K}$ ) is measured directly from the 1460 keV gamma-ray photons emitted by  $^{40}\text{K}$ , whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products ( $^{232}\text{Th}$  for uranium and  $^{230}\text{Th}$  for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e.  $^{232}\text{U}$  and  $^{230}\text{Tl}$ . The energy windows used to measure potassium, uranium and thorium are:

Potassium ( $^{40}\text{K}$ )	1360 - 1530 keV
Uranium ( $^{232}\text{U}$ )	1660 - 1860 keV
Thorium ( $^{230}\text{Tl}$ )	2410 - 2810 keV

Gamma-ray spectra were recorded at one-second intervals at a planned terrain clearance of 135 m and an air speed of 120 km/h. Noise Adjusted Singular Value Decomposition (NASVD) analysis was carried out on the full spectrum 256-channel data to reduce statistical noise in the windowed data. During processing, the spectra were energy calibrated, and counts were accumulated into the windows described above. Counts from the radon detectors were recorded in a 1660 - 1860 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window widths were constant in time, and for background activity from atmospheric radiation, the sensitivity of the aircraft was checked every 15 minutes. The window widths were corrected for the scattering of the atmosphere, air and detectors. Corrections for deviations of altitude from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium	56.5 cps/% (2004)	50.0 cps/% (2005)
Uranium ( $^{232}\text{U}$ )	9.0 cps/ppm (2004)	6.3 cps/ppm (2005)
Thorium ( $^{230}\text{Tl}$ )	3.7 cps/ppm (2004)	3.2 cps/ppm (2005)

Corrected data were filtered and interpolated to a 100m grid for both the 1:50 000 scale and 1:250 000 scale maps. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of overburden, vegetation, cover, soil moisture and surface water. As a result the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in nanograys per hour was produced from measured counts between 400 and 2810 keV.



**Magnetic Data**  
The helicopter was equipped with a Scintrex CS-2 cesium vapour magnetic sensor mounted in a bird suspended 30 m below the aircraft. The system recorded readings every 0.1 seconds with a noise level of less than 0.02 nT. Magnetic interferences caused by aircraft maneuvers were compensated using NAV-NTS (Navigation and Timing System) and GPS data. The magnetic field was calculated and removed for each flight. The airborne magnetometer data were IGRF corrected, using the location, altitude and date of each point. The IGRF was calculated using the IGRF 2000 model.

The corrected magnetic data was interpolated to a 100m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

**Positional Data**  
Survey line spacing of 500 m and control line spacing of 4000 m was used for the Prairie Creek, Caribou River and Flat River survey blocks. Survey line spacing of 400 m and control line spacing of 2400 m was used for the Sekwi Range survey block. Survey lines were oriented N-S for the Prairie Creek, Caribou River and Flat River survey blocks and E-W for the Sekwi Range survey block. Survey lines were spaced 400 m apart N-E. Survey and control line positions were pre-planned using Sander Geophysics Limited, Smooth Drift software. Terrain clearance was monitored by radar altimeter. Positional data were recorded using a dual frequency Novatel Millenium system. GPS ground station data were combined with airborne GPS data to produce differentially corrected positional data with an accuracy of 2 to 5 m.

**Data Presentation**  
Colour levels and contours were calculated for each grid and combined with map surround information to create HP RTL plot files, which were plotted using SGL's HP DesignJet colour plotters.

**Project Funding**  
The Prairie Creek, Caribou River and Flat River surveys were funded by Parks Canada through the Mineral and Energy Resource Assessment Project. The Sekwi Range survey was funded by the Northwest Territories Geoscience Office. Technical expertise and contract administration were provided by the Radiation Geophysics and Regional Geophysics Sections of the Geological Survey of Canada.



Recommended citation:  
Carson, J.M., Dumont, R., Potvin, J., Buckle, J., Shives, R.B.K., Harvey, B., and Fischer, B.  
2006: Geophysical Series - NTS 105 P/12, Northwest Territories;  
Geological Survey of Canada, Open File 5177;  
Northwest Territories Geoscience Office Contribution 0020;  
scale 1:50 000.

This airborne geophysical survey and the production of this map were funded by the Northwest Territories Geoscience Office.

### GEOPHYSICAL SERIES - NTS 105 P/12 NORTHWEST TERRITORIES

#### URANIUM / POTASSIUM MAP


Scale 1 : 50 000 - Échelle 1 / 50 000

km 1 0 2 4

Universal Transverse Mercator Projection  
North American Datum 1983  
© Her Majesty the Queen in Right of Canada 2006

Projection transversale universelle de Mercator  
Système de référence géodésique nord-américain, 1983  
© Sa Majesté la Reine du chef du Canada 2006

Digital Topographic Data provided by Geomatics Canada, Natural Resources Canada



OPEN FILE  
DOSSIER PUBLIC  
5177  
GEOLOGICAL SURVEY OF CANADA  
COMMISSION GÉOLOGIQUE DU CANADA  
2006

Open files are products that have not gone through the GSC formal publication process.  
Les fichiers ouverts sont des produits qui n'ont pas été soumis au processus officiel de publication de la CGC.

SHEET 6 OF 10  
FEUILLET 6 DE 10

NWT GEOSCIENCE  
OFFICE  
CONTRIBUTION  
0020  
2006

SHEET 6 OF 10