

This airborne geophysical survey and the production of this map were funded by the Northwest Territories Geoscience Office.

## GEOPHYSICAL SERIES - NTS 105 P/12 NORTHWEST TERRITORIES

### TERNARY RADIODELLEMENT IMAGE MAP

Scale 1 : 50 000 - Échelle 1 / 50 000

Universal Transverse Mercator Projection  
North American Datum 1983  
© Her Majesty the Queen in Right of Canada 2006  
Système de référence géodésique nord-américain, 1983  
© Sa Majesté la Reine du chef du Canada 2006

Digital Topographic Data provided by Geomatics Canada, Natural Resources Canada

**OPEN FILE  
DOSSIER PUBLIC**  
**5177**  
GEOLOGICAL SURVEY OF CANADA  
COMMISSION GÉOLOGIQUE DU CANADA  
2006  
SHEET 8 OF 10  
FEUILLET 8 DE 10

Open files are products that have not gone through the GSC formal publication process.  
Les dossiers publics sont des produits qui n'ont pas été soumis au processus officiel de publication de la CGC.

**NWT GEOSCIENCE  
OFFICE  
CONTRIBUTION**  
**0020**  
2006  
SHEET 8 OF 10

Recommended citation:  
Carson, J.M., Dumaine, P., Poirier, J., Shives, R.B.K., Harvey, B., and Fischer, B.,  
2006, Geological Series - NTS 105 P/12, Northwest Territories,  
Geological Survey of Canada, Open File 5177,  
Northwest Territories Geoscience Office Contribution 0020;  
scale 1:50 000.

In 2004 and 2005, Sander Geophysics Limited completed four multi-sensor airborne geophysical surveys in the Nahanni River area of the Northwest Territories (Prairie Creek, Caribou River and Flat River) and the Government of the Northwest Territories (Selkirk Range). The Geological Survey of Canada provides survey supervision and quality control. The purpose of the survey was to obtain quantitative gamma-ray spectrometric and aeromagnetic data. The survey was flown over two seasons, from August 26 to October 3, 2004 and the second season from July 30 to August 20, 2005 using the SGLAstar 350 B-3 helicopter C-GSGH.

#### Gamma-ray Spectrometer Data

The gamma-ray spectrometer data were made with an Explorair GRB20 gamma-ray spectrometer using nine 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of eight crystals (total volume 33.6 litres). One crystal (total volume 4.2 litres), shielded by the main array, was used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by  $K^40$ , whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products ( $^{232}U$  for uranium and  $^{233}Th$  for thorium). Although these daughters are far removed from their respective parents, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e.  $^{232}U$  and  $^{233}Th$ . The energy windows used to measure potassium, uranium and thorium are:

|                        |                    |
|------------------------|--------------------|
| Potassium ( $K^40$ )   | 56.5 cps/% (2004)  |
| Uranium ( $^{232}U$ )  | 9.0 cps/ppm (2004) |
| Thorium ( $^{233}Th$ ) | 3.7 cps/ppm (2004) |

Gamma-ray spectra were recorded at one-second intervals at a planned terrain clearance of 135 m and an air speed of 120 km/h. Noise Adjusted Standard Deviation (NASVD) analysis was carried out on the data to remove noise from the signal in the recorded data. During processing, counts were integrated into the windows described above. Counts from the radon detectors were recorded in a 1660 - 1860 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, and for background activity from cosmic radiation, the radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations of altitude from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

|           |                    |
|-----------|--------------------|
| Potassium | 56.5 cps/% (2004)  |
| Uranium   | 9.0 cps/ppm (2004) |
| Thorium   | 3.7 cps/ppm (2004) |

Corrected data were filtered and converted to ground concentrations for the 1:50 000 scale maps. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of overburden, vegetation cover, soil moisture and surface water. As a result the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in nanograys per hour was produced from measured counts between 400 and 2810 keV.

#### Magnetic Data

The helicopter magnetometer with a Sodarlex CS-4 cernier magnetic sensor was in a bird suspended 30 m below the aircraft. The system recorded readings every 10 seconds at a noise level of less than 0.02 nT. Magnetic anomalies caused by surface features were compensated using an RMS ADDCII Magnetic compensator. Diurnal variations and GPS fluctuations were recorded using a Sander Geophysics Ground Station Recording System. The International Geomagnetic Reference Field was calculated daily and removed for each flight. The airborne magnetometer data was IGRF corrected, using the location, altitude and date of each point. The IGRF was calculated using the IGRF 2003 model.

The corrected magnetic data was interpolated to a 100 m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

#### Positional Data

Survey line spacing of 500 m and control line spacing of 4000 m was used for the Prairie Creek, Caribou River and Flat River survey blocks. Survey line spacing of 400 m and control line spacing of 2400 m was used for the Selkirk Range survey block. Survey lines were oriented N-S for the Prairie Creek and Caribou River areas. For the Flat River area survey lines were oriented NW-SE and for the Selkirk Range survey lines were oriented SW-NE. Survey and control line positions were pre-planned using Sander Geophysics Limited, Smooth Drape software. Terrain clearance was monitored by radar altimeter. Positional data were recorded using a dual frequency Novatel Millenium GPS. Ground station data were combined with airborne GPS data to produce differentially corrected positional data with an accuracy of 2 to 3 m.




#### Data Presentation

Colour levels and contours were calculated for each grid and combined with map surround information to create HP RTL plot files, which were plotted using SGL's HP DesignJet colour plotters.

#### Project Funding

The Prairie Creek, Caribou River and Flat River surveys were funded by Parks Canada through the Mineral and Energy Resource Assessment Project. The Selkirk Range survey was funded by the Northwest Territories Geoscience Office. Technical expertise and contract administration were provided by the Radiation Geophysics and Regional Geophysics Sections of the Geological Survey of Canada.

#### PLANIMETRIC SYMBOLS



NATIONAL TOPOGRAPHICAL SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX  
SYSTÈME NATIONAL DE RÉFÉRENCE CARTOGRAPHIQUE ET INDEX DES CARTES GÉOPHYSIQUES