

In 2004 and 2005, Flu Airborne Surveys completed nine multi-sensor airborne geophysical surveys in the central region of British Columbia for the Geological Survey of Canada, the British Columbia and Yukon Chamber of Mines, Yukofone First Nation, and five industry partners, including Seabridge Resources Inc., Yankee Hat Minerals Ltd., Richfield Ventures Corp., GWR Resources Inc. and Amarc Resources Ltd. The Geological Survey of Canada provided survey supervision and quality control. The purpose of the surveys was to obtain quantitative gamma-ray spectrometric and magnetic data. The surveys were flown over two seasons, from September 18 to November 17, 2004 and from June 15 to August 8, 2005 using Agave 350-350 and 350-600 helicopters. C-GECC, Inc. C-GECC.

Gamma-ray Spectrometric Data

Gamma-ray Spectrometric Data

The dilute gamma-ray measurements were made with an Exploration GR60 gamma-ray spectrometer using nine $102 \times 102 \times 406$ mm NaI (Tl) crystals. The main detector array consisted of eight crystals (total volume 33.6 liters). One crystal (total volume 4.2 liters), shielded by the main array, was used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural potassium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by ^{40}K , whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (^{214}Bi for uranium and ^{208}Tl for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectroscopic measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are:

Potassium (^{40}K) 1360 - 1500 keV
 Uranium (^{234}Bq) 1660 - 1860 keV
 Thorium (^{230}Th) 2410 - 2310 keV

Gamma ray spectra were recorded at one-second intervals at a planned minimum clearance of 100m or 90m depending on the survey area and an air speed of 125km/h. The total, potassium, uranium and thorium window counts were derived from the recorded 256 channel spectra. During processing, the spectra were energy calibrated, and counts were accumulated into the windows of interest. The total window was divided into 1600 1400 keV windows and the total gamma radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, and for background activity from cosmic radiation, the radioactivity of the aircraft and atmospheric radionuclide decay products. The window data were then used to calculate the concentration of potassium, uranium and thorium in the air at the altitude from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium 57.3 cps/% (2004) 56.9 cps/% (2005)
Uranium 6.7 cps/ppm (2004) 8.4 cps/ppm (2005)
Thorium 3.6 cps/ppm (2004) 3.7 cps/ppm (2005)

Corrected data were filtered and interpolated to a 100m grid for the 1:250 000 scale maps and to a 50m grid for the 1:20 000 and 1:50 000 scale maps. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of outcrop, overburden, vegetation cover, soil moisture and surface water. As a result, the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in nanograys per hour was produced from measured counts between 410 and 2810 keV.

Magnetic Data

Magnetic Data
The helicopter was equipped with a Scintrex CS-2 cesium vapour magnetic sensor mounted in a HM1 high-resolution single sensor stinger mounted system. The system recorded readings every 0.1 seconds with a noise level of less than 0.01 nT. Magnetic interferences caused by aircraft maneuvers were compensated using an RMS AADCII magnetic compensator. Diurnal variations and GPS fluctuations were recorded using a Fugro CF1 base station.


After editing the survey data, the intersections of traverse and control lines were determined and the differences in the magnetic values were computed, analyzed and manually verified to obtain the leveling network. The International Geomagnetic Reference Field was calculated and removed using a fixed date of August 2, 2005 and an altitude of the differentially corrected GPS height for each data point. The corrected magnetic data was interpolated to a 50m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

Positional Data

Positional Data
Line spacing and direction for survey and control lines were selected for each block to ensure the best intersection of local geological features. Terrain clearance was monitored by radar altimeter. Positional data were recorded using a dual frequency Novatel Millennium system. GPS groundstation data were combined with airborne GPS data to produce differentially corrected positional data with an accuracy of 2 to 5 m.

Data Presentation

Data Presentation
Colour levels and contours were calculated for each grid and combined with map surround information to create postscript plot files, which were plotted using HP DesignJet colour plotters.



Planimetric Symbols


Topographic Contour ,
Distance

Drainage
Brooks

Culture

Railway

Flight lines, fiducial ...



NATIONAL TOPOGRAPHICAL SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX
SYSTÈME NATIONAL DE RÉFÉRENCE CARTOGRAPHIQUE ET INDEX DES CARTES GÉOPHYSIQUES

Recommended citation:
Cassidy, J.M., Dumont, R., Poivin, J., Shives, R.R.K., Harvey, B.J.A., Buckle, J.L. and Lane, B.
2009. Geophysical Series - NTG 909/0, 909/1, 909/2, 909/2 - Taltapin Lake, British Columbia;
Geophysical Survey of Canada, Open File 5267.