GEOPHYSICAL SERIES
FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD



GEOLOGICAL SURVEY OF CANADA COMMISSION GÉOLOGIQUE DU CANADA

High Sensitivity Airborne Gamma-Ray Spectrometric and Aeromagnetic Surveys
Central British Columbia, 2004 - 2005

In 2004 and 2006, Fugro Airborne Surveys completed nine multi-sensor airborne geophysical surveys in the central region of British Columbia for the Geological Survey of Canada, the British Columbia and Yukon Chamber of Mines, Yekooche First Nation, and five industry partners, including Serengeti Resources Inc., Yankee Hat Minerals Ltd.,Richfield Ventures Corp.,SIMR Resources Inc., and Arctos Resources Ltd. The Geological Survey of Canada provided survey, supervision, and quality control. The purpose of the surveys was to obtain quantitative gamma-ray spectrometric and magnetic data over the Wells area. Survey operations were carried out between April 30 and May 31, 2004 and June 15 to August 9, 2005 using AStar 350-B2 and 350-B3 helicopters, C-GECC, and C-FGSC.

Gamma-ray Spectrometric Data

The airborne gamma-ray measurements were made with an Exploranium GR820 gamma-ray spectrometer using nine 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of eight crystals (total volume 33.6 litres). One crystal (total volume 4.2 litres), shielded by the main array, was used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural potassium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by 40K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (214Bi for uranium and 208Tl for thorium). Although these daughters are far down their respective decay series, it is assumed that secular equilibrium exists. For this survey, uranium and spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are:

Potassium (40K): 1360 - 1560 keV
Uranium (214Bi): 1660 - 1860 keV
Thorium, (208Tl) 2410 - 2810 keV

Gamma-ray spectra were recorded at one-second intervals at a planned terrain clearance of 120m or 90m depending on the survey area and an air speed of 128km/h. The total, potassium, uranium and thorium window counts were derived from the recorded 256 channel spectra. During processing, the spectra were energy calibrated, and counts were accumulated into the windows described above. Counts from the radon detectors were recorded in a 1660 - 1860 keV window and subtracted from the uranium counts. The uranium, thorium and total counts, but not the potassium counts were corrected for dead time, and for background activity from cosmic radiation, the radioactivity of the aircraft and atmospheric radon decay products.The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations of altitude from the planned terrain clearance and for variation of temperature and pressure were made after the method of the International Atomic Energy Agency. Sensitivities to uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium 57.3 cps/% (2004) 56.8 cps/% (2005)
Uranium 6.7 cps/ppm (2004) 8.4 cps/ppm (2005)
Thorium 3.6 cps/ppm (2004) 3.7 cps/ppm (2005)

Corrected data were filtered and interpolated to a 100m grid for the 1:250 000 scale maps and to a 50m grid for the 1:25 000 and 1:50 000 scale maps. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of vegetation, overburden and bedrock exposure. Because of the shallow depth of soil, the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose rate in nanograys per hour was produced from measured counts between 410 and 2810 keV.

Magnetic Data

The helicopter was equipped with a Scintrex CS-3 cesium vapour magnetic sensor mounted in a HH1 high-resolution single sensor stinger mounted system. The system recorded readings every 0.1 seconds with a noise level of less than 0.01 nT. Magnetic interferences caused by aircraft manoeuvers were compensated using an RMS AADCII Magnetic compensator. Diurnal variations and GPS fluctuations were recorded using a Fugro CP1 base station.

After editing the survey data, the intersections of traverse and control lines were determined and the differences in the magnetic values were computed, analyzed and manually verified to obtain the leveling network. The International Geomagnetic Reference Field was calculated and removed using a fixed date of June 20, 2005 for western blocks and July 17, 2005 for eastern blocks and an altitude of the differentially corrected GPS height for each data point.The corrected magnetic data was interpolated into a grid using the minimum curvature algorithm.The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

Positional Data

Flight path and direction for survey and control lines were selected for each block to ensure the best intersection of local geological features. Terrain clearance was monitored by radar altimeter. Positional data were recorded using a dual frequency Novatel Millenium system.GPS groundstation data were combined with airborne GPS data to produce differentially corrected positional data with an accuracy of 2 to 5 m.

Data Presentation

Colour levels and contours were calculated for each grid and combined with map surround information to create postscript plot files, which were plotted using HP DesignJet colour plotters.

Planimetric Symbols

Topographic Contour 100
Drainage 100
Roads 100
Culture 100
Railway 100
Flight lines, fiducial 10100 4000



NATIONAL TOPOGRAPHICAL SYSTEM REFERENCE AND GEOPHYSICAL MAP INDEX
SYSTÈME NATIONAL DE RÉFÉRENCE CARTOGRAPHIQUE ET INDEX DES CARTES GÉOPHYSIQUES

Recommended citation:
Geological Survey of Canada, Pilkington, M., Pohon, J., Brown, R.B.K., Harvey, B.J.A. and Buhrke, J.L. 2006: Geophysical Series - NTS 93H/4, 93A/13 - Wells, British Columbia; Geological Survey of Canada, Open File 5289; scale 1:50 000.

This airborne geophysical survey and the production of this map were funded by Richfield Ventures Corp.

RICHFIELD VENTURES CORP.

Natural Resources Canada / Ressources naturelles Canada
Canada

GEOPHYSICAL SERIES - NTS 93H/4, 93A/13 - WELLS
BRITISH COLUMBIA

FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD

Scale 1:50 000 - Échelle 1:50 000
Kilometres 0 1 2 3 4 Kilometres
NAD 83 / UTM Zone 10N

Universal Transverse Mercator Projection
Projection universel transverse de Mercator
© Her Majesty the Queen in Right of Canada 2006
© Sa Majesté la Reine du Chef du Canada 2006

Digital Topographic Data provided by Geomatics Canada, Natural Resources Canada

OPEN FILE
DOSSIER PUBLIC
5289
GEOLOGICAL SURVEY OF CANADA
COMMISSION GÉOLOGIQUE DU CANADA
2006
SHEET 10 OF 10
FEUILLET 10 DE 10

Open files are products that have not gone through the formal publication process.

Les dossiers publics sont des produits qui n'ont pas été soumis au processus de publication de la CGC.

FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD

WELLS
BRITISH COLUMBIA

93H/4, 93A/13