

DESCRIPTIVE NOTES

This Radioactivity Map of the Athabasca Basin Region is one of a set of eight 1:1 000 000 regional compilation maps that include three measured variables (potassium (K), equivalent uranium (eU) and equivalent thorium (Th)) and their derived products. The derived products include the natural air-absorbed dose rate calculated from a linear combination of K, U, and Th; the ratios eU/K, eU/Th, and Th/K; and the binary radioactive element maps (Brome et al., 1997). This set of maps was produced using data from the digital archives of the Radiation Geophysics Section from airborne surveys conducted between 1974 and 2005. The surveys were flown by the Geological Survey of Canada (GSC) and contracted aircraft, using federal, provincial, and joint federal-provincial government funding. Most were originally published as 1:1 000 000 colour raster maps (Carson et al., 2002a, 2002b, 2002c) and as 1:250 000 or 1:500 000 line contour or colour interval maps and stacked profiles, as GSC Open Files or Geophysical Series Maps.

Data was collected using 50 lines of sodium iodide detectors, at a nominal terrain clearance of 120 metres along flight lines spaced at between 3000 and 400 metre intervals. The location of these surveys flown with flight lines spaced 1000 metres or less apart are indicated on the map. These surveys exhibit a higher frequency colour texture. The closer line spacing allows increased spatial resolution of radioactive element signatures, supporting more detailed interpretation.

Potassium is measured directly from the 1460 keV gamma ray photons emitted by <sup>40</sup>K. Uranium and thorium, however, are determined indirectly from gamma ray photons emitted by daughter products (214Pb and 208Tl), respectively, assuming equilibrium between daughter and parent isotopes. For this reason, gamma ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium (eU) and equivalent thorium (eTh).

Standard energy windows were used to record the gamma ray counts. These are 1370–1570 keV for potassium, 1600–1800 keV for uranium, 2410–2810 keV for thorium and 400–2810 keV for total radioactivity. Several corrections are applied to the raw window counts prior to conversion to standard concentration units, including system dead time, background activity from cosmic radiation, the aircraft and atmospheric radon decay products, spectral scattering in the ground, air and detectors, variations of altitude from the planned terrain clearance, and temperature and pressure variations.

These maps depict radioactivity originating from the upper 30 cm of the earth's surface. The influence of varying amounts of topsoil, overstorey, vegetation, soil moisture, and surface water results in measured concentrations that are usually lower than underlying bedrock concentrations.

Throughout the diverse lithotectonic terranes surveyed, the geochemical information provided by variations in potassium, uranium, and thorium concentrations presented in a coloured contour format supports mapping of bedrock surface geology and mineral exploration, at regional and local scales (Shives et al., 1995). More detailed interpretation is encouraged through the use of the original line data, available from the Geological Survey of Canada.

In areas with little or discontinuous drift cover, the radioactive element patterns provide direct assistance to bedrock geological mapping, depicting both macroscopic lithological variations and cryptic compositional variations (Shives et al., 1995). In areas covered by thick drift (and/or glaciolacustrine) glaciolacustrine or other reworked glacial deposits the radioactive element patterns may delineate the types of surficial materials but will reflect local bedrock compositions to a lesser degree, or not at all. Shives et al. (1995, 1997) show that radioactive element patterns offer valuable direct and indirect exploration guides for a variety of mineral commodities. Direct applications include the search for radiogenic mineral deposits where uranium and thorium are the primary targets, or where one or more of the radioactive elements are present as an associated trace element. Gamma ray spectrometry can also provide valuable indirect information for mineral exploration where one or more of the radioactive elements is either enriched or depleted as a result of alteration associated with mineralization.

The Radiation Geophysics Section acknowledges Drs. A.G. Darby, K.A. Richardson, G. Strain, and R.L. Gray for their contributions to program development and technical leadership.

REFERENCES

Brome, J., Carson, J.M., Grant, J.A., and Ford, K.L., 1997: A modified terrain radiometric mapping technique and its application to the South Coast of Newfoundland; Geological Survey of Canada, Paper 87-14.

Carson, J.M., Holman, P.B., Ford, K.L., Grant, J.A., and Shives, R.B.K., 2002a: Athabasca Gamma Ray Spectrometry Correlation Series, Lake Athabasca, Alberta-Saskatchewan; Geological Survey of Canada, Open File 4252, scale 1:1 000 000.

2002b: Athabasca Gamma Ray Spectrometry Correlation Series, Wollaston Lake, Saskatchewan; Geological Survey of Canada, Open File 4253, scale 1:1 000 000.

2002c: Athabasca Gamma Ray Spectrometry Correlation Series, Prince Albert, Saskatchewan; Geological Survey of Canada, Open File 4251, scale 1:1 000 000.

Shives, R.B.K., Ford, K.L., and Charbonneau, B.W., 1995: Applications of gamma ray spectrometry to VLF-EM surveys – Workshop Manual; Geological Survey of Canada, Open File 3061, 80p.

Shives, R.B.K., Charbonneau, B.W., and Ford, K.L., 1997: The detection of arsenic alteration by gamma-ray spectrometry – Recognition of alteration related to mineralization; p.741-752, in Proceedings of Exploration '97: Fourth Decennial International Conference.




Geophysical compilation by J.M. Carson, P.B. Holman, K.L. Ford, J.A. Grant, and R.B.K. Shives

Digital cartography by B. Blanchard Pilon, Data Dissemination Division (DDD)

This map was produced from processes that conform to the Scientific and Technical Publishing Services Subdivision (STPS) Quality Management System, registered to the ISO 9001:2000 standard

Any revisions or additional geological information known to the user would be welcomed by the Geological Survey of Canada

Digital base map at the scale of 1:1 000 000 from the Digital Chart of the World (DCW) from Environmental Systems Research Institute (ESRI), with modifications by DDD



GEOLOGICAL SURVEY OF CANADA OPEN FILE 5456  
SASKATCHEWAN INDUSTRY AND RESOURCES OPEN FILE 2007-19  
**EQUIVALENT URANIUM**  
**RADIOACTIVITY MAP OF THE ATHABASCA BASIN REGION**  
SASKATCHEWAN-ALBERTA

Scale 1:1 000 000/Echelle 1/1 000 000  
Kilometres 25 0 25 50 75 Kilomètres  
Lambert Conformal Conic Projection  
Standard Parallels 55°N and 59°N  
North American Datum 1983  
© Her Majesty the Queen in Right of Canada 2007  
Projection conique conforme de Lambert  
Parallèles d'échelle conservés: 55° N et 59° N  
Système de référence géodésique nord américain, 1983  
© Sa Majesté la Reine du chef du Canada 2007

OPEN FILE  
DOSSIER PUBLIC  
**5456**  
2007  
Qualité des produits  
qui n'ont pas été  
vérifiés par le GSC  
avant leur mise en  
publication.  
Les données publiées  
sont des produits du GSC  
et ne sont pas  
garanties par le GSC.

Recommended citation:  
Carson, J.M., Holman, P.B., Ford, K.L., Grant, J.A., and Shives, R.B.K., 2007: Equivalent Uranium radioactivity map of the Athabasca Basin region, Saskatchewan-Alberta; Geological Survey of Canada, Open File 5456; Saskatchewan Industry and Resources, Open File 2007-19, scale 1:1 000 000.