



This airborne geophysical survey and the production of this map were funded by Parks Canada through the Mineral and Energy Resource Assessment Project.

### GEOPHYSICAL SERIES - NTS 95 F/14 - WRIGLEY CREEK NORTHWEST TERRITORIES

#### TERNARY RADIODELEMENT IMAGE MAP

Scale 1 : 50 000 - Échelle 1 / 50 000

km 1 0 2 4  
Location Map  
Universal Transverse Mercator Projection  
North American Datum 1983  
Présage universelle de Mérétorique  
Système de référence géographique canadien, 1983  
© Her Majesty the Queen in Right of Canada 2007  
© Sa Majesté la Reine du chef du Canada 2007



OPEN FILE DOSSIER PUBLIC <b>5158</b>	Open files are products published through the GSC formal publication process. Les dossiers publics sont des produits qui n'ont pas été soumis au processus officiel de publication de la CGC.
GEOLOGICAL SURVEY OF CANADA COMMISSION GÉOLOGIQUE DU CANADA	2007
SHEET 8 OF 10 FEUILLET 8 DE 10	

Recommended citation:  
Carson, M., Dumont, R., Pawlis, J., Bushell, J., Shives, R.B.K., and Harvey, B.,  
2007, Geological Series - NTS 95 F/14 - Wrigley Creek, Northwest Territories,  
Geological Survey of Canada, Open File 5158,  
scale 1:50 000.

In 2004 and 2005, Sander Geophysics Limited completed four multi-sensor airborne geophysical surveys in the Nahanni River area of the Northwest Territories for Parks Canada (Prairie Creek, Caribou River and Flat River) and the Government of the Northwest Territories (Sekwi Range). The Geological Survey of Canada provided survey supervision and quality control. The purpose of the survey was to obtain quantitative radioelement spectral and geochemical data. The survey was flown over two seasons, from August 20 to October 3, 2004 and the second phase from June 13 to August 20, 2005 using the SGL ASAR 250B-3 helicopter. C-260H.

**Gamma-ray Spectrometric Data**  
The airborne gamma-ray measurements were made with an Exponentium GR820 gamma-ray spectrometer using nine 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of eight crystals (total volume 33.6 litres). One crystal (total volume 4.2 litres), shielded by the main array, was used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from an 1460 keV gamma-ray photons emitted by "K", whereas uranium and thorium are measured indirectly from the gamma-ray photons emitted by daughter products ("U" for uranium and "Th" for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are:

Potassium (*K)	1360 - 1560 keV
Uranium (*U)	1660 - 1860 keV
Thorium (*Th)	2410 - 2810 keV

Gamma-ray spectra were recorded at one-second intervals at a planned terrain clearance of 135 m and an air speed of 120 kmh. Noise Adjusted Singular Value Decomposition (NSVD) analysis was carried out on the full spectrum 256 channel data to reduce statistical noise in the data. The results of the NSVD analysis were then used to calculate the average surface concentrations. Counts from the radon detectors were recorded in a 1690 - 1860 keV window, and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, and for background activity from cosmic radiation, the radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations of altitude from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over a calibration range near Ottawa.

Potassium	5.6 cps/% (2004)	5.0 cps/% (2005)
Uranium	9.0 cps/ppm (2004)	6.3 cps/ppm (2005)
Thorium	3.7 cps/ppm (2004)	3.2 cps/ppm (2005)

Corrected data were filtered and interpolated to a 100m grid for both the 1:50 000 scale and 1:250 000 scale maps. The results of an airborne gamma-ray spectrometric survey represent the average surface concentrations that are influenced by varying amounts of outcrop, overburden, vegetation cover, soil moisture and surface water. As a result, the measured concentrations are usually lower than the actual bedrock concentration. The total air absorbed dose in nanogreys per hour was produced from measured counts between 400 and 2000 keV.

**Magnetic Data**  
The helicopter was equipped with a Scintrex CS-2 cesium vapour magnetic sensor mounted in a bird suspended 30 m below the aircraft. The system recorded readings every 0.1 s with a noise level of less than 0.02 nT. Magnetic interferences caused by aircraft maneuvers were compensated using an AADON 16-bit digital magnetometer. Diurnal variations and GPS time corrections were recorded at regular intervals using a Geophysical Ground Station Recording System. The International Geomagnetic Reference Field was calculated and removed for each flight. The airborne magnetometer data was IGRF corrected, using the location, altitude and date of each point. The IGRF was calculated using the IGRF 2000 model.

The corrected magnetic data was interpolated to a 100m grid using a minimum curvature algorithm. The first vertical derivative grid was calculated from the corrected total magnetic intensity grid using a FFT based frequency domain filtering algorithm.

**Positional Data**  
Survey line spacing of 500 m and control line spacing of 4000 m was used for the Prairie Creek, Caribou River and Flat River survey blocks. Survey lines in the Prairie Creek and Caribou River areas, and for the Flat River area survey lines were oriented NW-SE and the Sekwi Range survey lines were oriented SW-NE. Survey and control line positions were pre-planned using Sander Geophysics Limited, Smooth Drapé software. Terrain clearance was monitored by radar altimeter. Positional data were recorded using a dual frequency Novatel Millenium system. GPS ground station data were combined with airborne GPS data to produce differentially corrected position data with an accuracy of 2 to 5 m.

**Data Presentation**  
Colour levels and contours were calculated for each grid and combined with map surround information to create HP RTL plotfiles, which were plotted using SGL's HP DesignJet colour plotters.

**Project Funding**  
The Prairie Creek, Caribou River and Flat River surveys were funded by Parks Canada through the Mineral and Energy Resource Assessment Project. The Sekwi Range survey was funded by the Northwest Territories Geoscience Office. Technical expertise and contract administration were provided by the Radiation Geophysics and Regional Geophysics Sections of the Geological Survey of Canada.

#### PLANIMETRIC SYMBOLS

Topographic Contour .....	
Drainage .....	
Wetland .....	
Permanent Ice .....	
Roads .....	
Trails .....	
Flight Line .....	

