

**Quantitative gamma-ray spectrometric and aeromagnetic airborne geophysical survey of the Eastern Athabasca Basin, Saskatchewan**, was completed by Goldak Airborne Surveys. The survey was flown from June 9th to August 11th, 2009 using three Piper PA-31 Navajo (C-GJBA, C-GJBB and C-GJBG). The normal traverse and control line spacings were, respectively, 400 m and 2400 m, and the aircraft flew at a nominal terrain clearance of 125 m at an air speed between 200 and 270 km/h. Traverse lines were oriented 135° with orthogonal control lines. The flight path was received following post-flight differential corrections to raw data recorded by a Global Positioning System.

**Gamma-ray Spectrometric Data**  
The airborne gamma-ray measurements were made with Radiation Solutions RS-500 gamma-ray spectrometers using fourteen 102 x 102 x 406 mm NaI (Tl) crystals. The main detector array consisted of twelve crystals (total volume 50.4 litres). Two crystals (total volume 8.4 litres), shaded by the main array, were used to detect variations in background radiation caused by atmospheric radon. The system constantly monitored the natural thorium peak for each crystal, and using a Gaussian least squares algorithm, adjusted the gain for each crystal.

Potassium is measured directly from the 1460 keV gamma-ray photons emitted by <sup>40</sup>K, whereas uranium and thorium are measured indirectly from gamma-ray photons emitted by daughter products (Bi214 for uranium and Tl208 for thorium). Although these daughters are far down their respective decay chains, they are assumed to be in equilibrium with their parents; thus gamma-ray spectrometric measurements of uranium and thorium are referred to as equivalent uranium and equivalent thorium, i.e. eU and eTh. The energy windows used to measure potassium, uranium and thorium are, respectively, 1370–1570 keV, 1660–1860 keV, and 2410–2810 keV.

Gamma-ray spectra were recorded at one-second intervals. During processing, the spectra were energy calibrated, and the counts were accumulated into the windows described above. Counts from the radon detectors were recorded in a 1660–1860 keV window and radiation at energies greater than 3000 keV was recorded in the cosmic window. The window counts were corrected for dead time, background activity from cosmic radiation, radioactivity of the aircraft and atmospheric radon decay products. The window data were then corrected for spectral scattering in the ground, air and detectors. Corrections for deviations from the planned terrain clearance and for variation of temperature and pressure were made prior to conversion to ground concentrations of potassium, uranium and thorium, using factors determined from flights over the Dawson, Saskatchewan calibration range. The factors for potassium, uranium, and thorium are listed in Table 1.

	C-GJBA	C-GJBB	C-GJBG
Potassium (cps/%)	82.22	81.61	83.37
Uranium (cps/ppm)	11.65	12.11	12.39
Thorium (cps/ppm)	5.15	5.03	4.98

Table 1. Gamma Ray Spectrometer Sensitivities for each aircraft

Corrected data were filtered and interpolated to a 100 m grid interval. The results of an airborne gamma-ray spectrometer survey represent the average surface concentrations that are influenced by varying amounts of outcrop, overburden, vegetation cover, soil moisture and surface water. As a result the measured concentrations are usually lower than the actual bedrock concentrations. The total air absorbed dose rate in nanograys per hour was produced from measured counts between 400 and 2810 keV.

**Magnetic Data**  
The magnetic field was sampled 10 times per second using a cesium vapour magnetometer (sensitivity = 0.005 nT) rigidly mounted to the aircraft. Differences in magnetic values at the intersections of control and traverse lines were computer-analyzed to obtain a mutually leveled set of flight-line magnetic data. The leveled values were then interpolated to a 100 m grid. The International Geomagnetic Reference Field (IGRF) defined at the average GPS altitude of 566 m for the year 2009.53 was then removed. Removal of the IGRF represents the magnetic field of the Earth's core, produced by a residual component related essentially to magnetizations within the Earth's crust.

The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes low-wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of first vertical derivative maps is the coincidence of the zero-value contour with vertical contacts at high magnetic latitudes (Hood, 1965).

**References/References**  
Hood, P.J. 1965. Gradient measurements in aeromagnetic surveying. *Geophysics*, 30, 891-902.

**LEVÉ GÉOPHYSIQUE DE LA PARTIE EST DU BASSIN ATHABASCA, SASKATCHEWAN**

Un levé géophysique aérien combinant l'acquisition de données quantitatives de spectrométrie gamma et de données magnétiques a été réalisé dans la partie est du bassin Athabasca en Saskatchewan par la société Goldak Airborne Surveys. Le levé a été effectué du 9 juin au 11 août 2009, à bord de trois avions Piper PA-31 Navajo (C-GJBA, C-GJBB et C-GJBG). L'espacement normal des lignes de vol était de 400 m et celui des lignes de contrôle de 2400 m, alors que l'altitude nominale de vol était de 125 m au-dessus du sol et que la vitesse était de 200 et 270 km/h. Les lignes de vol étaient orientées 135° et les lignes de contrôle leur étaient perpendiculaires. La trajectoire de vol a été restituée par l'application après le vol de corrections différentielles aux données brutes enregistrées avec un récepteur GPS.

**Données de spectrométrie gamma**  
Les mesures du rayonnement gamma ont été effectuées à l'aide d'un spectromètre gamma Radiation Solutions RS-500 utilisant quatorze cristaux de NaI (Tl) de 102 x 102 x 406 mm. Le principal réseau de capteurs se composait de douze cristaux (volume total de 50,4 litres). Deux cristaux (volume total de 8,4 litres), protégés par un réseau principal, ont été utilisés pour détecter les variations du rayonnement naturel causées par le radon atmosphérique. Le dispositif permettait de faire un suivi constant des pics du thorium pour chacun des cristaux et, au moyen d'un algorithme de moindres carrés, d'ajuster le gain pour chacun des cristaux.

Le potassium est mesuré directement à partir des photons gamma de 1460 keV émis par le <sup>40</sup>K, tandis que l'uranium et le thorium sont mesurés indirectement à partir des photons gamma émis par des produits de fission (Bi214 pour l'uranium et Tl208 pour le thorium). Bien que ces radionucléides de fission se trouvent loin dans leur chaîne respective de désintégration, on presume qu'ils sont en équilibre avec leur radionucléide père, ainsi, les mesures spectrométriques du rayonnement gamma de l'uranium et du thorium sont désignées comme des équivalents d'uranium et des équivalents de thorium, soit eU et eTh. Les plages d'énergie utilisées pour mesurer le potassium, l'uranium et le thorium sont respectivement de 1370 à 1570 keV, de 1660 à 1860 keV et de 2410 à 2810 keV.

Les spectres du rayonnement gamma ont été enregistrés pendant des intervalles d'une seconde. Pendant le traitement, les spectres ont été soumis à un étalonnage énergétique et les coups ont été cumulés dans les plages décrites ci-dessus. Les coups enregistrés dans la plage de 1660 à 1860 keV et le rayonnement à des énergies supérieures à 3000 keV ont été enregistrés dans la plage du rayonnement cosmique. Les coups enregistrés dans les plages ont été corrigés pour tenir compte du temps mort, du rayonnement de fond et du rayonnement cosmique. Les coups enregistrés dans les plages ont été corrigés pour tenir compte du temps mort, du rayonnement de fond et du rayonnement cosmique. Les coups enregistrés dans les plages ont été corrigés pour tenir compte du temps mort, du rayonnement de fond et du rayonnement cosmique. Les données pour les plages ont ensuite été corrigées pour tenir compte de la diffusion spectrale dans le sol, l'air et les capteurs. Les corrections pour les écarts à la hauteur de vol prévue et les variations de température et de pression ont été effectuées avant la conversion en concentrations équivalentes au sol du potassium, de l'uranium et du thorium, en utilisant des facteurs déterminés par une comparaison avec des résultats obtenus lors de vols effectués au-dessus d'une bande d'étalonnage à Dawson, Saskatchewan. Les facteurs déterminés pour le potassium, l'uranium et le thorium sont présentés au Tableau 1.

	C-GJBA	C-GJBB	C-GJBG
Potassium (cps/%)	82.22	81.61	83.37
Uranium (cps/ppm)	11.65	12.11	12.39
Thorium (cps/ppm)	5.15	5.03	4.98

Tableau 1. Sensibilités des spectromètres de chacun des aéronefs.

Un filtre a été appliqué aux données corrigées, qui ont ensuite été interpolées suivant une grille à maille de 100 m. Les résultats d'un levé aérien de spectrométrie gamma représentent les concentrations moyennes à la surface, qui sont influencées par les étendues variables des affleurements, des forêts-terrestres, de la couverture végétale et de l'eau de surface. Par conséquent, les concentrations mesurées sont habituellement plus faibles que les concentrations réelles dans le substratum rocheux. Le débit total de la dose absorbée par far, en nanograys à l'heure, a été déterminé d'après les coups mesurés dans la plage de 400 à 2810 keV.

**Données sur le champ magnétique**  
Le champ magnétique a été échantillonné 10 fois par seconde à l'aide d'un magnétomètre à vapeur de césium à faisceau partagé (sensibilité = 0,005 nT) rigidement fixé à l'aéronef. Les différences de valeur du champ magnétique aux intersections des lignes de contrôle et des lignes de levé ont été analysées pour produire un jeu de données sur le champ magnétique mutuellement nivelées sur les lignes de vol. Ces valeurs nivelées ont ensuite été interpolées suivant une grille à maille de 100 m. Le champ géomagnétique international de référence International Geomagnetic Reference Field, IGRF, défini à l'altitude moyenne de 566 m fournie par les données GPS pour l'année 2009.53 a été soustrait. La soustraction de l'IGRF, qui représente le champ magnétique du noyau terrestre, fournit une composante résiduelle essentiellement liée à la magnétisation de l'écorce terrestre.

La dérivée première verticale du champ magnétique représente le taux auquel varie le champ magnétique suivant la verticale. Le calcul de la dérivée première verticale supprime les composantes de grande longueur d'onde du champ magnétique et améliore considérablement la résolution des anomalies rapprochées les unes des autres ou superposées. L'une des propriétés des cartes de la dérivée première verticale est la coïncidence de la ligne de valeur zéro et des contacts verticaux aux hautes latitudes magnétiques (Hood, 1965).


**References/References**  
Hood, P.J. (1965). Gradient measurements in aeromagnetic surveying. *Geophysics*, v. 30, p. 891-902.

**PLANIMETRIC SYMBOLS**

Drainage  
Highway  
Flight line


**SYMBOLS PLANIMÉTRIQUES**

Drainage  
Autoroute  
Ligne de vol



**MAP SHEET SUMMARY / SOMMAIRE DES FEUILLETS**

Sheet / Feuille	MAP / CARTE
1.	Natural Air Absorbed Dose Rate / Taux d'absorption naturel des rayons gamma dans l'air
2.	Potassium
3.	Uranium
4.	Thorium
5.	Uranium / Thorium
6.	Uranium / Potassium
7.	Thorium / Potassium
8.	Temary Radiometer Map / Diagramme terrain des radiomètres
9.	Reseau / Total Magnétique / Composite résiduelle du champ magnétique total
10.	First Vertical Derivative of the Magnetic Field / Dérivée première verticale du champ magnétique



This airborne geophysical survey and the production of this map were funded by the Saskatchewan Ministry of Energy and Resources and the GEM-Energy Program of the Earth Sciences Sector, Natural Resources Canada.

Ce levé géophysique aéroporté et la production de cette carte ont été financés par le ministère de l'Énergie et des Ressources de la Saskatchewan et le programme GEM-Energie du Secteur des sciences de la Terre, Ressources naturelles Canada.

GSC OPEN FILE 6383 / DOSSIER PUBLIC 6383 DE LA CGC  
SMER OPEN FILE 2010-37

Digital versions of this map, corresponding digital profile and gridded data, and similar data for adjacent aeromagnetic and gamma-ray spectrometric surveys can be downloaded, at no charge, from Natural Resources Canada's Geoscience Data Repository at <http://gdr.mnrc.gc.ca>. The same products are available, for a fee, from the Geophysical Data Centre, Geological Survey of Canada, 615 Booth Street, Ottawa, Ontario, K1A 0E9, Telephone: (613) 995-5326, email: [info@gsd.mnrc.gc.ca](mailto:info@gsd.mnrc.gc.ca)

On peut télécharger gratuitement depuis la section sur les Données géoscientifiques de Ressources naturelles Canada à l'adresse Web <http://gdr.mnrc.gc.ca>, des versions numériques de cette carte, des données numériques correspondantes en format profil et en format maille, ainsi que des données similaires issues des levés aéromagnétiques et spectrométriques adjacents. On peut se procurer les mêmes produits, moyennant des frais, en s'adressant au Centre de données géophysiques de la Commission géologique du Canada, 615, rue Booth, Ottawa (Ontario) K1A 0E9, Téléphone: (613) 995-5326, courriel: [info@gsd.mnrc.gc.ca](mailto:info@gsd.mnrc.gc.ca)

**GEOPHYSICAL SERIES / SÉRIE DES CARTES GÉOPHYSIQUES**  
**AIRBORNE GEOPHYSICAL SURVEY OF THE EASTERN ATHABASCA BASIN, SASKATCHEWAN**  
**LEVÉ GÉOPHYSIQUE AÉROPORTÉ DE LA PARTIE EST DU BASSIN ATHABASCA, SASKATCHEWAN**

NTS 74 P/01 and part of 64 M/04 Cyprian Lake / Misekumaw Lake / SNRC 74 P/01 et partie de 64 M/04 Cyprian Lake / Misekumaw Lake

**URANIUM / THORIUM**

Scale 1:50 000 - Échelle 1/50 000

Authors: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. and Hefford, S.W.

Auteurs: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W.

Map location / Localisation de la carte

Data acquisition, compilation and map production by Goldak Airborne Surveys, Saskatoon, Saskatchewan. Contract and project management by the Geological Survey of Canada, Ottawa, Ontario.

Acquisition, la compilation des données ainsi que la production des cartes furent effectuées par Goldak Airborne Surveys, Saskatoon, Saskatchewan. La gestion et la supervision du projet furent effectuées par la Commission géologique du Canada, Ottawa, Ontario.

Universal Transverse Mercator Projection / Système de coordonnées géographiques universelles de Mercator  
Saskatchewan Ministry of Energy and Resources

Projection transversale universelle de Mercator  
Commission géologique du Canada, Ressources naturelles Canada

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Recommended citation: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Saskatchewan Ministry of Energy and Resources (SMER), Open File 2010-37; Scale 1:50 000.

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W., 2010. Airborne Geophysical Survey of the Eastern Athabasca Basin, Saskatchewan, NTS 74 P/01 and part of 64 M/04, Cyprian Lake / Misekumaw Lake. Geological Survey of Canada, Open File 6383. Ministère de l'Énergie et des Ressources de la Saskatchewan (SMER), Open File 2010-37; échelle 1:50 000.

Open File 6383 / Dossier public 6383

2010

Scale 1:50 000

Notation bibliographique conseillée: Buckle, J.L., Coyle, M., Kiss, F., Carson, J.M., Delaney, G. et Hefford, S.W.,