



Natural Resources
Canada

Ressources naturelles
Canada

**GEOLOGICAL SURVEY OF CANADA
OPEN FILE 7781**

Rock-Eval/TOC data for selected samples from Devonian-Mississippian shale cores in the Liard Basin, northeast British Columbia

M.E. McMechan, M. Obermajer, F. Ferri, K.R. Stewart

2015

Canada 



**GEOLOGICAL SURVEY OF CANADA
OPEN FILE 7781**

Rock-Eval/TOC data for selected samples from Devono-Mississippian shale cores in the Liard Basin, northeast British Columbia

M.E. McMechan¹, M. Obermajer¹, F. Ferri², K.R. Stewart³

¹Geological Survey of Canada, 3303-33rd Street NW, Calgary, Alberta;

²B.C. Ministry of Natural Gas Development, 1810 Blanshard Street, Victoria, British Columbia;

³Arctic Geochemical Consultants, 63 Castlebrook Drive NE, Calgary, Alberta;

2015

© Her Majesty the Queen in Right of Canada, as represented by the Minister of Natural Resources Canada, 2015

doi:10.4095/296445

This publication is available for free download through GEOSCAN (<http://geoscan.nrcan.gc.ca/>).

Recommended citation

McMechan, M.E., Obermajer, M., Ferri, F., and Stewart, K.R., 2015. Rock-Eval 6/TOC data for selected samples from Devono-Mississippian shale cores in the Liard Basin, northeast British Columbia; Geological Survey of Canada, Open File 7781, 1 .zip file. doi:10.4095/296445

INTRODUCTION

Rock-Eval 6/TOC results were obtained for samples from 34 cores of Devonian-Mississippian shale in or adjacent to the Liard Basin area of British Columbia. Every non-confidential core of Devonian-Mississippian shale available from the B.C. part of the Liard Basin was sampled in the Fall of 2013. The cores came from 9 different boreholes that intersected several stratigraphic units including the Golata, Banff, Besa River, Mattson, Exshaw, Kotcho, Muskwa, Otter Park and Evie formations as listed below.

Well Name	Location	Licence	Core No.	Interval Sampled (ft)	Interval Sampled (m)	Unit
LTS HZ POPLAR HILLS A-040-G	A-040-G/094-O-03	WA25913	1		1216.5- 1227.8	Exshaw
LTS HZ POPLAR HILLS A-040-G	A-040-G/094-O-03	WA25913	1		1228 - 1233	Kotcho
LTS HZ POPLAR HILLS A-040-G	A-040-G/094-O-03	WA25913	2		2145.1 - 2145.8	Muskwa
BP ENERGY GROUP DEER LAKE A-090-I	A-090-I/094-O-06	WA0531	1		1658.6 - 1663.6	Kotcho
TRANSEURO BEAVER B-019-K	B-019-K/094-N-16	WA02563	1-2	12395 - 12420	3778.00 -3785.62	Besa River/Evie
TRANSEURO ET AL BEAVER B-036-K	B-036-K/094-N-16	WA21755	1-4, 6-9		1835-2114	Mattson/Besa River
JOINT VENTURE NO. 1 C-010-E	C-010-E/094-N-07	WA0038	35	5162 - 5187	1573.38 -1581	Besa River/ Muskwa
EOG MAXHAMISH D-012-L	D-012-L/094-O-15	WA21643	1-10		2956.15 -2975.3	Muskwa
EOG MAXHAMISH D-012-L	D-012-L/094-O-15	WA21643	11		2978.7	Otter Park
TRANSEURO BEAVER D-064-K	D-064-K/094-N-16	WA0325	1	8320 - 8360	2535.94 - 2548.13	Golata
TRANSEURO BEAVER D-064-K	D-064-K/094-N-16	WA0325	20	9500 - 9502	2895.60 - 2896.21	Banff
TRANSEURO BEAVER D-064-K	D-064-K/094-N-16	WA0325	21	11038 - 11063	3364.38 - 3372.00	Besa River/ Muskwa
TRANSEURO HZ BEAVER D-A064-K	D-A064-K/094-N-16	WA02547	6	6282 - 6312	1914.75 - 1923.90	Golata
IOE DUNEDIN D-075-E	D-075-E/094-N-08	WA01331	15	12103 - 12147	3688.99 - 3702.41	Besa River/ Golata?
IOE DUNEDIN D-075-E	D-075-E/094-N-08	WA01331	16	12379.3 - 12385.2	3773.2 - 3775.0	Besa River
IOE DUNEDIN D-075-E	D-075-E/094-N-08	WA01331	17	12761.5 - 12780.5	3889.7 - 3895.5	Besa River

Depths in feet are listed when that is the original unit of measure on the core box. The following cores had poorer recovery and the estimated depth for individual samples from these cores have more uncertainty: WA0325 core 1; WA531 core 1, 21; WA1331 core 16, 17; WA02547 core 6; WA2563 core 1 and WA21643 cores 1-5, 7, 8, 10, 11.

Other previously published Rock-Eval/TOC results are available for cuttings of Devonian-Mississippian shale from several wells in the Liard Basin area (Fowler et al., 2007, Obermajer et al., 2012; McMechan et al, 2013) and one surface section of the Besa River Formation (Ferri et al., 2011).

EXPERIMENTAL

Rock-Eval/TOC analysis provides fast and reliable characterization of the quantity and quality of sedimentary organic matter, as well as its thermal maturity. All samples were analyzed on a Rock-Eval 6 Turbo (RE 6) instrument equipped with a Total Organic Carbon analysis module. A typical RE 6 experiment is initiated with heating of a pulverized rock sample at 300°C for 3 min in nitrogen atmosphere, when naturally occurring hydrocarbons (free and adsorbed) are volatilized. The oven temperature is then steadily increased to 650°C at a rate of 25°C/min and decomposition of kerogen occurs. The amount of hydrocarbons volatilized at 300°C and evolved from kerogen during the ramped heating are quantitatively determined by a flame ionization detector, and recorded as the S1 and S2 peaks, respectively. The final stage involves oxidation and combustion of the residual organic matter at 850°C. The temperature measured at the maximum of the S2 peak is referred to as T_{peak} while T_{max} is calculated by subtracting about 40°C from T_{peak} (the exact correction is determined using a manufacturer standard). The amounts of CO and CO₂ are quantitatively determined by infrared detectors. Additional details on the RE6 instrument are available in Behar et al. (2001).

The percentage of carbon in CO₂ formed during oxidation and in the hydrocarbon peaks S1 and S2 is used to define the total organic carbon content (TOC), expressed as a weight percentage. The determination of the quality of organic matter is based upon the calculation of Hydrogen (HI) and Oxygen (OI) indices ($HI=100 \times S2/TOC$, $OI=100 \times S3/TOC$) which are related to the atomic H/C and O/C ratios (Espitalié et al., 1977). The OI versus HI cross plots ("pseudo van Krevelen diagrams") can be used as an organic matter type indicator at low and moderate maturities. The T_{max} is an indicator of relative thermal maturity. According to Espitalié et al. (1985) the oil window is defined by the following T_{max} ranges: 440°-448°C (Type I), 430°-455°C (Type II) and 430°-470°C (Type III). A cross plot of T_{max} versus HI is used to constrain estimations of organic matter type and its thermal maturity, while the Production Index ($PI=S1/[S1+S2]$) is used to indicate staining of a sample or as an additional maturity parameter.

Rock-Eval results correlate to other techniques (Espitalié et al., 1985; Tissot and Welte, 1978). Source rock potential is sensitive to lithology, TOC and S2 values. It is common practice to rate carbonate rocks with lower TOC comparable with richer clastic rocks. Extractable HC yields from leaner carbonate rocks are comparable to richer clastic rocks (Tissot and Welte, 1978, p. 430; Gehman, 1962). The organic matter associated with carbonate rocks is often more hydrogen-rich and thermally labile than that in fine-grained clastic rocks. As a result, more TOC in carbonate rocks may be transformed into bitumen compared with average clastic source rocks of comparable maturity.

Rock-Eval/TOC parameters have reliable significance only above threshold TOC, S1 and S2 values. If TOC is less than or equal to 0.3% then all parameters have questionable significance and the experiment suggests no petroleum source potential. Oxygen Index (OI) has questionable significance if TOC is less than or equal to 0.5%. Both Tmax and Production Index ($PI = S1/(S1+S2)$), have questionable significance if S1 and S2 values are less than or equal to about 0.2 mg HC/g rock. Results can be affected by rock mineral composition. The mineral matrix may either retain hydrocarbon compounds, generally lowering the S1 or S2 peaks, while increasing Tmax, or liberate inorganic CO₂ increasing S3 and OI. These effects are important if TOC, S1 and S2 are low, an effect not significant where sources have TOC values greater than 5%. OI values greater than 150 mg/g TOC suggest either low TOC or a mineral matrix CO₂ contribution during pyrolysis. Generally, a TOC content of at least 2% is needed for a source rock. Note that TOC and Hydrogen Index decrease with increasing thermal maturity due to hydrocarbon generation. Additional guidelines on the interpretation of Rock-Eval data may be found in Peters (1986), Snowdon (1995) and Sykes and Snowdon (2002).

SELECTED REFERENCES

Behar, F; Beaumont, V; Pentead, H L De B; 2001. Rock-Eval 6 Technology: Performances and developments. *Revue de l' Français du Pétrole*, v.56/2, p. 111-134.

http://ogst.ifp.fr/articles/ogst/pdf/2001/02/behar_v56n2.pdf

Espitalié, J; Laporte, J.L; Madec, M; Marquis, F; Leplat, P; Paulet, A; Boutefeu, J; 1977. Methode rapide de caracterisaion des roches meres de leur potential petrolier et de leur degre d'evolution. *Revue de l'Institut Français du Petrole* vol. 32, p. 23-42.

Espitalié, J., Deroo, G. and Marquis, F., 1985. Rock Eval Pyrolysis and Its Applications. Preprint; Institut Francais du Petrole, Geologie No. 27299, 72 p. English translation of, La pyrolyse Rock-Eval et ses applications, Premiere, Deuxieme et Troisieme Parties, in *Revue de l'Institut Francais du Petrole*, v. 40, p. 563-579 and 755-784; v. 41, p. 73-89.

Ferri, F., Hickin, A.S. and Huntley, D.H., 2011. Besa River Formation, western Liard Basin, British Columbia (NTS 094N): geochemistry and regional correlations; in *Geoscience Reports 2011*, British Columbia Ministry of Energy and Mines, p. 1–18.

Fowler, M.G., Obermajer, M. and Snowdon, L.R., 2007: Rock-Eval/TOC data for eleven NE British Columbia boreholes (map areas 94-I to 94-P) Geological Survey of Canada, Open File 5672, CD-Rom.

Gehman, H. M. Jr., 1962. Organic matter in limestones; *Geochimica et Cosmochimica Acta*, v. 26, p. 885-897.

McMechan, M.E., Obermajer, M., Stewart, K.R., Jiang, C., and Kung, L., 2013, Rock-Eval/TOC data for selected samples from boreholes in the Toad River area (NTS 94-N), Liard Basin, northeast British Columbia; Geological Survey of Canada, Open File 7480. doi: 10.4095/293114

Obermajer, M., Lane, L.S. and Osadetz, K.G., 2012. Rock-Eval/TOC data for selected samples from northeast British Columbia boreholes (map areas 94-N to 94-O); Geological Survey of Canada, Open File 7043, 1 CD-ROM. doi: 10.4095/289671.

Peters, K E, 1986. Guidelines for evaluating source rock using programmed pyrolysis; Bulletin of the American Association of Petroleum Geologists, v. 70, p. 318-329.

Snowdon, L R; 1995. Rock-Eval Tmax suppression: documentation and amelioration. American Association of Petroleum Geologists Bulletin, v. 79, p. 1337-1348.

Sykes, R; Snowdon, L R; 2002. Guidelines for assessing the petroleum potential of coaly source rocks using Rock-Eval pyrolysis. Organic Geochemistry v. 33/12, p. 1441-1455.

Tissot, B. P. and Welte, D. H., 1978. Petroleum formation and occurrence; Springer-Verlag, Berlin, 538 p.