



**CANMET**

Canada Centre  
for Mineral  
and Energy  
Technology

Centre canadien  
de la technologie  
des minéraux  
et de l'énergie

ERP/ERL 77-102 (J)

EMR FACILITIES IN WESTERN CANADA  
FOR PROCESSING CANADIAN COALS

M. Mikhail, C. Rozenhart and J.L. Picard

MAY 1977

01-0003556

ENERGY RESEARCH PROGRAM  
Energy Research Laboratories  
Report ERP/ERL 77-102 (J)

EMR FACILITIES IN WESTERN CANADA  
FOR PROCESSING CANADIAN COALS

by

M. Mikhail\*, C. Rozenhart\*\* and J.L. Picard\*\*\*

SYNOPSIS

The Department of Energy, Mines and Resources (EMR) has recently completed construction of a 10-tph CANMET-Process coal washing plant at the Western Research Laboratory (WRL) at Clover Bar near Edmonton.

The facility serves in part to support the department's own R & D programs in fine-coal beneficiation and washery water treatment; it is also available to the Canadian coal industry to assist in problem-solving programs for existing washeries and for providing data in relation to resource evaluation and design of new plants.

This paper describes the design and operational features of the facility and briefly touches upon related programs of research being carried out at WRL.

---

\*Coal Processing Engineer, \*\*Senior Technologist and \*\*\*Assistant Manager, Western Research Laboratory, Energy Research Laboratories, CANMET, Department of Energy, Mines & Resources, Edmonton, Alberta, Canada.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48

PLEASE THE ORIGINAL FILED IN THE LIBRARY OF THE DEPARTMENT OF ENERGY, MINES AND RESOURCES  
ANY PROPOSED REVISIONS ON THE CARBON COPY ONLY

## INTRODUCTION

In the main, proper design of coal washeries follows from three basic preliminary steps: laboratory analysis and testing of representative samples of the raw coal, prediction of washing results by calculation, and finally, confirmation of predictions by pilot plant testing.

Laboratory work provides size distribution and washability data for ash and sulphur plus other pertinent information such as free swelling index, grindability, fixed carbon, etc. Bench work may furthermore be performed for feasibility and behavioural determinations; parameters such as reagent dosages, pulp conditioning and choice of reagents can be studied on this scale.

Calculations for prediction of expected results (performance evaluations) are conducted to obtain first estimates of the quantity and quality of coal and reject that can be produced at various specific gravity (sp gr) cutpoints and efficiencies for a cleaning unit or system. Theoretical yield and ash and/or sulphur contents at different specific gravities and information on near-gravity material derived from the washability curves are necessary for estimation of the theoretical cutpoint. Calculation of performance evaluation is based on the well-known procedure of applying partition numbers from error curves, which represent the performance of a separator (or combination of separators), to the elementary washability data of the coal. The choice of probable errors and cutpoints for the calculation is made by reference to previous experience with washing similar coals or similar size fractions. In some cases, major discrepancies exist between predicted and actual results. This may be attributed to significant changes in washability characteristics resulting from degradation of the feed coal during handling and treatment, the presence of flat particles in the feed or other factors such as porosity, etc. Pilot plant testing is therefore essential for reliable prediction of industrial-scale performance.

The pilot plant described in this report brings together tangible results of various R & D efforts of the Western Research Laboratory (WRL)

NOT THE ORIGINAL DOCUMENT IS TO BE USED FOR REPRODUCTION  
ANY PROPOSED REVISIONS ON THE GAZON COPY ONLY

carried out within the CANMET energy program relating to the processing of fuels. The program objectives in this framework include developing improved methods of separating mineral matter from coal and methods of water treatment for water recycling and/or for pollution control.

A prime objective of the WRL pilot plant is to provide for thorough investigation of fine-coal preparation problems on a scale and in a manner consistent with the needs of commercial operations and, as such, to support a variety of investigative, R & D and advisory programs pertaining to fine-coal preparation and pollution control.

Programs originate within the department or may be undertaken at the specific request of coal producers. In the latter instance, the services may be provided on a full or shared cost-recovery basis. Recent cost-recovery projects have included washing tests on a wide range of metallurgical and thermal coals and laboratory studies supplemented by pilot plant work on flocculation, flotation, etc., to establish control parameters and optimize operation of existing water recovery and slimes beneficiation systems.

Characterization of the CANMET Process, formerly the EMR Process (1), is achieved through the washing tests which also provide information on the behaviour of the coals themselves during processing. Information on size degradation, breakdown of shales, etc., provides the project sponsor with first order design data and adds to the department's inventory on the processing and utilization potential of the Canadian coal resource.

The description that follows will serve to familiarize the coal producer with the CANMET Process and its pilot plant, and with other R & D facilities of the Dept. of Energy, Mines and Resources that are available in Edmonton, Alberta. These facilities are being utilized to help ensure maximum benefits to the Canadian people via the producer through WRL's continuing programs aimed at contributing to an improved technology of fine-coal preparation.

SECRET - INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE  
ANY PROPOSED MODIFICATIONS ON THE CARBON COPY ONLY

## CANMET PROCESS PILOT PLANT

Operations in the CANMET coal cleaning process comprise crushing the raw coal, cleaning the crushed coal in bulk with cyclones using water as the medium, drying the predewatered clean coal and the fine reject by centrifugal force, agglomerating and drying the coal slimes by using a small amount of oil as a dewatering aid, and finally, treating the process water by means of flocculation followed by clarification to recover clean water for recycling while maintaining acceptable levels of discharge of pollutants to the environment. A total of six WRL patents are incorporated into the process. As indicated on the schematic flowheet in Figure 1, the 10-tph pilot plant can be divided into the following four sections which will be described in detail:

1. Feed Preparation
2. Cleaning
3. Drying
4. Water Recovery

A more detailed flowsheet is given in Figure 2 and an equipment list in Table 1.

### 1. Feed Preparation Section

The raw coal (2-in. x 0) is fed by means of a scraper conveyor followed by a belt conveyor to a hammermill which is equipped with a 1-in. round-screen to produce 3/8 to 1/4-in. x 0 plant feed. The crushed coal is stored in a 10-ton bin ahead of the cleaning section.

It has been found essential to dry the raw coal when its surface moisture exceeds 7-9% to avoid plugging of the hammermill and resulting reduction in capacity with considerable production of fines.

### 2. Cleaning Section

Two basic circuits are used for cleaning of the coarse coal (1/4-in. x 0) and slimes (28-mesh x 0) respectively. The automedium (AM) water-only cyclone (synonymous with compound water cyclone) is the main process used because of its simplicity of operation and its capability for

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

washing coal in bulk without prior screening. Maximum flexibility is obtained, on the other hand, by providing for back-up or optional treatment using a heavy medium (HM) cyclone system and/or froth flotation.

#### Coarse Coal Cleaning

The 1/4-in. x 0 raw coal is fed to two primary 8-in.-diam AM cyclones operating in parallel. The overflow products are deslimed in two 8-in.-diam classifier cyclones (Cl.C) to produce an underflow (clean coal) product containing 30-40% solids. This product is dewatered on a 28-mesh sieve bend (SB). The sieve bend oversize goes to the drying section; the undersize is fed to the slimes cleaning circuit. A portion of the Cl.C overflow is bled to slimes cleaning with the remaining portion being recirculated to the main sump (dual-mix tank I). The underproduct of the primary cyclones is recleaned in a single second-stage 8-in.-diam AM cyclone to obtain finished reject and a middlings. The reject is deslimed on a 28-mesh vibrating screen and the middlings are either recirculated to the main sump (dual-mix tank I) or deslimed on a 28-mesh sieve bend and a vibrating screen. The coarse (plus 28-mesh) middlings may be loaded directly in drums or undergo other treatment if necessary; the middlings screen undersize proceeds to the slimes cleaning circuit.

#### Slimes Cleaning

The feed to this section originated from the slimes sump, i.e., dual-mix tank II (DMT II), where a number of streams including the clean coal sieve bend undersize, the middlings sieve bend undersize, a portion of the 8-in. classifier cyclones overflow and others are collected. Recovery of low-ash coal from these slimes is achieved in a two-stage 8-in. diameter AM cyclone circuit where the primary cyclone is fitted with a 4-in. cylindrical spacer to lengthen the feed chamber. This simple modification gives lower cutpoints and higher efficiencies for washing minus 28-mesh coal than can be obtained in AM cyclones with standard chamber length (2). The overflow product of the elongated cyclone is dewatered in a classifier cyclone; the classifier underflow is conditioned with emulsified light furnace oil to effect agglomeration of the coal and thereby assist its dewatering in a pusher centrifuge. A portion of the classifier overflow

ANY PROPOSED REVISIONS ON THE CANON COPY ONLY

is treated in the water recovery section and the remainder is recirculated to the slimes sump (DMT II). The primary reject from the elongated cyclone is cleaned in the second-stage AM cyclone, producing finished fine reject which is dewatered in a centrifuge and a middlings that recirculates to the primary cyclone via DMT II.

### 3. Drying Section

The dewatered coarse coal and the oil-conditioned minus 28-mesh fine coal are dried together in a pusher centrifuge and loaded directly into drums. Total moisture content of the clean product is usually 5-7% including 1% by weight of oil added to the fine product. Undersize of the coarse reject dewatering screen is sent directly to the water recovery section.

### 4. Water Recovery Section

Effluent from slimes cleaning and reject dewatering screen undersize are fed into a flocculator apparatus at 10 psi where mixing with flocculant solution injected at 50-80 psi inlet pressure is effected in one or two blenders (4). The flocculated effluent passes through two 8-in.-diam pulp dividers to two 4-in.-diam classifier cyclones. The pulp divider overflow combined with the classifier cyclone overflow proceeds to a bottom-feed thickener. Thickener sludge and classifier cyclone under-product are dewatered with the fine reject from slimes cleaning in a solid-bowl centrifuge before disposal. Clarified water is sent to a reservoir prior to recycling to the plant.

## ALTERNATIVE WASHING PROCESSES

As indicated earlier and as shown in Figure 1, a number of alternatives are available within the pilot plant to provide flexibility for dealing with coals which may differ widely in washing characteristics. The use of conventional heavy-medium or froth flotation systems may be dictated by these characteristics in order to obtain optimum results.

ANY PROPOSED REVISIONS OF THE CAPTION COPY ONLY

1. Coarse Coal or Bulk Cleaning

Four alternative circuits are available. Separation into two products (clean coal and reject) may be achieved in the pilot plant by simple recirculation of middlings (overflow, secondary cyclone) to the primary feed tank.

For a 3-product separation, the middlings may be deslimed and dewatered without further treatment provided it is of marketable thermal quality. The deslimed plus 28-mesh middlings may also be recleaned in a back-up 3-tph heavy medium cyclone (8-in. diam) circuit to produce clean coal and reject which can then be combined with their respective products from the AM cyclones. Alternatively, high-ash deslimed middlings can be crushed in a 5-tph Gundlach Cage-Paktor for liberation of inter-grown coal which is then recovered either in the AM-8L slimes cleaning section or by flotation.

2. Slimes Cleaning

In bulk cleaning using standard length AM cyclones as used in the coarse cleaning section, the minus 28-mesh sizes are usually separated at high cutpoints ( $dp \geq 1.8$  sp gr). In the 2-stage elongated AM cyclone circuit, these fines can be rewashed at lower specific gravities ( $dp = 1.4-1.8$ ) with froth flotation employed in a back-up role to recover minus 150-mesh coal from the effluent. The fine clean coal produced in both these processes is oil-conditioned to assist dewatering and drying in the centrifuge. An additional benefit of oil-conditioning is that stray high-ash particles which are not wetted by the oil will also be removed in the effluent of the centrifuge.

A combination elongated AM cyclone-froth flotation system is advantageous from the point of view that oversize (plus 28-mesh) and oxidized coals can be washed in the cyclones and flotation used on the cyclone effluent for recovery of the minus 150-mesh coal to improve overall yield and prevent overloading of the water recovery circuit.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48

ANY PROPOSED REVISIONS OF THE CANON COPY ONLY



WRL R & D PROGRAM

As stated earlier, the CANMET Process is the direct result of various WRL research efforts whose objective has been development of efficient, cheap, simple and rugged systems for fine-coal cleaning. In its supportive role for on-going R & D programs on fine-coal preparation and pollution control, the pilot plant gives the capability of testing concepts emanating from laboratory scientific and engineering studies.

Coal preparation projects now in progress at WRL include some of general applicability relating to novel and improved processes, and some of more specific application relating to particular characteristics of given coals. Examples in the former category are studies on development of an ash-monitoring system as a first step towards washery automation, continued testing of the elongated AM cyclone for washing of minus 28-mesh fines, studying the mechanism of bed formation in the AM cyclone, column flotation, etc. Projects of more specific application included in the latter category involve process development and design for treatment of high-sulphur coals, low-rank coals containing clay and/or alkali, pond and dump materials, and fundamental studies on surface and other characteristics of high- and low-rank coals as these relate to their processing.

Pollution control, which deals with fine particles on a more general basis, involves fundamental research into surface properties of fine particles, chemical and physical properties of solid-liquid systems including the solids themselves, the suspending liquid and the totality of the two, and chemical and physical characterization of commercial flocculants and their interactions with specific system properties. This information is aimed at establishing a scientific basis for sound engineering of washery pollution control and water recovery systems, taking into account the great number of flocculants from which the best choice must be made, possible variations in quantity and quality of slimes and other aspects of washery operation. In this respect, a survey of raw water at the mines has been initiated to determine seasonal variations in quality which may affect both flocculation and flotation processing. A mobile

ANY INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE

water-recovery unit is now in the first stages of being fitted and is scheduled to be ready for field tests in the summer of 1978.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45

ANY PROPOSED REVISIONS ON THE CANON COPY ONLY

REFERENCES

- (1) Visman, J. "Coal washery design-I, the EMR process"; EMR, TB141; Sept. 1971.
- (2) Picard, J.L., Mikhail, M.W. and Humeniuk, O.E. "Improved compound water cyclone for cleaning coal slimes"; CANMET, Laboratory report ERP/ERL 75-143 (IR); Nov. 1975.
- (3) Bearce, W.E. "The cyclo-cell"; Colliery Guardian; March 28, 1963.
- (4) Visman, J. and Hamza, H.A. "A method and apparatus for centrifugally separating finely divided solids from aqueous suspensions thereof"; U.S. Patent No. 3,929,633; Dec. 30, 1975. [Canadian Patent No. 995,148; Aug. 17, 1976]

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50

ANY PHOTO-COPYING OR REPRODUCTION ON THE CARBON COPY ONLY

TABLE 1: CANMET Processing Plant

<u>OPERATION</u>	<u>UNIT NO.</u>	<u>EQUIPMENT</u>	<u>FUNCTION</u>	
1. Feed Preparation	(1)	10-tph scraper and belt conveyor	Handling of raw coal (2-in. top size) with reduction to minus 3/8-in. and storage	
	(2)	20-tph hammermill		
	(3)	20-tph bucket elevator		
	(4)	10-ton bin		
2. Cleaning	(10) (11,12) (13-16)	regulated feeder (0 to 10 tph)	Slurrying of minus 3/8-in. bulk feed to 7-10% solids, cleaning in two-stage AM-8 system: two- or three-product separation	
		dual-mix tank I (coal slurry sump): 5 x 4-in. pump		
		AM-8: two stage		
	heavy-medium cyclone	(17,18)	sieve bend and desliming screen (2 x 4-ft)	Optional desliming and cleaning of middlings product of the two-stage AM-8 system to produce a two-product separation (coal and reject)
		(19)	holding tank	
		(20)	3 x 3-in. pump	
		(21)	8-in. HM Cyclone	
		(22,23)	rinsing screens: 2 x 4-ft and 1 1/2 x 3-ft	
		(24)	drum-type magnetic separator	
		(b) slimes cleaning- two stage AM-8L	(25,26)	
	(27-30)		AM-8L: two-stage	
	(31,32)		emulsifying tanks & pump	
	(33)		oil conditioning tank	
	(34)		5-tph Gundlach crusher	
froth flotation	(35)	Cyclo-cell (3)	Optional cleaning of minus 28-mesh fines from clean coal and middlings products of the coarse cleaning section or back-up to AM-8L	
	(36)	reagent feeder		

TABLE 1: CANMET Processing Plant (continued)

<u>OPERATION</u>	<u>UNIT NO.</u>	<u>EQUIPMENT</u>	<u>FUNCTION</u>
3. Dewatering	(40)	dewatering screen: 1 1/2 x 4-ft	
	(41)	sieve bend	
	(17,18)	sieve bend and desliming screen	
Drying	(42)	two-stage pusher centrifuge	Dewatering and drying of finished products
	(43)	solid bowl centrifuge	
	(44)	DeLaval pusher centrifuge	
		2 centrifuge effluent pumps:	
	(45)	2 1/2 x 2 1/2-in.	
	(46)	1 1/4 x 1/4-in.	
4. Water Recovery	(50,51)	dual-mix tank III: 5 x 4-in. pump	Flocculation, clarification and storage of water for re-use
	(52)	two-stage 8-in. blenders, 4-in. classifier	
	(53,54)	flocculant tank: metering and Moyno pumps	
	(55)	6-ft diam bottom feed thickener	
	(56)	Moyno pump	
	(57)	2 1/2 x 2 1/2-in. pump	
	(58)	water reservoir	




Figure 1: CANMET-Process Flowsheet - 10 STPH Pilot Plant

