

This document was produced  
by scanning the original publication.

Ce document est le produit d'une  
numérisation par balayage  
de la publication originale.



Energy, Mines and  
Resources Canada

Énergie, Mines et  
Ressources Canada

## CANMET

Canada Centre  
for Mineral  
and Energy  
Technology


Centre canadien  
de la technologie  
des minéraux  
et de l'énergie

MOVABLE-WALL COKE OVEN TESTS OF FOUR SMOKY RIVER COAL SAMPLES  
SUBMITTED BY McINTYRE MINES LIMITED

Project No. 03-5-1/20-9  
Job No. 3448R

J. G. Jorgensen  
Combustion and Carbonization Research Laboratory, Ottawa  
A. B. Fung  
Coal Research Laboratories, Edmonton

MARCH 1984



MOVABLE-WALL COKE OVEN TESTS OF FOUR SMOKEY RIVER COAL SAMPLES  
SUBMITTED BY McINTYRE MINES LIMITED

Project 03-5-1/20-9

Job No. 3448R

by

J.G. Jorgensen\* and A.B. Fung\*\*

SUMMARY

The evaluation of coals for McIntyre Mines Limited is a continuing divisional project in which periodic investigations are undertaken as requested by the company.

This report includes coke oven evaluation data on four samples from the Smoky River property. The project was initiated by K. Watai, Area Sales Manager, McIntyre Mines Limited in a letter dated November 2, 1983. A copy of this letter is given in Appendix 1.

The cleaned coal samples received from Birtley Coal and Mineral Testing, Calgary were crushed, blended and carbonized in the 460-mm wide Carbolite movable-wall coke oven located at the Coal Research Laboratories at Edmonton. The results of the testing program are tabulated in Tables 1 to 3.

---

\*Petrographer, Combustion and Carbonization Research Laboratory, Energy Research Laboratories, Ottawa and \*\*Carbonization Engineer, Coal Research Laboratory, Coal Research Laboratories, Edmonton; CANMET, Energy, Mines and Resources Canada , Ottawa, KIA 0G1.

Essais en four à coke à paroi mobile réalisés avec  
quatre échantillons de charbon de Smokey River fournis

par la McIntyre Mines Limited

Projet 03-5-1/20-9

Contrat n<sup>o</sup> 3448R

par

J.G. Jorgensen\* et A.B. Fung\*\*

#### RÉSUMÉ

À la demande de la McIntyre Mines Limited, la Division effectue périodiquement des essais visant à évaluer le charbon dans le cadre d'un projet continu.

Le présent rapport contient les données relatives à l'évaluation en four à coke de quatre échantillons provenant de Smokey River. Le projet a débuté par une lettre de K. Watai, Directeur régional des ventes de la McIntyre Mines Limited, datée du 2 novembre 1983. Une copie de cette lettre se trouve à l'Annexe 1.

Les échantillons de charbon nettoyés envoyés par la Birtley Coal and Mineral Testing de Calgary ont été broyés, mélangés et carbonisés dans le four à coke à paroi mobile de Carbolite (largeur de 460 mm) du laboratoire de recherche sur le charbon d'Edmonton. Les résultats du programme d'essai sont présentés aux tableaux 1 à 3.

---

\*Spécialiste en pétrographie, Laboratoire de recherches sur la combustion et la carbonisation, Laboratoires de recherche sur l'énergie, Ottawa et  
\*\*ingénieur spécialisé en carbonisation, Laboratoire d'Edmonton, Laboratoires de recherche sur le charbon; CANMET, Énergie, Mines et Ressources Canada, Ottawa KIA 0G1.

## CONTENTS

	<u>Page</u>
SUMMARY .....	i
SOMMAIRE .....	ii
APPENDIX 1.....	4

## TABLES

<u>No.</u>		
1	Carbonization conditions.....	1
2	Coke properties .....	2
3	Coal Pulverization for coking test .....	3



Table 1 - Carbonization conditions

	C-207	C-208	C-209	C-210
Test Identification Number .....				
Date of Test .....	16/11/83	17/11/83	21/11/83	24/11/83
Coke Oven Identification.....				
Description.....	Drums 1-2-3	Drums 4-5-6	Drums 7-8-9	Drums 10-11-12
	Ash 7.1%	Ash 8.2% (product)	Ash 8.2% (stockpile)	Ash 7.7%

Charge Properties

Proximate Analysis (db) Ash.....%				
Volatile Matter ....%				
Fixed Carbon.....%				
Moisture in Charge .....	3.8	3.6	3.5	3.7
Minus 3.35 mm .....	84.6	85.6	84.0	85.3
Other .....				
.....				

Carbonization Conditions

Net Weight of Charge (wet).....kg	296.7	297.1	298.1	297.0
ASTM Cone Bulk Density (wet).....kg/m <sup>3</sup>	783.4	788.2	793.0	788.2
Calc. Charge Dry Bulk Density in Oven... kg/m <sup>3</sup>	813.8	815.4	820.2	815.4

Carbonization Results

Gross Coking Time (at Push).....h:min	19:20	19:45	19:25	19:33
Final Centre Temp.....°C	1032	1050	1037	1052
Time to 900°C Centre Temp.....h:min	15:49	16:10	15:39	16:00
Time to 950°C Centre Temp.....h:min	16:20	16:45	16:25	16:33
Time to 1000°C Centre Temp.....h:min	17:21	17:43	17:51	17:36
Maximum Wall Pressure.....kPa	13.27	6.14	4.62	13.31
Coke Yield Actual .....	79.8	78.3	77.8	78.2

Table 2 - Coke properties

Test Identification Number.....	C-207	C-208	C-209	C-210
<u>Screen Analysis of Coke</u>				
(cum. % retained on)				
100 mm sieve.....%	3.0	3.3	3.1	1.4
75 mm sieve.....%	17.8	21.0	22.4	18.0
50 mm sieve.....%	61.4	59.0	59.6	61.1
37.5 mm sieve.....%	85.0	75.8	74.6	82.6
25.0 mm sieve.....%	91.9	83.4	80.7	91.0
19.0 mm sieve.....%	92.9	84.8	81.9	92.2
12.5 mm sieve.....%	93.7	85.9	83.0	93.0
Total -12.5 mm (breeze).....%	6.3	14.1	17.0	7.0
Mean Coke Size.....mm	57.66	54.86	54.36	56.90
<u>Coke Chemical Analysis</u>				
Proximate Analysis (db)				
Ash.....%				
Volatile Matter.....%				
Fixed Carbon.....%				
Sulphur (db).....%				
Coke Apparent Specific Gravity.....	0.919	0.988	0.985	0.956
<u>ASTM Coke Tumbler Test</u>				
Stability Factor (cum. % + 25.0 mm).	58.0	47.5	44.8	57.5
Hardness Factor (cum. % + 6.3 mm).	65.2	59.4	57.8	65.3
<u>JIS Coke Tumbler Test</u>				
(cum. % retained on)				
30 revs: 50 mm sieve.....%	23.0	16.4	16.1	14.4
25 mm sieve.....%	90.2	83.3	82.0	89.0
15 mm sieve.....%	94.1	88.2	87.2	93.5
150 revs: 50 mm sieve.....%	4.6	0.8	1.0	4.7
25 mm sieve.....%	75.4	63.6	60.9	72.1
15 mm sieve.....%	81.6	71.8	70.4	81.1



Table 3 - Coal pulverization for coking test

Table 3 - Coal pulverization for coking test

Identification

Laboratory Number.....	C-207	C-208	C-209	C-210
Description.....				

Coal Pulverization

Sieve Analysis

<u>Passing</u>	<u>Retained On</u>				
	6.3 mm %	6.0	4.5	5.9	4.8
6.3 mm	3.35 mm %	9.4	9.9	10.1	9.9
3.35 mm	1.70 mm %	14.4	15.2	13.9	14.5
1.70 mm	850 μm %	11.6	12.4	12.0	12.7
850 μm	.....%	58.6	58.0	58.1	58.1
Total Passing	3.35 mm %	84.6	85.6	84.0	85.3

Grindability

Hardgrove Index .....

Fusibility of Ash

Initial Deformation Temp.....°C  
 Softening Temp Spherical.....°C  
 Softening Temp Hemispherical.....°C  
 Fluid Temp.....°C

**MCINTYRE MINES**

EXECUTIVE OFFICES  
14TH FLOOR  
THREE CALGARY PLACE  
355 FOURTH AVENUE SW  
CALGARY ALBERTA T2P 0J3  
TELEPHONE (403) 267-4511  
TELEX 03-825840

November 2, 1983

Dr. B. Parsons  
Director  
Coal Resources Processing Laboratory  
Energy Research Laboratories  
CANMET  
555 Booth Street  
Ottawa, Ontario  
K1A 0G1

Dear Dr. Parsons:

Re: Coal Carbonization Test

McIntyre Mines is a member of the Coal Carbonization Research Association and the producer of Smoky River metallurgical coal. We would like to conduct three carbonization tests at your Edmonton facility and would appreciate your approval. We will be responsible for the cost recovery of these tests.

Yours sincerely,

MCINTYRE MINES LIMITED

  
Ken Watai  
Area Sales Manager

KW/pmf

cc: Mr. J.G Jorgensen, Head, Coal Resource & Processing Lab. ✓  
Mr. A. Fung, Engineer, Energy Mines & Resources Canada  
Dr. D. Brown, Director, Energy Mines & Resources Canada  
Dr. H. Hanzam, Manager, Energy Mines & Resources Canada



