



The Creighton area electromagnetic and magnetic survey was funded by the Saskatchewan Ministry of Energy and Resources in support of the province's Mineral Development Strategy. It also complements a National Geological Survey Committee (NGSC) pilot project in the Creighton/Flin Flon area that demonstrates how public geoscience supports Canada's junior mining sector. Natural Resources Canada provided survey oversight and data processing, and produced the maps as part of the Targeted Geoscience Initiative (TGI) program of the Lands and Minerals Sector, Natural Resources Canada.

This map was compiled from data acquired during an airborne electromagnetic/magnetic survey carried out by CGG Canada Inc. utilizing CGG's HELITEM 35C Time-Domain Electromagnetic (TDEM) system. The system was mounted on a Eurocopter AS350 B3 helicopter (registration C-GUJH) and the survey was carried out between March 30 and June 13, 2014. The helicopter flight altitude was maintained at an average ground clearance of 80 m with an average speed of 90 km/h. Aircraft navigation used a 4-channel NovAtel dual frequency GPS system. Post-flight differential corrections were applied to finalize the flight path position. A vertically mounted video camera was used to record images of the ground. The radar height was recorded ten times per second using a geosynchronous altimeter. The pressure was recorded five times per second using a Motorola precision pressure transducer. The magnetic data were recorded 10 times per second using a Scintrex CS-3A cesium magnetometer.

The TDEM system operating at a base frequency of 30 Hz transmits a 8.0 ms half sine signal from a four-turn, 962 m<sup>2</sup> horizontal loop mounted approximately 34.6 m below and 8 m behind the helicopter GPS. This configuration generates a dipole moment of 827 000 Am<sup>2</sup>. The response of conductors in the subsurface is recorded at 192 Hz over the entire waveform using a three axis (X, Y and Z) induction coil mounted on the helicopter. The data are recorded using a GPS (Global Positioning System Transmitter/Receiver). The EM system records data in a continuous stream for each of the three components. The EM receiver directly measures the change in the magnetic field with respect to time (dB/dt) from which the secondary total magnetic field (B) is numerically integrated. High-altitude background sections flown at the start and end of each flight allow a first-order removal of system drift.

The apparent conductivity values (mS/m) were derived from the electromagnetic decays using a selected early channel 5 (0.118 ms), middle channel 16 (0.802 ms) and late channel 30 (8.272 ms) of the off-time signal. The nomogram indicates the correspondence between the value of  $dBz/dt$  (nT/s) and halfspace conductivity. Forward thin plate modeling is used to estimate the depth to the top of target (m) for the HELITEM 35C TDEM system.

Decay constant ( $\tau$ ) values are obtained by fitting the data from selected early Z channels 6 to 10 (0.130 ms to 0.309 ms), middle channels 15 to 19 (0.618 ms to 1.440 ms) and late channels 26 to 30 (3.906 ms to 8.960 ms) of the off-time signal to a single exponential. In semi-log space, the slope of this function will reflect the exponential decay rate of the transient field and, therefore, the strength of the conductivity. A slow rate of decay, reflecting a high conductivity, will be represented by a high decay constant value.

The magnetic field was sampled 10 times per second using a cesium vapour magnetometer (sensitivity = 0.001 nT) mounted on the EM transmitter loop. Differences in magnetic values at the intersections of control and traverse lines were analysed to obtain a mutually levelled set of flight-line magnetic data. The levelled values were then interpolated to a 50 m grid. The International Geomagnetic Reference Field (IGRF) defined at a mean GPS altitude (378 m) for a constant mid-survey date (May 6, 2018) was then removed. Removal of the IGRF, representing the magnetic field of Earth's core, produces a residual component related essentially to magnetizations within Earth's crust.

The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes long-wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of first vertical derivative maps is the coincidence of the zero-value contour with vertical contacts at high magnetic latitudes (Hood, 1965). The first vertical derivative of the magnetic field was calculated using the fast Fourier transform on the gridded total magnetic field with a grid cell size of 50 m.

Digital versions of this map are available for free download through GEOSCAN (<http://geoscan.nrcan.gc.ca/>). Corresponding digital profile and gridded data as well as similar data for adjacent airborne geophysical surveys can be downloaded, at no charge, from Natural Resources Canada's Geoscience Data Repository for Geophysical Data at [http://gdr.aggr.nrcan.gc.ca/index\\_e.html](http://gdr.aggr.nrcan.gc.ca/index_e.html). The same products are also available, for a fee, from the Geophysical Data Centre, Geological Survey of Canada, 6016 Booth Street, Ottawa, Ontario K1A 0E8. Telephone: 613-995-5326, email: [info@geonrcan.gc.ca](mailto:info@geonrcan.gc.ca).

The authors thank the CGG Canada Inc. team, Brett Robinson, Imrie Russell, Adam Smiarowski, Elizabeth Bowslaugh and Mihai Szentesy for their cooperation. The authors thank Jim Craven and Mark Pilkington for helpful comments and suggestions to improve the maps.


**Reference**  
Hood, P.J., 1965. Gradient measurements in aeromagnetic surveying; *Geophysics*, v. 30, p. 891-902.

Sheet 1: Time Decay Constant (Tau-Z) - Early Channels (6 to 10)
Sheet 2: Time Decay Constant (Tau-Z) - Mid Channels (15 to 19)
Sheet 3: Time Decay Constant (Tau-Z) - Late Channels (26 to 30)
Sheet 4: Apparent Conductivity - Early Channel 5 (0.118 ms)
Sheet 5: Apparent Conductivity - Mid Channel 16 (0.802 ms)
Sheet 6: Apparent Conductivity - Late Channel 30 (8.272 ms)
Sheet 7: Residual Total Magnetic Field
Sheet 8: First Vertical Derivative of the Magnetic Field
Sheet 9: Interpretation


**Authors:** O. Boulanger, F. Kiss, M. Coyle and O. Mahmoodi

Data acquisition and data compilation by CGG Canada Limited, Toronto, Ontario.  
Contract, project management and map production by  
the Geological Survey of Canada, Ottawa, Ontario

Permanent link: <https://doi.org/10.4095/308435>



### MAP LOCATION

NATIONAL TOPOGRAPHIC REFERENCE SYSTEM  
AND GEOPHYSICAL MAP INDEX

GEOLOGICAL SURVEY OF CANADA OPEN FILE 8446


SASKATCHEWAN GEOLOGICAL SURVEY OPEN FILE REPORT 2018-5

# ELECTROMAGNETIC SURVEY OF THE CREIGHTON AREA

SASKATCHEWAN  
of NTS 63-L/2 and 63-L/3

### TIME DECAY CONSTANT - (TAU Z) - EARLY CHANNELS (6 to 10)

Scale 1:50 000



(metres)

Map projection Universal Transverse Mercator, zone 13N. World Geodetic System 1984  
© Her Majesty the Queen in Right of Canada, as represented by the Minister of Natural Resources, 2018

OPEN FILE / DOSSIER PUBLIC

Publications in this series have not been edited; they are released as submitted by the author.

Les publications de cette série ne sont pas révisées; elles sont publiées telles que soumises par l'auteur.

**Recommended citation**  
Boulanger, O., Kiss, F., Coyle, M. and Mahmoodi, O., 2018.  
Electromagnetic Survey of the Creighton Area, Saskatchewan,  
Parts of NTS 63-L/2 and 63-L/3;  
Geological Survey of Canada, Open File 8446;  
Saskatchewan Geological Survey, Open File Report 2018-5;  
Scale 1:50 000. <https://doi.org/10.4095/308435>

OPEN FILE REPORT  
RAPPORT DE DOSSIER PUBLIC  
2018-5

SASKATCHEWAN GEOLOGICAL SURVEY  
COMMISSION GÉOLOGIQUE DE LA  
SASKATCHEWAN  
2018

Sheet 1 of 9 / Feuille 1 de 9