


INTERPRETATION



Technical Information

This map was compiled from data acquired during an airborne electromagnetic/magnetic survey carried out by CCG Canada Inc. utilizing CCG's HELITEM 35C Time-Domain Electromagnetic (TDEM) system. The system was mounted on a Eurocopter AS350 B3 helicopter (registration C-GFUG) and the survey was carried out between March 30 and June 13, 2018. The helicopter flight altitude was maintained at an average ground clearance of 80 m with an average speed of 90 km/h. Aircraft navigation used a 14-channel NovaTel dual frequency GPS system. Post-flight differential corrections were applied to finalize the flight path position. A vertically mounted video camera was used to record images of the ground. The radar height was recorded ten times per second using a Honeywell altimeter and the barometric altitude was recorded five times per second using a Motorola precision pressure transducer. The magnetic data were recorded 10 times per second using a Scintrex CS-3A cesium magnetometer.

Electromagnetics

The TDEM system operating at a base frequency of 30 Hz transmits a 8.0 ms half sine signal from a four-turn, 962 m² horizontal loop mounted approximately 34.6 m below and 8 m behind the helicopter GPS. This configuration generates a dipole moment of 827 000 Am². The response of conductors in the subsurface is recorded at 192 kHz over the entire waveform using a three axis (X, Y and Z) electromagnetic receiver coincident with the transmitter loop (in-Loop Transmitter-Receiver). The EM system records data in a continuous stream for each of the three components. The EM receiver directly measures the change in the magnetic field with respect to time (dB/m) from which the secondary total magnetic field (B) is numerically integrated. High-altitude background sections flown at the start and end of each flight allow a first-order removal of system drift.

Apparent Conductivity

The apparent conductivity values (mS/m) were derived from the electromagnetic decays using a selected early channel 5 (0.118 ms), middle channel 16 (0.822 ms) and late channel 30 (8.272 ms) of the off-time signal. The nomogram indicates the correspondence between the value of dB/dt (nT/s) and halfspace conductivity. Forward thin plate modeling is used to estimate the depth to the top of target (m) for the HELITEM 35C TDEM system.

Electromagnetic Decay Constant

Decay constant (Tau) values are obtained by fitting the data from selected early Z channels 6 to 10 (0.130 ms to 0.309 ms), middle channels 15 to 19 (0.618 ms to 1.440 ms) and late channels 26 to 30 (3.906 ms to 8.560 ms) of the off-time signal to a single exponential. In semi-log space, the slope of this function will reflect the exponential decay rate of the transient field and, therefore, the strength of the conductivity. A slow rate of decay, reflecting a high conductivity, will be represented by a high decay constant value.

Magnetics

The magnetic field was sampled 10 times per second using a cesium vapour magnetometer (sensitivity = 0.001 nT) mounted on the EM transmitter loop. Differences in magnetic values at the intersections of control and traverse lines were analysed to obtain a mutually levelled set of flight-line magnetic data. The levelled values were then interpolated to a 50 m grid. The International Geomagnetic Reference Field (IGRF) defined at a mean GPS altitude (378 m) for a constant mid-survey date (May 6, 2018) was then removed. Removal of the IGRF, representing the magnetic field of Earth's core, produces a residual component related essentially to magnetizations within Earth's crust.

The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes long-wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of first vertical derivative maps is the coincidence of the zero-value contour with vertical contacts at high magnetic latitudes (Hood, 1965). The first vertical derivative of the magnetic field was calculated using the fast Fourier transform on the gridded total magnetic field with a grid cell size of 50 m.

Digital versions of this map are available for free download through GEOSCAN (<http://geoscan.nrcan.gc.ca>). Corresponding digital profile and gridded data as well as similar data for adjacent airborne geophysical surveys can be downloaded, at no charge, from Natural Resources Canada's Geoscience Data Repository for Geophysical Data at http://gdr.aggr.nrcan.gc.ca/index_e.html. The same products are also available, for a fee, from the Geophysical Data Centre, Geological Survey of Canada, 601 Booth Street, Ottawa, Ontario K1A 0E8. Telephone: 613-995-5326, email: info@geoscan.gc.ca.

Acknowledgments

The authors thank the CCG Canada Inc. team, Brett Robinson, Imrie Russell, Adam Smarowski, Elizabeth Bowslaugh and Mihai Scantley for their cooperation. The authors thank Jim Craven and Mark Pilkington for helpful comments and suggestions to improve the maps.

Reference

Hood, P.J., 1965. Gradient measurements in aeromagnetic surveying; Geophysics, v. 30, p. 891-902.

Authors: O. Boulanger, F. Kiss, M. Coyle and O. Mahmoodi

Data acquisition and data compilation by CCG Canada Limited, Toronto, Ontario. Contract, project management and map production by the Geological Survey of Canada, Ottawa, Ontario.

Permanent link: <https://doi.org/10.4095/308436>

NTS map sheet numbers in black

CGS open file numbers in red / SGS open file report numbers in blue

MAP LOCATION



NATIONAL TOPOGRAPHIC REFERENCE SYSTEM AND GEOGRAPHICAL MAP INDEX



GEOLOGICAL SURVEY OF CANADA OPEN FILE 8447

SASKATCHEWAN GEOLOGICAL SURVEY OPEN FILE REPORT 2018-6
ELECTROMAGNETIC SURVEY OF THE CRIGHTON AREA

SASKATCHEWAN

Parts of NTS 63-E/14 and 63-E/15

INTERPRETATION

Scale 1:50 000

WGS 84 / UTM zone 13N

Map projection: Universal Transverse Mercator, zone 13N, World Geodetic System 1984
© Her Majesty the Queen in Right of Canada, as represented by the Minister of Natural Resources, 2018
Topographic data from Natural Resources Canada
Contour interval 20 metres

OPEN FILE / DOSSIER PUBLIC 8447

Publications in this series have not been edited; they are released as submitted by the author.
Les publications de cette série ne sont pas révisées; elles sont publiées telles que soumises par l'auteur.

Recommended citation



Boulanger, O., Kiss, F., Coyle, M. and Mahmoodi, O., 2018. Electromagnetic Survey of the Crighton Area, Saskatchewan, Parts of NTS 63-E/14 and 63-E/15. Geological Survey of Canada, Open File 8447; Saskatchewan Geological Survey, Open File Report 2018-6; Scale 1:50 000. <https://doi.org/10.4095/308436>

Survey Area Parameters:

Traverse line azimuth	N88°E
Traverse line spacing	200 m
Tie line azimuth	N358°E
Tie line spacing	1200 m
Aircraft average clearance	80 m
EM transmitter nominal clearance	45 m
Magnetic sensor nominal clearance	45 m
EM receiver nominal clearance	45 m

Electromagnetic System Specifications:

Base frequency	30 Hz
Waveform	Half sinusoid
Transmitter pulse width	8 ms
Transmitter area	962 m ²
Transmitter off-time	8.9 ms
Transmitter loop diameter	35 m
Transmitter current	215 A
Dipole moment (approximately)	827 000 Am ² (4 turns)
Windowed data sampling rate	10 Hz
Receiver	3-component induction coil (Z, X, Y)
Measured response	Voltage (dB/dt)
Digital recording	Z, X, Y - 5-30 channels
1 st off-time Z channel	Channel 5 at ~8 ms after pulse turn off
Tx-Rx configuration	In-loop concentric



PLANIMETRIC SYMBOLS

- Drainage
- Topographic Contours (Contour Interval = 20 m)
- Building
- Trail
- Flight Path
- Project Limit

ELECTROMAGNETIC ANOMALIES

- Anomaly Conductance (mS)
 - >250
 - 100-250
 - 50-100
 - 25-50
 - 5-25
 - 0-5
 - culture
- Anomaly ID
- Depth