DV-05

Borehole:	DV-05	Easting:	541 104 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	New Dundee, ON	Northing:	4 800 483 m	Original Material:	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	109.7 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	352 m	Dwell Time:	60 seconds per High, Main, and Low filter		
				Mode Type:	Soil Mode, Compton normalization	Date Analyzed:	January 2017

Soil Mode



Borehole:	DV-05	Easting:	541 104 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	New Dundee, ON	Northing:	4 800 483 m	Original Material:	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	109.7 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	352 m	Dwell Time:	45 seconds per High, Main, Low and Light filter		
				Mode Type:	Mining Mode, Fundemental parameters	Date Analyzed:	January 2017

Mining Mode



DV-06

Borehole:	DV-06	Easting:	518 276 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	Wellesley Township, ON	Northing:	4 814 982 m	Original Material:	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	82.75 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	372 m	Dwell Time:	60 seconds per High, Main, and Low filter		
				Mode Type:	Soil Mode, Compton normalization	Date Analyzed:	January 2017

Soil Mode



Borehole:	DV-06	Easting:	518 276 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	Wesley Township, ON	Northing:	4 814 982 m	Original Material:	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	82.75 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	372 m	Dwell Time:	45 seconds per High, Main, Low and Light filter		
				Mode Type:	Mining Mode, Fundemental parameters	Date Analyzed:	January 2017

Mining Mode

DV-08

Borehole:	DV-08	Easting:	520 975 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	Wilmot Township, ON	Northing:	4 812 880 m	Original Material:	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	79.85 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	352 m	Dwell Time:	60 seconds per High, Main, and Low filter		
				Mode Type:	Soil Mode, Compton normalization	Date Analyzed:	January 2017

Soil Mode



Borehole:	DV-08	Easting:	541 104 m	Size Fraction:	<0.074 mm	Date Drilled:	July 2011
Location:	Wilmot Township, ON	Northing:	4 800 483 m	Original Material	Disaggregated, seived	Date Logged:	July 2011
Project:	Groundwater Assessment	UTM Zone:	17	Vial Window Material:	4 micron SpectroCertified Mylar polypropylene	Depth Drilled:	79.85 m
Study Area:	Dundas Valley	Datum:	NAD83	pXRF:	Niton XL3t GOLDD, 50-kV Cygnet X-ray tube	Borehole Diameter:	4 inch
		Elevation:	352 m	Dwell Time:	45 seconds per High, Main, Low and Light filter		
				Mode Type:	Mining Mode, Fundemental parameters	Date Analyzed:	January 2017

Mining Mode