


This document was produced
by scanning the original publication.
Ce document est le produit d'une
numérisation par balayage
de la publication originale.



RELIABILITY DIAGRAM - CROQUIS D'EXACTITUDE



A - Stereo-compiled from 1958 aerial photographs.
A - Rédigée par stéréorestitution d'après des photographies aériennes prises en 1958.

Compiled, 1965, by the SURVEYS AND MAPPING BRANCH,
DEPARTMENT OF MINES AND TECHNICAL SURVEYS.
Imprimé en 1965.

Magnetic declination 1965 varies from 52°23' westerly at
centre of west edge to 53°53' westerly at centre of east
edge. Mean annual change 17.7' easterly.

Road, dry weather.....Route, temps sec.....
Wagon or winter road.....Chemin de terre ou d'hiver.....
Trail or portage.....Sentier ou portage.....
Town.....Ville.....
Village or Settlement.....Village ou hameau.....
Post Office.....Bureau de poste.....
Horizontal control point.....Point géodésique.....
Boundary monument.....Borne frontière.....

PRINCE CHARLES ISLAND

DISTRICT OF FRANKLIN
NORTHWEST TERRITORIES

Scale 1:250,000 Échelle
Miles 5 0 5 10 15
Kilometres 5 0 5 10 15
Projection Transverse de Mercator
North American Datum 1927 (1956)
Contour Interval 100 feet
Elevations in feet above Mean Sea Level
Ces cartes sont en vente au Bureau de distribution des cartes,
ministère des Mines et des Relevés techniques, Ottawa.

Rédigée en 1965, par la DIRECTION DES LEVÉS ET DE LA
CARTOGRAPHIE, MINISTÈRE DES MINES ET DES RELEVÉS
TECHNIQUES. Imprimée en 1965.

La déclinaison magnétique pour 1965 varie de 52°23' Ouest
au centre de la limite Ouest à 53°53' Ouest au centre de la
limite Est. Variation moyenne annuelle 17.7' Est.

Stream intermittent or dry.....Cours d'eau intermittent ou à sec.....
Indefinite.....Imprécis.....
Rapids; falls.....Rapides; chute.....
Marsh or swamp.....Marais ou marécage.....
Intermittent lake.....Lac intermittent.....
Depression contours.....Courbes de cuvette.....
Spot Elevation, in feet.....Repère de nivellement en pieds.....2550.

GRID ZONE DESIGNATION		100,000 M. SQUARE IDENTIFICATION							
18 W	<table border="1"><tr><td>UL</td><td>VL</td></tr><tr><td>UR</td><td>VK</td></tr><tr><td colspan="2">4</td></tr></table>	UL	VL	UR	VK	4		75	4
		UL	VL						
		UR	VK						
		4							
TO GIVE A REFERENCE TO NEAREST 1000 METRES									
EXAMPLE:		LAKE							
SQUARE: Read letters of 100,000 m. square		VL							
EASTING: Read number on grid line immediately to left of point		3							
Estimate tenths of a square from this line eastward to point		6							
NORTHING: Read number on grid line immediately below point		1							
Estimate tenths of a square from this line northward to point		9							
MILITARY GRID REFERENCE (in metres, 1,000 metres)		VL 3619							
If reporting beyond 18° in any direction, prefix Grid Zone Designation as: 18WVL 3619									

TEN THOUSAND METRE
UNIVERSAL TRANSVERSE MERCATOR GRID
ZONE 18

