


TOPOGRAPHICAL SURVEY DIRECTORATE
SERVICE TOPOGRAPHIQUE
DATE 2-04-61
Q.C. APPROVES RELEASE
C.Q. APPROUVE

100,000 M. SQUARE IDENTIFICATION	
GRID ZONE DESIGNATION	CR 9537
16 U	CR 9537
TO GIVE A REFERENCE TO NEAREST 1000 METRES	
EXAMPLE: LAKE	
SQUARE: Read letters of 100,000 m. square	CR
EASTING: Read number on grid line immediately to left of point.	9
Estimate tenths of a square from this line eastward to point.	5
NORTHING: Read number on grid line immediately below point.	3
Estimate tenths of a square from this line northward to point.	7
MILITARY GRID REFERENCE (to nearest 1,000 metres)	CR9537
If reporting beyond 10° in any direction, prefix Grid Zone Designation as:	16UCR9537

TEN THOUSAND METRE
UNIVERSAL TRANSVERSE MERCATOR GRID
ZONE 16

RELIABILITY DIAGRAM - CROQUIS D'EXACTITUDE




A* Stereocompiled from 1954-56 aerial photographs.
A* Rédigé par Stéréostitution d'après des photographies aériennes prises en 1954-56.

Compiled 1963, by the SURVEYS AND MAPPING BRANCH,
DEPARTMENT OF MINES AND TECHNICAL SURVEYS.
Field surveys 1961-62. Printed 1964.
Magnetic declination 1965 varies from 01°00' westerly at
centre of west edge to 04°34' westerly at centre of east
edge. Mean annual change: 4.2' easterly.

Road, dry weather.....Route, temps sec.
Wagon or winter road.Chemin de terre ou d'hiver.....
Trail or portage.....Sentier ou portage.....
Town.....Ville.....
Village or Settlement.Village ou hameau.....
Post Office.....Bureau de poste.....
Horizontal control point.Point géodésique.....
Boundary monument.Borne frontière.....

FAWN RIVER
KENORA DISTRICT
ONTARIO

Scale 1:250,000 Échelle



Transverse Mercator Projection
North American Datum 1927
Contour Interval 100 feet
Elevations in feet above Mean Sea Level
Copies may be obtained from the Map Distribution Office,
Department of Mines and Technical Surveys, Ottawa.

Projection Transverse de Mercator
Niveau de référence nord-américain, 1927
Équidistance des courbes: 100 pieds
Élévations en pieds au-dessus du niveau moyen de la mer
Ces cartes sont en vente au Bureau de distribution des cartes,
ministère des Mines et des Relevés techniques, Ottawa.

Rédigée en 1963 par la DIRECTION DES LEVÉS ET DE LA
CARTOGRAPHIE, MINISTÈRE DES MINES ET DES RELEVÉS
TECHNIQUES. Levés sur le terrain en 1961-62. Imprimée en 1964.
La déclinaison magnétique pour 1965 varie de 01°00' Ouest au
centre de la limite Ouest à 04°34' Ouest au centre de la limite
Est. Variation moyenne annuelle: 4.2' Est.

Stream Cours d'eau
intermittent or dry.....intermittent ou à sec.....
Indefinite.....Impécis.....
Rapids; falls.....Rapides; chute.....
Marsh or swamp.....Marais ou marécage.....
Intermittent lake.....Lac intermittent.....
Depression contours.....Courbes de cuvette.....
Spot Elevation, in feet. Repère de nivellement en pieds.....2550.

