



ÉTABLIE PAR LA DIRECTION DES LEVÉS ET DE LA
CARTOGRAPHIE, MINISTÈRE DE L'ÉNERGIE, DES
MINES ET DES RESSOURCES, OTTAWA, EN 1973

ÉQUIDISTANCE DES COURBES 25 PIEDS

© CANADA 1973 TOUS DROITS RÉSERVÉS.

EXAMPLE OF METHOD USED
TO FIND A REFERENCE TO MEASURE 100 METRES
FROM THE POINT OF THE MEASURED END POINT
FOUR FEET OF THE RESPONSE A 100 METRES PRESS

EASTING. Read number on grid line immediately to left of point.

NORTHING. Note the number of a line of quadrangle immediately to gauche of point.

Estimate height of a square from this line northeast to point.

Estimate the number of double of carré entre cette ligne et le repère en direction est:

97

975

NORTHING. Read number on grid line immediately to left of point.

LATITUDE. Note the number of a line of quadrangle immediately to dessous of point.

Estimate height of a square from this line northeast to point.

Estimate the number of double of carré entre cette ligne et le repère en direction nord:

98

984

GRID REFERENCE

EXAMPLE OF QUADRANGLE

9752984

Notes: grid reference: 100,000 metres (about 32 miles). The practical difference involved is ca. 1,000,000 metres (about 625 miles).

ONE THOUSAND METRE
UNIVERSAL TRANSVERSE MERCATOR GRID
ZONE 12
QUADRILLAGE DE MILLE MÈTRES
UNIVERSEL TRANSVERSE DE MERCATOR

The 1973 MAGNETIC BEARING is 27°42' (492 miles)
EAST of GRID NORTH.

ANNUAL CHANGE DECREASING 4.3'

GRID NORTH is 1°04' (19 miles) WEST of TRUE NORTH
for centre of map.

Le REPERE MAGNÉTIQUE en 1973 est à 27°42' (492 miles)
EST du NORD DU QUADRILLAGE.

VARIATION ANNUELLE DÉCROISSANTE 4.3'

NORD DU QUADRILLAGE est 1°04' (19 miles) à l'ouest du
NORD GÉOGRAPHIQUE au centre de la carte.

CONVERSION SCALE FOR ELEVATIONS
ÉCHELLE DE CONVERSION DES ÉLEVATIONS

Metres 30 20 10 0 50 100 150 200 250 300 Mètres

Feet 100 50 0 100 200 300 400 500 600 700 800 900 1000 Pieds

PROVISIONAL PRINT IMPRESSION PROVISOIRE