


(TSR) MARINE SEISMIC OBSERVER'S DATA

FOR PROSPECT PAGES 1 TO 4

CLIENT: P6C
 PROSPECT: The Island
 AREA: QUEENSLAND
 VESSEL: E.O. VETTER
 PARTY NO.: 2972
 LINE NO.: QC88-2A
 LINE ID.: 1002
 DIRN: 2278
 DATE: 7 DAY 5 YR 88
 PARTY MANAGER: BARRETT
 SHIPMENT NO.:



GROUP LOCATIONS IN STREAMER OF:

| | | | | | | | | | | |
|-------------------|---|----|----|----|-----|-----|-----|-----|-----|-----|
| DEPTH TRANSDUCERS | 7 | 31 | 55 | 79 | 108 | 121 | 151 | 175 | 211 | 235 |
| DEPTH CONTROLLERS | / | / | / | / | / | / | / | / | / | / |
| COMPASS SENSORS | / | / | / | / | / | / | / | / | / | / |

COMPASS SENSORS: SAME

RECORDING PARAMETERS:
 INSTRUMENT TYPE: TSR
 S/N: 4
 FILTER SETTINGS: HI 90 HZ. SLOPE 72 DB/OCT
 LO 8 HZ. SLOPE 18 DB/OCT
 PREAMPLIFIER GAIN: 11 M 012 DB
 SAMPLE RATE: 4 MS
 RECORD LENGTH: 14 SECS
 TAPE FORMAT: SEG D
 PACKING DENSITY: 6250 GCR
 BYTES IN HEADER:
 EXTENDED HEADER USED: YES
 DELAY RECORD MODULE USED: YES
 TAPE LENGTH: 3600 FT.
 REVERSED TRACES (IN TSR):
 GAIN MODE: FLOAT
 TIMEBREAK WINDOW: 32 MS
 POLARITY: POSITIVE PRESSURE ON PHONE GIVES
 NEGATIVE UPBREAK
 POSITIVE NO. ON TAPE DOWNBREAK
 CAMERA DISPLAY METHOD: 0005/LEVELS
 SINGLE TRACE DISPLAY SOURCE: 235

REMARKS:
 Term due to excessive SAT update LGS P. 369
 9 SECS TO FRONT
 9 SECS TO CHECK PRE SPS FOR LOCATION.

LINE STATUS:
 PROC/COMPLETE - DNP - HOLD - DRESH - UNDS
 FSP: 101 FRN: 101
 LSP: 901 LFN: 900
 TOT SPS: 801 TOT RMS: 800

DEAD TRACES: 38
 NOISY TRACES: 38
 TAPES USED: 7

SOURCE DETAILS:
 SOURCE TYPE AND SIZE: 63 7 M
 SOURCE DEPTH: 7 M
 AIRGUN PRESSURE: 2000 PSI
 SOURCE FIRING DELAY: 51.2 MS
 STREAMER TYPE:
 CABLE DETAILS:
 NUMBER OF GROUPS: 240
 GROUP LENGTH: 15 M
 NUMBER OF PHONES/GROUP: 40
 TARGET STREAMER DEPTH: 12 M
 STREAMER LENGTH (TO CENTRE PAN OF 1) 3600 M
 GROUP CHARGE SENSITIVITY: 8.2 V/18
 NUMBER OF SEMS:
 NUMBER OF SEMS IN USE: 20
 LENGTH OF EACH STRETCH SECTION: 100 M
 NUMBER OF STRETCHES IN FRONT END: 2
 NUMBER OF REPEATERS IN USE: 5
 FOLD COVERAGE: 45%
 SHOT INTERVAL: 45 M

NOISE DETAILS:
 NOISE DETAIL: UB
 EDL: UB

